

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Workstation CELSIUS H780 Workstations

Mobility. Security. Virtual Reality.

Meet the FUJITSU CELSIUS H780, the world's first 39.6 cm (15.6-inch) mobile workstation combining ultimate security with future technologies. While creatives and innovators are working on increasingly huge datasets, this machine will not weigh them down when showcasing designs in virtual reality at events or at the customer site.

Need For Speed

When true workstation performance meets the elegant style of a laptop

- Choose between Intel® Core™ processors or powerful Intel® Xeon® processor E-2100M family supporting ECC memory
- Support of Windows 10 Pro
- UHD/4k and Full HD LED anti-glare displays (incl. touch option)
- Up to 64 GB DDR4 2400 MHz memory (ECC optional)
- Dual M.2 SSDs PCIe NVMe technology supports quick loading of core applications
- Made in Germany



Full connectivity and worry-free docking experience

No compromise in terms of port connectivities, regardless of whether you are away, in a meeting or at your desk

- 2x USB Type-C™ connector offering speed (40 Gbps), protocols (including Thunderbolt™ 3) and charging capabilities (power delivery of 15W)
- Full monitor connectivity support: 1x VGA and 1x HDMI
- Choice of port replicators with mechanical or Thunderbolt™ 3 connector

Mobility Meets Security

Data security and peace of mind

- Optional PalmSecure™, a leading-edge highly secure authentication system using biometric technology that authenticates users through vein pattern recognition
- Integrated SmartCard reader
- TPM 2.0 and Advanced Theft Protection

We are (VR) ready

Architects, engineers and designers can now showcase their work in a real-time, fully immersive VR environment

- Powered by the NVIDIA® Quadro® P3200 VR-ready graphics card
- Ideal for mobile VR showcases at the customer site or at an event
- Easy connectivity of the head-mount display to the HDMI port



Components

Base unit	CELSIUS H780
Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Pro for Workstations
Operating system compatible	Windows 10 Pro Windows 10 Pro for Workstations
Operating system notes	Certified for SUSE Enterprise Desktop (pending)
Processor	
	Intel® Xeon® processor E-2186M (6 Cores / 12 Threads, 2.90 GHz, up to 4.6 GHz) *
	Intel® Xeon® processor E-2176M (6 Cores / 12 Threads, 2.70 GHz, up to 4.4 GHz) *
	Intel® Core™ i7-8850H processor (6 Cores / 12 Threads, 2.60 GHz, up to 4.3 GHz) *
	Intel® Core™ i7-8750H processor (6 Cores / 12 Threads, 2.20 GHz, up to 4.1 GHz) *, **
	Intel® vPro™ with all Intel® Xeon® processors Please note that only certain combinations of processors, graphics and displays can be ordered *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) **not for corporate projects (only for retail, SMB, education and government)
Graphics	
	Midrange 3D: NVIDIA® Quadro® P2000, 4 GB (GDDR5), 768 CUDA® Processing Cores
	Midrange 3D: NVIDIA® Quadro® P3200, 6 GB (GDDR5), 1792 CUDA® Processing Cores
	Entry 3D: NVIDIA® Quadro® P600, 4 GB (GDDR5), 384 CUDA® Processing Cores
	Entry 3D: NVIDIA® Quadro® P1000, 4 GB (GDDR5), 512 CUDA® Processing Cores
Memory modules	
	8 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, PC4-2400, SO DIMM
	16 GB (2 module(s) 8 GB) DDR4, 2,400 MHz, PC4-2400, SO DIMM
	16 GB (2 module(s) 8 GB) DDR4, ECC, 2,400 MHz, PC4-2400, SO DIMM
	32 GB (2 module(s) 16 GB) DDR4, 2,400 MHz, PC4-2400, SO DIMM
	32 GB (2 module(s) 16 GB) DDR4, ECC, 2,400 MHz, PC4-2400, SO DIMM
Hard disk drives (internal)	
	HDD SATA III, 5,400 rpm, 500 GB
	HDD SATA III, 5,400 rpm, 1000 GB
	PCIe-SSD, NVMe, 256 GB, M.2 module
	PCIe-SSD, NVMe, 512 GB, M.2 module
	PCIe-SSD, NVMe, 256 GB Highend, M.2 module
	PCIe-SSD, NVMe, 512 GB Highend, M.2 module, SED
	PCIe-SSD, NVMe, 512 GB Highend, M.2 module
	PCIe-SSD, NVMe, 1024 GB Highend, M.2 module
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software.
Interface add on cards/components (optional)	
3G/4G (optional)	Sierra Wireless EM7455 (Cat. 6)
Display	
	39.6 cm (15.6-inch),LED backlit,(UHD/4K),Anti-glare IPS display,3,840 x 2,160 pixel,Viewing angle: Left/Right/Top/Bottom 80°min,Color Gamut: 72%,Contrast Ratio: 700 typ.,Brightness: 300cd/m ²
	39.6 cm (15.6-inch),LED backlit,(Full HD Premium Touch Panel),Anti-glare IPS touchscreen,1,920 x 1,080 pixel,Viewing angle: Left/Right/Top/Bottom 80°min,Color Gamut: 72%,Contrast Ratio: 700 typ.,Brightness: 300cd/m ²
	39.6 cm (15.6-inch),LED backlit,(Full HD Premium),Anti-glare IPS display,1,920 x 1,080 pixel,Viewing angle: Left/Right/Top/Bottom 80°min,Color Gamut: 72%,Contrast Ratio: 700 typ.,Brightness: 300cd/m ²
	39.6 cm (15.6-inch),LED backlit,(Full HD),Anti-glare IPS display,1,920 x 1,080 pixel,Viewing angle: Left/Right/Top/Bottom 80°min,Color Gamut: 45%,Contrast Ratio: 700 typ.,Brightness: 250cd/m ²

Base unit

Base unit	CELSIUS H780	
Mainboard		
Chipset	Intel® QM370 or CM246 (depending on CPU)	
Supported capacity RAM (min.)	8 GB	
Supported capacity RAM (max.)	64 GB	
Memory slots	4 SO DIMM (DDR4, 2400 MHz)	
LAN	10/100/1,000 MBit/s Intel® I219LM	
Integrated WLAN	Intel Dual Band Wireless-AC9560	
BIOS features	InsydeH20 Bios	
Audio type	On board	
Audio codec	Realtek ALC255 with MaxxAudio	
Audio features	Stereo speakers, 2 digital microphones	
MIL-STD tested	Yes, selected MIL-STD-810G tests passed. MIL-STD-810G test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.	
Display		
Display notes	ISO 9241-307 - Pixel class II - anti-glare level	
Graphics		
Base unit	CELSIUS H780	
Max. resolution external display	up to 4,096 x 2,160 @ 60Hz	
Max. resolution display port	3,840 x 2,160 pixel via DisplayPort and Type-C and 1,920 x 1,200 pixel via VGA	
Interfaces		
DC-in	1	
Internal microphones	2 digital array microphones	
Internal speakers	2	
USB 3.1 Gen1 (USB 3.0) total	1	
USB 3.1 Gen2 total	4	
USB Type-C	2 (USB 3.1 Gen2 (10 Gbps), Thunderbolt 3 (20/40Gbps), Power Delivery (15W), DP 1.4)	
VGA	1	
HDMI	1	
Ethernet (RJ-45)	1	
SmartCard slot	1	
SIM card slot	1	
Multicardreader	1 (SD/SDXC, UHS-II support) SD/microSD = 2GB, SDHC/micro SDHC = 32GB, SDXC = 512GB	
Interface Module notes	1x Kensington Lock support, 1x Docking connector	
Port Replicator interfaces (optional)		
Notes	Thunderbolt Port Replicator	Mechanical Port Replicator
DC-in	1	1
Power on switch	---	1
Audio: line-in / microphone	1	1
Audio: line-out / headphone	1	1
USB 2.0 total	2	---
USB 3.1 Gen1 (USB 3.0) total	2	6 (4x USB Type-A, 2x USB Type-C)
DisplayPort	2	2
VGA	1	1
DVI	1	1

Port Replicator interfaces (optional)

Ethernet (RJ-45)	1	1
Interface Notes	---	DisplayPort#1 on Port Replicator and HDMI on the workstation are alternative

Keyboard

Keyboard w/o touchstick (spill-resistant)#Keyboard w/ touchstick#Backlight keyboard w/o touchstick (spill-resistant)
 Number of keyboard keys: 106, Keyboard pitch: 18.4 mm, Keyboard stroke: 1.7 mm
 Touchpad with three mouse buttons

Input devices (optional)

TouchStick

Antennas

Bluetooth	5.0
Integrated WLAN	Intel Dual Band Wireless-AC9560

Fast IDE/Ultra DMA-100

SATA RAID support	0,1
-------------------	-----

Power supply

AC adapter	19.5 V / 230 W (11.8 A)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
1st battery	1st Li-Ion battery 8-cell, 96 Wh, 6700 mAh
Runtime 1st battery	up to 9 hours
Battery charging time	up to 80% within 1.3 hrs; up to 100% within 2.5hrs.

Dimensions / Weight / Environmental

Dimensions (W x D x H)	380.0 x 258.0 x 31.9 mm 14.96 x 10.16 x 1.26 inch
Weight	from 2.7 kg
Weight (lbs)	from 5.95 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	20 - 80 % (relative humidity, non-condensing)

Compliance

Product	CELSIUS H780
Europe	CE Marking
USA/Canada	cULus FCC Class B part 15C/E + 22 + 24 (depending on wireless configuration)
Global	RoHS (EU & China) ENERGY STAR® 7.0 EPEAT® in progress (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Fujitsu Display Manager EasyGuide online user documentation Power Saving Utility ShockSensor Utility SmartAccess Fujitsu Plugfree Network (network management utility) Intel® SBA (manageability suite for local administration) DTS® Sound Enhance Software Fujitsu Application Button Utility Fujitsu DeskUpdate (driver and utility tool) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
------------------------------------	--

Additional Software

Additional software (optional)	Drivers & Utilities DVD (DUDVD) LTE / UMTS Connection Manager (if configured with 4G/LTE or 3G/UMTS) Workplace Protect (secure authentication solution)
---------------------------------------	---

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) iAMT 12.0 (depending on processor) Intel® vPro™ technology WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/solutions/high-tech/dynamic-infrastructure/solutions/workplace/manageability/feature-finder.html

Security

Physical Security	Kensington Lock support
System and BIOS Security	Advanced Theft Protection Computrace® enabled BIOS EraseDisk (optional) Write protect option for the Flash EPROM Trusted Platform Module (TPM 2.0)
User Security	Embedded fingerprint sensor (optional) Embedded palm vein sensor (optional) Separate SmartCard slot Hard disk password User and supervisor BIOS password Preboot Authentication with SystemLock 3

Warranty

Warranty period	3 years (depending on country)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Product Related Services - the perfect extension

Recommended Service	- 9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Thunderbolt 3 Port-Replicator

Take advantage of the USB Type-C™ connector offering more speed (40 Gbps), more protocols and charging capabilities.

Order Code:
S26391-F2249-L100

Prestige Trolley 17.3

The FUJITSU Prestige Trolley 17.3 protects and transports notebooks with up to 17.3-inch screens, along with clothes and toiletries. It is the perfect companion in a city environment or for overnight stays with four spacious compartments. Smooth running wheels and a telescopic handle ensure convenience, while the central section protects your notebook with shock-absorbing foam.

Order Code:
S26391-F2249-L300

Order Code:
S26391-F1194-L130

Display P27-8 TS UHD

The FUJITSU Display P27-8 TS UHD has a 3840 x 2160 Ultra HD resolution ships with a thin bezel housing ideal for multi-monitor use scenarios. The monitor has a 178°/178° wide viewing angle that delivers consistent picture quality, a 100% sRGB color space, ECO function, DisplayView™ IT Suite manageability software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:
S26361-K1610-V160

Keyboard KB950 Phone

The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4** (**:
Country specific variation)

More information

Fujitsu products, solutions & services

In addition to the FUJITSU Workstation CELSIUS H780, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the FUJITSU Workstation CELSIUS H780, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2018-07-26 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2018 Fujitsu Technology Solutions GmbH