EB-Z9870



DATASHEET / BROCHURE

























With 8,700 lumens and a XGA resolution, the EB-Z9870 large venue projector is simple to set-up and benefits from 3LCD technology.

The white EB-Z9870 is an impressive and versatile installation projector, featuring 8,700 lumens brightness and XGA resolution. Able to project portrait aspect images for digital signage, the EB-Z9870 has a flexible installation angle, lens shift for off-centre positioning and plenty of calibration options, with optional Wi-Fi and HDBaseT connectivity.

Clear images and 3LCD technology

At 8,700 lumens the EB-Z9870 is an ultra-bright XGA resolution projector. This projector benefits from Epson's 3LCD technology, which ensures high-quality images with equally high White and Colour Light Output for vivid colours and bright images, even in daylight, and three times brighter colours than competitive projectors 1.

Perfect for large venues

Museums, auditoriums and corporate environments can benefit from the EB-Z9870's large projected image, ideal for making a big impact.

Portrait projection

Able to project portrait aspect images, the EB-Z9870 is ideal for digital signage. Welcome to a whole new way of seeing things; portrait mode is also useful when a venue or event, such a fashion show, doesn't lend itself to landscape projection.

Easy set-up

As well as a flexible installation angle and lens shift for off-centre positioning, the EB-Z9870 includes plenty of calibration options such as edge blending, test patterns and Epson's Super Resolution feature.

Connectivity

The EB-Z9870 includes HDBaseT, which allows up to five connections in one. Optional Wi-Fi is also included for extra flexibility.

Short-throw capability

Great news for auditoriums and lecture theatres; a new and exclusive LU02 short throw lens allows this projector to be positioned closer to the screen.

KEY FEATURES

- High brightness
 Very bright 8,700 lumens
- Flexible
 Choose different installation angles
- 3LCD technology
 For vivid colours and bright images
- Connectivity

 HDBaseT and optional Wi-Fi connectivity
- Portrait projection
 When landscape isn't suitable





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 1.06 inch with C2 Fine

IMAGE

Color Light Output 8,700 Lumen - 7,300 Lumen (economy)
White Light Output 8,700 Lumen - 7,300 Lumen (economy)

Portrait Colour Light Output 8,500 lm
Portrait White Light Output 8,500 lm

Resolution XGA, 1024 x 768, 4:3

Contrast Ratio 15,000 : 1

Lamp 380 W, 3,000 h durability, 4,000 h durability (economy mode)

Lamp (portrait mode) 304 Watt, 1,000 hours Durability

Keystone Correction Manual vertical: \pm 30 °, Manual horizontal \pm 30 °

OPTICAL

Throw Ratio 1.65 - 2.65:1

Zoom Motorized, Factor: 1 - 1.61

Lens Shift Motorized - Vertical ± 56 %, horizontal ± 19 %

Screen Size 60 inches - 500 inches

Projection Lens F Number 1.65 - 2.51

Projection Lens Focal Length 36 mm - 57.5 mm

Projection Lens Focus Motorized

Projection Distance Wide 1.9 m - 16.8 m

Projection Distance Tele 3.2 m - 27.2 m

CONNECTIVITY

Interfaces USB 1.1 Type A, USB 2.0 Type B (Service Only), RS-232C, WLAN, VGA in, VGA out, DVI in,

HDMI in, Composite in, Component in, BNC in (6x), S-Video in, HDBaseT

GENERAL

Power consumption 809 Watt, 721 Watt (economy), 0.37 Watt (standby)

Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 741 x 534 x 197 mm (Width x Depth x Height)

Product weight 25 kg

Noise Level Normal: 38 dB (A) - Economy: 35 dB (A)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

Included Software EasyMP Monitor, iProjection, EasyMP Network Projection

ADVANCED FEATURES

Security Kensington lock, Security cable hole

Video Color Modes Dynamic, Photo, Presentation, sRGB, Theatre, DICOM SIM

OTHER

Warranty 36 months Carry in or 20,000 h, Lamp: 12 months or 1,000 h

Optional warranty extension available

EB-Z9870

WHAT'S IN THE BOX

- Computer cable
- HDMI Cable Clamp
- Power cable
- Remote control incl. batteries
- User's Manual Set



OPTIONAL ACCESSORIES

- 3D Polarizer ELPPL01 V12H618A01
- HDBaseT Transmitter ELPHD01 V12H547041
- Lamp ELPLP81V13H010L81
- Lamp (x2) ELPLP82 V13H010L82
- Lamp (Portrait, x1) ELPLP83 V13H010L83
- Lamp (Portrait, x2) ELPLP84 V13H010L84
- Air Filter ELPAF46V13H134A46

LOGISTICS INFORMATION

SKU	V11H607040
EAN code	8715946541242
Country of Origin	China
Layer	1 Units
Layer Block	1 Units

Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO

EB-Z9870



www.epson.co.uk

www.epson.ie