


Name	Type-model	Slot x bay	Processor	GHz	Cores	Memory ⁶	SATA disk	SATA optical	Graphics	Monitor connectors	DisplayPort dongle	Intel vPro	Vista preload	Global Educ	Avail date
M58	7360-AJU	2x3	Pentium E2200	2.20	2	1GB	160GB ²	DVD	GMA	VGA, DP		No	Bus32	No	Nov 08
M58	7360-ADU	2x3	Pentium E2220	2.40	2	2GB	250GB	DVD±RW	GMA	VGA, DP	DP-to-DVI-D	No	Bus32	No	Nov 08
M58	7360-AKU	2x3	Pentium E5200	2.50	2	2GB	160GB	DVD±RW	GMA	VGA, DP	DP-to-DVI-D	No	Bus32	No	Nov 08
M58	7360-ALU	2x3	Core 2 Duo E7300	2.66	2	1GB	160GB	DVD	GMA	VGA, DP		No	Bus32	No	Nov 08
M58	7360-APU	2x3	Core 2 Duo E7300	2.66	2	2GB	160GB	DVD±RW	GMA	VGA, DP	DP-to-DVI-D	No	Bus32	No	Nov 08
M58	7360-AQU	2x3	Core 2 Duo E7300	2.66	2	2GB	250GB	DVD±RW	3470	VGA, DP	DP-to-DVI-D	No	Bus32	No	Nov 08
M58	7360-ARU	2x3	Core 2 Quad Q8200	2.33	4	2GB	250GB	DVD±RW	3470	VGA, DP	DP-to-DVI-D	No	Bus32	No	Nov 08

• These models have a 3-year limited warranty¹

Positioning Processor	<p><i>Ultimate stability for small and medium businesses</i></p> <p>Intel® Pentium® Dual-Core Processor E2200 or E2220 with dual-core, 800MHz system bus, and 1MB L2 cache or Intel Pentium Dual-Core Processor E5200 with dual-core, 800MHz system bus, and 2MB L2 cache or Intel Core™ 2 Duo Processor E7300 with dual-core, 1066MHz system bus, and 3MB L2 cache or Intel Core 2 Quad Processor Q8200 with quad-core, 1333MHz system bus, and 4MB L2 cache</p> <p>Processor in FC-LGA6 or FC-LGA8 package in LGA775 socket</p>		<p>Small</p>  <p>Bay ① 5.25", 1.6" high, access, std optical Bay ② 3.5", 1" high, no access, std disk Bay ③ 3.5", .5" high, access, open (reader)</p> <p>Slot 1: Low Profile, PCI Express 2.0 x16* Slot 2: Low Profile, 32-bit PCI 2.3</p> <p>* used in some models</p> <ul style="list-style-type: none"> • Business black color; metal case • 12.5" W X 14.0" D X 3.9" H • 317mm W X 355mm D X 99mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk, optical drive removal • Toolless adapter retention • Toolless systemboard retention • System floor stand for vertical orientation
Implementation			<p>Security</p> <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® Microsaver® cable) - optional cable also locks the cover by deactivating the cover release buttons • Power-on password • Administrator password • Hard disk password (user and master) • Boot sequence control • Boot without diskette, keyboard • Serial port I/O control • Individual USB port disablement <p>Supports ThinkVantage® technologies</p> <p>GREENGUARD® certified RoHS-compliant</p> <p>Limited Warranty¹</p> <ul style="list-style-type: none"> ↪ 3-year parts and labor ↪ International Warranty Service⁹ ↪ Customer Replaceable Unit (CRU) parts only (with limited onsite service for selected parts³, 8 am - 5 pm, Mon - Fri coverage excluding holidays, next business day response time) ↪ Onsite service upgrade options (in eligible locations):⁷ <ul style="list-style-type: none"> • 3-year LOR 9x5, 4 hour response (ThinkPlus™ part number 41C9192) • 3-year LOR 24x7, 4 hour response (ThinkPlus part number 41C9193) • 4-year LOR 9x5, Next Business Day (ThinkPlus part number 41C9194) • 4-year LOR 9x5, 4 hour response (ThinkPlus part number 41C9195) • 4-year LOR 24x7, 4 hour response (ThinkPlus part number 41C9196) ↪ ThinkPlus services at lenovo.com/thinkplus/warranty ↪ Post warranty maintenance services available ↪ 24 hour x 7 day¹⁴ toll-free support during the warranty period¹ via 800-426-7378
Memory	<p>1GB or 2GB std, 8GB max⁸, PC3-8500 1066MHz DDR3, non-parity, dual-channel capable, four 240-pin DIMM sockets;</p> <p><i>Italics:</i> standard memory in two sockets; two sockets available; <i>Non-italics:</i> standard memory in one socket; 3 sockets available</p>		
Graphics	<p><i>Some:</i> Intel Graphics Media Accelerator 4500 (GMA 4500), integrated graphics in Q45, uses main memory (up to 253MB [1GB models], 765MB [2GB models]), one analog VGA DB-15 connector, one DisplayPort™ conn, HDCP, DirectX® 10, supports dual independent display</p> <p><i>Some:</i> ATI™ Radeon™ HD 3470, PCI Express® 2.0 x16 adapter, 256MB, one analog VGA DB-15 connector, one DisplayPort connector, HDCP, DirectX 10.1, ATI Avivo™, 25 watts</p>		
DP dongle	<p><i>Some:</i> DisplayPort to Single-link DVI-D Cable (45J7915)</p>		
SATA disk	<p>160GB or 250GB, SATA 3.0Gb/s 7200 rpm, vibration dampening mounts</p>		
SATA controller	<p>Serial ATA, SATA 3.0Gb/s, integrated in ICH10DO, RAID 0/1 support</p>		
SATA DVD	<p><i>Some:</i> DVD-ROM DL SATA 1.5Gb/s 16-48X Max⁴ Drive (41N5618)</p>		
SATA DVD±RW	<p><i>Some:</i> Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive (41N5620)</p>		
SATA cables	<p>Two SATA cables (each 1-drop to device), two SATA connectors on planar</p>		
eSATA port	<p>One external SATA (eSATA) port</p>		
Diskette drive	<p>None</p>		
Media reader	<p>None</p>		
Chipset	<p>Intel Q45 Express Chipset (PCI Express 2.0 x16), I/O Controller Hub 10 Digital Office [ICH10DO] (SATA 3.0Gb/s with RAID 0/1 support, PCI Express x1, ethernet MAC, PCI 2.3, USB, LPC bus), SMSC® SCH5617 Super I/O</p>		
Front ports	<p>Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</p>		
Rear ports	<p>Six USB 2.0, serial (9-pin), ethernet (RJ-45), monitor (VGA DB-15, DisplayPort), eSATA</p>		
Internal connector	<p>Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports)</p>		
Rear audio ports	<p>Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)</p>		
Audio	<p>High Definition (HD) Audio, Analog Devices AD1882 codec</p>		
Speaker	<p>One internal speaker for business audio</p>		
Ethernet	<p>Gigabit ethernet on planar, Intel 82567LM, Wake on LAN®, ASF2.0, DASH 1.0</p>		
Intel AMT	<p>None</p>		
Modem	<p>None</p>		
Security chip	<p>Winbond® WPCT200 SafeKeeper™ Trusted Platform Module, TCG 1.2-compliant</p>		
Keyboard	<p>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</p>		
Mouse	<p>Optical Wheel Mouse (USB connector), 400 dpi, black, Lenovo logo</p>		
Power supply	<p>280 watts with variable speed fan, autosensing, two diagnostic LEDs</p>		
Preloaded operating system²⁰	<p>Accessories</p> <ul style="list-style-type: none"> - Microsoft® Windows® Vista® Business Edition (32-bit) 45J5434 ↪ Vista Premium logo 45J5435 • 1GB PC3-8500 DDR3 UDIMM 43R1990 • 2GB PC3-8500 DDR3 UDIMM 45J7918 • 500GB SATA 3.0Gb/s Disk (7200 rpm) 05K9276 • 1TB SATA 3.0Gb/s Disk (7200 rpm) 40Y8518 • USB Portable Diskette Drive 40Y8519 • USB 2.0 Lenovo Multimedia Headset 45K1258 • USB 2.0 Lenovo Webcam 45J5918 • USB 2.0 Essential Memory Key 32GB 43R2019 • USB 2.0 Ultra Secure Memory Key 8GB 41N5565 • USB 2.0 Portable Secure 320GB Hard Disk 4421HB2 • USB 2.0 Super Multi-Burner Drive 73P4067 • ThinkVision® L2440x Wide 24" Monitor 41U3074 • Wireless Kbd & Opt Wheel Mouse (via USB) 73P2582 • Laser Tilt Wheel Mouse (USB, PS/2) 45K1620 • Kensington Cable Lock from Lenovo 45K1620 • Kensington Twin Head Cable Lock 45K1636 • ATI Radeon HD 3470 256MB (DP, VGA) 45K1636 • Acc Guide in pdf lenovo.com/accessoriesguide • Other accessories at lenovo.com/accessories 		

See footnotes for important warranty information
 US models announced October 21, 2008