WorkCentre[™] 3550

Black and White Multifunction Printer





WorkCentre 3550X Includes one 500-sheet tray



WorkCentre 3550XT Includes two 500-sheet trays



WorkCentre 3550XTS Includes two 500-sheet trays and

			Stand
	WorkCentre 3550X	WorkCentre 3550XT	WorkCentre 3550XTS
Output Speed			
Single-Sided	Up to 33 ppm A4 (210 x 297 mm)		
Automatic Two-Sided	Up to 16 ppm A4 (210 x 297 mm)		
Paper Handling - Input			
Duplex Automatic Docum	ent Feeder		
Capacity ¹	60 sheets		
Sizes	Custom Sizes: 69.9 x 145 mm to 216 x	356 mm	
Weights	50 to 120 gsm		
Multipurpose Tray			
Capacity ¹	50 sheets		
Sizes	Custom Sizes: 76 x 127 mm to 216 x 3	56 mm	
Weights	60 to 163 gsm		
Mediα Types	Plain paper Letterhead Bond Heavyweight Lightweight Recycled Archive Labels Drilled Postcard Transparencies Envelopes Custom 1-7		
Main Tray			
Capacity ¹	500 sheets		
Sizes	Custom Sizes: 148 x 210 mm to 216 x	356 mm	
Weights	60 to 105 gsm		

¹ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Mediα Types	Plain paper Heavyweight Lightweight Recycled Archive Letterhead Drilled
Additional Tray (Optional	with WorkCentre 3550X, standard with WorkCentre 3550XT and 3550XTS)
Capacity ¹	500 sheets
Sizes	Custom Sizes: 148 x 210 mm to 216 x 356 mm
Weights	60 to 105 gsm
Mediα Types	Plain paper Heavyweight Lightweight Recycled Archive Letterhead Drilled
Paper Handling - Output	
Standard Output	WorkCentre 3550X: 250 sheets WorkCentre 3550XT: 500 sheets WorkCentre 3550XTS: 500 sheets
Print	
First-Page-Out-Time	As fast as 8.5 seconds
Print Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
Memory (Std/max)	256 MB / 512 MB
Processor	360 MHz
Language Support	Postscript® 3™ compatibility PCL® 5e emulation PCL® 6 emulation
Connectivity	10/100 Base-TX Ethernet, USB 2.0
Printing Features	Automatic two-sided printing Custom page size Toner save mode Proof print Secure print Watermarks N-up Fit to page Overlay Reduce/Enlarge Poster Scaling Booklet printing Print from USB memory device

 $^{^{\}rm 1}$ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Print Drivers	Windows® XP (32/64bit) / 2003 (32/64bit) / 2008 Server (32/64 bit) / Vista (32/64bit) / Windows 7 (32/64bit) / 2008 R2 (64bit) Macintosh® OS X v10.3-10.6 RedHat Enterprise Linux WS 4, 5 (32/64bit) Fedora Core 2-10 (32/64bit) SuSE Linux 9.1 (32bit) OpenSuSE 9.2, 9.3, 10.0, 10.1, 10.2 10.3, 11.0, 11.1 (32/64bit) Mandrake 10.0, 10.1 (32/64bit) Mandriva 2005, 2006, 2007, 2008 (32/64bit) Ubuntu 6.06, 6.10, 7.04, 7.10, 8.04, 8.10 (32/64bit) SuSE Linux Enterprise Desktop 9, 10 (32/64bit) Debian 3.1, 4.0, 5.0 (32/64bit) Xerox® Mobile Express Driver™ Xerox® Global Print Driver®
Font Capability	136 PostScript® fonts 111 PCL® fonts
Сору	
Document Scanner	Duplex Automatic Document Feeder with 60-sheet capacity
Sides (input:output)	1:1, 1:2, 2:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
Concurrency	Concurrent scanning and printing
First-Copy-Out-Time	As fast as 10 seconds
Copy Features	Automatic two-sided Reduce/Enlarge Background Suppression Collation (DADF only) ID Card Copy N-up (2-up/4-up) Book copy Booklet creation Clone copy (Platen only) Poster copy (Platen only)
Foreign Device Interface (Optional)	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Alliance Partner Programme
Fax	
Embedded Fax, PC Fax (1 l	ine)
Fax Speed	33.6 Kbps
Memory	Up to 7 MB
Resolution	Up to 600 x 600 dpi (superfine) resolution
Compression	MH, MR, MMR, JPEG and JBIG

Fax Features	Colour fax send Two-sided Fax forward to Fax/Email and Server (FTP, SMB) PC Fax (send only) Secure fax receive Searchable address book Auto redial Last number redial Pause Distinctive ring External phone interface Journal Confirmation reports Auto dial list Junk fax barrier Persistent Flash Memory Up to 209 group dial locations Broadcast fax Delayed fax Memory receive Auto file size reduction
Scan	
Capability	Black and white, greyscale and colour scanning
Concurrency	Scan while the system is printing copy or network print jobs or while it is transferring scan to network or fax jobs
Input Speed	Scan at 33 ipm (images per minute) black and white (A4) Scan at 22 ipm colour (A4) @ 300 dpi
Resolution	300 x 300 dpi 200 x 200 dpi 100 x 100 dpi
Maximum Scan Area	216 x 356 mm
Network Protocol	FTP SMTP SMB
File Formats	JPG PDF TIFF Multipage TIFF
Supported Scan Destinations	Scan to Email (includes support for Global Address Book via LDAP and up to 200 local address book entries Network Scan to PC Scan to FTP and SMB Direct Scan to Applications, including OCR (software included) Scan to USB memory device
Scanning Solutions	
Scan to PC Desktop® Personal Edition	 A desktop and server-based offering that provides document imaging, archiving, editing and organisation tools Nuance® PaperPort SE 11.0 – image viewing and file management software OmniPage® 16 SE (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops

Security Security Features 802.1x Kerberos SNMPv3 **HTTPS** Secure Fax SSL IPv6 LDAP IP Filtering Scan to Email with authentication **Device Management** Xerox CentreWare® Web • A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system · Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic Accounting and asset management Xerox CentreWare® Internet Services - Integrated Device Web Page **Device Status** Web server embedded • Tray status/contents Consumables status Job print queue management **Print Queue Viewing** Job Submission Print-ready files (PS, PCL, TIFF, PDF) Output feature selection **Device Administration** Allows simple, remote installation setting of configuration options and management of the device **Browsers** Netscape® 6.2 Netscape® 7.x (Mozilla 1.x) Netscape® 8.x Microsoft® Internet Explorer 5.5.x, 6.x, 7.x Apple® Safari™ 1.2.x, 2.x Firefox® 1.5.x, 2.x **Device Specifications Duty Cycle** Up to 75,000 pages / month² **Electrical Requirements** 220-240 VAC, 50/60 Hz ENERGY STAR® qualified **Power Consumption** 600 watts **Printing** Standby <60 watts <20 watts Power save Warm up <15 seconds (from sleep mode) 10° to 32° C Operating

20 % to 80 %

Temperature Range

Relative **Humidity Range**

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Sound Pressure Levels				
Printing	55 dB(A)			
Standby	39 dB(A)			
Dimensions and Weights	Width	Depth	Height	Weight
Product (without print cartridge)	582 mm	488 mm	554 mm	23.4 kg
Package	676 mm	619 mm	696 mm	29.7 kg
Certifications				
	Listed UL 60950 CE Mark applicable to Directives 2006/95/EC 2004/108/EC and 99/5/EC, FCC Part 15 Class A, FCC Part 68 ENERGY STAR® qualified			
What Comes in the Box				
	 WorkCentre 3550 Multifunction Printer Print cartridge (5,000 print capacity) World Kit CD (includes Printer Installer, utilities, Software and documentation) Power cord 			

Supplies and Options	Description	Order Number
	High-Capacity Print Cartridge – approximately 11,000 standard pages ³	106R01530
	Standard-Capacity Print Cartridge – approximately 5,000 pages ³	106R01528
	500-sheet Tray	098N02190
	256 MB Memory Upgrade	098N02189
	Stand	097N01674
	Foreign Device Interface	097N01676
	Wireless Network Adaptor - European Power Adaptor ⁴ - UK Power Adaptor	097S03741 097S03742

³ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and media used.

















 $^{^{\}rm 4}\,{\rm Not}$ available in Denmark and Switzerland