

Specifications

Model	fi-7160	fi-7260	fi-7180	fi-7280
Supported operating systems	Windows® 8 (32/64), Windows® 7 (32/64), Windows Vista® (32/64), Windows® XP (32/64), Windows Server® 2012, Windows Server® 2008 (32-bit / 64)			
Scanner type	ADF	ADF and Flatbed	ADF	ADF and Flatbed
Scanning modes	Simplex / Duplex, Colour / Greyscale / Monochrome			
Image sensor type	Colour CCD x2	Colour CCD x3	Colour CCD x2	Colour CCD x3
Light source	White LED Array x 2 (front x 1, back x 1), Flatbed x 1			
Document size	ADF	Maximum: A4 Portrait 210 x 297 mm, Legal 216 x 355.6 mm / Minimum ¹¹ : A8 Portrait 52 x 74 mm		
	Long paper scanning ¹² : Flatbed:	Maximum 210 x 863 mm or 210 x 5,588 mm		
Paper weight (no limitation for flatbed) ³	27 to 413 g/m ² / supports 127 to 209 g/m ² for A8 size ID card types (ADF): Portrait / Landscape, 1.4 mm thickness or less ¹⁴			
Scanning speed ¹⁵ (A4 portrait) Colour ¹⁶ / Greyscale ¹⁶ / Mono ¹⁷ :	60ppm, 120ipm (200 and 300 dpi)		80ppm, 160ipm (200 and 300 dpi)	
	Flatbed:	1.7 seconds (200 dpi)		1.7 seconds (200 dpi)
Paper chute capacity ⁸	80 sheets (A4: 80 g/m ²)			
Typical daily throughput	800 - 4,000 sheets per day		1,200 - 6,000 sheets per day	
Background colours	White or Black (selectable)			
Optical resolution	600 dpi			
Output resolution ¹⁹ Colour / Greyscale / Mono:	50 to 600 dpi (adjust by 1 dpi increments), 1200 dpi ¹⁰			
Output format	Colour: 24 bit / 8 bit / 4 bit (8 bit and 4 bit with driver), Greyscale: 8 bit / 4 bit (4 bit with driver), Monochrome: 1 bit			
Internal video processing	65,536 levels (16 bit)			
Interface ¹¹	USB 3.0 (USB 2.0 compatible)			
Connector shape	USB: B type			
Image processing function	Hardware-based	Dropout colour (R, G, B), Deskew cropping		
	Software-based	Multi-image, Auto colour, Blank page skip, i-DTC, Advanced-DTC, Simplified-DTC, Error diffusion, Dither, Moire removal, Image emphasis, Colour cleanup, Dropout colour (None, Specified, Colour saturation), sRGB, Punch hole removal, Tab cropping, Upper lower separation		
Power requirements	AC 100 to 240 V, ±10%			
Power consumption	Operating: 38W _≤ , sleep mode ≤1.8	Operating: 41W _≤ , sleep mode ≤1.8	Operating: 42W _≤ , sleep mode ≤1.8	Operating: 43W _≤ , sleep mode ≤1.8
Operational environment	Temperature: 5°C to 35°C, Relative humidity: 20 to 80% (Non-condensing)			
Dimensions (W x D x H base unit) ¹²	300 x 170 x 163 mm	300 x 577 x 234 mm	300 x 170 x 163 mm	300 x 577 x 234 mm
Weight	4.2 kg	8.8 kg	4.2 kg	8.8 kg
Bundled software / drivers	PaperStream IP (TWAIN/ISIS) Driver, Software Operation Panel, Error Recovery Guide, PaperStream Capture, ScanSnap Manager for fi-Series, Scan to Microsoft SharePoint (web download only), ABBYY FineReader for ScanSnap, Scanner Central Admin tools			
Environmental compliance	ENERGY STAR® and RoHS			
Included items	ADF paper chute, AC cable, AC adapter, USB cable, Setup DVD-ROM			

- ¹ The minimum scanning area only applies to using the ADF. There is no limitation when using the flatbed.
- ² Can scan documents longer than A4 size. When using PaperStream IP (TWAIN/ISIS) to scan at 200 dpi, the maximum scanning length is 5,588 mm
- ³ The paper weight only applies to using the ADF. There is no limitation when using the flatbed.
- ⁴ Capable of scanning up to 3 cards at a time. (Note: does not support multi-embossed card feeding.)
- ⁵ Actual scanning speeds are affected by data transmission and software processing times.
- ⁶ JPEG compressed figures.
- ⁷ TIFF G4 compressed figures.
- ⁸ Maximum capacity varies, depending upon paper weight.
- ⁹ Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
- ¹⁰ Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600 dpi or higher).
- ¹¹ Connection with USB3.0 / 2.0 requires the USB port and the hub to support USB3.0 / 2.0. Also note that the scanning speed slows down when using USB1.1.
- ¹² Excluding the ADF paper chute and stacker.



ENERGY STAR® compliant



"Adobe", "Acrobat" and the Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Consumables	Parts number	Comments
Consumable Kit	CON-3670-002A	Contents: 2 x Pick Roller / 2 x Break Roller / Total Lifetime of this kit will be 400,000 documents or 1 year
Cleaning Kit	SC-CLE-WGD	72 cleaning fluid impregnated wipes
Print Cartridge (fi-C200PC)	CA00050-0262	Only for fi-718PR Imprinter Lifetime: 4,000,000 printed characters fi-614PR print head

Options	Parts number	Comments
Post Imprinter (fi-718PR) (fi-7180 and fi-7160)	PA03670-D201	Assists document management by printing numbers, Roman characters and codes on original documents after they have been scanned.
Black Document Pad (fi-728BK) (fi-7280 and fi-7260)	PA03670-D801	This is a flatbed black background attachment. Use of this option facilitates the auto-deskewing and auto-orientation of flatbed images.
ScanSnap Carrier Sheets	PA03360-0013	Each package contains 5 carrier sheets. It is recommended that each carrier sheet be replaced after it has been used for 500 scans.

Warranty and Service Plans	Remarks
Standard Warranty	1 year Advance Exchange within 1-2 days; Hotline and Online support; parts, labour and shipping included
Upgrade Options	1-5 year upgrades available on new scanners at time of scanner purchase or within 30 days of purchase, upgrades the warranty
Renewal Options	1-2 year renewals available when warranty or previous service plan has expired

Visit <http://emea.fujitsu.com/assurance> for further information on standard warranty and our Bronze, Silver, Gold and Platinum upgrade options.



PFU Imaging Solutions Europe Limited
 Hayes Park Central
 Hayes End Road, Hayes
 Middlesex UB4 8FE
 UK
 Tel: +44-(0)20 8573 4444
 Fax: +44-(0)20 8573 2643

PFU Imaging Solutions GmbH
 Frankfurter Ring 211
 80807 Munich
 Germany
 Tel: +49-(0)89 32378-0
 Fax: +49-(0)89 32378-100

PFU Imaging Solutions S.p.A.
 Via Nazario Sauro, 38
 20099 Sesto San Giovanni (MI)
 Italy
 Tel: (+39) 0226294.1
 Fax: (+39) 0226294.201

<http://emea.fujitsu.com/scanners>

