

# Horizontal Slab Coils



## Features:

- Insulated embossed, galvanized steel case
- Aluminum or Rifled Copper tubing
- Corrosion resistant aluminum fins and end plates
- Pressure tested to 500 PSI
- Polymer drain pan
- Factory installed Thermal Expansion Valve
- Dual rated for R-22 and R-410a
- 5 - Year Functional Parts Warranty
- 3/4" MPT. Drain Connections
- 3/8" Liquid Line
- Suction Line Connections  
3/4" on 1.5 to 3.0 Tons  
7/8" on 3.5 to 5.0 Tons

**AS H 24 - 20 3 4 G + \_ - 5B**

**OEM**

**Cabinet Type**

H - Standard Slab Coil  
HL - Low Profile Horizontal Slab Coil

**Nominal Cooling Capacity (MBTUH)**

**Slab Coil Length**

**Coil Number of Rows**

**Fins Per Inch**

0 - 10 FPI    2 - 12 FPI    4 - 14 FPI  
6 - 16 FPI    8 - 18 FPI

**Cabinet Code**

\* See Cabinet Chart

**Option 1**

+D - Time Delay Required  
+V - Expansion Valve (Cooling Only)  
+VP - Expansion Valve (Heat Pump)

**Tube Type**

G - Aluminum  
T/E - Rifled Copper