

Speed Queen®

Multi-Housing

Micro-Display Control

SDEY07 (elec)

SDGY09 (gas)

Commercial Heavy-Duty Single Load Dryer

Description

- Four heat / cycle selections
- Factory default cycle 45 minutes
- 1/3 HP motor; 120/60/1 - 15 amp
- Cycle status indicators
- Micro-Display CARD operated control
 - Vend price programmable
 - Time countdown
 - Non-resettable cycle counter
- Touch pad control
 - Sound annunciator
- One-piece control panel
- **Activation - Card Ready**



Nobody Compares with Speed Queen Quality

- Extra large 7.0 cu. ft., 18 lb capacity galvanized steel cylinder.
- Wide door opening of 2.06 sq. ft. is the industry largest, offering residents easy loading and unloading.
- Durable porcelain enamel top for long-lasting appearance.
- 100% serviceable from the front.
- Door is reversible for installation flexibility.



- Efficient dryer heating.
 - 25,000 Btu (gas models)
 - 5,350 Watts (electric models)
- High efficiency exhaust blower with superior airflow of 220 cfm.
- Up-front lint filter is easy to clean and secured.
- Space-saving narrow cabinet (26⁷/₈" wide).



Commercial Built to Last Longer

Specifications

Model	SDEY07 (elec) SDGY09 (gas)
Width - in (mm)	26 7/8" (683)
Depth - in (mm)	28" (711)
Height - in (mm) To work surface	43" (1092) 36" (914)
Cylinder Volume (capacity) - cu. ft. (liters)	7.0 (198)
Btu Per Hour - Gas Heating (kcal)	25,000 (6300)
Heating Element - Electric Heating	5350 W 240 V (also 4750 W 208 V)
Type of Gas (gas models only)	Factory-Equipped Natural / Mixed Gas Convertible to LP Gas+
Utility Connections - in (mm)	3/8" NPT (9.5)
Air Outlet Diameter - in (mm)	4" (102)
Exhaust Airflow - (liters/sec)	220 (105)
Maximum Exhaust Static Back Pressure	0.6" W.C.
Electrical Specifications Circuit Requirements	Gas 120/60/1 - 15 amp Elec 120/240/60/1 - 30 amp 120/208/60/1 - 30 amp
Colors	White
Net Weight - lbs (kg)	Gas 140 (64) Elec 135 (61)
Shipping Weight - lbs (kg)	Gas 150 (68) Elec 145 (66)
Code Standard	Gas CSA Elec cULus

At Speed Queen, we're so confident that our heavy-duty commercial washers and dryers are Commercial Built to Last Longer, that we're offering the following limited warranty to prove it:
 Through three years† — Any part of the washer, dryer or stack dryer.
 Through five years† — The washer transmission assembly, base and cabinet assembly including top, lid and door, against rust from inside out.
 Lifetime† — The stainless steel washtub.

†Parts only. Labor not included. See Speed Queen Warranty Bond for specifics.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

Temperature Selection	
Temperature	Setting
Delicate	115°
Low	145°
Medium	155°
High	160°

