

VS Series

Single Cartridge Filter Housings



- Heavy duty stainless steel construction for maximum reliability and durability
- Accepts Double Open End (DOE) cartridges
- Available with ¾" and 1" in-line connections for easy installation
- Designed for residential, commercial and light industrial applications
- Ring nut closure allows quick cartridge change-outs
- Spring loaded knife edge seal plate provides positive sealing for variable length cartridges
- Mounting bracket kit allows easy installation
- Double gasket design enhances closure seal
- Optional gasket materials available for compatibility with most fluids

Applications

Water	Chemicals	Paints / Coatings
Food & Beverage	Electronics	Coolants
Oil	Ink	Pulp & Paper

SPECIFICATIONS

Maximum Operating Pressure

300 psig (20.7 bar) @ 200 °F (93 °C)

Connections

Inlet /Outlet: ¾" or 1" FNPT
Drain Port: Petcock or ¼" Plug

Materials of Construction

Head / Shell: 304L Stainless Steel
Optional: 316L Stainless Steel

Gaskets

EPR
Optional: Buna N, Silicone, Viton

ORDERING GUIDE (Example: VS-116E)

VS-1	1	6		E
Model	Cartridge Length	Pipe Size (FNPT)	Options	Gasket
VS-1	1 - 9 ¾-10" 2 - 19 ½ - 20"	6 - ¾" 8 - 1"	Blank – None BSP – BSP thread 316 – 316L SS PLUG – Drain Plug	E = EPR (Standard) B = Buna N S = Silicone V = Viton