




| Model | | Digital Signage "QM-Serie" UHD Full Display | | |
|--------------------------------------|-------------------------|--|--|--|
| QM65F LH65QMFLGC/EN | |   | | |
| Panel | Diagonal Size | 65" | | |
| | Type | 60Hz E-LED BLU | | |
| | Resolution | 3840x2160(16:9) | | |
| | Pixel Pitch(mm) | 0.105 x 0.315 (mm) | | |
| | Active Display Area(mm) | 1438.48(H) x 814.52(V) | | |
| | Brightness(Typ.) | 500nit | | |
| | Contrast Ratio(Typ.) | 4700:1 | | |
| | Viewing Angle(H/V) | 178/178 | | |
| | Response Time(G-to-G) | 8ms (Typ) | | |
| | Display Colors | 16.7M(True Display), 1.07B(Ditherd 10bit) | | |
| | Color Gamut | 72% | | |
| | Operation Hour | 24/7 | | |
| | Haze | 25% | | |
| Display | Dynamic C/R | Mega | | |
| | H-Scanning Frequency | 30 ~ 81KHZ | | |
| | V-Scanning Frequency | 48 ~ 75HZ | | |
| | Maximum Pixel Frequency | 148.5MHz | | |
| Sound | Speaker Type | Built in Speaker(10W + 10W) | | |
| Connectivity | INPUT | RGB | DVI-I(D-Sub Common), Display Port 1.2 (2) | |
| | | VIDEO | HDMI (4) | |
| | | AUDIO | Stereo mini Jack | |
| | | USB | USB (S/W update only) | |
| | OUTPUT | RGB | N/A | |
| | | VIDEO | N/A | |
| | | AUDIO | Stereo mini Jack | |
| | | Power Out | N/A | |
| | EXTERNAL CONTROL | | RS232C (in/out), RJ45 | |
| | EXTERNAL SENSOR | | IR | |
| Tuner | | N/A | | |
| Type | | Internal | | |
| Power Supply | | AC 100 - 240 V~ (+/- 10 %), 50/60 Hz | | |
| Power | Power Consumption | On mode (W) | TBD | |
| | | Sleep/Off mode | less than 0.5W | |
| Mechanical Specs | Dimension (mm) | Set | 1456.1 x 835.6 x 37.5 | |
| | | Package | TBD | |
| | Weight (kg) | Set | 23,1 | |
| | | Package | 31,3 | |
| | VESA Mount | | 400x400 | |
| | Protection Glass | | N/A | |
| Stand Type | | Foot Stand (Optional) | | |
| Bezel Width (Top/Side/Bot) (mm) | | 12.0/12.0/12.0 | | |
| Operation | Operating Temperature | | 0°C~ 40°C | |
| | Humidity | | 10~80% | |
| Feature | Key | | UHD LFD Display | |
| | Special | H/W | Temperature Sensor,Pivot Display, Clock Battery(80hrs Clock Keeping), Built in Speaker(10W 2ch), IP5x | |
| | | S/W | FHD 4 PBP Support (2/3/4 PBP), Auto Source Switching & Recovery, LFD Home UI, Button Lock, DHCP with RJ45 MDC, Hot key option, Plug&Play (Initial Setting) | |

| QM65F LH65QMFPLGC/EN | |  | |
|---------------------------------------|-----------------------------------|--|---|
| Feature | Internal Player (Embedded H/W) | Processor | N/A |
| | | On-Chip Cache Memory | |
| | | Clock Speed | |
| | | Main Memory Interface | |
| | | Graphics | |
| | | Storage | |
| | | Multimedia | |
| | | IO Ports Operating System | |
| Certification | Safety | | 60950-1 |
| | EMC | | Class A |
| | Environment | | ENERGY STAR 7.0 (USA) |
| Accessories | Included | | Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries |
| | Optional | Stand | STN-L6500E |
| | | Mount | WMN6575SD |
| | | Specialty | - |
| | | Media Player | SBB-DA/DI |