

VPL-FH65

6,000 lumens WUXGA 3LCD installation projector



Overview

Bring presentations to life with impressive brightness and picture quality - plus easy, flexible integration and powerful picture features.

The VPL-FH65 installation projector is ideal for a wide range of business, education and entertainment applications. The energy-efficient High Pressure Mercury (HPM) lamp source is teamed with Sony's advanced BrightEra 3LCD projection engine, delivering extremely bright, detail-packed WUXGA resolution images with generous 6000 lumens brightness and rich, stable colours. Reality Creation and Contrast Enhancer technologies fine-tune image quality even further to assure exceptional clarity, realism and punch with every presentation.

With a stylish blend-in design, neat cable management and low fan noise, the VPL-FH65 integrates smoothly into almost any environment - from academic institutions, corporate, medical training and public sector organisations to visitor attractions and retail spaces. Easy set-up's assisted by a friendly new installation menu.

Features

- **Very high image quality with BrightEra 3LCD projection engine**

The energy-efficient High Pressure Mercury (HPM) lamp source is coupled with Sony's acclaimed BrightEra 3LCD projection engine to ensure high 6000 lumen image brightness with vivid, natural colour reproduction.

- **Advanced picture refinement technologies**

Picture quality is boosted by advanced processing featured on Sony home cinema projectors. Reality Creation uses a powerful pattern-matching database to optimise every pixel. Contrast Enhancer actively analyses and refines dark and light image areas for sparkling highlights and rich, deep blacks.

- **Crisp, detail-packed WUXGA resolution images**

See the finest detail in PC presentations, videos or multimedia signage with WUXGA (1920 x 1200) 16:10 resolution.

- **Hassle-free automatic filter cleaning**

Focus on great-looking images instead of arduous maintenance: automated filter cleaning system removes dust every 100 hours.

- **Energy-saving Lamp Dimming mode**

Gradually reduces lamp brightness and power consumption without compromising picture quality when the projector isn't being actively used. As soon as it's needed, full brightness is restored instantly.

- **Powered Wide Lens Shift**

Generous lens shift adjustments give more flexibility for positioning the projector where you need it: close to ceilings or even horizontally offset.

- **Included powered standard zoom lens plus wide choice of lens options**

Installation flexibility is increased by a wide range of compatible lens options to suit virtually any size of room and throw requirements. New quick-release bayonet mount simplifies quick lens exchange.

- **Supports HDBaseT**

Simpler, more cost-effective installation and connectivity with digital transmission of HD video, audio and networking/control over a single Ethernet cable.

- **Create super-size displays with Edge Blending**

Seamlessly join accurately colour-matched images from multiple projectors, simplifying creation of stunning super-size displays for corporate and education.

- **Project onto non-flat surfaces with Image Warping**

Easily correct image geometry for natural-looking projections, even on convex or concave surfaces. Corner and edge correction can be easily adjusted with the supplied remote and on-screen menu.

- **Quiet operation**

Low fan noise ensures discreet, unobtrusive operation in quiet environments from museums and galleries to lecture theatres.

- **Slim, attractive new blend-in design**

The slim, stylish case design features a flat top surface that blends in discreetly when the projector is ceiling

mounted. The clean appearance is accentuated by a new terminal cover that reduces cable clutter.

- **Choice of Picture Modes**

New Picture Mode ensures great-looking presentations in a wide range of operating conditions. Select Standard, Dynamic, Brightness Priority or Multi Screen mode for optimised image quality, with any source and in every room.

- **Simple set-up with friendly new Installation menu**

Easily adjust projector settings with remote commander, including image warping and edge blending.

- **Project Side by Side**

Project images from two inputs at the same time: ideal for applications such as video conferencing and medical training where two images need to be seen simultaneously.

Technical Specifications

Display system	
● Display system	3 LCD system

Display device	
● Size of effective display area	0.76" (19 mm) x 3 BrightEra LCD Panel, Aspect ratio: 16:10
● Number of pixels	6,912,000 (1920 x 1200 x 3) pixels

Projection lens *1	
● Focus	Powered
● Zoom - Powered/Manual	Powered (Approx. 1.6 x)
● Throw ratio	1.39:1 to 2.23:1
● Lens shift - Powered/Manual	Powered
● Lens shift - Range Vertical	-5.0%, +60%
● Lens shift - Range Horizontal	+/- 32%

Light source	
● Type	Ultra high pressure mercury lamp
● Wattage	370 W type

Recommended lamp replacement time *2	
● Lamp mode: High	3000 H
● Lamp mode: Low	4000 H

Filter cleaning / replacement cycle (Max.)*2	
● Filter cleaning / replacement cycle (Max.)	20000 H (service maintenance)

Screen size	
● Screen size	40" to 600" (1.02 m to 15.24 m) (measured diagonally)

Light output	
● Lamp mode: High	6000 lm
● Lamp mode: Standard	4400 lm

Color light output	
● Lamp mode: High	6000 lm
● Lamp mode: Standard	4400 lm

Contrast ratio (full white / full black) *3	
● Contrast ratio (full white / full black)	2000:1

Displayable scanning frequency	
● Horizontal	15 kHz to 92 kHz

● Vertical	48 Hz to 92 Hz
Display resolution	
● Computer signal input	Maximum display resolution: 1920 x 1200 dots *4
● Video signal input	NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i The following items are available for digital signal (HDMI input) only; 1080/60P, 1080/50p, 1080/24p
Color system	
● Color system	NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL60
Keystone correction (Max.)	
● Horizontal	+/- 30 degrees
● Vertical	+/- 30 degrees
OSD language	
● OSD language	24-language (English, Dutch, French, Italian, German, Spanish, Portuguese, Turkish, Polish, Russian, Swedish, Norwegian, Japanese, Simplified Chinese, Traditional Chinese, Korean, Thai, Vietnamese, Arabic, Farsi, Finnish, Indonesian, Hungarian, Greek)
INPUT OUTPUT (Computer/Video/Control)	
● INPUT A	RGB / Y PB PR input connector: Mini D-sub 15-pin (female) Audio input connector: Stereo mini jack
● INPUT B	DVI input connector: DVI-D 24-pin (single link), HDCP support Audio input connector: Shared with INPUT A
● INPUT C	HDMI input connector: HDMI 19-pin, HDCP support Audio input connector: HDMI audio support
● INPUT D	HDBaseT interface connector: RJ45, 4 play (Video, Audio, LAN, Control)
● VIDEO IN	Video input connector: BNC Audio input connector: Shared with INPUT A
● OUTPUT A	Monitor output for INPUT A connector: Mini D-sub 15-pin (female) Audio output connector: Stereo mini jack
● OUTPUT B	Monitor output for INPUT B connector: DVD-D 24-pin (single link), HDCP not supported Audio output Monitor out connector: Stereo mini jack
● REMOTE	D-sub 9-pin (male) / RS232C
● LAN	RJ45, 10BASE-T/100BASE-TX
● IR (Control S)	Stereo mini jack, Plug in power DC5V
Acoustic Noise	
● Lamp mode: Standard	28 dB
Operating temperature / Operating humidity	
● Operating temperature / Operating humidity	0°C to 40°C (32°F to 104°F) / 20% to 80% (no condensation)
Storage temperature / Storage humidity	
● Storage temperature / Storage humidity	-10°C to +60°C (14°F to +140°F) / 20% to 80% (no condensation)
Power requirements	
● Power requirements	AC 100 V to 240 V, 5.0 A to 2.1 A, 50 Hz / 60 Hz
Power consumption	
● AC 100 V to 120 V	Lamp mode: High: 498 W
● AC 220 V to 240 V	Lamp mode: High: 483 W

Power Consumption (Standby Mode)	
● AC 100 V to 120 V	0.5 W (when "Standby mode" is set to "Low")
● AC 220 V to 240 V	0.5 W (when "Standby mode" is set to "Low")

Power Consumption (Networked Standby Mode)	
● AC 100 V to 120 V	15.0 W (LAN) 15.0 W (HDBaseT) 15.0 W (All Terminals and Networks Connected) (when "Standby Mode" is set to "Standard")
● AC 220 V to 240 V	13.3 W (LAN) 13.3 W (HDBaseT) 13.3 W (All Terminals and Networks Connected) (when "Standby Mode" is set to "Standard")

Standby Mode / Networked Standby Mode Activated	
● Standby Mode / Networked Standby Mode Activated	Approx. 10 Minutes

Heat dissipation	
● AC 100 V to 120 V	1699 BTU/h
● AC 220 V to 240 V	1648 BTU/h

Dimensions (W x H x D)	
● Dimensions (W x H x D) (without protrusions)	460 x 169 x 515 mm 18 1/8 x 6 21/32 x 20 9/32 inches

Mass	
● Mass	Approx. 13 kg (28 lb)

Supplied accessories	
● Remote commander	RM-PJ27

Optional accessories	
● Projection Lens	VPLL3007 / Z3009/ Z3024 / Z3032

Notes	
● *1	With supplied standard lens.
● *2	This figure is expected maintenance time, not guaranteed time. The actual value depends on the environment and how the projector is used.
● *3	The value is average.
● *4	Available for VESA Reduced Blanking signal.

Accessories

Ceiling Brackets



PSS-610
Projector Ceiling Bracket for
the VPL-F Series

Lamps



LMP-F370
Replacement Lamp for the
VPL-F Series

Lenses



VPLL-3007
Projection Lens for the VPL-F
Series



VPLL-Z3009
Short focus zoom lens



VPLL-Z3024
Projection Lens for the VPL-F
Series



VPLL-Z3032
Long focus zoom lens