IN124STx

Bright, short throw projector at a great low price Part #: IN124STx

The InFocus IN124STx short throw projector combines short throw, high brightness, networking, and low cost – making it perfect for the classroom, office or other tight space.

Key Features

- XGA (1024 x 768) native resolution
- Short throw lens (0.65 throw ratio)
- Up to 3700 lumens of brightness
- Display over HDMI, VGA, composite or S-video
- Networkable for easy management
- Incredible, sharp images with 14,000:1 contrast ratio
- Compact and light weight for easy portability
- Display 3D content from Blu-ray, PCs and more





Why Choose the IN124STx Short Throw Projector?

- Big, vivid images from a short distance with no shadow interference
- High brightness that delivers clear images with the lights on
- 14,000:1 contrast ratio delivers incredible sharpness with darker blacks and whiter whites
- Instantly stop projecting from the remote control to lengthen lamp life and save money and energy
- Easily move the projector from room to room or install and manage remotely over the network
- An exceptional 10-watt speaker fills the room with sound

Priced Right

The ultra-low purchase price is just the beginning – the lamp is long-lasting and no filters.

- Great low price to fit your budget
- Use Eco Blanking when the projector isn't used to lower the lamp's power usage and extend its life

- Average lamp life is 5,000 hours in Eco Blanking mode, 3,500 hours when in Eco Mode, and 2,000 hours in normal mode
- No filters to clean or replace

Count on Quality

Even at this incredible low price this projector is made to perform with high-quality image technology you can count on.

- Quality images and true-to-life colors with DLP[®] technology with InFocus BrilliantColor[™] implementation
- Amazing 14,000:1 contrast ratio adds sharpness with darker blacks and whiter whites
- Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface
- 3D-ready: project Blu-ray and PC-based 3D content via HDMI to improve learning and retention of complex concepts



Compact Powerhouse

Compact size makes it easy to move from room-to-room, but powerful enough to install

- HDMI input for fast, high quality display of digital devices
- High brightness that can combat bright lighting situations
- Built in speaker and 3.5mm audio out port provides clear audio
- RS232 port means it can be easily integrated into room control systems





Specifications*

Projector	IN124STx
Resolution – Native	XGA (1024 x 768)
Resolution – Maximum	WUXGA (1920 x 1200)
Display Technology	DLP
Video Standard Compatibility	NTSC, PAL, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	3,700 lumens
Lamp Brightness – Low Power	2,960 lumens
Lamp Life	2,000 hours
Lamp Life – Low Power	3,500 hours
Lamp Life – Eco Mode	5,000 hours
Lamp Power	260W
Lamp Power – Low Power	220W
Lamp Power – Eco Mode	65W
Replacement Lamp	SP-LAMP-094
Contrast Ratio	14,000:1
Color Wheel	6 segments, 2 vitesses
Number of Colors	1.07 billion
Synch Scan Frequency – Horizontal	15 - 91 KHz
Synch Scan Frequency – Vertical	24 - 120 KHz
Aspect Ratio	4:3
Aspect Ratio Compatibility	16:9, 16:10
Lens Type	Manual focus
Projection Offset	15
Keystone Correction	± 40°V
Connectors – Inputs	3.5mm stereo audio ×2, RS232, HDMI 1.4 (rear), Composite video, S-video, VGA x2, USB Type B (control & firmware), RJ-45 (Ethernet)
Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Control	RS232, USB-B for presentation control, Ethernet
Audible Noise	< 34 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 32 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, VGA cable, Documentation
3D Support	720p @ 120Hz, 1080p @ 60Hz, All HDMI 1.4a 3D formats from Blu-Ray, DLP Link 3D glasses required
Product Warranty	2 years
Lamp Warranty	6 months
Accessories Warranty	90 days
Operating Conditions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian

Projector	IN124STx
Security Features	User PIN, Security bar, Security lock slot
Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC
Throw and Zoom	
Throw Ratio	0.65:1
Zoom Ratio	1.0:1
Shipping	
Product Dimensions	5.1 x 11.8 x 9.1 in / 129.5 x 299.7 x 231.1 mm
Product Weight	5.1 lbs / 2.3 kg
Shipping Dimensions	7.8 x 14.3 x 12 in / 196.9 x 362 x 304.8 mm
Shipping Weight	7.1 lbs / 3.2 kg

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV) Manual Pull Up Projector Screen: 73 in., 16:9 (SC-PUW-73) Projector Lamp for the IN120x, IN120STx, and IN2120x Series (SP-LAMP-094) LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+) Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4) Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4) Soft Carry Case for Value Projectors (CA-SOFTVAL-2) Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB) Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW) VGA Cable (36 ft / 11 m) (SP-VGA-11M) Manual Pull Down Projector Screen: 84 in., 4:3 (SC-MAN-84) Motorized Electric Projector Screen: 84 in., 4:3 (SC-MOT-84) Motorized Electric Projector Screen: 100 in., 4:3 (SC-MOT-100) Fixed Frame Projector Screen: 100 in., 4:3 (SC-FF-100) Fixed Frame Projector Screen: 120 in., 4:3 (SC-FF-120) Manual Pull Down Projector Screen: 100 in., 4:3 (SC-MAN-100) Manual Pull Down Projector Screen: 120 in., 4:3 (SC-MAN-120) Fixed Frame Projector Screen: 84 in., 4:3 (SC-FF-84) Manual Pull Down Projector Screen: 92 in., 16:9 (SC-PDHD-92) Manual Pull Down Projector Screen: 106 in., 16:9 (SC-PDHD-106) DLP Link 3D Glasses by XPAND (X103-EDUX3-R1) SMART Mount Adapter (INA-SMRTADPT) 1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1) 2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)