

Projectors Overview



©National Trust Images / John Miller

InFocus contact:

Jeremy J. Farren

Presentation Solutions EMEA

jeremy.farren@infocus.com

UK: 020 8123 0082

Germany: 089 2351 5519




France: 0970 408 022

Sweden: 08-559 20 929




ROE: +84(0)126 4121110



Portable Series

LED Projector	WXGA Projector	1080 Full HD Projector
		
IN1146	IN1116	IN1118HD
DLP with LED lamp	DLP	DLP
WXGA 1280 x 800	WXGA 1280 x 800	1080p 1920 x 1080
1000	2400	2400
10,000	14,000	15,000
16:10	16:10	16:09
30,000	6000/10,000	6000/10,000
32 dBA	33 dBA	33 dBA
1.4	1.18 - 1.54	1.15 - 1.5
1:1	1.3:1	1.3:1
+/- 40° vert.	Auto Keystone, ± 40°	Auto Keystone, ± 40°
2 x 2W	1 x 2W	1 x 2W
0.8	1.59	1.59
N/A	SP-LAMP-095	SP-LAMP-095
1 / - / -	1 / - / -	1 / - / -
1 / -	1 / -	1 / -
- / - / -	Y / Y / -	Y / Y / -
Y	Y	Y
- / -	- / -	- / -
- / - / -	- / - / -	- / - / -
Y	Y	Y
-	Y	Y
Y	-	-
-	4 GB	4 GB
-	Y	Y
(O)	(O)	(O), (H), (E)
7-97212-96985-9	7-97212-98334-3	7-97212-98236-0
Available	Available	Available

Value Series

SVGA Projectors		
		
IN112v	IN112xv	IN112xa
DLP	DLP	DLP
SVGA 800 x 600	SVGA 800 x 600	SVGA 800 x 600
3500	3400	3500
17,000	16,000	18,000
4:3	4:3	4:3
5000/10,000	5000/15,000	5000/15,000
29 dBA	28dBA	28dBA
1.95 - 2.15	1.95 - 2.15	1.95 - 2.15
1.1:1	1.1:1	1.1:1
+/- 40° vert.	+/- 40° vert.	+/- 40° vert.
1 x 2W	N/A	1 x 3W
2.35	2.5	2.5
SP-LAMP-089	SP-LAMP-097	SP-LAMP-097
1 / - / -	1 / - / -	2 / - / -
2 / 1	1 / -	1 / 1
Y / Y / -	Y / Y / -	Y / Y / -
-	-	-
Y / -	Y / -	Y / -
Y / Y / -	Y / Y / -	Y / Y / -
-	-	-
-	-	-
-	-	-
Y	Y	Y
(O), (E)	(O), (E)	(O), (E)
7-97212-98743-3	7-97212-98759-4	7-97212-98756-3
Available	Available	Available



Model

Projection System
Resolution
Brightness
Contrast
Aspect Ratio
Lamp Life (STD/ECO)
Audible Noise (ECO)
Throw Ratio
Zoom Ratio
Keystone Correction/Lens Shift
Speakers
Product Weight (kg)
Lamp MIC

HDMI/with MHL/DP
VGA In/Out
S-Video/Composite/Component
USB-A (PC-less Presentation)
RS232/RJ45
AMX/CESTRON/ProjectorNet
Internal Media Player
Wireless option with LightCast Key
Wireless option with WIFI USB dongle
Internal Memory
3D support
Suitable for (H)ome, (O)ffice, (E)ducation or (V)enue

EAN/UPC

Planned introduction:

Value Series





XGA Projectors			WXGA Projectors			1080 Full HD Projector
IN114v	IN114xv	IN114xa	IN116v	IN116xv	IN116xa	IN119HDx
DLP	DLP	DLP	DLP	DLP	DLP	DLP
XGA 1024 x 768	XGA 1024 x 768	XGA 1024 x 768	WXGA 1280 x 800	WXGA 1280 x 800	WXGA 1280 x 800	1080p 1920 x 1080
3500	3400	3500	3500	3400	3500	3200
17,000	16,000	18,000	17,000	16,000	18,000	15,000
4:3	4:3	4:3	16:10	16:10	16:10	16:09
5000/10,000	5000/15,000	5000/15,000	5000/10,000	5000/15,000	5000/15,000	6000/10,000
29 dBA	28dBA	28dBA	29 dBA	28dBA	28dBA	30 dBA
1.95 - 2.15	1.95 - 2.15	1.95 - 2.15	1.15 - 1.5	1.55 - 1.7	1.55 - 1.7	1.15 - 1.5
1.1:1	1.1:1	1.1:1	1.3:1	1.1:1	1.1:1	1.3:1
+/- 40° vert.	+/- 40° vert.	+/- 40° vert.	+/- 40° vert.	+/- 40° vert.	+/- 40° vert.	+/- 40° vert.
1 x 2W	N/A	1 x 3W	1 x 2W	N/A	1 x 3W	1 x 2W
2.35	2.5	2.5	2.35	2.5	2.5	2.45
SP-LAMP-089	SP-LAMP-097	SP-LAMP-097	SP-LAMP-089	SP-LAMP-097	SP-LAMP-097	SP-LAMP-093
1/-/-	1/-/-	2/-/-	1/-/-	1/-/-	2/-/-	1/-/-
2/1	1/-	1/1	2/1	1/-	1/1	1/1
Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-
-	-	-	-	-	-	-
Y/-	Y/-	Y/-	Y/-	Y/-	Y/-	Y/-
Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-	Y/Y/-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
-	-	-	-	-	-	-
Y	Y	Y	Y	Y	Y	Y
(O), (E)	(O), (E)	(O), (E)	(O), (E)	(O), (E)	(O), (E)	(O), (E), (H)
7-97212-98742-6	7-97212-98758-7	7-97212-98755-6	7-97212-98741-9	7-97212-98757-0	7-97212-98754-9	7-97212-98226-1
Available	Available	Available	Available	Available	Available	Available



Midrange Series

XGA Projector	WXGA Projector	1080 Full HD Projector
		
IN124x	IN126x	IN128HDx
DLP	DLP	DLP
XGA 1024 x 768	WXGA 1280 x 800	1080p 1920 x 1080
4200	4200	4000
14,000	15,000	15,000
4:3	16:10	16:09
2000/5000	2000/5000	2000/5000
32 dBA	32 dBA	32 dBA
1.9 - 2.09	1.47 - 1.83	1.15 - 1.5
1:1:1	1.24:1	1.3:1
+/- 40° vert.	+/- 40° vert.	+/- 40° vert.
1 x 10W	1 x 10W	1 x 10W
2.7	2.7	2.7
SP-LAMP-094	SP-LAMP-094	SP-LAMP-094
1/-/-	1/-/-	1/-/-
2/1	2/1	2/1
Y/Y/-	Y/Y/-	Y/Y/-
-	-	-
Y/Y	Y/Y	Y/Y
Y/Y/Y	Y/Y/Y	Y/Y/Y
-	-	-
-	-	-
-	-	-
-	-	-
Y	Y	Y
(O), (E)	(O), (E)	(O), (E), (H)
7-97212-98226-1	7-97212-98203-2	7-97212-98202-5
Available	Available	Available

Short Throw Series

XGA Projectors		WXGA Projector	1080 Full HD Projector
			
INV30	IN124STx	IN126STx	IN128HDSTx
DLP	DLP	DLP	DLP
XGA 1024 x 768	XGA 1024 x 768	WXGA 1280 x 800	1080p 1920 x 1080
3000	3700	3700	3500
17,000	14,000	14,000	15,000
4:3	4:3	16:10	16:09
6500/8000	2000/5000	2000/5000	2000/5000
32 dBA	32 dBA	32 dBA	32 dBA
0.63	0.65	0.52	0.495
1:1 fixed	1:1 fixed	1:1 fixed	1:1 fixed
vertical	+/- 40° vert.	+/- 40° vert.	+/- 40° vert.
1 x 5W	1 x 10W	1 x 10W	1 x 10W
2.6	2.8	2.8	2.8
SP-LAMP-099	SP-LAMP-094	SP-LAMP-094	SP-LAMP-094
1/-/-	1/-/-	1/-/-	1/-/-
2/1	1/1	1/1	1/1
-/-/-	Y/Y/-	Y/Y/-	Y/Y/-
-	-	-	-
Y/Y	Y/Y	Y/Y	Y/Y
Y/Y/Y	Y/Y/Y	Y/Y/Y	Y/Y/Y
-	-	-	-
-	-	-	-
-	-	-	-
-	Y	Y	Y
(E)	(O), (E)	(O), (E)	(O), (E)
7-97212-98808-9	7-97212-98214-8	7-97212-98213-1	7-97212-98212-4
Available	Available	Available	Available



Meeting Room Series

XGA Projectors

WXGA
Projector

1080 Full HD
Projector



IN2124a

IN2124x

IN2126x

IN2128HDx

DLP

DLP

DLP

DLP

XGA
1024 x 768

XGA
1024 x 768

WXGA
1280 x 800

1080p
1920 x 1080

3500

4200

4200

4000

15,000

14,000

14,000

15,000

4:3

4:3

16:10

16:09

3500/7000

2000/5000

2000/5000

2000/5000

30 dBA

32 dBA

32 dBA

32 dBA

1.9 - 2.2

1.9 - 2.09

1.47 - 1.83

1.15 - 1.5

1.15:1

1.1:1

1.24:1

1.3:1 manual

+/- 40° vert.

+/- 40° vert.

+/- 40° vert.

+/- 40° vert.

1 x 2W

1 x 10W

1 x 10W

1 x 10W

2.5

2.7

2.7

2.7

SP-LAMP-087

SP-LAMP-094

SP-LAMP-094

SP-LAMP-094

1 / - / -

1 / - / -

1 / - / -

1 / - / -

2 / 1

2 / 1

2 / 1

2 / 1

Y / Y / -

Y / Y / -

Y / Y / -

Y / Y / -

Y

Y

Y

Y

Y / Y

Y / Y

Y / Y

Y / Y

Y / Y / Y

Y / Y / Y

Y / Y / Y

Y / Y / Y

Y

Y

Y

Y

-

Y

Y

Y

Y

-

-

-

2 GB

4 GB

4 GB

4 GB

Y

Y

Y

Y

(O), (E)

(O), (E)

(O), (E)

(O), (E)

Model

Projection System

Resolution

Brightness

Contrast

Aspect Ratio

Lamp Life (STD/ECO)

Audible Noise (ECO)

Throw Ratio

Zoom Ratio

Keystone Correction/Lens Shift

Speakers

Product Weight (kg)

Lamp MIC

HDMI/with MHL/DP

VGA In/Out

S-Video/Composite/Component

USB-A (PC-less Presentation)

RS232/RJ45

AMX/CESTRON/ProjectorNet

Internal Media Player

Wireless option with LightCast Key

Wireless option with WIFI USB dongle

Internal Memory

3D support

Suitable for (H)ome, (O)ffice,
(E)ducation or (V)enue

EAN/UPC

Planned introduction:

7-97212-96862-3

7-97212-98237-7

7-97212-98238-4

7-97212-98239-1

Available

Available

Available

Available



Model
Projection System
Resolution
Brightness
Contrast
Aspect Ratio
Lamp Life (STD/ECO)
Audible Noise (ECO)
Throw Ratio
Zoom Ratio
Keystone Correction/Lens Shift
Speakers
Product Weight (kg)
Lamp MIC
HDMI /with MHL/DP
VGA In/Out
S-Video/Composite/Component
USB-A (PC-less Presentation)
RS232/RJ45
AMX/CESTRON/ProjectorNet
Internal Media Player
Wireless option with LightCast Key
Wireless option with WIFI USB dongle
Internal Memory
3D support
Suitable for (H)ome, (O)ffice, (E)ducation or (V)enue
EAN/UPC
Planned introduction:

Performance Series						
1080 Full HD Projector	XGA Projector	WXGA Projector	1080 Full HD Projectors		XGA Projector	1080 Full HD Projector
IN3138HDa	IN3144	IN3146	IN3148HD	IN5148HD	IN5312a	IN5316HDa
DLP	DLP	DLP	DLP	DLP	DLP	DLP
1080p 1920 x 1080	XGA 1024 x 768	WXGA 1280 x 800	1080p 1920 x 1080	1080p 1920 x 1080	XGA 1024 x 768	1080p 1920 x 1080
4500	5000	5000	5000	5000	6000	5000
20,000	11,000	16,000	16,000	12,000	2,000	2,000
16:09	4:3	16:10	16:09	16:09	4:3	16:09
3200/4000	3500/6000	3500/6000	3500/6000	3000/4500	1500/3500	1500/3500
35 dBA	30 dBA	30 dBA	30 dBA	32 dBA	31 dBA	31 dBA
1.39 - 2.09	1.83-2.75	1.46-2.20	1.46-2.20	1.49 - 3.02	1.55 - 1.7	1.54 - 1.93
1.5:1	1.5:1	1.5:1	1.5:1	2.0:1	1.1:1	1.25:1
+/- 40° vert.	+/- 40° vert.	+/- 40° vert.	+/- 40° vert.	+/- 40° vert.	- 40° - 0° vert. +/- 5° horiz.	- 35° - 5° vert. +/- 5° horiz.
1 x 10W	1 x 10W	1 x 10W	1 x 10W	2 x 10W	2 x 3W	2 x 3W
3.15	3.2	3.2	3.2	8.6	8.6	8.6
SP-LAMP-092	SP-LAMP-098	SP-LAMP-098	SP-LAMP-098	SP-LAMP-096	SP-LAMP-090	SP-LAMP-090
2 / 1 / -	2 / 1 / -	2 / 1 / -	2 / 1 / -	2 / - / -	1 / - / 1	1 / - / 1
1 / 1	2 / 1	2 / 1	2 / 1	2 / 1	1 / 1	1 / 1
Y / Y / -	Y / Y / -	Y / Y / -	Y / Y / -	Y / Y / -	Y / Y / Y	Y / Y / Y
-	-	-	-	Y	-	-
Y / Y	Y / Y	Y / Y	Y / Y	Y / Y (HDBaseT)	Y / Y	Y / Y
Y / Y / Y	Y / Y / Y	Y / Y / Y	Y / Y / Y	Y / Y / Y	Y / Y / Y	Y / Y / Y
-	-	-	-	Y	-	-
-	-	-	-	Y	-	-
-	-	-	-	-	-	-
-	-	-	-	4 GB	-	-
NVIDIA 3DTV Play	Y	Y	Y	Y	Y	Y
(H), (O)	(O), (E), (V)	(O), (E), (V)	(H), (O), (E), (V)	(O), (V)	(V)	(V)
7-97212-98135-6	7-97212-98771-6	7-97212-98770-9	7-97212-98769-3	7-97212-98356-5	7-97212-98104-2	7-97212-98105-9
Available	February 2018	February 2018	January 2018	Available	Available	Available



Model
Projection System
Resolution
Brightness
Contrast
Aspect Ratio
Lamp Life (STD/ECO)
Audible Noise (ECO)
Throw Ratio
Zoom Ratio
Keystone Correction/Lens Shift
Speakers
Product Weight (kg)
Lamp MIC
HDMI/with MHL/DP
VGA In/Out
S-Video/Composite/Component
USB-A (PC-less Presentation)
RS232/RJ45
AMX/CESTRON/ProjectorNet
Internal Media Player
Wireless option with LightCast Key
Wireless option with WIFI USB dongle
Internal Memory
3D support
Suitable for (H)ome, (O)ffice, (E)ducation or (V)enue
EAN/UPC
Planned introduction:

Installation Series		
XGA Projector	WXGA Projector	WUXGA Projector
		
IN5552L	IN5554L	IN5555L
DLP	DLP	DLP
XGA 1024 x 768	WXGA 1280 x 800	WUXGA 1920 x 1200
8300	7000	7000
2.400	2.400	2.400
4:3	16:10	16:10
2500/3000	2000/3000	2000/3000
39 dBA	39 dBA	39 dBA
lens dependent	lens dependent	lens dependent
Motorised focus zoom and lens shift	Motorised focus zoom and lens shift	Motorised focus zoom and lens shift
+/- 30° vert. +/- 30° horiz.	+/- 30° vert. +/- 30° horiz.	+/- 30° vert. +/- 30° horiz.
N/A	N/A	N/A
20	20	20
SP-LAMP-082*	SP-LAMP-082*	SP-LAMP-082*
1/-/-	1/-/-	1/-/-
1/-	1/-	1/-
Y/Y/Y	Y/Y/Y	Y/Y/Y
-	-	-
Y/Y	Y/Y	Y/Y
Y/Y/Y	Y/Y/Y	Y/Y/Y
-	-	-
-	-	-
-	-	-
Y	Y	Y
(M)	(M)	(M)
7-97212-96717-6	7-97212-96718-3	7-97212-96719-0
Available	Available	Available

* Not included.

Accessories



- All projectors have optional wireless connectivity with LiteShow 4 (INLITESHOW4) or LightCast Hub (INA-LC100).
- LightCast Key (INA-LCKEY2) or WiFi USB dongle (SP-WIFIUSB-2) are optional and need to be purchased separately.
- LightCast Technology enables digital whiteboard, web site browser and Document viewer functionality. Visit www.infocus.com/lightcast for more information.

Projector Lens Overview

	Short Throw Fixed	Long Throw Fixed	Standard Throw	Wide Throw Fixed	Long Throw Zoom	Long Throw Zoom	Ultra Long Throw Zoom	Semi Long Throw Zoom
								
Lens Model	LENS-060	LENS-061	LENS-074	LENS-075	LENS-076	LENS-077	LENS-078	LENS-079
Works with:								
IN5312a	Yes	Yes						
IN5316HDa	Yes	Yes						
IN5552L			Yes	Yes	Yes	Yes	Yes	Yes
IN5554L			Yes	Yes	Yes	Yes	Yes	Yes
IN5555L			Yes	Yes	Yes	Yes	Yes	Yes
F-Stop	2.5	2.5 - 3.1	IN5552L: 1.8 - 14.9 m IN5554L: 1.8 - 14.9 m IN5555L: 1.83 - 14.9 m	1,85	IN5552L: 1.85 - 2.5 IN5554L: 1.85 - 2.5 IN5555L: 1.9 - 2.5	IN5552L: 1.86 - 2.41 IN5554L: 1.86 - 2.41 IN5555L: 1.9 - 2.4	IN5552L: 1.85 - 2.48 IN5554L: 1.85 - 2.48 IN5555L: 1.9 - 2.5	IN5552L: 1.86 - 2.48 IN5554L: 1.86 - 2.48 IN5555L: 1.9 - 2.5
Zoom Ratio	1:1 fixed	1.5:1	1.31:1	1:1 fixed	1.42:1	1.5:1	1.55:1	1.65:1
Throw Distance	1.5 - 7 m	1.5 - 7 m	IN5552L: 1.8 - 14.9 m IN5554L: 1.8 - 14.9 m IN5555L: 1.83 - 14.9 m	IN5552L: 0.8 - 5.1 m IN5554L: 0.8 - 5.1m IN5555L: 0.81 - 5.08 m	IN5552L: 1.3 - 11.7 m IN5554L: 1.3 - 11.7 m IN5555L: 1.33 - 11.73 m	IN5552L: 3.8 - 35.4 m IN5554L: 3.8 - 35.4 m IN5555L: 3.8 - 35.35 m	IN5552L: 5.6 - 54.8 m IN5554L: 5.6 - 54.8 m IN5555L: 5.59 - 54.8 m	IN5552L: 2.4 - 24.1 m IN5554L: 2.4 - 24.1 m IN5555L: 2.36 - 24.2 m
Throw Ratio	IN5312a: 0.8:1 IN5316HDa: 0.77:1	IN5312a: 2.0 - 3.0:1 IN5316HDa: 1.93 - 2.89:1	IN5552L: 1.75 - 2.35:1 IN5554L: 1.81 - 2.38:1 IN5555L: 1.73 - 2.27:1	IN5552L: 0.79:1 IN5554L: 0.8:1 IN5555L: 0.76:1	IN5552L: 1.3 - 1.85:1 IN5554L: 1.31 - 1.87:1 IN5555L: 1.25 - 1.79:1	IN5552L: 3.71 - 5.57:1 IN5554L: 3.76 - 5.64:1 IN5555L: 3.58 - 5.38:1	IN5552L: 5.5 - 8.56:1 IN5554L: 5.56 - 8.67:1 IN5555L: 5.31 - 8.26:1	IN5552L: 2.3 - 3.81:1 IN5554L: 2.33 - 3.86:1 IN5555L: 2.22 - 3.67:1
Lens Shift (H)	+/- 5°	+/- 5°	+/- 10%	Fixed Center	+/- 10%	+/- 10%	+/- 10%	+/- 10%
Lens Shift (V)	IN5312a: - 40° - 0° IN5316HDa: - 35° - 5°	IN5312a: - 40° - 0° IN5316HDa: - 35° - 5°	+ 20% to - 60%	Fixed Center	+ 20% to - 60%	+ 20% to - 60%	+ 20% to - 60%	+ 20% to - 60%
EAN/UPC	7-97212-95723-8	7-97212-95721-4	7-97212-96707-7	7-97212-96708-4	7-97212-96709-1	7-97212-96710-7	7-97212-96711-4	7-97212-96712-1
Planned introduction:	Available	Available	Available	Available	Available	Available	Available	Available