

HP 5120 EI Switch Series



Product overview

The HP 5120 EI Switch Series is comprised of Gigabit Ethernet switches that support static Layer 3 routing, diversified services, and IPv6 forwarding, as well as provide up to four 10-Gigabit Ethernet (10GbE) extended interfaces. Unique Intelligent Resilient Framework (IRF) technology creates a virtual fabric by managing several switches as one logical device, which increases network resilience, performance, and availability, while reducing operational complexity.

These switches provide Gigabit Ethernet access and can be used at the edge of a network or to connect server clusters in data centers. High scalability provides investment protection with two expansion slots, each of which can support two-port 10GbE expansion modules. High availability, simplified management, and comprehensive security control policies are among the key features that distinguish this series.

Key features

- High scalability for investment protection
- Support for multiple services
- Comprehensive security control policies
- Diversified quality of service (QoS) policies
- Excellent manageability

Features and benefits

Quality of Service (QoS)

- **Broadcast control**
allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic
- **Advanced classifier-based QoS**
classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information; applies QoS policies such as setting priority level and rate limit to selected traffic on a port, VLAN, or whole switch
- **Powerful QoS feature**
supports the following congestion actions: strict priority (SP) queuing, weighted round robin (WRR), and SP+WRR
- **Traffic policing**
supports Committed Access Rate (CAR) and line rate

Management

- **Friendly port names**
allows assignment of descriptive names to ports
- **Remote configuration and management**
enables configuration and management through a secure Web browser or a CLI located on a remote device
- **Manager and operator privilege levels**
provides read-only (operator) and read/write (manager) access on CLI and Web browser management interfaces
- **Command authorization**
leverages HWTACACS to link a custom list of CLI commands to an individual network administrator's login; also provides an audit trail
- **Secure Web GUI**
provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Multiple configuration files**
stores easily to the flash image
- **Complete session logging**
provides detailed information for problem identification and resolution
- **SNMPv1, v2c, and v3**
facilitate centralized discovery, monitoring, and secure management of networking devices
- **Remote monitoring (RMON)**
uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- **sFlow (RFC 3176)**
provides scalable ASIC-based wirespeed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **Management VLAN**
segments traffic to and from management interfaces, including CLI/Telnet, a Web browser interface, and SNMP

- **Remote intelligent mirroring**

mirrors ingress/egress ACL-selected traffic from a switch port or VLAN to a local or remote switch port anywhere on the network

- **Device Link Detection Protocol (DLDP)**

monitors a cable between two switches and shuts down the ports on both ends if the cable is broken, which prevents network problems such as loops

- **IPv6 management**

provides future-proof networking because the switch is capable of being managed whether the attached network is running IPv4 or IPv6; supports pingv6, tracertv6, Telnetv6, TFTPv6, DNSv6, syslogv6, FTPv6, SNMPv6, DHCPv6, and RADIUS for IPv6

- **Troubleshooting**

ingress and egress port monitoring enables network problem-solving; virtual cable tests provide visibility into cable problems

Connectivity

- **Auto-MDIX**

automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports

- **Flow control**

provides back pressure using standard IEEE 802.3x, reducing congestion in heavy traffic situations

- **Jumbo packet support**

supports up to 9216-byte frame size to improve the performance of large data transfers

- **High-density connectivity**

provides up to 48 fixed 10/100/1000BASE-T ports in a Layer 2/Layer 3 switch

- **Optional 10GbE ports**

deliver, through the use of optional modules, additional 10GbE connections, which are available for uplinks or high-bandwidth server connections; flexibly support copper, XFP, SFP+, or CX4 local connections

- **IEEE 802.3at Power over Ethernet (PoE+) support**

simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location

- **Ethernet operations, administration and maintenance (OAM)**

detects data link layer problems that occurred in the “last mile” using the IEEE 802.3ah OAM standard; monitors the status of the link between two devices

- **High-bandwidth CX4 local stacking**

achieves 12 Gb/s per connection when using local CX4 stacking, allowing for up to 96 Gb/s total stacking bandwidth (full duplex) in a resilient stacking configuration

Performance

- **Nonblocking architecture**

up to 192 Gb/s nonblocking switching fabric provides wirespeed switching with up to 143 million pps throughput

- **Hardware-based wirespeed access control lists (ACLs)**

help provide high levels of security and ease of administration without impacting network performance with a feature-rich TCAM-based ACL implementation

Resiliency and high availability

- **Separate data and control paths**

separates control from services and keeps service processing isolated; increases security and performance

- **External redundant power supply**

provides high reliability

- **Smart link**

allows 50 ms failover between links

- **Spanning Tree/MSTP, RSTP**

provides redundant links while preventing network loops

- **Rapid Ring Protection Protocol (RRPP)**

connects multiple switches in a high-performance ring using standard Ethernet technology; traffic can be rerouted around the ring in less than 50 ms, reducing the impact on traffic and applications

- **Intelligent Resilient Framework (IRF)**

creates virtual resilient switching fabrics, where two or more switches perform as a single L2 switch and L3 router; switches do not have to be co-located and can be part of a disaster-recovery system; servers or switches can be attached using standard LACP for automatic load balancing and high availability; can eliminate the need for complex protocols like Spanning Tree Protocol, Equal-Cost Multipath (ECMP), or VRRP, thereby simplifying network operation

Layer 2 switching

- **16K MAC address table**

provides access to many Layer 2 devices

- **VLAN support and tagging**

supports IEEE 802.1Q with 4,094 simultaneous VLAN IDs

- **GARP VLAN Registration Protocol**

allows automatic learning and dynamic assignment of VLANs

- **IEEE 802.1ad QinQ and selective QinQ**

increase the scalability of an Ethernet network by providing a hierarchical structure; connect multiple LANs on a high-speed campus or metro network

- **10GbE port aggregation**

allows grouping of ports to increase overall data throughput to a remote device

- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping**

controls and manages the flooding of multicast packets in a Layer 2 network

- **Per-VLAN Spanning Tree Plus (PVST+)**

allows each VLAN to build a separate spanning tree to improve link bandwidth usage in network environments with multiple VLANs

Layer 3 services

- **Address Resolution Protocol (ARP)**

determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network

- **Dynamic Host Configuration Protocol (DHCP)**

simplifies the management of large IP networks; supports client; DHCP Relay enables DHCP operation across subnets

- **Loopback interface address**

defines an address that can always be reachable, improving diagnostic capability

- **User Datagram Protocol (UDP) helper function**

allows UDP broadcasts to be directed across router interfaces to specific IP unicast or subnet broadcast addresses and prevents server spoofing for UDP services such as DHCP

- **Route maps**

provide more control during route redistribution; allow filtering and altering of route metrics

Layer 3 routing

- **Static IP routing**

provides manually configured routing for both IPv4 and IPv6 networks

Security

- **Access control lists (ACLs)**

provides IP Layer 2 to Layer 4 traffic filtering; supports global ACL, VLAN ACL, port ACL, and IPv6 ACL

- **IEEE 802.1X**

industry-standard method of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server

- **MAC-based authentication**

client is authenticated with the RADIUS server based on the client's MAC address

- **Identity-driven security and access control**

- **Per-user ACLs**

permits or denies user access to specific network resources based on user identity and time of day, allowing multiple types of users on the same network to access specific network services without risking network security or providing unauthorized access to sensitive data

- **Automatic VLAN assignment**

automatically assigns users to the appropriate VLAN based on their identities

- **Secure management access**

delivers secure encryption of all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3

- **Secure FTP**

allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file

- **Guest VLAN**

provides a browser-based environment to authenticated clients that is similar to IEEE 802.1X

- **Endpoint Admission Defense (EAD)**

provides security policies to users accessing a network

- **Port security**

allows access only to specified MAC addresses, which can be learned or specified by the administrator

- **Port isolation**

secures and adds privacy, and prevents malicious attackers from obtaining user information

- **STP BPDU port protection**

blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks

- **STP root guard**

protects the root bridge from malicious attacks or configuration mistakes

- **DHCP protection**

blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks

- **IP source guard**

helps prevent IP spoofing attacks

- **Dynamic ARP protection**

blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data

- **RADIUS/HWTACACS**

eases switch management security administration by using a password authentication server

Convergence

- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**

facilitates easy mapping using network management applications with LLDP automated device discovery protocol

- **LLDP-MED**

is a standard extension that automatically configures network devices, including LLDP-capable IP phones

- **LLDP-CDP compatibility**

receives and recognizes CDP packets from Cisco's IP phones for seamless interoperation

- **IEEE 802.3af Power over Ethernet**

provides up to 15.4 W per port to PoE-powered devices such as IP phones, wireless access points, and video cameras

- **PoE allocations**

supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings

- **Voice VLAN**

automatically assigns VLAN and priority for IP phones, simplifying network configuration and maintenance

- **IP multicast snooping (data-driven IGMP)**

prevents flooding of IP multicast traffic

Device support

- **Cisco prestandard PoE support**

detects and provides power to Cisco's prestandard PoE devices such as wireless LAN access points and IP phones

Additional information

- **Green IT and power**

improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs

- **Green initiative support**

provides support for RoHS and WEEE regulations

Warranty and support

- **Lifetime Warranty 2.0**

advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)¹

- **Electronic and telephone support (for Lifetime Warranty 2.0)**

limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to hp.com/networking/warrantysummary

- **Software releases**

to find software for your product, refer to hp.com/networking/support; for details on the software releases available with your product purchase, refer to hp.com/networking/warrantysummary

¹ HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services z1 Modules, HP Threat Management Services z1 Module, HP AllianceOne Extended z1 Module with Riverbed Steelhead, HP MSM765 z1 Mobility Controller and HP Survivable Branch Communication z1 Module powered by Microsoft® Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at hp.com/networking/warranty.

HP 5120 EI Switch Series

Specifications



**HP 5120-48G EI Switch with
2 Interface Slots (JE069A)**



HP 5120-48G EI Switch (JE067A)



**HP 5120-24G EI Switch with
2 Interface Slots (JE068A)**

I/O ports and slots

48 RJ-45 autosensing 10/100/1000 ports; Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)

4 dual-personality ports; autosensing 10/100/1000BASE-T or SFP

1 RJ-45 serial console port

2 port expansion module slots

Supports a maximum of 48 autosensing 10/100/1000 ports

48 RJ-45 autosensing 10/100/1000 ports; Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)

4 dual-personality ports; autosensing 10/100/1000BASE-T or SFP

1 RJ-45 serial console port

Supports a maximum of 48 autosensing 10/100/1000 ports

24 RJ-45 autosensing 10/100/1000 ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)

4 dual-personality ports; autosensing 10/100/1000BASE-T or SFP

1 RJ-45 serial console port

2 port expansion module slots

Physical characteristics

Dimensions

17.32(w) x 11.81(d) x 1.72(h) in.
(44 x 30 x 4.36 cm) (1U height)

17.32(w) x 11.81(d) x 1.72(h) in.
(44 x 30 x 4.37 cm) (1U height)

17.32(w) x 11.81(d) x 1.72(h) in.
(44 x 30 x 4.37 cm) (1U height)

Weight

11.02 lb (5 kg)

11.02 lb (5 kg)

9.92 lb (4.5 kg)

Memory and processor

128 MB SDRAM, 16 MB flash; packet buffer size: 4 MB

128 MB SRAM, 16 MB flash; packet buffer size: 4 MB

128 MB SDRAM, 16 MB flash; packet buffer size: 2 M

Mounting and enclosure

Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)

Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)

Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)

Performance

1000 Mb Latency

< 3.2 μ s

< 3.2 μ s

< 3.2 μ s

10 Gb/s Latency

< 2.6 μ s

< 2.6 μ s

Throughput

142.9 million pps

71.4 million pps

107.2 million pps

Routing/Switching capacity

192 Gb/s

96 Gb/s

144 Gb/s

Routing table size

32 entries (IPv4)

32 entries (IPv4)

32 entries (IPv4)

Environment

Operating temperature

32°F to 113°F (0°C to 45°C)

32°F to 113°F (0°C to 45°C)

32°F to 113°F (0°C to 45°C)

Operating relative humidity

10% to 90%, noncondensing

10% to 90%, noncondensing

10% to 90%, noncondensing

Nonoperating/Storage temperature

-40°F to 158°F (-40°C to 70°C)

-40°F to 158°F (-40°C to 70°C)

-40°F to 158°F (-40°C to 70°C)

Nonoperating/Storage relative humidity

5% to 95%, noncondensing

5% to 95%, noncondensing

5% to 95%, noncondensing

Acoustic

ISO 7779

ISO 7779

ISO 7779

Electrical characteristics

Frequency

50/60 Hz

50/60 Hz

50/60 Hz

Maximum heat dissipation

495 BTU/hr (522.23 kJ/hr)

375 BTU/hr (395.63 kJ/hr)

362 BTU/hr (381.91 kJ/hr)

AC voltage

100–240 VAC

100–240 VAC

100–240 VAC

Maximum power rating

145 W

110 W

106 W

Idle power

55 W

54 W

36 W

HP 5120 EI Switch Series

Specifications (continued)

	HP 5120-48G EI Switch with 2 Interface Slots (JE069A)	HP 5120-48G EI Switch (JE067A)	HP 5120-24G EI Switch with 2 Interface Slots (JE068A)
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 v1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 v1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 v1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Management	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager
Services	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV864E)</p> <p>3-year, 24x7 SW phone support, software updates (UV867E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR584E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR585E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR586E)</p> <p>Installation with minimum configuration, system-based pricing (UX116E)</p> <p>Installation with HP-provided configuration, system-based pricing (UX117E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV864E)</p> <p>3-year, 24x7 SW phone support, software updates (UV867E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR584E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR585E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR586E)</p> <p>Installation with minimum configuration, system-based pricing (UX116E)</p> <p>Installation with HP-provided configuration, system-based pricing (UX117E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)</p>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV864E)</p> <p>3-year, 24x7 SW phone support, software updates (UV867E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR584E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR585E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR586E)</p> <p>Installation with minimum configuration, system-based pricing (UX116E)</p> <p>Installation with HP-provided configuration, system-based pricing (UX117E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)</p>

HP 5120 EI Switch Series

Specifications (continued)

	HP 5120-48G EI Switch with 2 Interface Slots (JE069A)	HP 5120-48G EI Switch (JE067A)	HP 5120-24G EI Switch with 2 Interface Slots (JE068A)
Services (continued)	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)
	4-year, 24x7 SW phone support, software updates (UV868E)	4-year, 24x7 SW phone support, software updates (UV868E)	4-year, 24x7 SW phone support, software updates (UV868E)
	5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)
	5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)	5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)	5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)
	5-year, 24x7 SW phone support, software updates (UV869E)	5-year, 24x7 SW phone support, software updates (UV869E)	5-year, 24x7 SW phone support, software updates (UV869E)
	3 Yr 6 hr Call-to-Repair Onsite (UW963E)	3 Yr 6 hr Call-to-Repair Onsite (UW963E)	3 Yr 6 hr Call-to-Repair Onsite (UW963E)
	4 Yr 6 hr Call-to-Repair Onsite (UW964E)	4 Yr 6 hr Call-to-Repair Onsite (UW964E)	4 Yr 6 hr Call-to-Repair Onsite (UW964E)
	5 Yr 6 hr Call-to-Repair Onsite (UW965E)	5 Yr 6 hr Call-to-Repair Onsite (UW965E)	5 Yr 6 hr Call-to-Repair Onsite (UW965E)
	1-year, 6 hour Call-To-Repair Onsite for hardware (HR588E)	1-year, 6 hour Call-To-Repair Onsite for hardware (HR588E)	1-year, 6 hour Call-To-Repair Onsite for hardware (HR588E)
	1-year, 24x7 software phone support, software updates (HR587E)	1-year, 24x7 software phone support, software updates (HR587E)	1-year, 24x7 software phone support, software updates (HR587E)
	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS682E)	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS682E)	1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS682E)
	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS683E)	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS683E)	1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS683E)
	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS686E)	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS686E)	4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS686E)
	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS687E)	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS687E)	4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS687E)
	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS688E)	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS688E)	5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS688E)
	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5120 EI Switch Series

Specifications



HP 5120-24G EI Switch (JE066A)



HP 5120-48G-PoE+ EI Switch with 2 Interface Slots (JG237A)



HP 5120-24G-PoE+ EI Switch with 2 Interface Slots (JG236A)

I/O ports and slots	24 RJ-45 autosensing 10/100/1000 ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 4 dual-personality ports; autosensing 10/100/1000BASE-T or SFP 1 RJ-45 serial console port	48 RJ-45 autosensing 10/100/1000 PoE+ ports; Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+) 4 dual-personality ports; PoE autosensing 10/100/1000BASE-T or SFP 1 RJ-45 serial console port 2 port expansion module slots Supports a maximum of 48 autosensing 10/100/1000 ports	24 RJ-45 autosensing 10/100/1000 PoE+ ports; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+) 4 dual-personality ports; PoE autosensing 10/100/1000BASE-T or SFP 1 RJ-45 serial console port 2 port expansion module slots
Physical characteristics			
Dimensions	17.32(w) x 11.81(d) x 1.72(h) in. (44 x 30 x 4.36 cm) (1U height)	17.32(w) x 16.54(d) x 1.72(h) in. (43.99 x 42.01 x 4.37 cm) (1U height)	17.32(w) x 16.54(d) x 1.72(h) in. (43.99 x 42.01 x 4.37 cm) (1U height)
Weight	9.92 lb (4.5 kg)	16.53 lb (7.5 kg)	15.43 lb (7 kg)
Memory and processor	128 MB SDRAM, 16 MB flash; packet buffer size: 2 MB	128 MB SDRAM, 16 MB flash; packet buffer size: 4 MB	128 MB SDRAM, 16 MB flash; packet buffer size: 2 MB
Mounting and enclosure	Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included)
Performance			
1000 Mb Latency	< 3.2 μ s	< 3.2 μ s	< 3.2 μ s
10 Gb/s Latency		< 2.6 μ s	< 2.6 μ s
Throughput	35.7 million pps	142.9 million pps	107.2 million pps
Routing/Switching capacity	48 Gb/s	192 Gb/s	144 Gb/s
Routing table size	32 entries (IPv4)	32 entries (IPv4)	32 entries (IPv4)

HP 5120 EI Switch Series

Specifications (continued)

	HP 5120-24G EI Switch (JE066A)	HP 5120-48G-PoE+ EI Switch with 2 Interface Slots (JG237A)	HP 5120-24G-PoE+ EI Switch with 2 Interface Slots (JG236A)
Environment			
Operating temperature	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)
Operating relative humidity	10% to 90%, noncondensing	10% to 90%, noncondensing	10% to 90%, noncondensing
Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Nonoperating/Storage relative humidity	5% to 95%, noncondensing	10% to 90%, noncondensing	5% to 95%, noncondensing
Acoustic	ISO 7779	ISO 7779	ISO 7779
Electrical characteristics			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Maximum heat dissipation	212 BTU/hr (223.66 kJ/hr)	614 BTU/hr (647.77 kJ/hr)	425 BTU/hr (448.38 kJ/hr)
AC voltage	100–240 VAC	100–240 VAC	100–240 VAC
Maximum power rating	62 W	920 W	495 W
Idle power	35 W	78 W	55 W
PoE power		740 W	370 W
Safety			
	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance
Emissions			
	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 v1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 v1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 v1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Management			
	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager

HP 5120 EI Switch Series

Specifications (continued)

	HP 5120-24G EI Switch (JE066A)	HP 5120-48G-PoE+ EI Switch with 2 Interface Slots (JG237A)	HP 5120-24G-PoE+ EI Switch with 2 Interface Slots (JG236A)
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)	3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)	3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)
	3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)	3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)	3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)
	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV864E)	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV864E)	3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV864E)
	3-year, 24x7 SW phone support, software updates (UV867E)	3-year, 24x7 SW phone support, software updates (UV867E)	3-year, 24x7 SW phone support, software updates (UV867E)
	1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR584E)	Installation with minimum configuration, system-based pricing (UX116E)	Installation with minimum configuration, system-based pricing (UX116E)
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR585E)	Installation with HP-provided configuration, system-based pricing (UX117E)	Installation with HP-provided configuration, system-based pricing (UX117E)
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR586E)	4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)	4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)
	1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR670E)	4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)	4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)
	Installation with minimum configuration, system-based pricing (UX116E)	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)
	Installation with HP-provided configuration, system-based pricing (UX117E)	4-year, 24x7 SW phone support, software updates (UV868E)	4-year, 24x7 SW phone support, software updates (UV868E)
	4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)	5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)
	4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)	5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)	5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)
	4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)
	4-year, 24x7 SW phone support, software updates (UV868E)	5-year, 24x7 SW phone support, software updates (UV869E)	5-year, 24x7 SW phone support, software updates (UV869E)
	5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)	3 Yr 6 hr Call-to-Repair Onsite (UW963E)	3 Yr 6 hr Call-to-Repair Onsite (UW963E)
	5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)	4 Yr 6 hr Call-to-Repair Onsite (UW964E)	4 Yr 6 hr Call-to-Repair Onsite (UW964E)
	5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)	5 Yr 6 hr Call-to-Repair Onsite (UW965E)	5 Yr 6 hr Call-to-Repair Onsite (UW965E)
	5-year, 24x7 SW phone support, software updates (UV869E)	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5120 EI Switch Series

Specifications (continued)

	HP 5120-24G EI Switch (JE066A)	HP 5120-48G-PoE+ EI Switch with 2 Interface Slots (JG237A)	HP 5120-24G-PoE+ EI Switch with 2 Interface Slots (JG236A)
Services (continued)	<p>3 Yr 6 hr Call-to-Repair Onsite (UW963E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW964E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW965E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR588E)</p> <p>1-year, 24x7 software phone support, software updates (HR587E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS682E)</p> <p>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS683E)</p> <p>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS686E)</p> <p>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS687E)</p> <p>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS688E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>		

Standards and protocols

(applies to all products in series)

Device management	RFC 1157 SNMPv1/v2c RFC 1305 NTPv3 RFC 2573 (SNMPv3 Applications)	RFC 2819 (RMON groups Alarm, Event, History and Statistics only) RFC 3416 (SNMP Protocol Operations v2) HTML and Telnet management	Multiple Configuration Files SNMPv3 and RMON RFC support SSHv1/SSHv2 Secure Shell TACACS/TACACS+ Web UI
General protocols	IEEE 802.1ad Q-in-Q IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.1X PAE IEEE 802.3 Type 10BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3ae 10-Gigabit Ethernet IEEE 802.3af Power over Ethernet IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-X IEEE 802.3x Flow Control IEEE 802.3z 1000BASE-X	RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 791 IP RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 Telnet RFC 951 BOOTP RFC 1213 Management Information Base for Network Management of TCP/IP-based Internets RFC 1305 NTPv3 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1812 IPv4 Routing RFC 1866 Hypertext Markup Language-2.0 RFC 2131 DHCP RFC 2236 IGMP Snooping	RFC 2616 HTTP Compatibility v1.1 RFC 2665 Definitions of Managed Objects for the Ethernet-like Interface Types RFC 2668 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs) RFC 2865 Remote Authentication Dial In User Service (RADIUS) RFC 2866 RADIUS Accounting RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3) RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP) RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP) RFC 3576 Ext to RADIUS (CoA only) RFC 4213 Basic IPv6 Transition Mechanisms 802.1r—GARP Proprietary Attribute Registration Protocol (GPRP)
IPv6	RFC 2461 IPv6 Neighbor Discovery RFC 2463 ICMPv6	RFC 3162 RADIUS and IPv6 RFC 3306 Unicast-Prefix-based IPv6 Multicast Addresses	RFC 3315 DHCPv6 (client and relay)
MIBs	RFC 1212 Concise MIB Definitions RFC 1213 MIB II RFC 1493 Bridge MIB RFC 1757 Remote Network Monitoring MIB RFC 2096 IP Forwarding Table MIB RFC 2233 Interface MIB RFC 2571 SNMP Framework MIB RFC 2572 SNMP-MPD MIB	RFC 2573 SNMP-Notification MIB RFC 2573 SNMP-Target MIB RFC 2574 SNMP USM MIB RFC 2618 RADIUS Authentication Client MIB RFC 2620 RADIUS Accounting Client MIB RFC 2665 Ethernet-Like-MIB RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB	RFC 2737 Entity MIB (Version 2) RFC 2819 RMON MIB RFC 2863 The Interfaces Group MIB RFC 2925 Ping MIB RFC 3414 SNMP-User based-SM MIB RFC 3415 SNMP-View based-ACM MIB RFC 3418 MIB for SNMPv3 RFC 3621 Power Ethernet MIB
Network management	IEEE 802.1AB Link Layer Discovery Protocol (LLDP)	RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)	ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) SNMPv1/v2c/v3
Security	IEEE 802.1X Port Based Network Access Control RFC 1492 TACACS+ RFC 2138 RADIUS Authentication	RFC 2139 RADIUS Accounting RFC 2865 RADIUS (client only) RFC 2866 RADIUS Accounting	Secure Sockets Layer (SSL) SSHv2 Secure Shell

HP 5120 EI Switch Series accessories

Modules

HP 5500 2-port 10GbE XFP Module (JD359B)

HP 5500 2-port 10GbE Local Connect Module (JD360B)

HP 5500 1-port 10GbE XFP Module (JD361B)

HP 5500/5120 2-port 10GbE SFP+ Module (JD368B)

HP 5500/4800 2-port GbE SFP Module (JD367A)

NEW HP 5500/5120 2-port 10GBASE-T Module (JG535A)

Transceivers

HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A)

HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A)

HP X125 1G SFP LC LH70 Transceiver (JD063B)

HP X130 10G SFP+ LC SR Transceiver (JD092B)

HP X130 10G SFP+ LC LRM Transceiver (JD093B)

HP X130 10G SFP+ LC LR Transceiver (JD094B)

HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable (JD095C)

HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable (JD096C)

HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable (JD097C)

HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable (JG081C)

HP X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable (JC784C)

HP X130 10G XFP LC LR Transceiver (JD108B)

HP X130 10G XFP LC SR Transceiver (JD117B)

HP X120 1G SFP LC SX Transceiver (JD118B)

HP X120 1G SFP LC LX Transceiver (JD119B)

HP X135 10G XFP LC ER Transceiver (JD121A)

HP X120 1G SFP LC BX 10-U Transceiver (JD098B)

HP X120 1G SFP LC BX 10-D Transceiver (JD099B)

HP X120 1G SFP RJ45 T Transceiver (JD089B)

HP X130 10G SFP+ LC ER 40km Transceiver (JG234A)

Cables

HP X230 Local Connect 100cm CX4 Cable (JD364B)

HP X230 CX4 to CX4 3m Cable (JD365A)

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)

HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)

HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)

HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)

HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)

HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)
HP X230 Local Connect 50cm CX4 Cable (JD363B)

Power supply

HP RPS 800 Redundant Power Supply (JD183A)
HP RPS1600 Redundant Power System (JG136A)
HP RPS1600 1600W AC Power Supply (JG137A)

Power cords

HP X290 1000 A JD5 2m RPS Cable (JD187A)
HP X290 500/800 1m RPS Cable (JD190A)

Learn more at
hp.com/networking

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2010–2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft is a U.S. registered trademark of the Microsoft group of companies.

4AA3-0725ENW, February 2014, Rev. 6

