



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided equipment	Installation guide Warranty card
--------------------	-------------------------------------

Physical

Color	Black
Depth	26.88 in (68.27 cm)
Height	5.12 in (13 cm)
Net Weight	200.62 lb(US) (91 kg)
Number of rack unit	3U
Maximum Width	17.01 in (43.2 cm)

Conformance

Standards	OSHDP
-----------	-------

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery voltage	192V
Battery type	Lead-Acid battery
RBC Quantity	2

Ordering and shipping details

GTIN	00731304301776
Package weight(Lbs)	232.59 lb(US) (105.5 kg)

Packing Units

Package 1 Height	16.54 in (42 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	39.37 in (100 cm)
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------