



Touchboards
205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

REALiS
USA.CANON.COM/PROJECTORS

2015 CANON PROJECTOR LINE-UP

REALiS LCOS AND DLP / LCD MODELS



BRING CONTENT TO LIFE IN CANON CLARITY

Canon REALiS LCOS Projectors are engineered to meet the exacting requirements of professionals who accept nothing but the best. At its core, every REALiS LCOS projector features these three key Canon components that were developed to work as a whole to provide outstanding image quality and performance.

- Genuine Canon Optics
- Canon's LCOS Technology with AISYS-enhancement
- Canon's Advanced Color Management

REALiS LCOS projectors feature a line-up of installation, compact installation and portable models that are designed for a variety of professional applications and environments, including higher education, corporate, simulation, engineering, and museums and galleries.

Canon DLP and LCD projectors also deliver high image quality and value. A variety of models are available in this line to satisfy a wide range of users with different needs, including ultra short throw, short throw, and portable models that are compact and economical to run.



REALiS LCOS PROJECTORS



DLP & LCD
PROJECTORS

INSTALLATION LCOS PROJECTORS

REALiS



REALiS WUX6000 WUX6000 D

INSTALLATION LCOS PROJECTORS

WUXGA 1920 X 1200	6000 Lumens
-----------------------------	-----------------------

- LCOS Technology with AISYS-Enhancement
- Native WUXGA Resolution (1920 x 1200)
- 6000 Lumens with up to 2000:1 Contrast Ratio
- Multiple Genuine Canon Interchangeable Lens Options Provide Exceptional Quality and Flexibility
- Motorized Lens Shift, 4-Point Keystone Correction and Lens Position Memory
- Built-in Edge Blending
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- WUX6000 D Features DICOM Simulation Mode*



REALiS WUX5000 WUX5000 D

INSTALLATION LCOS PROJECTORS

WUXGA 1920 X 1200	5000 Lumens
-----------------------------	-----------------------

- LCOS Technology with AISYS-Enhancement
- Native WUXGA Resolution (1920 x 1200)
- 5000 Lumens with 1000:1 Contrast Ratio
- Multiple Genuine Canon Interchangeable Lens Options Provide Exceptional Quality and Flexibility
- Motorized Lens Shift and Keystone Correction
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- WUX5000 D Features DICOM Simulation Mode*







REALiS SX6000 SX6000 D

INSTALLATION LCOS PROJECTORS

SXGA+ 1400 X 1050	6000 Lumens
-----------------------------	-----------------------

- LCOS Technology with AISYS-Enhancement
- Native SXGA+ Resolution (1400 x 1050)
- 6000 Lumens with 1000:1 Contrast Ratio
- Multiple Genuine Canon Interchangeable Lens Options Provide Exceptional Quality and Flexibility
- Motorized Lens Shift and Keystone Correction
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- SX6000 D Features DICOM Simulation Mode*

GENUINE CANON LENS OPTIONS FOR INSTALLATION LCOS PROJECTORS

					
	ULTRA WIDE ANGLE LENS RS-IL03WF	SHORT FOCUS ZOOM LENS RS-IL05WZ	STANDARD ZOOM LENS RS-IL01ST	LONG FOCUS ZOOM LENS RS-IL02LZ	ULTRA LONG FOCUS ZOOM LENS RS-IL04UL
THROW DISTANCE	2.2 - 17 ft. (0.7 - 5.2m) ●● 2.2 - 16.7 ft. (0.7 - 5.1m) ●●	2.9 - 64 ft. (0.9 - 19.5m) ●● 2.9 - 65.2 ft. (0.9 - 19.9m) ●●	4.2 - 95.1 ft. (1.3 - 29m) ●● 4.2 - 94.5 ft. (1.3 - 28.8m) ●●	6.2 - 159.1 ft. (1.9 - 48.5m) ●● 6.2 - 158.4 ft. (1.9 - 48.3m) ●●	15 - 292 ft. (4.6 - 89.0m) ●● 15 - 290.6 ft. (4.6 - 88.6m) ●●
THROW RATIO	0.80:1 ●● 0.85:1 ●●	1.00 - 1.50:1 ●● 1.06 - 1.58:1 ●●	1.49 - 2.24:1 ●● 1.57 - 2.36:1 ●●	2.19 - 3.74:1 ●● 2.31 - 3.94:1 ●●	3.55 - 6.94:1 ●● 3.74 - 7.32:1 ●●
ZOOM RATIO	Fixed	1.5x Optical Zoom Lens (Powered)	1.5x Optical Zoom Lens (Powered)	1.7x Optical Zoom Lens (Powered)	1.95x Optical Zoom Lens (Powered)
IMAGE SIZE	40" - 300"	40" - 600"	40" - 600"	40" - 600"	60" - 600"
F NUMBER	F2.0	F2.09 - 2.34	F1.89 - 2.65	F1.99 - 2.83	F2.34 - 2.81
FOCAL LENGTH	12.8mm	15.56 - 23.34mm	23.0 - 34.5mm	34.0 - 57.7mm	53.6 - 105.6mm
LENS SHIFT⁹	V: ±5% / H: ±2%	V: -15% - 55% / H: ±10% ●● V: -12% - 50% / H: ±10% ●●	V: -15% - 55% / H: ±10% ●● V: -12% - 50% / H: ±10% ●●	V: -15% - 55% / H: ±10% ●● V: -12% - 50% / H: ±10% ●●	V: -15% - 55% / H: ±10% ●● V: -12% - 50% / H: ±10% ●●

Specified with: ● WUX6000 / WUX6000 D ● WUX5000 / WUX5000 D ● SX6000 / SX6000 D

*DICOM Simulation Mode available on D Models only. These models have not been cleared or approved for medical diagnosis and should not be used for these purposes.

⁹The maximum upward shift and the maximum horizontal shift cannot be used simultaneously.

COMPACT INSTALLATION & PORTABLE LCOS PROJECTORS REALiS



REALiS WUX500 WUX500D

COMPACT INSTALLATION

WUXGA
1920 X 1200

5000
Lumens

- LCOS Technology with AISYS-Enhancement
- Native WUXGA Resolution (1920 x 1200)
- 5000 Lumens with up to 2000:1 Contrast Ratio
- Throw Ratio: 1.39-2.51:1
- HDBaseT™ & Wi-Fi*
- Genuine Canon Lens with Consistent Brightness throughout 1.8x Zoom Range
- Compact Design, 4-Point Keystone Correction and Manual Lens Shift
- Built-in Edge Blending
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- WUX500 D Features DICOM Simulation Mode*



REALiS WUX450 WUX450D

COMPACT INSTALLATION

WUXGA
1920 X 1200

4500
Lumens

- LCOS Technology with AISYS-Enhancement
- Native WUXGA Resolution (1920 x 1200)
- 4500 Lumens with up to 2000:1 Contrast Ratio
- Throw Ratio: 1.39-2.51:1
- Genuine Canon Lens with Consistent Brightness throughout 1.8x Zoom Range
- Compact Design, 4-Point Keystone Correction and Manual Lens Shift
- Built-in Edge Blending
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- WUX450 D Features DICOM Simulation Mode*



REALiS WUX400ST WUX400ST D

SHORT THROW COMPACT INSTALLATION

WUXGA
1920 X 1200

4000
Lumens

- LCOS Technology with AISYS-Enhancement
- Native WUXGA Resolution (1920 x 1200)
- 4000 Lumens with up to 2000:1 Contrast Ratio
- Short Throw Capability with 0.56:1 Throw Ratio
- Genuine Canon Lens with 0-75% Vertical Lens Shift for Flexible Installation
- Compact Design, 4-Point Keystone Correction and Manual Lens Shift
- Built-in Edge Blending
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- WUX400ST D Features DICOM Simulation Mode*



REALiS WX520 WX520D

COMPACT INSTALLATION

WXGA+
1440 X 900

5200
Lumens

- LCOS Technology with AISYS-Enhancement
- Native WXGA+ Resolution (1440 x 900)
- 5200 Lumens with up to 2000:1 Contrast Ratio
- Throw Ratio: 1.43-2.57:1
- Genuine Canon Lens with Consistent Brightness throughout 1.8x Zoom Range
- Compact Design, 4-Point Keystone Correction and Manual Lens Shift
- Built-in Edge Blending
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- WX520 D Features DICOM Simulation Mode*



REALiS WX450ST WX450ST D

SHORT THROW COMPACT INSTALLATION

WXGA+
1440 X 900

4500
Lumens

- LCOS Technology with AISYS-Enhancement
- Native WXGA+ Resolution (1440 x 900)
- 4500 Lumens with up to 2000:1 Contrast Ratio
- Short Throw Capability with 0.57:1 Throw Ratio
- Genuine Canon Lens with 0-77% Vertical Lens Shift for Flexible Installation
- Compact Design, 4-Point Keystone Correction and Manual Lens Shift
- Built-in Edge Blending
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- WUX400ST D Features DICOM Simulation Mode*



REALiS SX80 Mark II SX80 Mark IID

PORTABLE LCOS PROJECTORS

SXGA+
1400 X 1050

3000
Lumens

- LCOS Technology with AISYS-Enhancement
- Native SXGA+ Resolution (1400 x 1050)
- 3000 Lumens with 900:1 Contrast Ratio
- Genuine Canon 1.5x Powered Zoom Lens
- Vertical Keystone Correction
- Compact, Ultra-Portable Design
- Photo Image Mode
- Versatile Connectivity including HDMI and DVI
- Network Management including Creston Connectivity and AMX Device Discovery
- SX80 Mark II D Features DICOM Simulation Mode*



LV-WX300USTi

ULTRA SHORT THROW INTERACTIVE

WXGA
1280 X 800

3000
Lumens

- DLP Technology with BrilliantColor™ System
- Native WXGA Resolution (1280 x 800)
- 3000 Lumens with up to 7500:1 Contrast Ratio
- Ultra Short Throw with 0.35:1 Throw Ratio
- Project 100" Diagonal Image from Only 18-Inches from Projector
- Interactive Projection
- Dual HDMI Inputs



LV-WX300

COMPACT PORTABLE

WXGA
1280 X 800

3000
Lumens

- DLP Technology with BrilliantColor™ System
- Native WXGA Resolution (1280 x 800)
- 3000 Lumens with 2300:1 Contrast Ratio
- Throw Ratio: 1.50-1.65:1
- 1.1x Optical Zoom Lens
- Versatile Connectivity including HDMI and Network Management



LV-X300

COMPACT PORTABLE

XGA
1024 X 768

3000
Lumens

- DLP Technology with BrilliantColor™ System
- Native XGA Resolution (1024 x 768)
- 3000 Lumens with 2300:1 Contrast Ratio
- Throw Ratio: 1.86-2.04:1
- 1.1x Optical Zoom Lens
- Versatile Connectivity including HDMI and Network Management



LV-WX300UST

ULTRA SHORT THROW

WXGA
1280 X 800

3000
Lumens

- DLP Technology with BrilliantColor™ System
- Native WXGA Resolution (1280 x 800)
- 3000 Lumens with up to 7500:1 Contrast Ratio
- Ultra Short Throw with 0.35:1 Throw Ratio
- Project 100" Diagonal Image from Only 18-Inches from Projector
- Dual HDMI Inputs



LV-7490

COMPACT PORTABLE

XGA
1024 X 768

4000
Lumens

- LCD Technology
- Native XGA Resolution (1024 x 768)
- 4000 Lumens with 2000:1 Contrast Ratio
- 1.2x Optical Zoom Lens
- Versatile Connectivity including HDMI and Network Management



LV-S300

COMPACT PORTABLE

SVGA
800 X 600

3000
Lumens

- DLP Technology with BrilliantColor™ System
- Native SVGA Resolution (800 x 600)
- 3000 Lumens with 2300:1 Contrast Ratio
- Throw Ratio: 1.86-2.04:1
- 1.1x Optical Zoom Lens
- Versatile Connectivity including HDMI and Network Management



LV-WX300ST

COMPACT SHORT THROW

WXGA
1280 X 800

3000
Lumens

- DLP Technology with BrilliantColor™ System
- Native WXGA Resolution (1280 x 800)
- 3000 Lumens with 2300:1 Contrast Ratio
- Short Throw Capability with 0.49:1 Throw Ratio
- Versatile Connectivity including HDMI and Network Management



LV-X300ST

COMPACT SHORT THROW


















XGA
1024 X 768

3000
Lumens

- DLP Technology with BrilliantColor™ System
- Native XGA Resolution (1024 x 768)
- 3000 Lumens with 2300:1 Contrast Ratio
- Short Throw Capability with 0.61:1 Throw Ratio
- Versatile Connectivity including HDMI and Network Management

*DICOM Simulation Mode available on D Models only. These models have not been cleared or approved for medical diagnosis and should not be used for these purposes.

SPECIFICATIONS CHART

REALIS PRO AV LCOS PROJECTORS										DLP & LCD PROJECTORS																								
INSTALLATION			COMPACT INSTALLATION						PORTABLE	PORTABLE																								
 REALiS WUX6000 WUX6000 D			 REALiS WUX5000 WUX5000 D		 REALiS SX6000 SX6000 D		 REALiS WUX500 WUX500 D		 REALiS WUX450 WUX450 D		 REALiS WUX400ST WUX400ST D		 REALiS WX520 WX520 D		 REALiS WX450ST WX450ST D		 REALiS SX80 Mark II SX80 Mark II D		 LV-WX300USTi		 LV-WX300UST		 LV-WX300ST		 LV-WX300		 LV-7490		 LV-X300ST		 LV-X300		 LV-S300	
ITEM CODE	9726B002 9726B008 (D Model)		5748B002 5748B008 (D Model)		5749B002 5749B013 (D Model)		0071C002 0071C011 (D Model)		8264B002 8264B010 (D Model)		8678B002 8678B010 (D Model)		8265B002 8265B010 (D Model)		8679B002 8679B010 (D Model)		4232B002 4232B005 (D Model)		0647C002		0646C002		9880B002		9877B002		5315B002		9882B002		9878B002		9964B002	
BRIGHTNESS FULL POWER SAVER	6000 Lumens 4660 Lumens		5000 Lumens 4000 Lumens		6000 Lumens		5000 Lumens 3800 Lumens		4500 Lumens 3460 Lumens		4000 Lumens 3080 Lumens		5200 Lumens 4000 Lumens		4500 Lumens 3460 Lumens		3000 Lumens		3000 Lumens 2500 Lumens		3000 Lumens 2100 Lumens		4000 Lumens		3000 Lumens 2100 Lumens									
NATIVE RESOLUTION	1920 x 1200 (WUXGA)			1400 x 1050 (SXGA+)			1920 x 1200 (WUXGA)			1440 x 900 (WXGA+)			1400 x 1050 (SXGA+)			1280 x 800 (WXGA)				1024 x 768 (XGA)		1024 x 768 (XGA)		800 x 600 (SVGA)										
CONTRAST	2000:1		1000:1			2000:1						900:1			7500:1				2300:1		2000:1		2300:1											
LENS	THROW DISTANCE	3.9 – 53.1 ft. (1.2 – 16.2m)						1.15 – 11.94 ft. (0.35 – 3.64m)		3.9 – 54.5 ft. (1.2 – 16.6m)		1.18 – 12.24 ft. (0.36 – 3.73m)		3.9–29.9 ft. (1.2–9.1m)		11.10–17.55 in. (0.282–0.446m)				29.1–49.9 in. (0.74–1.26m)		W: 6.23–15.7 ft. (1.9–4.8m) T: 6.88–14.10 ft. (2.1–4.3m)		4.59–41.66 ft. (1.4–12.7m)		29.1–58.2 in. (0.74–1.48m)		W: 7.54–18.7 ft. (2.3–5.7m) T: 8.20–16.40 ft. (2.5–5.0m)		W: 7.54–18.7 ft. (2.3–5.7m) T: 8.20–16.40 ft. (2.5–5.0m)				
	THROW RATIO	5 OPTIONAL INTERCHANGEABLE LENSES • ULTRA WIDE ANGLE LENS RS-IL03WF • SHORT FOCUS ZOOM LENS RS-IL05WZ • STANDARD ZOOM LENS RS-IL01ST • LONG FOCUS ZOOM LENS RS-IL02LZ • ULTRA LONG FOCUS ZOOM LENS RS-IL04UL						1.39 – 2.51:1		0.56:1		1.43 – 2.57:1		0.57:1		1.48–2.18:1		0.35:1				0.49:1		1.50–1.65:1		1.75–2.13:1		0.61:1		1.86–2.04:1		1.86–2.04:1		
	ZOOM RATIO	See lens chart on INSTALLATION LCOS PROJECTORS line-up page for more information.						1.8x		1.35x		1.8x		1.35x		1.5x		Fixed				Fixed		1.1x, Manual		1.2x, Manual		Fixed		1.1x, Manual		1.1x, Manual		
	IMAGE SIZE	See lens chart on INSTALLATION LCOS PROJECTORS line-up page for more information.						40 – 300"		30 – 300"		40 – 300"		30 – 300"		40 – 300"		80 – 100"				70–120"		W: 60–150" T: 60–120"		40–300"		60–120"		W: 60–150" T: 60–120"		W: 60–150" T: 60–120"		
	F NUMBER	See lens chart on INSTALLATION LCOS PROJECTORS line-up page for more information.						F2.8		F2.7		F2.8		F2.7		F1.95 – 2.6		F2.5				F2.60		F2.56 – 2.8		F1.6–1.76		F2.60		F2.56 – 2.8		F2.56 – 2.8		
	FOCAL LENGTH	See lens chart on INSTALLATION LCOS PROJECTORS line-up page for more information.						21.7 – 39.0mm		8.8mm		21.7 – 39.0 mm		8.8mm		16.6 – 24.8mm		5.1mm				6.9mm		21.0 – 23.1mm		22.3–26.8mm		6.9mm		21.0 – 23.1mm		21.0 – 23.1mm		
	LENS SHIFT	See lens chart on INSTALLATION LCOS PROJECTORS line-up page for more information.						V: 0 – 60%; H: ±10%		V: 0 – 75%; H: ±10%		V: 0 – 62%; H: ±10%		V: 0 – 77%; H: ±10%		-		75%, Fixed				-		-		-		-		-		-		
IMAGE MODES	Standard, Presentation, Dynamic, Video, Cinema, Photo, sRGB, Vivid Photo, User 1–5, DICOM SIM*						Standard, Presentation, Dynamic, Video, Photo/sRGB, User 1–5, DICOM SIM*		Standard, Presentation, Dynamic, Video, Photo/sRGB, User 1 – 5, DICOM SIM*						Standard, Presentation, Movie, sRGB, Photo, DICOM SIM*		Standard, Presentation, Dynamic, Photo/sRGB, User				Presentation, Standard, sRGB, Movie, User 1–2		Presentation, Standard, High Contrast, Cinema, Blackboard (Green), Colorboard, User 1–4		Presentation, Standard, sRGB, Movie, User 1–2									
INPUTS	HDMI	Digital PC / Digital Video Input (Supports Deep Color)														Digital Video Input (Supports Deep Color)		Digital PC / Digital Video Input		Digital PC / Digital Video Input		-		Digital PC / Digital Video Input		-								
	DVI	DVI-I: Analog PC / Digital PC Input		DVI-D: Digital PC Input		DVI-I: Analog PC / Digital PC Input						DVI-I: Analog PC / Digital PC Input / Digital Video Input		-		-		-		-		-		-		-		-						
	RJ-45	Network (1000BASE-T / 100BASE-TX / 10BASE-T)		Network (100BASE-TX / 10BASE-T)		Network (1000BASE-T / 100BASE-TX / 10BASE-T)						Yes		Network Connection (100BASE-TX / 10BASE-T)				Yes		Network Connection (100BASE-TX / 10BASE-T)		-												
	MINI D-SUB 15	Analog RGB / Component Video Input						Analog PC / Component Video Input						Analog PC Input		Analog PC / Component Video Input				Analog RGB / Component Video / S-video Input		Analog PC / Component Video Input												
	MINI JACK	Audio Input x2, Audio Output x1, Wired Remote Control Connection		Audio Input x2, Audio Output x1		Audio Input x2, Audio Output x1, Wired Remote Control Connection						Audio Input x 3, Audio Output x 1		Audio Input, Audio Output, Mic Input				Audio Input x1, Audio Output x1		Audio Input x2, Audio Output x1		Audio Input x1, Audio Output x1												
	DSUB9	RS-232C Control																																
	USB TYPE A	USB data transfer (JPEG still images) / Service Port		-		-		USB data transfer (JPEG still images) / Service Port						USB Connection / PictBridge input		For LV-FM01 (Finger Touch Module)		-		-		-		-		-		-		-				
	USB TYPE B	-		-		-		-		-		-		-		-		Mouse Control / Firmware Update / Mini USB B: Interactive Function*				Service Port		-		Service Port								
	WI-FI*	-		-		-		802.11 b/g/n		-		-		-		-		-				-		-		-		-		-				
	HDBaseT	-		-		-		Image, audio and control signal		-		-		-		-		-				-		-		-		-		-				
INTERNAL SPEAKER	5W Built-in Mono Speakers														1W Built-in Mono Speakers		Dual 10W Built-in Stereo Speakers		10W Built-in Mono Speakers		10W Built-in Mono Speakers		10W Built-in Mono Speakers		10W Built-in Mono Speakers		2W Built-in Mono Speakers							
LAMP LIFE (FULL/ POWER SAVER)	3000 Hours / 4000 Hours		3000 Hours			3000 Hours / 5000 Hours						2000 Hours / 2500 Hours		5000 Hours / 8000 Hours				4000 Hours / 6000 Hour		5000 Hours / 6000 Hours		3000 Hours / 5000 Hour		4000 Hours / 6000 Hour		5000 Hours / 6000 Hours		5000 Hours / 6000 Hours						
FAN NOISE (FULL/ POWER SAVER)	40dB / 36dB		40dB			37dB / 30dB		38dB / 32dB				35dB / 31dB		33dB / 29dB				36db / 29dB		35db / 29dB		29db / 25dB		36db / 29dB		35db / 29dB		35db / 29dB						
POWER CONSUMPTION (FULL/ POWER SAVER)	455W / 360W		450W		435W		365W / 295W		365W / 295W		365W / 295W		365W / 295W		355W / 285W		330W / 270W				300W / 240W		330W / 270W		330W / 275W		322W		330W / 270W		330W / 275W		330W / 275W	
DIMENSIONS (W X D X H)	15.0" x 16.9" x 6.7"			13.3" x 14.6" x 5.4"		13.3" x 16.3" x 5.3"		13.3" x 16.3" x 5.3"		13.3" x 16.3" x 5.3"		13.3" x 16.3" x 5.3"		13.3" x 16.3" x 5.3"		13.3" x 13.6" x 4.8"		11.3" x 14.7" x 7.6"		11.3" x 14.7" x 6.6"		11.1" x 10.53" x 4.64"		11.1" x 9.13" x 4.5"		13.8" x 10.0" x 3.4"		11.1" x 10.53" x 4.64"		11.1" x 9.13" x 4.5"		11.1" x 9.13" x 4.5"		
WEIGHT	18.7 lb. (8.4kg)			13 lb. (5.9kg)			13.9 lb. (6.3kg)		13 lb. (5.9kg)		13.9 lb. (6.3kg)		11.4 lb. (5.2kg)		11 lb. (5kg)				6.2 lb. (2.8kg)		5.5 lb. (2.5kg)		7.28 lb. (3.3kg)		6.2 lb. (2.8kg)		5.5 lb. (2.5kg)		5.5 lb. (2.5kg)					

*DICOM Simulation Mode available in D Models only. These models have not been cleared or approved for medical diagnosis and should not be used for these purposes. *LV-WX300USTi Only

RECOMMENDED ACCESSORIES (List includes most common accessories. For a complete list, including pricing, please speak with a Canon representative.)

ITEM	 ULTRA WIDE ANGLE LENS RS-IL03WF	 SHORT FOCUS ZOOM LENS RS-IL05WZ	 STANDARD ZOOM LENS RS-IL01ST	 LONG FOCUS ZOOM LENS RS-IL02LZ
ITEM CODE	4968B001	8168B001	4966B001	4967B001
COMPATIBILITY	REALiS WUX6000 / WUX6000 D, REALiS WUX5000 / WUX5000 D, REALiS SX6000 / SX6000 D			
ITEM	 ULTRA LONG FOCUS ZOOM LENS RS-IL04UL	 REPLACEMENT LAMP RS-LP09	 REPLACEMENT LAMP RS-LP08	 REPLACEMENT LAMP RS-LP07
ITEM CODE	6064B001	9963B001	8377B001	5017B001
COMPATIBILITY	REALiS WUX6000 / WUX6000 D, REALiS WUX5000 / WUX5000 D, REALiS SX6000 / SX6000 D	REALiS WUX6000 / WUX6000 D	REALiS WUX500 / WUX500 D, REALiS WUX450 / WUX450 D, REALiS WUX400ST / WUX400ST D, REALiS WX520 / WX520 D, REALiS WX450ST / WX450ST D	REALiS WUX5000 / WUX5000 D, REALiS SX6000 / SX6000 D
ITEM	 REMOTE CONTROLLER RS-RC05	 COMPACT INSTALL SHIPPING CASE	 COMPACT INSTALL SOFT CARRYING CASE	 PORTRAIT MODE MIRROR ADAPTER
ITEM CODE	5750B001	2482V754	2482V755	2829V783
COMPATIBILITY	REALiS WUX6000 / WUX6000 D, REALiS SX6000 / SX6000 D, REALiS WUX500 / WUX500 D, REALiS WUX450 / WUX450 D, REALiS WUX400ST / WUX400ST D, REALiS WX520 / WX520 D, REALiS WX450ST / WX450ST D*	REALiS WUX500 / WUX500 D, REALiS WUX450 / WUX450 D, REALiS WUX400ST / WUX400ST D, REALiS WX520 / WX520 D, REALiS WX450ST / WX450ST D	REALiS WUX500 / WUX500 D, REALiS WUX450 / WUX450 D, REALiS WX520 / WX520 D	
ITEM	 JRWX450 UNDER TABLE MOUNT	 REPLACEMENT AIR FILTER RS-FL02	 TOP COVER RS-TC01 (DARK GRAY)	 OPTIONAL FEET RS-FT01 (PACK OF FOUR)
ITEM CODE	Item available through Crimson AV	8379B001	5471B001	8380B001
COMPATIBILITY	REALiS WUX400ST / WUX400ST D, REALiS WX450ST / WX450ST D	REALiS WUX500 / WUX500 D, REALiS WUX450 / WUX450 D, REALiS WUX400ST / WUX400ST D, REALiS WX520 / WX520 D, REALiS WX450ST / WX450ST D	REALiS WUX6000 / WUX6000 D, REALiS WUX5000 / WUX5000 D, REALiS SX6000 / SX6000 D	REALiS WUX500 / WUX500 D, REALiS WUX450 / WUX450 D, REALiS WUX400ST / WUX400ST D, REALiS WX520 / WX520 D, REALiS WX450ST / WX450ST D

*With wired connection option.



©2015 Canon U.S.A., Inc. All rights reserved. Not responsible for typographical errors. Specifications subject to change without notice. Products not shown to scale. Certain images and effects are simulated. Canon and REALiS are registered trademarks of Canon Inc. in the United States and may also be trademarks or registered trademarks in other countries. DICOM is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information. HDBaseT(TM) and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. Wi-Fi and the Wi-Fi CERTIFIED logo are registered trademarks of the Wi-Fi Alliance. All other products and brand names may be registered trademarks, trademarks or service marks of their respective owners in the United States and/or other countries.



USA.CANON.COM/PROJECTORS | 1-800-OK-CANON
Canon U.S.A., Inc. One Canon Park, Melville, NY 11747