

SmartRack® Euro-Series Rack Enclosures







Key Features

- 42U (2000 mm) or 47U (2200 mm) height
- 600 mm or 800 mm width
- 1000 mm or 1200 mm depth
- Load capacity up to 1360 kg
- Toolless mounting for vertical PDUs
- Available with or without modular side panels

House Critical Equipment

SmartRack enclosures have sturdy steel frames and locking cabinets to secure and organize up to 1360 kg of EIA-standard rack equipment. They provide safe homes for servers, storage, network hardware and all the indispensable devices that keep organizations efficient and productive.

Provide Efficient Cooling

Front-to-rear airflow supports efficient hot-aisle/cold-aisle configurations and exceeds server manufacturer requirements to keep equipment operating reliably.

Support Diverse Applications

Several heights, widths, depths and other variations are available, with a wide range of configuration options.

Make Installation Fasier

SmartRack enclosures have been designed from the perspective of the installer, and that philosophy shows in the little details that make every installation task quicker and easier. Features like quick-adjust mounting rails, modular side panels and toolless mounting slots for



Toolless Mounting Slots

vertical PDUs and cable managers facilitate installation and configuration. Seamless compatibility with all EIA-standard rack equipment ensures trouble-free setup.



SRX42UB – SmartRack 42U Standard-Width, Standard-Depth Rack Enclosure with Side Panels

SPECIFICATIONS

C €	Rack Spaces	Unit Height (mm)	Unit Width (mm)	Unit Depth (mm)	Maximum Device Depth (mm)	Side Panels	Stationary Weight Capacity (kg)	Rolling Weight Capacity (kg)	C €	Rack Spaces	Unit Height (mm)	Unit Width (mm)	Unit Depth (mm)	Maximum Device Depth (mm)	Side Panels	Stationary Weight Capacity (kg)	Rolling Weight Capacity (kg)	
Standard Width & Standard Depth – Low/medium-density server applications. Standard Width & Extra Depth – Medium/high-density server applications.																		
SRX42UB	42U	2000	600	1000	850	Yes (4)	1360	1020	SRX42UBDP	42U	2000	600	1200	1050	Yes (4)	1360	1020	
SRX42UBEXP	42U	2000	600	1000	850	No	1360	1020	SRX42UBDPEXP	42U	2000	600	1200	1050	No	1360	1020	
SRX47UB	47U	2200	600	1000	850	Yes (4)	1360	1020	SRX47UBDP	47U	2200	600	1200	1050	Yes (4)	1360	1020	
SRX47UBEXP	47U	2200	600	1000	850	No	1360	1020	SRX47UBDPEXP	47U	2200	600	1200	1050	No	1360	1020	
Extra Width & Standar	d Depti	ı – Netwo	orking ar	nd blade :	server ap	plications.			Extra Width & Extra Dep	Extra Width & Extra Depth – High-density networking and blade server applications.								
SRX42UBWD	42U	2000	800	1000	850	Yes (4)	1360	1020	SRX42UBDPWD	42U	2000	800	1200	1050	Yes (4)	1360	1020	
SRX42UBWDEXP	42U	2000	800	1000	850	No	1360	1020	SRX42UBDPWDEXP	42U	2000	800	1200	1050	No	1360	1020	
SRX47UBWD	47U	2200	800	1000	850	Yes (4)	1360	1020	SRX47UBDPWD	47U	2200	800	1200	1050	Yes (4)	1360	1020	
SRX47UBWDEXP	47U	2200	800	1000	850	No	1360	1020	SRX47UBDPWDEXP	47U	2200	800	1200	1050	No	1360	1020	

Standards include EIA/ECA-310-E, IEC 60297-3-100, UL 60950 and RoHS. 5-year limited warranty. See www.tripplite.com for details, including complete warranty terms and conditions.

Contact Tripp Lite for more information:

Tripp Lite United Kingdom +44.01635.887396 | info-uk@tripplite.com

Tripp Lite Middle East +971.4.887.1633 | infome@tripplite.com

Tripp Lite East/West Africa +254.731.137.202 | salesint@tripplite.com

Tripp Lite Asia Pacific and Israel +972.54.530.4120 | salesint@tripplite.com

Tripp Lite Eastern Europe +36.70.388.7680 | salesint@tripplite.com

Tripp Lite France +33.0.68.388.9150 | salesint@tripplite.com



Tripp Lite Corporate Headquarters 1111 West 35th Street, Chicago, IL 60609 USA +1.773.869.1212 • www.tripplite.com