



# Power Extension Cord, NEMA 5-15P to NEMA 5-15R - 13A, 120V, 16 AWG, 1 ft. (0.31 m), Black

# MODEL NUMBER: P024-001-13A



1 ft. extension cord with 5-15P and 5-15R connectors connects bulky power transformers without blocking adjacent outlets on your PDU.

### Features

1-ft. (0.31 m) Extension Cord Connects PCs, Printers, Monitors and Other EquipmentThis cord is recommended for home/office desktop computer applications, home theater setups or other applications where multiple devices are plugged into a surge protector, PDU or UPS system. It allows you to connect bulky power adapters to a NEMA 5-15R outlet without blocking adjacent outlets. The 1-ft. (0.31 m) length helps reduce cable clutter.

## Highlights

- Recommended for powering computers, printers and other home/office peripherals
- 1-ft. (0.31 m) length allows flexibility in placing devices, while avoiding cable clutter
- Ideal replacement for worn-out or missing 1-ft. (0.31 m) extension cord

#### **Applications**

- Connect devices like computers, servers and monitors to a PDU in your data center
- Extend an existing power connection up to 1-ft. (0.31 m) to more easily place a device or reach a power source in a rack
- Provide a high-quality replacement for a worn-out or missing power cord

#### **Package Includes**

 P024-001-13A 1-ft. (0.31 m) Extension Cord, NEMA 5-15P to NEMA 5-15R, 1-ft. (0.31 m), Black

# **Specifications**

OVERVIEW		
UPC Code	037332180391	
Device Compatibility	Computer; Monitor/HDTV; Printer; Server; UPS; PDU	
Country/Region	North America	
INPUT		
Maximum Input Amps	13	
Voltage Compatibility (VAC)	125	
CONNECTIONS		
Side A - Connector 1	NEMA 5-15P	
Side B - Connector 1	NEMA 5-15R	
PHYSICAL		





Product Warranty Period (Worldwide)	Lifetime limited warranty
WARRANTY & SUPPORT	
Product Compliance	RoHS
Product Certifications	cUL Listed; UL Listed
STANDARDS & COMPLIANCE	
Coiled Power Cord	No
Locking Plug	No
High Voltage	No
Angled Plug	No
Antibacterial	No
FEATURES & SPECIFICATIONS	
Storage Humidity Range	10% to 65% RH
Operating Humidity Range	10% to 65% RH
Storage Temperature Range	-4° to 140°F (-20° to 60°C)
Operating Temperature Range	-4° to 140°F (-20° to 60°C)
ENVIRONMENTAL	
Shipping Weight (kg)	0.09
Shipping Weight (lbs.)	0.20
Shipping Dimensions (hwd / cm)	25.40 x 18.03 x 0.25
Shipping Dimensions (hwd / in.)	10.00 x 7.10 x 0.10
Cable Length (m)	
Cable Length (ft.)	
Wire Gauge (OD - mm <sup>2</sup> )	1.31
Wire Gauge (AWG)	16
Number of Conductors	3
Cable Outer Diameter (OD)	8.5mm
Power Cord Jacket Type	SJT
Cable Jacket Rating	VW-1
Cable Jacket Material	PVC
Cable Jacket Color	Black
Plug Color	Black





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.