



USB 3.0 SuperSpeed Extension Cable (A M/F), Black, 6 ft. (1.83 m)

MODEL NUMBER: U324-006-BK





Highlights

- 6-ft. SuperSpeed USB 3.0 A-A Extension Cable
- 10 times faster than USB 2.0, with transfer rates up to 5 Gbps

System Requirements

• Computers and Peripherals with USB 3.0 capabilities

Package Includes

• 6-ft. SuperSpeed USB 3.0 A-A Extension cable - Black

Extends a USB 3.0 cable an additional 6ft

Features

- 6-ft. USB 3.0 SuperSpeed Extension Cable Black
- SuperSpeed USB is 10 times faster than Hi-Speed USB, with transfer rates up to 5 Gbps.
- Sync-N-Go technology minimizes user wait-time.
- Provides Optimized Power Efficiency...No device polling and lower active and idle power requirements.
- Backwards compatible with USB 2.0. Devices interoperate with USB 2.0 platforms. Hostssupport USB 2.0 legacy devices.

Specifications

OVERVIEW		
UPC Code	037332183156	
Technology	USB 3.x	
Cable Type	Passive	
CONNECTIONS		
Side A - Connector 1	USB 3.0 A (MALE)	
Side B - Connector 1	USB 3.0 A (FEMALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
Connector Style	Straight	
PHYSICAL		





Material of Construction	PVC
Cable Jacket Color	Black
Cable Jacket Rating	VW-1
Cable Outer Diameter (OD)	5.5MM
Cable Length (ft.)	6
Cable Length (m)	1.83
Shipping Dimensions (hwd / in.)	7.00 x 9.00 x 0.50
Shipping Dimensions (hwd / cm)	17.78 x 22.86 x 1.27
Shipping Weight (lbs.)	0.18
Shipping Weight (kg)	0.08
ENVIRONMENTAL	
Operating Temperature Range	14° to 140°F (-10° to 60°C)
Storage Temperature Range	-4° to 185°F (-20° to 85°C)
Relative Humidity	10% to 85%, Non-Condensing
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps)
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.