

HP LaserJet Enterprise M806 Printer series

Ideal for boosting productivity and efficiency across your business. Equip your teams to handle even the biggest print jobs quickly with HP's top-of-the line A3 printer – and print while on the go. Your investment is protected with easy upgrades.





Boost productivity: give workgroups the speed they need.

- Print big jobs fast at up to 56 ppm A4, and easily thanks to the extra-large input capacity of up to 4,600 pages3. Versatile paper handling options include a stapler/stacker/hole punch and booklet maker4.
- Simplify tasks with the right touch equip users to fly through tasks with the large 10.9 cm (4.3-inch) colour touchscreen.
- Simplicity all around make it easy for all to print with one common drivers.
- Don't wait, just print right away and save energy with Instant-on Technology.



- Keep a close watch, even from afar monitor and control printers centrally with HP Web Jetadmin⁶.
- Apply fleet-wide policies to protect all your HP devices with the HP Imaging and Printing Center7.
- Safeguard your printers right away with HP Instant-on Security8, and protect the sensitive data sent to your printer with the HP High-Performance Secure Hard Disk9.
- Prints with a positive ID authenticate users at the device to help secure print jobs.



- Mobile printing is simple with wireless direct printing, and enable touch-to-print convenience from a mobile
- Let employees print from mobile devices with built-in print capability or HP ePrint app and software¹⁰.
- Printing made Apple® simple let users print wirelessly from an iPad®, iPhone®, or iPod touch®11.
- Give users the power to print wirelessly from an iPad®, iPhone®, or iPod touch®.7





connected to the same network as your OS X or iOS device. Wireless performance is dependent on physical environment and distance from the access point. OS X, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the United States and other countries. AirPrint™ and the AirPrint logo are trademarks of Apple Inc.









¹ Wireless direct printing is standard in the HP Laser Jet Enterprise M806x+ D7P69A, and may be added as an option to the HP Laser Jet Enterprise M806dn and M806x+ CZ245A. Mobile device may require an app or driver. Wireless performance is dependent on physical environment and distance from the printer. For details, see hp.com/go/wirelessprinting.

² Touch-to-print capability is standard in the HP LaserJet Enterprise M806x+ D7P69A model, and may be added as an option to the HP LaserJet Enterprise M806dn and M806x+ CZ245A. Mobile device must support near field communications-enabled

A Maximum paper capacity of 4,600 sheets is standard in the HP LaserJet Enterprise M806x+ D7P69A and M806x+ CZ245A and available in the HP LaserJet Enterprise M806dn model with the optional 3,500-sheet high-capacity input tray ⁴ 2 bin stapler/stacker, 2 bin stapler/stacker/hole punch and booklet maker are optional accessories. Please purchase separately.

⁵ The HP Universal Print Driver is free and available for download at hp.com/go/upd. ⁶ HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.

⁷ HP Imaging and Printing Security Center must be purchased separately.

⁸ HP Instant-on Security is part of HP Imaging and Printing Security Center, which must be purchased separately.

⁹ HP High-Performance Secure Hard Drive is not available on the HP LaserJet Enterprise M806dn and can't be purchased separately

¹⁰ Local printing requires mobile device and printer to be on the same network or have a direct wireless connection to printer. Wireless performance is dependent upon physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP Web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See hp.com/go/mobileprinting for more details.

11 Supports OS X® Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: iPad® (all models), iPhone® (3GS or later), and iPod touch® (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be

Product walkaround

- 1. Intuitive 10.9 cm (4.3 in) colortouchscreen control panel
- 2. 500-page output bin
- 3. Hardware integration pocket (HIP) for solution integration
- 4. 100-sheet face-up straight-through output bin
- 5. Easy front-door access to HP all-in-one toner cartridge
- 6. Built-in automatic two-sided printing
- 7. Two 500-sheet input trays support media up to A3 (11 x 17 in)
- 8. 3,500-sheet high-capacity input tray supports A4/letter media
- 9. Easy-access USB port to print files directly
- 10. 100-sheet multipurpose tray handles media up to 220 g/m² (53 lb
- 11. Right-side doors provide access for clearing jams
- 12. 800 MHz processor, 1 GB standard memory
- 13. HP High-Performance Secure Hard Disk
- 14. Access port for optional Kensington-style lock
- 15. USB port (for connecting third-party devices)
- 16. Hi-Speed USB 2.0 printing port
- 17. HP Jetdirect Gigabit Ethernet print server
- 18. Foreign interface harness (for connecting third-party devices)



Series at a glance



HP LaserJet Enterprise M806dn Printer

- print speed A4 black: up to 56 ppm (duplex: up to 56
- print speed A3 black: up to 28 ppm
- up to 1200 x 1200 dpi (HP FastRes 1200)
- 1 GB RAM expandable to 1.5 GB
- 800 MHz processor
- 2 Hi-Speed USB 2.0 Host
- 1 Hi-Speed USB 2.0 Device
- 1 Gigabit Ethernet 10/100/1000T network
- 1 Foreign Interface
- 1 Hardware Integration Pocket
- 2 Internal USB Host
- Two 500-sheet input trays
- 100-sheet multi-purpose tray



HP LaserJet Enterprise M806x+ NFC/Wireless Direct HP LaserJet Enterprise M806x+ Printer Printer

- as HP LaserJet Enterprise M806dn with:
- Near Field Communications (NFC) Module for wireless direct printing
- 320 GB HP High-Performance Secure Hard Disk
- 3,500 sheet High-capacity tray (tray 4: 1500 sheets A4 or letter only, tray 5: 2000 sheets A4 or letter



- as HP LaserJet Enterprise M806dn with:
- 320 GB HP High-Performance Secure Hard Disk
- 3,500 sheet High-capacity tray (tray 4: 1500 sheets A4 or letter only, tray 5: 2000 sheets A4 or letter onlv)

Recommended accessories



HP LaserJet 3500-sheet High-capacity Input

The HP LaserJet 3500-sheet High-Capacity Input Tray allows users to spend more time focusing on business and less time reloading paper. Support the productivity of growing work groups with this high-performance, robust input feeder and stand



CZ285A HP Laser Jet Booklet Maker/Finisher

The HP Laser let Booklet Maker/Finisher provides the ability to create more complex finished documents in-house without the time and expense of going to an outside service.



CZ994A **HP LaserJet Stapler/Stacker**

The HP LaserJet Stapler/Stacker provides automatic stapling and stacking for improved efficiency and increased output capacity.



CZ996A

HP LaserJet Stapler/Stacker with 2/4 hole punch

The HP Laser let Stapler/Stacker with 2/4 hole punch provides automatic stapling and stacking for improved efficiency and increased output capacity.

Ordering information



HP LaserJet Enterprise M806dn Printer (CZ244A)

HP LaserJet M806dn Printer; HP Black LaserJet Toner Cartridge (~34.5K pages); Hardware Install Guide, Support flyer, Warranty card; Printer documentation and driver on CD-ROM; power cord



HP LaserJet Enterprise M806x+ NFC/Wireless Direct Printer

HP LaserJet M806x+ Printer; HP Black LaserJet Toner Cartridge (~34.5K pages); Hardware Install Guide, Support flyer, Warranty card; Printer documentation and driver on CD-ROM; power cord; NFC module



HP LaserJet Enterprise M806x+ Printer (CZ245A)

HP LaserJet M806x+ Printer; HP Black LaserJet Toner Cartridge (~34.5K pages); Hardware Install Guide, Support flyer, Warranty card; Printer documentation and driver on CD-ROM; power cord

Accessories, Supplies and Support

| Accessories | | | | |
|-------------|---|--|--|--|
| C3F79A | HP LaserJet 3500-sheet High-capacity Input Tray | | | |
| CZ285A | HP LaserJet Booklet Maker/Finisher | | | |
| CZ994A | HP LaserJet Stapler/Stacker | | | |
| CZ996A | HP LaserJet Stapler/Stacker with 2/4 hole punch | | | |
| C8091A | HP Staple Cartridge Refill (5000 staples) for | | | |

Stapler/Stacker accessories CC383A HP 2-pack 2000-staple Cartridge for booklet maker

Connectivity

Accessories

HP Jetdirect 2700w USB Wireless Print Server J8026A J8029A HP Jetdirect 2800w NFC/Wireless Direct Accessory

| Supplies | | | | |
|----------|---|--|--|--|
| C2H57A | HP LaserJet 220V Maintenance/Fuser Kit | | | |
| | Average yield: 200,000 pages | | | |
| CF325X | HP 25X High Yield Black Original LaserJet Toner | | | |
| | Cartridge | | | |
| | Average cartridge yields 34,500 standard pages. | | | |
| | Declared yield based on ISO/IEC 19752 and | | | |
| | continuous printing. | | | |

Service & support

U8C50E - HP 3 year Next Business Day LaserJet Enterprise M806 Hardware Support

U8C53E - HP 3 year 4 hour 9x5 LaserJet Enterprise M806 Hardware Support

U8C51E - HP 4 year Next Business Day LaserJet Enterprise M806 Hardware Support

U8C52E - HP 5 year Next Business Day LaserJet Enterprise M806 Hardware Support

U8C71PE - HP 1 year Post Warranty Next Business Day LaserJet Enterprise M806 Hardware Support **U8C72PE** - HP 2 year Post Warranty Next Business Day

LaserJet Enterprise M806 Hardware Support

U8C73PE - HP 1 year Post Warrant 4 hour 9x5 9x5 LaserJet Enterprise M806 Hardware Support

For a complete list of supplies, accessories and services, please refer to http://www.hp.com For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies. Actual yields vary considerably based on images printed and other factors. For details see

Technical specifications

| Print technology | | Laser | | | | |
|---|--|--|---|--|--|--|
| Print speed | A4 black: Up to 56 ppm, A4 duple | ex: Up to 56 ipm | | | | |
| | A3 black: Up to 28 ppm | | | | | |
| | First page out black (A4): As fast as 8.5 sec | | | | | |
| | Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. | | | | | |
| rocessor | urve, and occurrent comprexity. 80 MHz | | | | | |
| | | | | | | |
| Memory | 1 GB. Expandable to 1.5 GB through 1 GB industry-standard DIMM | | | | | |
| lard disk | 320 GB HP High-Performance Secure Hard Disk (only on D7P69A and CZ245A) | | | | | |
| Print | Quality | HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi with | HP Resolution Enhancement technolog | ly | | |
| | Resolution Printer languages | Black: Up to 1200 x 1200 dpi HP PCL 6, HP PCL 5e, HP Postscript Level 3 emulation, native PDF printing (v 1.4) | | | | |
| | Typefaces/fonts | The FCL OF, The FCL SE, The FCL SE SET ACCUSAGE AND ADDRESS AND AD | | | | |
| | Typeraces/Tories | Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IP Emulation available at hp.com/go/laserjetfonts | | | | |
| | Duty cycle (monthly, A4) | Emulation available at np.com/gorlaserjetronts Up to 300,000 pages Up to 300,000 pages | | | | |
| | Recommended monthly page | 10,000 to 50,000 | | | | |
| | volume | | | | | |
| | Print margins (mm) | Top: 2.0 mm. Left: 2.0 mm. Right: 2.0 mm. Bottom: 2.0 | mm | | | |
| Media handling | Input: | Capacity | Weight | Size | | |
| | Tray 1 | sheets: 100; envelopes: 100; labels: 100 | 60 to 220 g/m ² | A3, A4, A5, RA3, B4, B5, post cards (JIS double); envelopes (DL, C5, B5); 98 x 191 to 312 x 470 mm | | |
| | Tray 2 | sheets: 500; labels: small quantities | 60 to 199 g/m² | A3; A4; A5; B4; B5; 148 x 210 to 297 x 431.8 mm | | |
| | Tray 3 | CZ244A: optional High-capacity Input tray, tray 4: | 60 to 199 g/m² | CZ244A: Optional High-capacity Input, Tray 4/5: A4, | | |
| | | sheets: 1500 (A4 only), tray 5: sheets: 2000 (A4 | 00 to 133 g/ | 210 to 297 mm; D7P69A: High-capacity Input, Tray | | |
| | | only); D7P69A: High-capacity Input tray, tray 4: | | 4/5: A4, 210 to 297 mm; CZ245A: as D7P69A | | |
| | | sheets: 1500 (A4 only), tray 5: sheets: 2000 (A4 | | product; | | |
| | | only); CZ245A: as D7P69A product; | | | | |
| | Maximum input capacity | Up to 4600 sheets | | | | |
| | Output: | Sheets: Up to 600 sheets. Transparencies: Up to 100 sh | | tacker with healiful maker) | | |
| | Maximum output capacity: Up to 3500 sheets (with optional stapler/stacker, stapler/stacker with hole punch, or stapler/stacker with booklet maker) Duplor printing without standard. | | | | | |
| nterface and connectivity | Duplex printing: Automatic (standard) Standard: CZ244A: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host; D7P69A: 2 | | | | | |
| iterrace and connectivity | | | | | | |
| | Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host; | | | | | |
| | | | | | | |
| | Optional: CZ244A: HP Jetdirect 2800w NFC & Wireless Direct Accessory, HP Jetdirect 2700w USB Wireless Print Server, HP Jetdirect ew2500 802.11g Wireless Print Server. For more information on HP networking solutions visit hp.com/go/jetdirect; D7P69A: HP Jetdirect 2700w USB Wireless Print Server, HP Jetdirect ew2500 802.11g Wireless Print Server. For more information on HP networking | | | | | |
| | solutions wish the composite the Decomposite of the | | | | | |
| | more information on HP networking solutions visit hp.com/go/jetdirect; | | | | | |
| Operating systems compatibility | Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows XP (SP2 or higher) (32-bit/64-bit), Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), | | | | | |
| | Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac OS X version 10.6.8, 10.7.5 Lion, 10.8 Mountain Lion. For the latest operating system support see: AirPrint™ | | | | | |
| | (support.apple.com/kb/ht4356); Android (android.com); Citrix and Windows Terminal Services (hp.com/go/upd); HP ePrint Software Driver (hp.com/go/eprintsoftware); Linux (hplip.net); Novell | | | | | |
| | (novell.com/fiprint); SAP device types (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); UNIX (hp.com/go/unix); UNIX JetDirect (hp.com/go/jetdirectunix_software). LaserJet driver information and support usailable at the com/support IMM96: he com/support in SAP device types (hp.com/support IMM96: hp.com/support IMM96: hp. | | | | | |
| | support available at: hp.com/support/ljM806; hp.com/go/hpsc; hp.com/support IPv4/IPv6: Apple Bonjour (AirPrint) compatible, SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, IPP, Secure-IPP, WS Discovery, WS Print, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-If | | | | | |
| Supported Network Protocols | | | | | | |
| W-1 | SLP, Telnet, I, GMPv2, BOOTP/DHCP, WINS, IP Direct Mode Management security: SNMPv3, SSL/TLS (HTTPS), IPsec/Firewall; Port authentication (802.1x EAP-PEAP, EAP-TLS) | | | | | |
| Minimum system requirements | Windows 8, Windows 7 SP1+, Windows Vista, Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2 (64 bit), Windows Server 2012 (64-bit), Windows XP (SP2+); CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection; 200 MB available hard disk space; Operating system compatible hardware system requirements see | | | | | |
| | | | | | | |
| | microsoft.com. Mac OS X v10.6.8, OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of available hard-disk space; CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 or network connection (Operating system compatible hardware system requirements see apple.com) | | | | | |
| Standard software | or network connection (operating system compation en arounder system requirements see apple.com) HP PCL 6 Discrete Printer Driver, Mac SW Link to Web (Mac Installer), Windows Installer | | | | | |
| Control panel | <u> </u> | | nd capacitive Home button (for quick ret | urn to the Home menu); Easy Access USB; Hardware Integration Pocket | | |
| <u> </u> | | | | <u> </u> | | |
| Power | Requirements: input Voltage: 220 to 240 VAC, 50/60 Hz, 5.5 A. Consumption: 1000 watts (printing), 38 watts (ready), 6.5 watts (sleep), 2.2 watts (Auto On/Auto Off), 0.3 watts (off). Typical Electricity Consumption (TEC): 40 MM/M/M/Grant (A DMM/M/M/GRANT). | | | | | |
| Dimensions (w x d x h) | Consumption (TEC): 4.0 kWh/Week Out of package: CZ244A: 1095 x 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ245A: 1095 x 715 x 1040 mm; Packaged: CZ244A: 856 x 760 x 978 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 1095 x 715 x 1040 mm; CZ245A: 1095 x 1040 mm; CZ245 | | | | | |
| Dimensions (w x a x n) | 856 x 790 x 1368 mm; | . 040 x 033 Hilli, D7F03R. 1033 x 713 x 1040 Hilli, C2243 | . 1055 x 7 15 x 1040 IIIII, , Packageu. C | 2244R. 030 X 700 X 976 HIIII, D7F03R. 030 X 750 X 1300 HIIII, C2243R | | |
| Veight | | n: N7P69A • 108 4 kg: C7245A • 108 4 kg: • Packagod: C7244 | A• 88 84 ka: N7P69A• 130 87 ka: C724 | 130 67 kg | | |
| Printer management | Out of package: CZ244A: 76.1 kg; D7P69A: 108.4 kg; CZ245A: 108.4 kg; Packaged: CZ244A: 88.84 kg; D7P69A: 130.87 kg; CZ245A: 130.67 kg; | | | | | |
| | HP Web Jetadmin; HP Utility (Mac) | | | | | |
| | | CZ244A: Identity Management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, optional HP Access Control and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPSec/firewall with Certificate, Pre-Shared Key, and Kerberos authentication, Supports WJA-10 IPsec configuration Pluq-in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, | | | | |
| | | | | | | |
| | Network: IPSec/firewall with Cert | tificate, Pre-Shared Key, and Kerberos authentication, Supp | | | | |
| | Network: IPSec/firewall with Cert Certificates, Access Control List; I | tificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; I | Device: Security lock slot, USB port disab | lement, Hardware Integration Pocket for security solutions; Security | | |
| | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H | tificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; I IP Imaging & Printing Security Center; D7P69A: Identity Mai | Device: Security lock slot, USB port disab nagement: Kerberos authentication, LDA | lement, Hardware Integration Pocket for security solutions; Security Pauthentication, 1000 user PIN codes, optional HP Access Control and | | |
| | Network: IPSec/firewall with Cerl Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatio | tificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; D7P69A : Identity Mai on solutions (e.g., badge readers); Network: IPSec/firewall v | Device: Security lock slot, USB port disab nagement: Kerberos authentication, LDA vith Certificate, Pre-Shared Key, and Kerl | lement, Hardware Integration Pocket for security solutions; Security P authentication, 1000 user PIN codes, optional HP Access Control and peros authentication, Supports WJA-10 IPsec configuration Plug-in, | | |
| | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatic 802.1X authentication (EAP-PEA | tificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; D7P69A : Identity Mai on solutions (e.g., badge readers); Network: IPSec/firewall v | Device: Security lock slot, USB port disab nagement: Kerberos authentication, LDA vith Certificate, Pre-Shared Key, and Kerl st; Data: Storage Encryption, Secure Era | lement, Hardware Integration Pocket for security solutions; Security P authentication, 1000 user PIN codes, optional HP Access Control and beros authentication, Supports WIA-10 IPsec configuration Plug-in, se, SSL/TLS, Encrypted (redentials; Device: Security lock slot, USB port | | |
| ecurity management | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatic 802.1X authentication (EAP-PEA disablement, Hardware Integrati Operating temperature: 10 to 3 | utificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; 17P69A: Identity Maon solutions (e.g., badge readers); Network: IPSec/firewall v IP, EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control Lion Pocket for security solutions; Security Management: Corn Pocket for Security of Management Corn. 5°C. Recommended operating temperature: 10 to 32.5°C. | Device: Security lock slot, USB port disab hagement: Kerberos authentication, LDA vith Certificate, Pre-Shared Key, and Kerl st; Data: Storage Encryption, Secure Era npatible with HP Imaging & Printing Sec | lement, Hardware Integration Pocket for security solutions; Security IP authentication, 1000 user PIN codes, optional HP Access Control and seros authentication, Supports WJA-10 IPsec configuration Plug-in, se, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port urity Center; CZ245A: as D7P69A product; | | |
| Decarity management | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatic 802.1X authentication (EAP-PEA disablement, Hardware Integrati Operating temperature: 10 to 32 to 40°C. Storage humidity: 10 to | tificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP IP Imaging & Printing Security Center; D7P69A: Identity Main on solutions (e.g., badge readers); Network: IPSec/firewall v IP, EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control Li on Pocket for security solutions; Security Management: Cor C.5°C. Recommended operating temperature: 10 to 32.5°C p. 90% RH | Device: Security lock slot, USB port disab hagement: Kerberos authentication, LDA vith Certificate, Pre-Shared Key, and Kerl st; Data: Storage Encryption, Secure Era npatible with HP Imaging & Printing Sec | lement, Hardware Integration Pocket for security solutions; Security IP authentication, 1000 user PIN codes, optional HP Access Control and seros authentication, Supports WJA-10 IPsec configuration Plug-in, se, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port urity Center; CZ245A: as D7P69A product; | | |
| Security management Operating environment Acoustics | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatic 802.1X authentication (EAP-PEA disablement, Hardware Integrati Operating temperature: 10 to 32 to 40°C. Storage humidity: 10 to Acoustic Power Emissions: 7.2 B | tificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; D7P59A: Identity Mai on solutions (e.g., badge readers); Network: IPSec/firewall v IP, EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control Li on Pocket for security solutions; Security Management: Cor 2.5°C. Recommended operating temperature: 10 to 32.5°C 90% RH (A); Acoustic Pressure Emissions: 55 dB(A) | Device: Security lock slot, USB port disab nagement: Kerberos authentication, LDA ith Certificate, Pre-Shared Key, and Kert st; Data: Storage Encryption, Secure Era npatible with HP Imaging & Printing Sec. Operating humidity: 10 to 80% RH. Op | lement, Hardware Integration Pocket for security solutions; Security IP authentication, 1000 user PIN codes, optional HP Access Control and peros authentication, Supports WIA-10 IPsec configuration Plug-in, se, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port urity Center; CZ245A: as D7P69A product; erating humidity recommended: 10 to 80% RH. Storage temperature: to | | |
| Security management Operating environment Acoustics | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatie 802.1X authentication (EAP-PEA disablement, Hardware Integrati Operating temperature: 10 to 32 to 40°C. Storage humidity: 10 to Acoustic Power Emissions: 7.2 & CISPR 22:2008 / EN 55022:2010 | Lificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; D7P69A: Identity Main solutions (e.g., badge readers); Network: IPSec/firewall vip, EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control Lion Pocket for security solutions; Security Management: Cor. SSC. Recommended operating temperature: 10 to 32.5°C 190% RH (A): Acoustic Pressure Emissions: 55 dB(A) (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 6 | Device: Security lock slot, USB port disab hagement: Kerberos authentication, LDP ith Certificate, Pre-Shared Key, and Kert st; Data: Storage Encryption, Secure Era npatible with HP Imaging & Printing Sec Operating humidity: 10 to 80% RH . Op | lement, Hardware Integration Pocket for security solutions; Security Pauthentication, 1000 user PIN codes, optional HP Access Control an peros authentication, Supports WIA-10 IPsec configuration Plug-in, se, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port urity Center; CZ245A: as D7P69A product; erating humidity recommended: 10 to 80% RH. Storage temperature: Directive 2004/108/EC with CE Marking (Europe); other EMC approvals a | | |
| Security management Operating environment Acoustics | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatic 802.1 X authentication (EAP-PEA disablement, Hardware Integrati Operating temperature: 10 to 32 to 40°C. Storage humidity: 10 to Acoustic Power Emissior 7.2 B CISPR 22:2008 / EN 55022:2010 required by individual countries. | utificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; B7P69A: Identity Man on solutions (e.g., badge readers); Network: IPSec/firewall v P, EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control Li on Pocket for security solutions; Security Management: Cor 1.5°C. Recommended operating temperature: 10 to 32.5°C 190% RH (A); Acoustic Pressure Emissions: 55 dB(A) 0 (Class A), EN 61000-3-2:2006+A1:2009+A2:2009; EN 6 Regulatory standards: IEC 60950-1:2005+A1; EN60950-1 | Jewice: Security lock slot, USB port disab nagement: Kerberos authentication, LDA vith Certificate, Pre-Shared Key, and Kert st; Data: Storage Encryption, Secure Era npatible with HP Imaging & Printing Sec. . Operating humidity: 10 to 80% RH. Op 1000-3-3:2008; EN 55024:2010; EMC I 2006 +A11:2009 +A1:2010 +A12:2011 | Iement, Hardware Integration Pocket for security solutions; Security AP authentication, 1000 user PIN codes, optional HP Access Control and beros authentication, Supports WIA-10 IP-sec configuration Plug-in, se, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port urity Center; CZ245A: as D7P69A product; erating humidity recommended: 10 to 80% RH. Storage temperature: Option of the Commended: 10 to 80% RH. Storage temperature: (2007) Commended: 10 to 80% RH. Storage temperature: (2007) Commended: 10 to 80% RH. Storage temperature: (2008) Commended: (20 | | |
| Departing environment Acoustics Certifications | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatic 802.11 Authentication (EAP-PEA disablement, Hardware Integrati Operating temperature: 10 to 32 to 40°C. Storage humidity: 10 to Acoustic Power Emissions: 7.2 B CISPR 22:2008 / EN 55022:2016 required by individual countries. (Class 1 Laser/LED Product); 65 C | Lificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; D7P69A: Identity Man on solutions (e.g., badge readers); Network: IPSec/firewall values, Access Control Li on Pocket for security solutions; Security Management: Cor 1.59°C. Recommended operating temperature: 10 to 32.59°C 909% RH (A); Acoustic Pressure Emissions: 55 dB(A) 0 (Class A), EN 61000-3-2: 2006 +A1:2009 +A2:2009; EN 6 Regulatory standards: IEC 60950-1:2005 +A1; EN60950-1 Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2 | Jewice: Security lock slot, USB port disab nagement: Kerberos authentication, LDA vith Certificate, Pre-Shared Key, and Kert st; Data: Storage Encryption, Secure Era npatible with HP Imaging & Printing Sec. . Operating humidity: 10 to 80% RH. Op 1000-3-3:2008; EN 55024:2010; EMC I 2006 +A11:2009 +A1:2010 +A12:2011 | lement, Hardware Integration Pocket for security solutions; Security IP authentication, 1000 user PIN codes, optional HP Access Control and peros authentication, Supports WJA-10 IPsec configuration Plug-in, se, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port urity Center; CZ245A: as D7P69A product; erating humidity recommended: 10 to 80% RH. Storage temperature: C | | |
| Security management Operating environment Acoustics | Network: IPSec/firewall with Cert Certificates, Access Control List; I Management: Compatible with H 3rd party advanced authenticatie 802.1X authentication (EAP-PEA disablement, Hardware Integratii Operating temperature: 10 to 32 to 40°C. Storage humidity: 10 to Acoustic Power Emissions: 7.2 B CISPR 22:2008 / EN 55022:2010 required by individual countries. (Class 1 Laser/LED Product); 65 individual countries. ENERGY STA | Lificate, Pre-Shared Key, and Kerberos authentication, Supp Data: Storage Encryption, SSL/TLS, Encrypted Credentials; IP Imaging & Printing Security Center; D7P69A: Identity Main solutions (e.g., badge readers); Network: IPSec/firewall vip. EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control Lion Pocket for security solutions; Security Management: Cort. SFC. Recommended operating temperature: 10 to 32.5°C 90% RH (A); Acoustic Pressure Emissions: 55 dB(A) 0 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 6 Regulatory standards: IEC 60950-1:2005 +A1; EN60950-1 Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2 R: Yes | Device: Security lock slot, USB port disab hagement: Kerberos authentication, LDA ith Certificate, Pre-Shared Key, and Kert st; Data: Storage Encryption, Secure Era npatible with HP Imaging & Printing Sec. Operating humidity: 10 to 80% RH. Op 1000-3-3:2008; EN 55024:2010; EMC I 2.2006 +A11:2009 +A1:2010 +A12:201 010; Low Voltage Directive 2006/95/EC | Iement, Hardware Integration Pocket for security solutions; Security AP authentication, 1000 user PIN codes, optional HP Access Control and beros authentication, Supports WIA-10 IP-sec configuration Plug-in, se, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port urity Center; CZ245A: as D7P69A product; erating humidity recommended: 10 to 80% RH. Storage temperature: Option of the Commended: 10 to 80% RH. Storage temperature: (2007) Commended: 10 to 80% RH. Storage temperature: (2007) Commended: 10 to 80% RH. Storage temperature: (2008) Commended: (20 | | |



