

Refurbished CISCO 4G-CAB-ULL-20 Datasheet

CISCO > ROUTERS

Cisco 4000 Series Integrated Services Routers

Antenna Specifications	
Item	
Item	Specification
Diversity (dual antenna) MIMO	Cisco LTE Advanced 3.0 NIM-LTEA-EA and NIM-LTEA-LA
Multiband indoor omnidirectional antenna ceiling mount (4G-ANTM-OM-CM)	Electrical Specifications Frequency range: 698 to 960 MHz, 1575 MHz, and 1710 to 2690 MHz Gain: 1 and 1.5 decibels relative to isotropic (dBi) (700 to 960 MHz), 1.7 and 3.2 dBi (1700 to 2200 MHz), 3 and 4 dBi (2500 to 2700 MHz) Maximum power: 50W Connector: TNC male Voltage standing wave ratio (VSWR): 2.0:1 and 3.01:1 or less for GPS Nominal impedance: 50 ohms Polarization: Linear vertical
Multiband swivel-mount dipole antenna (LTE-ANTM-D)	Articulating joint; can be rotated 360 degrees and is capable of maneuvering into three stop positions: 0, 45, and 90 degrees Plug-threaded TNC connector: Directly mount the antenna on any Cisco 4000 or ENCS 5400 Series wireless ISR NIM with a TNC connector; the threads on the connector must comply with the ANSI 7/16-28 UNEF 2B thread specification Multiband swivel-mount dipole antenna Faceplate mount (dual units included with all Cisco 4000 Series ISR and ENCS 5400 WWAN NIMs)
Single-unit antenna extension base (4G-AE015-R)	Dimensions: Single-unit antenna extension base (15 ft [457.2 cm])
Single-unit antenna extension base (4G-AE010-R)	10-ft [304.8-cm] cable included
Outdoor omnidirectional antenna for 2G, 3G, and 4G cellular (ANT-4G-OMNI-OUT-N*)	UV-stable radome Mast-mounting bracket Applicable for both 3G and 4G solutions Domestic LTE 700 band and global LTE 2600 band Domestic cellular and global GSM WiMAX 2300 and 2500
Integrated 4G low-profile outdoor saucer antenna (ANT-4G-SR-OUT-TNC)	Applicable for both 3G and 4G solutions Domestic LTE 700 band and global LTE 2600 band Domestic cellular and global GSM Weatherproof UV-stable radome Performance optimized Excellent flame rating
Cisco Multiband Panel Outdoor 4G Antenna (ANT-4G-PNL-OUT-N*)	Supports 3G and 4G solutions Supports bands Wall or mast mount Indoor and outdoor Dual type-N socket connector
Cisco Lightning Arrestors (CGR-LA-NM-NF* and (CGR-LA-NF-NF*))	Broadband operation DC continuity for outdoor powering Reversed installation Permanently installed gas capsule CGR-LA-NM-NF: Male-to-female connector CGR-LA-NF-NF: Female-to-female connector

The next steps...

ORDER NOW

VIEW ONLINE

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com