

Weight-
Approx. 21.5kg (23.14 Kg w/consumables)



EPSON AcuLaser™ M4000N

CONSUMABLES

IMAGING CARTRIDGE	(20,000 pages*6*7) C13S051170
RETURN IMAGING CARTRIDGE	(20,000 pages*6*7) C13S051173
FUSER UNIT (220 - 240V)	(200,000 pages*6*7) C13S053038

*1 From Standby mode

*2 The duration between the power being turned on and [Ready] being displayed is 17 seconds or less (at 23°C and 55% RH, with rated voltage and standard memory).

*3 The duration to recover from sleep mode till [Ready] is displayed is 17 seconds or less (at 23°C and 55% RH, with rated voltage).

*4 Weight including Imaging Cartridges.

*5 For Euro only

*6 The figures are approximate number of sheets pointed under conditions of continuous printing on A4 size paper with ISO 19752 pattern.

*7 Depending on various usages and environments page yield may reduce and come to its end of service life. It may occur even with toner left due to reaching the other parts' end of service life.



PRINTER TYPE

PRINTING TECHNOLOGY
RESOLUTION
PRINT SPEED
FIRST PAGE OUT
WARM UP TIME
MAXIMUM MONTHLY VOLUME

Laser
1200dpi
43ppm / 26.4ppm (Simplex/Duplex)
7.9 sec*1
17 sec*2*3
200,000 pages

PAPER HANDLING

STANDARD PAPER INPUT
MULTI PURPOSE TRAY

PAPER SIZE

700 sheets (150 Multi Purpose Tray + 550-sheet Cassette Unit)
A4, A5, B5, LT, HLT, LGL, GLT, GLG, EXE, F4, C5, C6, DL, Com10, Monarch, IB5

WIDTH
LENGTH
PAPER WEIGHT
PAPER SIZE
PAPER WEIGHT
PAPER SIZE
PAPER WEIGHT
PAPER SIZE
PAPER WEIGHT

76.2 - 215.9 mm
127.0 - 355.6 mm
64 - 216 g/m²
A4, A5, B5, LT, HLT, LGL, GLT, GLG, EXE, F4, C6, DL, Com10, Monarch, IB5
64 - 216 g/m²
Same as Standard Paper Cassette
Same as Standard Paper Cassette
A4, A5, B5, LT, HLT, LGL, GLT, GLG, EXE, F4
64 - 216g/m²
1800 sheets (150 MP Tray + 550 Sheet Paper Cassette + 2x extra 550 Sheet Paper Cassette)
500 sheets (Face Down), 70 sheets (Face Up)
500 sheets (Stacker)

550-SHEER PAPER CASSETTE UNIT

550-SHEER PAPER CASSETTE UNIT (OPTION)

DUPLEX UNIT (OPTION)

MAXIMUM PAPER INPUT

PAPER OUTPUT STANDARD/MAXIMUM
PAPER OUTPUT STANDARD/MAXIMUM (OPTION)

INTERFACES

Hi-Speed USB (2.0 compatible), Parallel Interface (IEEE 1284), and 10/100 Base TX Ethernet Interface

MEMORY

STANDARD/MAXIMUM

64 MB / 576 MB

POWER REQUIREMENT

ENERGY STAR COMPLIANT
RATED FREQUENCY
RATED CURRENT
POWER CONSUMPTION

OPERATING
STANDBY
SLEEP

50Hz / 60Hz (220 - 240V)
5.5A / 11A (220 - 240V)
Max. 1120 Wh / 1090 Wh (220 - 240V) Ave. 654 Wh (220 - 240V)
77 Wh / 78 Wh (220 - 240V)
10 Wh / 7Wh (220 - 240V)

ENVIRONMENTAL CONDITIONS

TEMPERATURE

OPERATION
STORAGE

10 to 32°C
0 to 35°C

HUMIDITY

OPERATION
STORAGE

15 to 85% RH
15 to 80% RH

SOUND POWER

OPERATING
STANDBY

7.25 B (A)
5.3 B (A)

SOUND PRESSURE

OPERATING
STANDBY

56.1 dB (A)
28 dB (A)

DIMENSION AND WEIGHT*4

AL-M4000N
AL-M4000N with 550-sheet Paper Cassette
AL-M4000N with 2x 550-sheet Paper Cassette
AL-M4000N with Duplex Unit
AL-M4000N with Stacker
AL-M4000N with 550-sheet Paper Cassette and Stacker
AL-M4000N with 2x 550-sheet Paper Cassette and Stacker
AL-M4000N with 2x 550-sheet Paper Cassette, Duplex Unit and Stacker

428 x 480 x 404 mm, 21.5 Kg (23.14 Kg w / consumables)
428 x 480 x 499 mm, 27.8 Kg (29.44 Kg w / consumables)
428 x 480 x 589 mm, 34.1 Kg (35.74 Kg w / consumables)
428 x 572 x 404 mm, 23.4 Kg (25.04 Kg w / consumables)
428 x 480 x 539 mm, 24.1 Kg (25.74 Kg w / consumables)
428 x 480 x 634 mm, 30.4 Kg (32.04 Kg w / consumables)
428 x 480 x 724 mm, 36.7 Kg (38.34 Kg w / consumables)
428 x 572 x 724 mm, 38.6 Kg (40.24 Kg w / consumables)

PRINTER DRIVER/UTILITY

PRINTER DRIVER
EPSON STATUS MONITOR
POSTSCRIPT™ PRINTER DRIVER
EPSON SCREEN FONT
EPSON BARCODE FONTS
EPSONNET PRINT
EPSONNET CONFIGURATION
EPSONNET EASYINSTALL
EPSON WEB-TO-PAGE
JAVA RUNTIME ENVIRONMENT SE
USER GUIDES
DATA FILE FOR*5

Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64 and Mac™ OS X
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64 and Mac™ OS X
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
Microsoft® Windows® 2000/XP
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64 and Mac™ OS X
Microsoft® Windows® 2000/XP/Server2003/Vista/Server2003 x64/XP x64/Vista x64

PRINTER CONTROL LANGUAGE EMULATIONS

STANDARD

ESC/Page™, ESC/P2™, FX 1239X, PCL5e, PCL6, A-PS (Level 3), PDF 1.3

RESIDENT TYPEFACES

SCALABLE
BITMAP
TYPEFACE

84 ESC / Page, 95 PCL5c, 80 PCL6, 17 PS3
7 ESC / Page, 5 PCL5c, 1 PCL6
10 ESC / P2, 8 FX, 81239X

OPTIONS

550-SHEET PAPER CASSETTE UNIT
DUPLEX UNIT
STACKER
HARDDISK
DIMM MEMORY 64MB RAM (90 pin)
DIMM MEMORY 128MB RAM (90 pin)
DIMM MEMORY 256MB RAM (90 pin)

C12C802471
C12C802481
C12C802111
C12C824172
7100742
7100744
7102850

EPSON is the registered trademark of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

EPSON disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON

EXCEED YOUR VISION

INDIA - (91) 80-305-15000, CALCUTTA - 228 31589/90,
CHENNAI - 302 77500, MUMBAI - 282 61515/16/17,
NEW DELHI - 306 15000

INDONESIA - (62) 21-572-3161

MALAYSIA - (60) 3-562-88288

PHILIPPINES - (632) 706-2663

SINGAPORE - (65) 6586-5500, (65) 6586-3111

THAILAND / INDOCHINA - (662) 685-9888

Dealer's Stamp