

# Tripp Lite 3-Phase PDUs

NOW IN  
**STOCK!**

- ✓ **POWER DISTRIBUTION FOR 3-PHASE APPLICATIONS**
- ✓ **LOCAL AND REMOTE DISPLAY OF POWER LOAD**
- ✓ **3-PHASE INPUT, SINGLE-PHASE OUTPUT**

**ALL TRIPP LITE 3-PHASE PDUs ARE COMPATIBLE WITH 3-PHASE UPS SYSTEMS FROM TRIPP LITE, APC AND OTHER MANUFACTURERS!**

- Support real-time monitoring of all reported functions with support for user-specified alarm and notification thresholds
- Support in-rack environmental and security monitoring with optional ENVIROSENSE temperature/humidity probe and rack access notification for up to four door sensors (SRSWITCH) or other user-supplied contact-closure sensors
- Lighted display with scroll-button offers IP-address self-identification, power consumption in amps and 180° rotation for overhead or raised floor power feeds
- Fully compatible with PowerAlert Network Management System, available via FREE download from [www.tripplite.com](http://www.tripplite.com)
- PowerAlert interface supports custom notification and control of user-specified remote conditions via email, secure web, SNMP, Telnet or SSH interface

**3-Phase Monitored PDUs** support real-time remote monitoring of load level, voltage and frequency with options for environmental and security monitoring.

**3-Phase Switched PDUs** support remote individual outlet control, monitoring of output load level per outlet or per load bank, input voltage and frequency reporting with options for environmental and security monitoring.

## 3-PHASE PDU FEATURES BY GROUPING

	Monitored PDUs	Switched PDUs
<b>COMPATIBLE WITH 3-PHASE UPS SYSTEMS</b> from Tripp Lite, APC, and Other Manufacturers	✓	✓
<b>DISTRIBUTE POWER</b> to multiple devices (multiple outlets)	✓	✓
<b>LOCALLY VIEW PDU LOAD</b> (amps) (digital load meter)	✓	✓
<b>REMOTELY VIEW PDU LOAD</b> (amps) & alarm conditions (network interface/software)	✓	✓
<b>REMOTELY CONTROL</b> individual outlets (network interface/software/switchable outlets)		✓
<b>MONITOR CURRENT</b> of individual outlets, in amps, per phase		✓

See Reverse for Individual Product Specifications.

**Tripp Lite has a complete line of 3-Phase UPS Systems, 20kVA-80kVA!**

**For More Information, Contact:**  
Tripp Lite Datacom/Telecom Sales  
773.869.1286



Tripp Lite has been a trusted manufacturer of innovative solutions for over 85 years!



# Tripp Lite 3-Phase PDUs

## 3-Phase Monitored PDU Systems

Model	Input Voltage / Phase	Output Voltage / Phase	Capacity	Output Breakers	Input Plug Type	Cord Length	Outlets
PDU3VN10L2120LV	208V / 3-phase	120V / single-phase	5.7kVA / 16A per bank	n/a	NEMA L21-20P	10 ft.	(36) 5-15/20R
PDU3VN3L2120LV	208V / 3-phase	120V / single-phase	5.7kVA / 16A per bank	n/a	NEMA L21-20P	3 ft.	(36) 5-15/20R
PDU3VN10L1520	208V / 3-phase	208V / single-phase	5.7kVA / 9.2A per bank	n/a	NEMA L15-20P	10 ft.	(30) C13, (6) C19
PDU3VN3L1520	208V / 3-phase	208V / single-phase	5.7kVA / 9.2A per bank	n/a	NEMA L15-20P	3 ft.	(30) C13, (6) C19
PDU3VN10L2120	208V / 3-phase	208V / single-phase	5.7kVA / 9.2A per bank	n/a	NEMA L21-20P	10 ft.	(30) C13, (6) C19
PDU3VN3L2120	208V / 3-phase	208V / single-phase	5.7kVA / 9.2A per bank	n/a	NEMA L21-20P	3 ft.	(30) C13, (6) C19
PDU3VN10G30	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	IEC-309 (3P+G 30A)	10 ft.	(30) C13, (6) C19
PDU3VN3G30	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	IEC-309 (3P+G 30A)	3 ft.	(30) C13, (6) C19
PDU3VN10L1530	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L15-30P	10 ft.	(30) C13, (6) C19
PDU3VN3L1530	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L15-30P	3 ft.	(30) C13, (6) C19
PDU3VN10L2130	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L21-30P	10 ft.	(30) C13, (6) C19
PDU3VN3L2130	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L21-30P	3 ft.	(30) C13, (6) C19
PDU3VN10H50	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	HUBBELL CS8365C	10 ft.	(30) C13, (6) C19
PDU3VN3H50	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	HUBBELL CS8365C	3 ft.	(30) C13, (6) C19
PDU3VN10G60	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	IEC-309 Blue (3P+G 60A)	10 ft.	(30) C13, (6) C19
PDU3VN3G60	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	IEC-309 Blue (3P+G 60A)	3 ft.	(30) C13, (6) C19
PDU3XVN10G16	400V / 3-phase	230V / single-phase	11kVA / 16A per bank	n/a	IEC-309 Red 16A (3P+N+E)	10 ft.	(30) C13, (6) C19
PDU3XVN3G16	400V / 3-phase	230V / single-phase	11kVA / 16A per bank	n/a	IEC-309 Red 16A (3P+N+E)	3 ft.	(30) C13, (6) C19

## 3-Phase Switched PDU Systems

Model	Input Voltage / Phase	Output Voltage / Phase	Capacity	Output Breakers	Input Plug Type	Cord Length	Outlets
PDU3VSR10L1520	208V / 3-phase	208V / single phase	5.7kVA / 9.2A per bank	20A (x3)	NEMA L15-20P	10 ft.	(21) C13, (3) C19
PDU3VSR3L1520	208V / 3-phase	208V / single-phase	5.7kVA / 9.2A per bank	20A (x3)	NEMA L15-20P	3 ft.	(21) C13, (3) C19
PDU3VSR10L2120	208V / 3-phase	208V / single-phase	5.7kVA / 9.2A per bank	n/a	NEMA L21-20P	10 ft.	(21) C13, (3) C19
PDU3VSR3L2120	208V / 3-phase	208V / single-phase	5.7kVA / 9.2A per bank	n/a	NEMA L21-20P	3 ft.	(21) C13, (3) C19
PDU3VSR10G30	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	IEC-309 (3P+G 30A)	10 ft.	(21) C13, (3) C19
PDU3VSR3G30	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	IEC-309 (3P+G 30A)	3 ft.	(21) C13, (3) C19
PDU3VSR10L1530	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L15-30P	10 ft.	(21) C13, (3) C19
PDU3VSR3L1530	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L15-30P	3 ft.	(21) C13, (3) C19
PDU3VSR10L2130	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L21-30P	10 ft.	(21) C13, (3) C19
PDU3VSR3L2130	208V / 3-phase	208V / single-phase	8.6kVA / 13.9A per bank	20A (x3)	NEMA L21-30P	3 ft.	(21) C13, (3) C19
PDU3VSR10H50	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	HUBBELL CS8365C	10 ft.	(21) C13, (3) C19
PDU3VSR3H50	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	HUBBELL CS8365C	3 ft.	(21) C13, (3) C19
PDU3VSR10G60	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	IEC-309 Blue (3P+G 60A)	10 ft.	(21) C13, (3) C19
PDU3VSR3G60	208V / 3-phase	208V / single-phase	12.6kVA / 20A per bank	20A (x3)	IEC-309 Blue (3P+G 60A)	3 ft.	(21) C13, (3) C19
PDU3XVSR10G16	400V / 3-phase	230V / single-phase	11kVA / 16A per bank	n/a	IEC-309 Red 16A (3P+N+E)	10 ft.	(21) C13, (3) C19
PDU3XVSR3G16	400V / 3-phase	230V / single-phase	11kVA / 16A per bank	n/a	IEC-309 Red 16A (3P+N+E)	3 ft.	(21) C13, (3) C19

**For More Information, Contact:**  
 Tripp Lite Datacom/Telecom Sales  
 773.869.1286



Tripp Lite has been a trusted manufacturer of innovative solutions for over 85 years!

