

Xerox Phaser® 3600 Laser Printer Value-packed performance



# Phaser® 3600 Laser Printer

**Pure printing pleasure.** Combining surprisingly high-end performance features with consistent reliability – all in a compact device that's built to keep your productivity high and your costs low.

# The power to please

The Phaser 3600 laser printer brings Xerox quality and superior performance to single users and small workgroups with demanding productivity.

- Fast printing performance. Delivers results at up to 38 ppm plenty of speed to keep up with your print workload.
- A first-page-out time as fast as nine seconds. This means you spend less time waiting for print jobs and more time staying productive.
- Complex print jobs, handled with ease. A robust 400 MHz processor works behind the scenes to quickly take care of whatever comes its way – even multi-page jobs loaded with graphics.
- Network printing. Network printing (standard on the N and EDN configurations) makes the Phaser 3600 laser printer a more powerful office ally, helping more users get more work done.
- Get even more helpful capabilities.
  Features include Secure Print, which keeps a private print job in the queue until released by the job owner, and RAM collation, which speeds up larger print jobs by quickly processing multiple sets of multi-page documents.

# Unbeatable value

With advanced features typically found on higher-priced laser printers, the Phaser 3600 offers more performance for less.

- More speed, better features and a robust, user-friendly design. No other printer in its class matches the Phaser 3600 laser printer's total value.
- Print more without interruption. There are two standard paper trays holding a total of 600 sheets. Need more capacity? An additional 500-sheet tray is available.
- Affordability comes standard. Low cost per page and helpful cost-saving features like toner-save and energy-save modes, plus automatic two-sided printing\* and N-Up printing means more efficient paper usage.
- The print cartridge is easy to replace.
   You may choose standard-capacity at a lower price, or high-capacity, for greater print volumes and reduced total cost of ownership.
- We stand behind our promise.
   Outstanding reliability and performance are backed by a standard one-year on-site warranty.

\*standard on EDN configuration



# Xerox simplicity

Helpful administration tools, like CentreWare IS internal web server, make it fast and easy to manage everyday usage. You get quick and convenient access to a wealth of features, including printer and job status, and toner volume updates, media availability, in-depth accounting information, simplified printer installation and network administration and more.

# The security your business needs

### Safe documents

- Secure print holds jobs in the queue until released with a PIN.
- Watermark customises documents with words, such as "Confidential".

## A good network citizen

- IEEE 802.1x protocol ensures that connected printers have proper authorisation.
- HTTP enables secure device administration.
- SNMP v3.0 provides encrypted network management.

## Phaser® 3600 Quick Facts

- Print up to 38 ppm
- 600 x 600 dpi (up to 1200 x 1200 enhanced image quality)
- 400 MHz processor
- 200,000 pages/month duty cycle
- 600-sheet capacity, expandable to 1,100 sheets



399 x 478 x 383 mm



# The capacity to do more

The Phaser 3600 laser printer offers more printing features for fast-paced businesses on a budget. A choice of configurations are available to meet the needs of a busy single user or a small work team, while more options further expand the printer's capabilities.

Simple layout and easy-to-read two-line front panel user interface displays the printer status, error messages and jobs in progress.





- 1 Automatic two-sided printing. Standard on the Phaser 3600EDN and available as an option on the Phaser 3600B and 3600N models.
- 2 100-sheet multipurpose tray. Handles a variety of paper, from 60 – 163 gsm, including envelopes, labels, business cards and other speciality media.
- **3 500-sheet input tray.** Feeds 60 105 gsm paper.
- 4 Add an additional 500-sheet input tray. Boosts total paper input capacity to 1,100 sheets.









## Phaser® 3600 Printer Configurations

# Phaser 3600B

- 2-Tray, 600-sheet capacity
- 64 MB memory (expandable to 512 MB)

### Phaser 3600N

- 2-Tray, 600-sheet capacity
- 10/100Base-TX Ethernet
- 128 MB memory (expandable to 512 MB)

# Phaser 3600EDN

- 2-Tray, 600-sheet capacity
- Automatic two-sided printing
- 10/100Base-TX Ethernet
- 128 MB memory (expandable to 512 MB)

# Options

- Automatic two-sided printing (standard on 3600EDN)
- One additional 500-sheet input tray
- Additional memory
- Wireless network adaptor

# Phaser® 3600

# Black and white laser printer







		3600B	3600N	3600EDN	
Speed		Up to 38 ppm			
Duty Cycle		200,000 pages / month			
Paper Handling Paper input Stand		<b>Tray 1 (MPT):</b> 100 sheets; Custom sizes: 76 x 127 mm to 216 x 356 mm			
		Tray 2: 500 sheets; Selectable sizes from A5 to A4			
	Optional	Tray 3: 500 sheets; Selectable sizes from A5 to A4 (1,100-sheet total capacity)			
Paper output		250 sheet face-down, 100 sheet face-up			
Automatic two-sided printing		Optional		Standard	
<b>Print</b> First-page-out-time		As fast as 9 seconds			
Resolution (max)		600 x 600 dpi (up to 1200 x 1200 enhanced image quality)			
Processor		400 MHz			
Memory (std / max)		64 MB / 512 MB	128 MB	128 MB / 512 MB	
Connectivity		Parallel, USB 2.0	10/100Base-TX Ethernet, Parallel, USB 2.0		
Page description languages		PostScript® 3" compatibility, PCL®6, PCL®5e emulation			
Print features	Standard	Smart Trays, Booklet printing, Scaling, Fit to page, Watermarks, Overlays, Posters, Custom-size pages, Covers, N-up, Toner save mode, Secure print*, Collation*			
Warranty		One-year on-site warranty			

<sup>\*</sup>Standard on N/EDN Configurations, Optional on B Configuration

### Device Management

Phaser Installer, CentreWare® IS Embedded Web Server\*, CentreWare® Web\*, Font management utility\*

### **Print Drivers**

Windows® 2000/XP/7/Server 2003/2008/Vista, Mac OS® 10.2 and above. Novell Netware® 4.x/5.x/6. Various Linux OS including Red Hat® 8–9, Fedora™ Core 1–4, Mandrake 9.2–10.1, SuSE 8.2–9.2, Unix HP-UX, Sun Solaris, Xerox Walk-Up® Printer Drivers

# Font Capability

4 MB flash memory for fonts and macros 136 PostScript® fonts; 68 PCL® fonts

### Media Handling

Tray 1: 60-163 gsm Tray 2 and Tray 3 (optional): 60–105 gsm Two-sided output: 75–90 gsm

### Media types

Plain paper, envelopes, labels, transparencies, card stock

### Operating Environment

Temperature: 10° to 32°C Humidity: 20 % to 80 % Sound pressure: Printing: 56.0 dB(A), Standby: 35.0 dB(A) Warm-up time (from power save): 31 seconds or less, FPOT from power save: 40 seconds

### Electrical

Power: 220-240 VAC, 50/60 Hz Power consumption: Printing: 700 W, Standby: 130 W, Power save: 13 W

### Dimensions (WxDxH)

399 x 478 x 383 mm Weiaht: 17.9 ka

### Certifications

Listed to UL 60950-1/CSA 60950-1-03, 1st Edition, FDA/ CDRH – Class 1 Laser Product, FCC Part 15, Class B, Canada ICES-003, Class B, CE marked, Low Voltage Directive 2006/95/ FC FN 60950-1 1st Edition FN 60825-1 - Class 1 Laser Product, EMC Directive 2004/108/EC, EN 55022, Class B. EN 55022, Class B, RoHS Directive 2002/95/EC, WEEE Directive 2002/96/EC

### What comes in the box

- Phaser 3600 Printer
- Print cartridge (7,000 print capacity)
- World Kit (includes Software and documentation CD, Registration card, Warranty booklet)
- USB Cable
- Power cord

# Supplies Recycling Programme

Consumables for the Phaser 3600 are part of the Xerox Green World Alliance Supplies Recycling Programme. For more information, please visit the Green World Alliance website at www.xerox.com/gwa

### Supplies

106R01370 Print cartridge: 7,000 pages<sup>1</sup> Print cartridge: 14,000 pages<sup>1</sup> 106R01371

### Options

Duplex Module 097S03756 500-Sheet Feeder 097N01673 097S03759 64 MB Memory 128 MB Memory 097503760 256 MB Memory 097S03761 Wireless Network Adaptor (not available on 3600B)

097S03741 - Furopean Power Converter<sup>2</sup> - UK Power Converter 097503742

<sup>1</sup>Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

<sup>2</sup> Not available in Denmark and Switzerland















