## Workman<sup>®</sup> Reusable Roof Anchor



Whether your roof is flat or sloped, the Workman Reusable Roof Anchor is the perfect fit.

## **Features include:**

- Meets ANSI Z359.1-2007
- Center holes are offset to reduce possibility of truss splitting during installation
- Can be used off roof peak in flat position without compromising strength
- Can be used with screws or nails
- Fits any wooden roof up to 12/12 pitch
- Standard product includes fastening hardware
- 400-pound maximum worker capacity
- Available with labels and user instructions in English & Spanish





Reusable Roof Anchor installed off roof peak



*Reusable Roof Anchor installed at peak* 

Note: this bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.

ID 2302-43-MC / July 2009 © MSA 2009 Printed in U.S.A. Corporate Headquarters P.O. Box 426, Pittsburgh, PA 15230 USA Phone 412-967-3000 www.MSAnet.com U.S. Customer Service Center

 Phone
 1-800-MSA-2222

 Fax
 1-800-967-0398

MSA Canada Phone 1-800-672-2222 Fax 1-800-967-0398

 MSA Mexico

 Phone
 01 800 672 7222

 Fax
 52 - 44 2227 3943

 MSA International

 Phone
 412-967-3354

 FAX
 412-967-3451

## SPECIFICATIONS

Material type:	Zinc-plated carbon steel
Net weight:	2.1 pounds
Dimensions:	18.4″L x 3.0″W x 2.9″H (46.7cm x 7.6cm x 7.4cm)
Approvals:	With nails ANSI A10.32-2004, OSHA 1926.502 With screws ANSI Z359.1-2007, ANSI A10.32-2004, OSHA 1926.502

PART NO.	DESCRIPTION
10102686	Workman Reusable Roof Anchor with 12 mounting screws

Offices and representatives worldwide For further information:

