

5-Port USB 3.1 PCIe Card - 1x USB-C (10Gbps), 2x USB-A (5Gbps) + 1x 2-Port IDC (5Gbps)


Product ID: PEXUSB312EIC



This 5-port USB 3.1 combo card makes it easy to add to the performance and connectivity of your computer. It's one of the only USB 3.1 cards to offer a USB Type- C^{TM} port (10Gbps), traditional USB Type-A ports (5Gbps), and a motherboard header.

By offering a range of USB port types, you can easily connect a variety of modern and legacy USB devices, both inside and outside your computer.

Because the card offers a 10Gbps USB- C^{TM} port (USB 3.1 Gen 2), you can save time and avoid the performance bottlenecks that are often associated with other connectivity technologies.







Work faster and prepare for the future

This versatile PCI Express combo card leverages the performance potential of USB 3.1 to help you work faster. The USB-C port offers a data throughput of up to 10Gbps, so you can spend less time waiting for file transfers to complete or for access to your external peripherals.

Plus, you can rest assured that you're set for the future, as USB-C devices become more popular and more standardized.

Connect different types of USB devices

Now you can easily add a variety of types and speeds (generations) of USB ports to your desktop or server, using a single adapter card. The card features:

- One external USB-C port (USB 3.1 Gen 2 10Gbps)
- Two external USB-A ports (USB 3.1 Gen 1 5Gbps)
- One internal 20-pin IDC motherboard header port that can provide two internal USB-A ports (5Gbps)

With a range of port types, the card lets you bridge the gap between older and newer devices that use different connectors. You can simultaneously connect and access USB Type-A and USB Type-C devices, while using only a single PCI Express expansion slot.

By adding three types of USB ports in one combo card, you can free up space in your PC case, and eliminate the nuisance of having different cards for different USB devices.

Ideal for building or upgrading your computer

With two internal motherboard-style headers, this dynamic USB 3.1 card is perfect for upgrading or building your own computer. If your existing headers are occupied, or if you don't have any motherboard headers, you can connect front panel hubs or card readers using this versatile alternative to costly motherboard or computer upgrades.

Connect your older USB devices

Connecting your older peripherals isn't a problem. This 5-port USB 3.1 card is backward compatible with legacy USB 3.0 and 2.0 devices, so you can eliminate the added expense and aggravation of purchasing new devices. (USB 3.0 is also known USB 3.1 Gen 1).

The PEXUSB312EIC is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Note: The card does not support DP alt mode or USB Power Delivery.





Certifications, Reports and Compatibility







((





Applications

- Connect USB-A or USB-C devices, plus add USB motherboard headers for future expansion
- Use at home or in the office and connect the latest USB-C devices, such as HDD enclosures
- Install the card as a vital hardware component when building a PC, or upgrade an older PCIe based desktop from USB 3.0 or 2.0 to USB 3.1 Gen 2 (10Gbps)
- Connect your legacy USB devices to your computer

Features

- Connect a USB-C device, plus a range of other USB devices, to your computer, regardless of their speed or connector type
- Offers a high-performance USB-C port (10Gbps), two USB-A ports (5Gbps), and one 20-pin internal IDC motherboard header that can provide two USB-A ports (5Gbps)
- Works with your existing USB 3.0 and USB 2.0 devices, for costeffective backward compatibility
- Compatible with high-powered USB devices, with an integrated SATA power connector
- Fits into full or low-profile systems, with its dual-profile design
- USB-C port is Thunderbolt 3 data port compatible (10Gbps data only)
- PCIe x4 interface compliant with PCI Express Base Specification Revision 3.0
- Compliant with UASP (USB Attached SCSI Protocol) Revision 1.0, as well as USB 3.1 Revision 1.0
- Fast, hassle-free setup



Data Sheet

	Warranty	2 Years
Hardware	Bus Type	PCI Express
	Card Type	Standard Profile (LP bracket incl.)
	Chipset ID	ASMedia - ASM1142 VIA/VLI - VL812
	Industry Standards	USB 3.1 Specification Rev. 1.0 USB Specification Rev. 2.0 PCI Express Base Specification Rev. 3.0 Intel xHCI Specification Rev. 1.1 UASP (USB Attached SCSI Protocol) Rev. 1.0
	Interface	USB 3.0
		USB 3.1 Gen 2
	Port Style	Integrated on Card
	Ports	5
Performance	Maximum Data Transfer Rate	10Gbps
	MTBF	50,000 Hours
	Type and Rate	USB 3.1 Gen 2 - 10 Gbit/s
		USB 3.0 - 5 Gbit/s
	UASP Support	Yes
Connector(s)	UASP Support Connector Type(s)	Yes 1 - PCI Express x4 Male
Connector(s)		
Connector(s)	Connector Type(s)	1 - PCI Express x4 Male
Connector(s)	Connector Type(s)	1 - PCI Express x4 Male 2 - USB Type-A (9 pin) USB 3.0 Female
Connector(s)	Connector Type(s) External Ports	1 - PCI Express x4 Male 2 - USB Type-A (9 pin) USB 3.0 Female 1 - USB Type-C (24 pin) USB 3.1 (10Gbps) Female
Connector(s) Software	Connector Type(s) External Ports	1 - PCI Express x4 Male 2 - USB Type-A (9 pin) USB 3.0 Female 1 - USB Type-C (24 pin) USB 3.1 (10Gbps) Female 1 - IDC (20 pin, USB 3.0, Motherboard Header) Receptacle
	Connector Type(s) External Ports Internal Ports	1 - PCI Express x4 Male 2 - USB Type-A (9 pin) USB 3.0 Female 1 - USB Type-C (24 pin) USB 3.1 (10Gbps) Female 1 - IDC (20 pin, USB 3.0, Motherboard Header) Receptacle 1 - SATA Power (15 pin) Plug Windows® 7, 8, 8.1, 10 Windows Server® 2008 R2, 2012, 2016, 2019 Mac OS® 10.8 - 10.10
Software Special Notes /	Connector Type(s) External Ports Internal Ports OS Compatibility	1 - PCI Express x4 Male 2 - USB Type-A (9 pin) USB 3.0 Female 1 - USB Type-C (24 pin) USB 3.1 (10Gbps) Female 1 - IDC (20 pin, USB 3.0, Motherboard Header) Receptacle 1 - SATA Power (15 pin) Plug Windows® 7, 8, 8.1, 10 Windows Server® 2008 R2, 2012, 2016, 2019 Mac OS® 10.8 - 10.10 Linux® 3.5, 4.11.x The maximum throughput of this card is limited by the bus interface. PCI Express Gen 1.0 max throughput is 2.5Gbps. PCI Express Gen 2.0 max throughput is 5Gbps. PCI Express Gen 3.0 max throughput is 10Gbps. The card does not support DP alt mode or USB Power



Data Sheet

Environmental	Humidity	5~95% RH (Non-condensing)
	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Physical Characteristics	Product Height	4.7 in [12 cm]
	Product Length	3.1 in [79.3 mm]
	Product Width	0.7 in [18 mm]
	Weight of Product	2.4 oz [67 g]
Packaging Information	Package Height	1.3 in [32 mm]
	Package Length	5.2 in [13.1 cm]
	Package Width	6.4 in [16.2 cm]
	Shipping (Package) Weight	4.4 oz [124 g]
What's in the Box	Included in Package	1 - 5-port USB 3.1 combo card
		1 - low-profile bracket
		1 - quick-start guide

Product appearance and specifications are subject to change without notice.