

# TQ4600

## Enterprise-Class Wireless Access Point

The Allied Telesis TQ4600 Enterprise-class Wireless Access Point features an IEEE 802.11ac 3ss dual-band 2.4/5GHz radio and embedded antenna, capable of 1750Mbps raw wireless capacity.



The TQ4600 is based on IEEE 802.11ac, with three-spatial-stream Multiple Input and Multiple Output (MIMO), which can deliver more than twice the wireless capacity of 802.11n Access Points (APs). The TQ4600 can operate in standalone or AP cluster mode, or it can be controlled by the UWC controller. It is suitable for a wide range of deployments—from SMBs to large enterprises.

In large deployments with centralized control and management by the UWC controller, operating costs are kept low because the network is simple to configure, monitor, and manage. For smaller deployments without the UWC controller, the TQ4600 can function either as a standalone AP or in a cluster. When operating as a cluster, APs are grouped to share the configuration and manage the channel automatically, and there is a single point of management—allowing easy management of all APs. This reduces the cost for multiple AP configuration and management.

The TQ4600 is equipped with advanced encryption and authentication IEEE 802.11i capabilities. It protects WLANs, by segmenting public and private access with multiple Service Set Identifications (SSIDs) and VLAN Tagging. Rogue AP detection provides the ability to detect unauthorized APs, thus preventing unauthorized entry to the wireless network.

The TQ4600 can be deployed on the desktop, or mounted on a wall or ceiling. Power can be provided via Power over Ethernet (IEEE 802.3at PoE) or with the optional AC/DC power adapter.

## Key Features

### Flexible management

- ▶ The TQ4600 can operate in either standalone or companion mode with a wireless access controller. This flexibility allows you to select the management approach that best fits your network.

For large-scale network deployment, a wireless controller offers a single point of management for operation, administration, and maintenance of all your access points.

Clustering offers a single management point, which synchronizes provisioning for a group of access points. It also optimizes wireless coverage, due to dynamic channel selection among group members.

As a standalone access point, the TQ4600 detects adjacent access points and acts promptly to prevent radio interference.

### IEEE 802.11ac technology

- ▶ Advanced IEEE 802.11ac technology provides a high-performance wireless link with improved bandwidth, efficiency and robustness, and allows for backward compatibility with older IEEE 802.11a/b/g/n clients. This high level of throughput and range performance supports multimedia applications such as high definition video streaming.

The MIMO system improves reliability and capacity, mitigating the fading effects of a multipath environment.

### IEEE 802.11e Wireless Multimedia (WMM)

- ▶ Quality of Service (QoS) on WLAN optimizes resource use and fulfills the requirements of video, voice and data applications. Each of these applications creates different latency, bandwidth and packet error rate needs, and QoS caters to each of these needs using data traffic prioritization.

### IEEE 802.11i (security)

- ▶ This feature set facilitates strong encryption, authentication and key management strategies, guaranteeing data and system security. In addition to Counter Mode with Cipher Block Chaining Message Authentication Code Protocol (CCMP), IEEE 802.1X key distribution via RADIUS controls access to the network.

### Multiple-SSIDs and SSID-to-VLAN mapping

- ▶ SSID enables wireless connectivity for client devices that are assigned different security policies. Mapping SSIDs to VLANs creates logical

network separation, which differentiates between communication by application, functions or user communities.

### Dynamic VLANs

- ▶ Dynamic VLANs allow VLANs to be dynamically assigned on a per-user (wireless client) basis. The Dynamic VLAN feature interacts with an external RADIUS server, so that user information is centralized in RADIUS for ease of management. It is not necessary to configure user information on APs.

The TQ4600 also supports RADIUS server redundancy, via configuration of a secondary RADIUS server.

### PoE - IEEE 802.3af/at conformance

The TQ4600 conforms to the IEEE 802.3at standard and may operate under IEEE 802.3af power feeding.

At boot up time, the device adapts itself to the available power source and will limit the WiFi performance accordingly; if the device is powered via IEEE 802.3at, then the radio will provide the full operational capabilities, otherwise it works as 2x2:2ss MIMO access point.

This enables simplified deployment, lower installation costs, and centralized power management capabilities for critical network devices.

### Graphical User Interface

- ▶ The Web-based user interface is user-friendly and intuitive, minimizing training needs.

### Mounting options

- ▶ As well as simple desktop installation, the TQ4600 includes a kit for wall and ceiling mounting. A Kensington lock or padlock are suitable for anti-theft security.

- ▶ TQ4600 is certified in accordance with UL 2043, for use in plenums, ducts and other space used for environmental air.

### SDN-ready

- ▶ The OpenFlow feature is available for a true SDN solution. The SES SDN Controller offers both wired and wireless connectivity, for a seamless SDN solution. Please visit our website for more information about SDN.

## Specifications

### Operational Mode

Centrally controlled and managed by Allied Telesis Unified Wireless Controller  
 AP Cluster (up to 16 members)  
 Standalone

### Management

Graphical User Interface (HTTP, HTTPS)  
 Simple Network Management Protocol (SNMPv1, v2c)  
 Extended MIB set

### Bridging

VLAN tagging (up to 4094 VLANs)

### Security

Authentication, authorization, and accounting:

- ▶ 128-bit hardware-accelerated AES encryption/decryption
- ▶ IEEE 802.1x authentication
- ▶ WPA/TKIP, WPA2/CCMP
- ▶ Extensible Authentication Protocol (EAP)
- ▶ Protected Extensible Authentication Protocol (PEAP)
- ▶ IEEE 802.1X RADIUS support
- ▶ Layer 2 ACLs (up to 1024 MAC filters)
- ▶ Layer 4 ACLs
- ▶ IEEE 802.1X dynamic VLAN assignment
- ▶ Rogue AP detection

### Utilities

DHCP client  
 DNS client  
 NTP client  
 File transfer  
 Logging  
 Statistic information gathering

### Wireless

IEEE 802.11a/n 3x3:3ss SU-MIMO  
 IEEE 802.11ac 3x3:3ss SU-MIMO  
 IEEE 802.11b/g/n 3x3:3ss SU-MIMO  
 IEEE 802.11d  
 IEEE 802.11e (WMM)  
 IEEE 802.11h (DFS/TPC)  
 IEEE 802.11i (enhanced security)

- ▶ WPA/WPA2-Personal
- ▶ WPA/WPA2-Enterprise

Extensible Authentication Protocol (EAP):

- ▶ 3rd Generation Authentication and Key Agreement (EAP-AKA)
- ▶ Flexible Authentication via Secure Tunneling (EAP-FAST)
- ▶ GSM Subscriber Identity (EAP-SIM)
- ▶ Transport Layer Security (EAP-TLS)
- ▶ Tunneled Transport Layer Security (EAP-TTLS/MSCHAPv2)
- ▶ Protected Extensible Authentication Protocol (PEAP)
- ▶ Generic Token Card (PEAPv0/EAP-MSCHAPv2)
- ▶ Microsoft CHAP v2 (PEAPv1/EAP-GTC)

Regulatory domain compliance  
 Operating mode:

- ▶ Access point (up to 200 clients)
- ▶ Wireless Distribution System

Auto channel selection, with periodical refresh  
 Band steering  
 Beamforming  
 Indoor/Outdoor eligible channel list  
 Open Loop Power Control (OLPC)  
 SSID hiding/ignoring

Multiple SSID (up to 16 per port)  
 VLAN to SSID mapping  
 Extended Service Set (ESS)  
 User scan list  
 Advanced wireless interface tuning:

- ▶ Beacon period
- ▶ Client isolation
- ▶ Client max association
- ▶ IEEE 802.11b fall-back control
- ▶ IEEE 802.11n guard Interval
- ▶ Short radio preamble
- ▶ Short slot time

Advanced wireless service via UWC:

- ▶ Captive portal
- ▶ Dynamic channel planning
- ▶ Dynamic RF coverage optimization
- ▶ Plug and Play support (authentication and configuration)
- ▶ Standalone fallback
- ▶ Wireless IDS

Media access protocol

- ▶ CSMA/CA with ACK architecture 32-bit MAC

## Compliance Certificates

CE  
 EAC  
 FCC  
 IC  
 KC  
 RCM  
 TUV-T  
 Wi-Fi Certified (ID: WFA55543)

## ElectroMagnetic Compatibility

EN 301 489-1  
 EN 301 489-17  
 EN 55022, Class B  
 EN 55024  
 EN 61000-3-2, Class A  
 EN 61000-3-3  
 EN 61000-4-2  
 EN 61000-4-3  
 EN 61000-4-4  
 EN 61000-4-5  
 EN 61000-4-6  
 EN 61000-4-11  
 AS/NZS CISPR 22, Class B  
 FCC 47 CFR Part 15, Subpart B  
 ICES-003

## Medical (EMC)

EN 60601-1-2  
 CISPR 11

## Radio Equipment

EN 300 328  
 EN 301 893  
 AS/NZS 4268  
 FCC 47 CFR Part 15, Subpart C  
 FCC 47 CFR Part 15, Subpart E  
 FCC part 2  
 RSS-210  
 RSS-Gen  
 RSS-102

## Safety

CSA c22.2 No.60950-1 1st Ed. April 1, 2003  
 EN 60950-1  
 IEC 60950-1  
 UL 60950-1: 2003, First Edition  
 UL 2043 (plenum rated)

## Technical Specifications

### MTBF

1,172,600 hours (30°C)  
 646,600 hours (40°C)  
 Telcordia SR-332 Issue 3

### Power Characteristics

PoE

- ▶ Input voltage: IEEE 802.3at
- ▶ Max. consumption: 16W
- ▶ Avg. consumption: 9.8W

AC/DC power adapter

- ▶ Rated input voltage: AC 100–240 V
- ▶ Input voltage range: AC 90–264 V
- ▶ Rated frequency: 50/60 Hz
- ▶ Max. consumption: 16W
- ▶ Avg. consumption: 10.9W

### Environmental Specifications

Operating temperature: 0° to 40°C (32° to 104°F)  
 Operating humidity: ≤80% relative (non-condensing)  
 Storage temperature: -20° to 60°C (-4° to 140°F)  
 Storage humidity: ≤95% relative (non-condensing)

### Physical Specifications

Dimensions (W x D x H): 170 mm x 170 mm x 35 mm  
 (6.70 in x 6.70 in x 1.38 in)  
 Weight: 476g (1.05 lbs)  
 Enclosure: Metal base, plastic cover

## Interfaces

### Wired

Ethernet

- Standard: IEEE 802.3 (10T)  
 IEEE 802.3u (100TX)  
 IEEE 802.3ab (1000T)
- Ports: 1
- Connector: RJ-45 female

Console

- Standard: RS232
- Ports: 1
- Connector: RJ-45 female

### Wireless

WLAN radio 0

- Standard: IEEE 802.11b/g/n
- Ports: 1

WLAN radio 1

- Standard: IEEE 802.11ac
- Ports: 1

### Embedded Antennas

Omni-directional

- Frequency band: 2.4 GHz
- Max. peak gain: 3 dBi

Omni-directional

- Frequency band: 5 GHz
- Max. peak gain: 4 dBi

# TQ4600 | Enterprise-Class Wireless Access Point

## Radio Characteristics

### Standard

- ▶ IEEE 802.11 a/b/g/n/ac

### Supported frequencies (country-specific restrictions apply)

- ▶ 2.400 ~ 2.4835 GHz (ISM)
- ▶ 5.150 ~ 5.250 GHz (UNII-1)
- ▶ 5.250 ~ 5.350 GHz (UNII-2)
- ▶ 5.470 ~ 5.725 GHz (UNII-2 Extended)
- ▶ 5.725 ~ 5.850 GHz (UNII-3)

### Modulation Technique

- ▶ 802.11a/g/n/ac: OFDM
- ▶ 802.11b: DSSS, CCK, DQPSK, DBPSK
- ▶ 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
- ▶ 802.11a/g/n: BPSK, QPSK, 16QAM, 64QAM

### Media access

- ▶ CSMA/CA + Ack with RTS/CTS

### Diversity

- ▶ Spatial diversity

### Data Rate

- ▶ 802.11a/g: 54/48/36/24/18/12/9/6Mbps
- ▶ 802.11b: 11/5.5/2/1Mbps
- ▶ 802.11n: 6.5 – 450Mbps (MCS 0 - 23)
- ▶ 802.11ac: 6.5 – 1,300Mbps (MCS 0 - 9, NSS 1 - 3)

<sup>1</sup> Output power is the maximum signal level delivered by the radio. The signal level is automatically limited in accordance to the selected regulatory domain.



## Ordering Information

### AT-TQ4600-xx

Enterprise-Class Wireless Access Point with IEEE 802.11ac dual-band radio and embedded antenna

Where xx =

[none] Regulatory Domain: Worldwide (except United States and Canada)

01 Regulatory Domain: United States and Canada Reserved

## Related Products

### AT-UWC-60-APL

Wireless LAN controller for enterprises (hardware appliance)

### AT-UWC-BaseST

Wireless LAN controller for enterprises (software appliance installer, including licenses to manage 10 access points)

### AT-TQ0091

AC/DC power adapter for the TQ Series

## Feature Licenses

NAME	DESCRIPTION
AT-TQ4600-OF13	TQ4600 with OpenFlow enabled