

## Null Modem Serial RS232 Cable (DB9 M/F), 6-ft.

MODEL NUMBER: **P454-006**



### Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 6ft cable has a DB9 female connector on one end and a DB9 male connector on the other, and is considered a "Full Handshake" null modem cable. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

### Features

- DB9 female to DB9 male
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity

## Specifications

General Info	
Product Group	COMPUTER & STORAGE CABLES
OVERVIEW	
Intended Application	Connecting Peripherals
Cable Type	NULL MODEM
INPUT	
Cable Length (ft.)	6
Cable Length (m)	1.83

### Highlights

- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

### System Requirements

- Two serial devices (one with a DB9 Male connector and the Other with a DB9 Female connector) requiring a null modem (cross-wired) configuration

### Package Includes

- 6-ft. Null Modem Gold Cable DB9F to DB9M



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

<b>UPC ASSIGNMENT</b>	
Unit Carton UPC#	037332013347
<b>PHYSICAL</b>	
Color	Black
Style	Null Modem Cables
<b>CONNECTIONS</b>	
Connector A	DB9 (MALE)
Connector B	DB9 (FEMALE)
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.