DATASHEET - NZM1-XKAV



Toggle lever locking device

Part no. NZM1-XKAV

260199 4358739

EL Number

(Norway)



General specifications	
Product name	Eaton Moeller series NZM operating element accessory
Part no.	NZM1-XKAV
EAN	4015082601997
Product Length/Depth	38 millimetre
Product height	50 millimetre
Product width	75 millimetre
Product weight	0.036 kilogram
Compliances	IEC
Certifications	RoHS conform CE marking UL listed CSA (File No. 22086) UL489 CSA certified IEC60947 CSA-C22.2 No. 5-09 CSA (Class No. 1437-01) UL (File No. E140305) UL (Category Control Number DIHS)
Product Tradename	NZM
Product Type	Accessories
Product Sub Type	Operating element accessory
Delivery program	
Туре	Accessory, other Toggle lever interlock device
Features	Lockable
Frame	NZM1
Fitted with:	Padlock
Suitable for	Switch disconnector Power circuit breaker
Used with	NZM1(-4) N(S)1(-4) NZM1(-1) PN1(-4)
Technical Data - Mechanical	
Color	Other
Degree of protection / NEMA enclosure type	Other
Design verification as per IEC/EN 61439	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

$Low-voltage\ industrial\ components\ (EG000017)\ /\ Handle\ for\ power\ circuit\ breaker\ (Includes the components)\ for\ power\ circuit\ breaker\ (Includes the co$	EC000229)	
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage	No	
With key lock	No	
Padlock locking	Yes	
Colour	Other	
Suitable for emergency stop	No	
With extension shaft	No	
Suitable for power circuit breaker	Yes	
Suitable for switch disconnector	Yes	
Degree of protection (NEMA)	Other	