



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: BP24V70-3U

### BP24V70-3U - External Battery Pack for UPS System

#### Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 24VDC external battery connector
- Simple installation; 3U rackmount, tower and stack adaptable
- Supports multi-battery pack installations via built-in daisychain connector



#### Description

BP24V70-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Supports the connection of multiple BP24V70-3U battery packs via built-in daisychain connector. Includes heavy gauge cabling with high current DC connector for simple installation.

Compatible UPS Systems - OMNIVS1500XL, OMNIVSINT1500XL, SU750XL, SU750RTXL2U, SU1000XL, SU1000RTXL2Ua, SUINT1000RTXL2Ua, SMART750RML2U and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

#### Package Includes

- BP24V70-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports multi-battery pack installation via built-in daisychain connector
- Includes heavy gauge cabling with high current DC connectors for simple installation

#### Specifications

BATTERY	
DC system voltage (VDC)	24

<b>Connects to UPS via</b>	Attached cable with red/black 75 amp male DC connector
<b>Typical battery lifespan</b>	4-6 years typical (North America)
<b>PHYSICAL</b>	
<b>Shipping Dimensions (HWD/in)</b>	11.25 x 23 x 31.5
<b>Shipping Dimensions (HWD/cm)</b>	28.56 x 58.42 x 80.01
<b>Shipping weight (lbs)</b>	176.37
<b>Shipping weight (kg)</b>	80.07
<b>Unit Dimensions (HWD/in)</b>	5.25 x 17.5 x 25
<b>Unit Dimensions (HWD/cm)</b>	13.33 x 44.45 x 63.5
<b>Unit weight (lbs)</b>	138.89
<b>Unit weight (kg)</b>	63.06
<b>Material of construction</b>	Steel
<b>Form factors supported</b>	3U rack/tower
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S. &amp; Canada)</b>	2-year limited warranty
<b>Product Warranty Period (International)</b>	1-year limited warranty
<b>Product Warranty Period (Mexico)</b>	1-year limited warranty
<b>Product Warranty Period (Puerto Rico)</b>	1-year limited warranty
<b>Optional Coverage</b>	3 year, 5 year, next day and on-site warranty coverage available

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">WEXT3-BP24V</a>	3-Year Extended Warranty - For All 24V Battery Packs	1
<a href="#">WEXT5-BP24V</a>	5-Year Extended Warranty - For All 24V Battery Packs	1
<a href="#">2-9USTAND</a>	Enables Tower Placement of Rackmount UPS Systems	1
<a href="#">2POSTRMKITHD</a>	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3016](http://www.tripplite.com/en/products/model.cfm?txtModelID=3016).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.