

VersaLink C605 Colour Multifunction Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to www.connectkey.com.

System Specifications	VersaLink 605/X	
<b>One-sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 55 ppm colour and black and white Up to 53 ppm colour and black and white Up to 45 ppm colour and black and white	
<b>Two-sided Speed</b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 52 ppm colour and black and white Up to 50 ppm colour and black and white Up to 26 ppm colour and black and white	
Monthly Duty Cycle <sup>1</sup>	Up to 120,000 pages / month <sup>1</sup>	
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 15,000 pages	
Hard Drive	250 GB HDD	
Processor	1.05 GHz	
Memory	4 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform <sup>®</sup> , Xerox App Gallery, Xerox <sup>®</sup> Standard Accounting, Role Based Permissions, Convenience Authentication Enabled, Online Support	
Device Specifications		
Electrical Requirements		
North America	Voltage: 110-127V +/-10 % Frequency: 50/60 Hz +/-3 % , 12A	
Europe	Voltage: 220-240V +/- 10 % Frequency: 50/60 Hz +/-3 % , 8A	
Power Consumption		
Continuous Printing <sup>4</sup>	820 watts or less	
Ready (Standby) Mode <sup>4</sup>	90 watts or less	
Energy Saver (Sleep) Mode <sup>4</sup>	0.9 watts or less	
Operating Environment		
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)	
Required Temperature Range (Operating)	50° to 90° F (10° to 32° C)	
Required Relative Humidity	15% to 85%	
Sound Power Levels	Operating: 7.27 B(A) or less; Standby 4.84 B(A) or less	
Sound Pressure Levels	Operating 57.4 dB(A) or less, Standby 33.5 dB(A) or less	

Boot Time (from Off to UI Ready)	As fast as 65 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
VersaLink C605/X	18.5 in. / 470 mm	19.8 in. / 503 mm	25.4 in. / 643.7 mm	79.6 lb. / 36.1 kg
VersaLink C605/XL	19.2 in. / 487.5 mm	19.8 in. / 503 mm	33.2 in. / 843.7 mm	79.6 lb. / 36.1 kg
550-sheet Paper Tray	16.5 in. / 420 mm	18.3 in. / 464.5 mm	4.8 in. / 123 mm	4.1 lb. / 6.6 kg
High Capacity Feeder	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	18.1 in. / 459 mm	43.4 lb. / 19.7 kg
Stand	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	13.2 in. / 336 mm	37 lb. / 16.6 kg
Caster Base	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	3.5 in. / 90 mm	18.7 lb. / 8.5 kg
Mailbox	17.7 in. / 450.8 mm	18.8 in. / 477.6 mm	9.8 in. / 248.0 mm	11.7 lb. / 5.3 kg
Finisher	17.7 in. / 450.8 mm	16.2 in. / 411.0 mm	9.8 in. / 248.0 mm	15 lb. / 6.8 kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
VersaLink C605/X	23.4 in. / 594 mm	25.8 in. / 655 mm	31.1 in. / 789 mm	97 lb. / 44 kg
VersaLink C605/XL	24 in. / 610 mm	26.4 in. / 670 mm	43.7 in. / 1110 mm	97 lb. / 44 kg
550-sheet Paper Tray	21.1 in. / 535 mm	23 in. / 584 mm	9.8 in. / 248 mm	18.7 lb. / 8.5 kg
High Capacity Feeder	22.4 in. / 568 mm	26.1 in. / 663 mm	28 in. / 711 mm	83.8 lb. / 38 kg
Stand	23 in. / 584 mm	24.8 in. / 629 mm	23.5 in. / 597 mm	57.3 lb. / 28 kg
Caster Base	23 in. / 585 mm	24.4 in. / 619 mm	13 in. / 330 mm	39.7 lb. / 18 kg
Mailbox	22.6 in. / 573 mm	20.4 in. / 518 mm	15.2 in. / 386 mm	16.3 lb. / 7.8 kg
Finisher	22.6 in. / 573 mm	15.7 in. / 398 mm	15.2 in. / 386 mm	18.6 lb. / 8.8 kg
Certifications				
	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
Print				
First-print-out Time	As fast as 10 seconds co	As fast as 10 seconds colour and black and white		
Print Resolution	Up to 1200 x 2400 dpi			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from edge of paper			

Print Feαtures	Application DefaultsBi-directional Real-time StatusBooklet CreationDraft ModeJob IdentificationJob MonitoringPersonal PrintPrint from USBSample SetSaved JobScalingSecure PrintSkip Blank PagesStore and Recall Driver SettingsTwo-sided Printing (as default)Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS	
Operating Systems	Windows <sup>®</sup> , 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2 Server 2012 Mac OS <sup>®</sup> version 10.10, 10.11, & 10.12 Citrix Redhat <sup>®</sup> Enterprise Linux <sup>®</sup> IBM <sup>®</sup> AIX <sup>®</sup> 7.2 HP-UX <sup>®</sup> 11iv3 Oracle <sup>®</sup> Solaris 11.3 Fedora Core 24 SUSE <sup>®</sup> 13.2	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ FTP Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Сору		
Document Scanner	100-sheet Single-Pass Duplex Automatic Document Feeder (DADF)	
Maximum Scan Area	Platen: Up to 8.5 x 14 in. / 216 x 356 mm DADF: Up to 8.5 x 14 in. / 216 x 356 mm	
Simplex Copy Speed	Up to 55 cpm (copies per minute) 8.5 x 11 in. Up to 53 cpm A4 / 210 x 297 mm	
Duplex Copy Speed	Up to 50 cpm (copies per minute) 8.5 x 11 in. Up to 47 cpm A4 (210 x 297 mm)	
First-copy-out Time	As fast as 7 seconds colour / 5 seconds black and white	
Sides (input:output)	1:1, 1:2, 2:2 and 2:1	
Quantity	1 to 999	
Resolution (max.)	Up to 600 x 400 dpi	
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Concurrent scanning and printing	

Copy Features	Automatic Background Suppression Book Copying with Center Erase Collation Darkness Control Edge Erase ID Card Copy N-up Reduce / Enlarge 25 % to 400 % Image Shift Original Type Sample Copy Sharpness	
Scan		
Capability	Black and white and colour scanning	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Simplex Input Speed	Black-and-white: Scan up to 49 ipm 8.5 x 11 in. / 46 ipm A4 Color: Scan up to 47 ipm 8.5 x 11 in. / 46 ipm A4	
Duplex Input Speed	Black-and-white: Scan up to 75 ipm 8.5 x 11 in. / 71 ipm A4 Color: Scan up to 55 ipm 8.5 x 11 in. / 52 ipm A4	
Resolution	Optical – 600 x 600 dpi	
Bit Depth	24-bit colour / 8-bit grayscale	
Maximum Scan Area	Platen: Up to 8.5 x 14 in. / 216 x 356 mm Document Feeder: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocols	FTP SMTP SMB	
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A	
Scan Driver Compatibility (Network Only)	WIA TWAIN	
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)	
Network Scanning – Software Solu	itions	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.	
Fax		
Fax <sup>5</sup>		
Fax Speed	33.6 Kbps	
Memory	4 MB	
Resolution	Up to 600 x 600 dpi resolution	
Compression	MH, MR, MMR, JBIG	

Fax Features	Walk-up Fax, LAN Fax, Direct Fax, Fax Forward to Email		
	Fax dialing via Unified Address Book (up to 2,000 contacts)		
Mobile Solutions and Mobile Devi	Mobile Solutions and Mobile Device Apps		
Xerox <sup>®</sup> Mobile Express Driver <sup>®</sup>	Makes it easy for mobile users to find, use and manage Xerox <sup>®</sup> and non-Xerox <sup>®</sup> devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favourite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox <sup>®</sup> Global Print Driver <sup>®</sup>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.		
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox <sup>®</sup> Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play <sup>™</sup> store.		
Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)	The Xerox <sup>®</sup> Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox <sup>®</sup> multifunction printer.		
Xerox <sup>®</sup> Print Management and Mobility Suite, Xerox <sup>®</sup> Print Management and Mobility Service	Xerox <sup>®</sup> Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.		
Security			
Standard Security Features	Firmware Verification Security Certificate Management Automatic Self-Signed Certificate Creation Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP) Certificate Path Validation Immediate Disk Overwrite AES 256-bit Encryption FIPS 140-2 TLS/SSL SNMPv3 Smart Card Enablement (CAC/PIV/.NET) Detection of external programme falsification (XCP Plug-in) Network Authentication Access Controls Role Based Permissions Domain Filtering IP Address Filtering Port Filtering Audit Log Secure Email Secure Fax Secure Fax		

Accounting		
Xerox® Standard Accounting / Network Accounting (Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage	
Accounting	Xerox <sup>®</sup> Standard Accounting Up to 9,999 User Accounts with HDD installed, 1,000 User Accounts without HDD installed Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs Up to 14,000 accounting records (transactions)	
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools</li> <li>Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file</li> </ul>	
Accounting Options – N	etwo <mark>r</mark> k Accounting (Allows central server to manage all accounting)	
	<ul> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com</li> <li>Security enhancements includes support for HTTPS protocol</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>	
Paper Handling		
Document Feeder		
Capacity <sup>3</sup>	Single-Pass Duplex Automatic Document Feeder (DADF): 100 sheets	
Sizes	Custom sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 140 x 140 mm to 216 x 356 mm	
Weights	Simplex: 16 lb. bond to 32 lb. bond / 60 to 128 gsm Duplex: 16 lb. bond to 32 lb. bond / 60 to 128 gsm	
Bypass Tray		
Capacity <sup>3</sup>	150 sheets	
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm	
Media Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled	
Tray 1		
Capacity <sup>3</sup>	550 sheets	
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 190 mm to 216 x 356 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm	

Media Types Up to Four Additional Trays (Opt	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled Envelope ional	
Capacity <sup>3</sup>	550 sheets	
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in. / 76 x 190 mm to 216 x 356 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm	
Media Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled	
High Capacity Feeder (Optional -	- only one additional 550-sheet Tray can be added to High Capacity Feeder)	
Capacity <sup>3</sup>	2,000 sheets	
Sizes	Letter/A4	
Weights	16 lb. bond to 65 lb. cover / 60 to 176 gsm	
Media Types	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled	
Total Capacity		
Standard Device Capacity <sup>3</sup>	700 sheets	
Maximum Device Capacity <sup>3</sup>	3,250 sheets	
Paper Output / Finishing		
Capacity <sup>3</sup>	Up to 400 sheets	
Automatic Two-sided Printing	Standard	
Finisher (Optional)		
Capacity <sup>3</sup>	500-sheet tray, 50-sheet stapling	
Mailbox (Optional)		
Capacity <sup>3</sup>	Four 100-sheet bins	

Device Management			
Xerox® CentreWare® Web Software			
	<ul> <li>A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		
Xerox <sup>®</sup> Embedded Web Server – I	ntegrated Device Web Page		
Device Status	<ul> <li>Tray status/contents</li> <li>Consumables status</li> <li>Billing/Usage</li> <li>Quick Links</li> </ul>		
Print Queue Viewing	Job print queue management—view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft® Internet Explorer® 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52		
Remote Services			
Xerox <sup>®</sup> Meter Assistant <sup>®</sup> Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox <sup>®</sup> device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox <sup>®</sup> Supplies Assistant <sup>®</sup> Service	Automatically orders supplies for Xerox <sup>®</sup> output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
What's In The Box			
	VersaLink C605 Colour Multifunction Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 6,000 print capacity <sup>6</sup> , Black: 10,000 print capacity <sup>6</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord Fax cord		

Supplies and Accessories	Quantity	Part Number		
Supplies				
Standard Capacity Print Cartridges	Black: 6,000 standard pages <sup>6</sup> Cyan: 6,000 standard pages <sup>6</sup> Magenta: 6,000 standard pages <sup>6</sup> Yellow: 6,000 standard pages <sup>6</sup>	106R03911 106R03908 106R03909 106R03910		
High Capacity Print Cartridges	Black: 12,200 standard pages <sup>6</sup> Cyan: 10,100 standard pages <sup>6</sup> Magenta: 10,100 standard pages <sup>6</sup> Yellow: 10,100 standard pages <sup>6</sup>	106R03915 106R03912 106R03913 106R03914		
Extra High Capacity Print Cartridges	Black: 16,900 standard pages <sup>6</sup> Cyan: 16,800 standard pages <sup>6</sup> Magenta: 16,800 standard pages <sup>6</sup> Yellow: 16,800 standard pages <sup>6</sup>	106R03939 106R03936 106R03937 106R03938		
Routine Maintenance Items	Routine Maintenance Items			
Drum Cartridges	Cyan: 40,000 pages <sup>7</sup> Magenta: 40,000 pages <sup>7</sup> Yellow: 40,000 pages <sup>7</sup> Black: 40,000 pages <sup>7</sup>	108R01485 108R01486 108R01487 108R01488		
Waste Cartridge	30,000 pages <sup>7</sup>	108R01416		
Accessories	Accessories			
550-sheet Feeder		097504949		
High Capacity Feeder		097504948		
Cabinet		097S04955		
Stand/Casters (included with High Capacity Feeder and Cabinet)		097S04954		
Finisher (500 sheets, 50-sheet stapler)		097S04952		
4-Bin Mailbox (100 sheets per bin)		097S04953		
Wireless Network Adapter (Wi-Fi Kit)		497K16750		

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis. <sup>2</sup> Expected regular monthly throughput. <sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks. <sup>4</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment. <sup>5</sup> Requires analog phone line. <sup>6</sup> Avarance transford program per performance in programme requirements for Imaging Equipment.

<sup>7</sup>Approximate pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode. <sup>7</sup>Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

Configurations vary by geography.

