

HIGH QUALITY VIDEO AND AUDIO

- MJPEG and MPEG4 dual-codec
- 30 fps (NTSC) / 25 fps (PAL)
- Adjustable video quality

POWERFUL VIDEO MANAGEMENT

- Instant local video recording
- Intuitive web-based GUI
- Pre/post buffer for video recording
- D-Link DDNS support
- Upload snapshots via e-mail
- Upload video clips via FTP

ADVANCED ALARM HANDLING

- Motion detection with configurable detection areas
- FTP and e-mail event handler

OPTIONAL ACCESSORIES*

Straight Tube



DCS-32-1: Long
DCS-32-2: Short

Standard Pendant



DCS-32-3

Mini Pendant



DCS-32-4

Outdoor Power Box



DCS-80-5: INPUT: 100 ~ 115VAC +/- 10 %
DCS-80-6: INPUT: 220 ~ 230VAC +/- 10 %

- AC 24V linear power adapter
- IP66 case

*not included with camera



D-Link Corporation
No. 289 Xinhu 3rd Road, Neihu, Taipei 114, Taiwan
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2010 D-Link Corporation. All rights reserved.
Release 02 (April 2010)