



# Xerox<sup>®</sup> VersaLink<sup>®</sup> B615 Multifunction Printer

VersaLink B615 Multifunction Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com).

System Specifications		B615/X	B615/XL
<b>One-sided Speed</b> A4 / 210 x 297 mm		Up to 63 ppm black and white	
<b>Two-sided Speed</b> A4 / 210 x 297 mm		Up to 56 ppm black and white	
<b>Monthly Duty Cycle<sup>1</sup></b>		Up to 275,000 pages / month	
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>		Up to 25,000 pages	
<b>Hard Drive</b>		250 GB HDD	
<b>Processor</b>		1.05 GHz ARM Dual Core	
<b>Memory</b>		2 GB	
<b>Connectivity</b>		Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
<b>Controller Features</b>		Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform <sup>®</sup> , Xerox App Gallery, Xerox <sup>®</sup> Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled, Online Support (accessed from the user interface and print driver)	
Device Specifications			
Electrical Requirements			
<b>Europe</b>		Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % Hz, 8 A	
Power Consumption			
<b>Continuous Print<sup>3</sup></b>		950 watts or less	
<b>Ready (Standby)<sup>3</sup></b>		79 watts or less	
<b>Energy Saver (Sleep Mode)<sup>3</sup></b>		1.1 watts or less	
<b>Power Off Mode<sup>3</sup></b>		0.3 watts or less	
Operating Environment			
<b>Required Temperature Range (Storage)</b>		0° to 35° C	
<b>Required Temperature Range (Operating)</b>		10 to 32° C	
<b>Required Relative Humidity</b>		15% to 85%	
<b>Sound Power Levels</b> Running Standby		70 dB(A) or less 43 dB(A) or less	

## Xerox® VersaLink® B615 Multifunction Printer

<b>Sound Pressure Levels</b> Running Standby	58.3 dB(A) or less 29 dB(A) or less			
<b>Warm up (from Sleep Mode)</b>	Less than 47 seconds			
<b>Boot Time</b>	Less than 79 seconds			
<b>Dimensions and Weight (Unpackaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
<b>B615/X</b>	470 mm	502.8 mm	643.7 mm	30.5 kg
<b>B615/XL</b>	470 mm	502.8 mm	843.7 mm	32.5 kg
<b>B615/XL with Finisher</b>	470 mm	502.8 mm	843.7 mm	39.3 kg
<b>B615/XL with Mailbox</b>	470 mm	502.8 mm	843.7 mm	37.8 kg
<b>B615/X with High Capacity Feeder</b>	724.2 mm	772.1 mm	1,102.7 mm	50.2 kg
<b>B615/XL with High Capacity Feeder and Finisher</b>	724.2 mm	772.1 mm	1,302.7 mm	59 kg
<b>B615/XL with High Capacity Feeder and Mailbox</b>	724.2 mm	772.1 mm	1,302.7 mm	57.5 kg
<b>550-sheet Tray</b>	420 mm	464.5 mm	123 mm	6.6 kg
<b>High Capacity Feeder (includes Caster Base)</b>	724.2 mm	772.1 mm	459 mm	19.7 kg
<b>Stand (includes Caster Base)</b>	724.2 mm	772.1 mm	336 mm	16.6 kg
<b>Caster Base</b>	724.2 mm	772.1 mm	90 mm	8.5 kg
<b>Mailbox</b>	450.8 mm	477.6 mm	248 mm	5.3 kg
<b>Finisher</b>	450.8 mm	411.0 mm	248 mm	6.8 kg
<b>Dimensions and Weight (Packaged)</b>	<b>Width</b>	<b>Depth</b>	<b>Height</b>	<b>Weight</b>
<b>B615/X</b>	594 mm	655 mm	789 mm	38 kg
<b>B615/XL</b>	594 mm	655 mm	996 mm	43 kg
<b>550-sheet Tray</b>	535 mm	584 mm	248 mm	8.5 kg
<b>High Capacity Feeder</b>	568 mm	663 mm	711 mm	38 kg
<b>Stand</b>	584 mm	629 mm	597 mm	28 kg
<b>Caster Base</b>	585 mm	619 mm	330 mm	18 kg
<b>Mailbox</b>	573 mm	518 mm	386 mm	7.8 kg
<b>Finisher</b>	573 mm	398 mm	386 mm	8.8 kg
<b>Wireless Network Adapter (Wi-Fi Kit)</b>	188 mm	136 mm	55 mm	0.1 kg
<b>Certifications</b>				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				
<b>Print</b>				
<b>First-print-out Time</b>	As fast as 6.6 seconds			
<b>Print Resolution</b>	Up to 1200 x 1200 dpi			

## Xerox® VersaLink® B615 Multifunction Printer

<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™
<b>Maximum Print Area</b>	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper
<b>Print Features</b>	Application Defaults Bi-directional Real-time Status Booklet Creation Draft Mode Job Identification Job Monitoring Personal Print Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Store and Recall Driver Settings Two-sided Printing (as default) Xerox® Earth Smart Driver Settings
<b>Print from USB</b>	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS
<b>Operating Systems</b>	Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2 Server 2012 Mac OS® version 10.10, 10.11, 10.12 Citrix Redhat® Enterprise Linux® IBM® AIX® 7.2 HP-UX® 11iv3 Oracle® Solaris 11.3 Fedora Core 24 SUSE® 13.2
<b>Fonts</b>	PostScript fonts: 136 PCL fonts: 83
<b>Copy</b>	
<b>Document Scanner</b>	100-sheet Single-pass Duplex Automatic Document Feeder (DADF)
<b>Maximum Scan Area</b>	Platen: Up to 215.9 mm x 355.6 mm DADF: Up to 215.9 mm x 355.6 mm
<b>Simplex Copy Speed</b>	Up to 65 cpm (copies per minute) A4 black and white
<b>Duplex Copy Speed</b>	Up to 58.5 cpm A4 black and white
<b>First-copy-out Time</b>	As fast as 5.4 seconds
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1
<b>Quantity</b>	1 to 999
<b>Resolution (max.)</b>	Up to 600 x 600 dpi
<b>Reduction / Enlargement</b>	Variable zoom from 25 % to 400 % in 1 % increments
<b>Concurrency</b>	Concurrent scanning and printing

# Xerox® VersaLink® B615 Multifunction Printer

<b>Copy Features</b>	Automatic Background Suppression Book Copying with Center Erase Collation Darkness Control Edge Erase ID Card Copy N-up Reduce / Enlarge 25 % to 400 % Image Shift Original Type Sample Copy Sharpness
<b>Scan</b>	
<b>Capability</b>	Black and white and colour scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Simplex Input Speed</b>	Black and white: Scan up to 65 ipm (images per minute) – 215.9 x 279.4 mm Colour: Scan up to 55 ipm – 215.9 x 279.4 mm
<b>Duplex Input Speed</b>	Black-and-white: Scan up to 65 ipm (images per minute) – 215.9 x 279.4 mm Colour: Scan up to 55 ipm – 215.9 x 279.4 mm
<b>Resolution</b>	600 x 600 dpi
<b>Bit Depth</b>	24-bit colour / 8-bit grayscale
<b>Maximum Scan Area</b>	Platen: Up to 215.9 x 355.6 mm Document Feeder: Up to 215.9 x 355.6 mm
<b>Network Filing Protocols</b>	FTP SMTP SNMB
<b>File Formats</b>	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A
<b>Scan Driver Compatibility (Network Only)</b>	WIA TWAIN
<b>Supported Scan Destinations</b>	Scan to Home Scan to USB Scan to Email Scan to Network (FTP or Browse SMB)
<b>Network Scanning – Software Solutions</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled device.
<b>Fax</b>	
<b>Fax<sup>4</sup></b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Memory</b>	4 MB
<b>Resolution</b>	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi
<b>Compression</b>	MH/MR/MMR/JBIG
<b>Fax Features</b>	Walk-up Fax, LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)

# Xerox® VersaLink® B615 Multifunction Printer

Mobile Solutions and Mobile Device Apps	
<b>Xerox® Mobile Express Driver®</b>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favourite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
<b>Apple® AirPrint®</b>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
<b>Google Cloud Print™</b>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)</b>	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.
<b>Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service</b>	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.
Security	
<b>Standard Security Features</b>	<ul style="list-style-type: none"> <li>Firmware Verification</li> <li>Security Certificate Management</li> <li>Automatic Self-Signed Certificate Creation</li> <li>Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP)</li> <li>Certificate Path Validation</li> <li>Immediate Disk Overwrite</li> <li>AES 256-bit Encryption</li> <li>FIPS 140-2</li> <li>TLS/SSL</li> <li>SNMPv3</li> <li>Smart Card Enablement (CAC/PIV/.NET)</li> <li>Detection of external programme falsification (XCP Plug-in)</li> <li>Network Authentication</li> <li>Access Controls</li> <li>Role Based Permissions</li> <li>Domain Filtering</li> <li>IP Address Filtering</li> <li>Port Filtering</li> <li>Audit Log</li> <li>Secure Email</li> <li>Secure Fax</li> <li>Secure Print</li> <li>Secure Scan</li> </ul>
Accounting	
<b>Xerox® Standard Accounting / Network Accounting (Standard)</b>	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage

# Xerox® VersaLink® B615 Multifunction Printer

<b>Accounting</b>	Up to 9,999 User Accounts Up to 500 General Accounts (Client)
<b>Features</b>	<ul style="list-style-type: none"> <li>• Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>• Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file.</li> </ul>
<b>Accounting Options – Network Accounting (Allows central server to manage all accounting)</b>	
	<ul style="list-style-type: none"> <li>• Enhanced network accounting with up to the minute data on how the system is being used</li> <li>• Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax</li> <li>• Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>• Security enhancements with the addition of HTTPS protocol support</li> <li>• Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>• Accept Authentication Login at control panel and pass to third party Networking Account</li> <li>• Interface with third party accounting terminal for accounting user interface</li> </ul>
<b>Paper Handling</b>	
<b>Document Feeder</b>	
<b>Capacity<sup>5</sup></b>	Single-pass Duplex Automatic Document Feeder (DADF): 100 sheets
<b>Sizes</b>	Custom sizes: 140 x 140 mm to 216 x 356 mm
<b>Weights</b>	60 to 128 gsm
<b>Bypass Tray</b>	
<b>Capacity<sup>5</sup></b>	150 sheets
<b>Sizes</b>	Custom sizes: 76 x 127 mm to 216 x 356 mm
<b>Weights</b>	60 to 220 gsm
<b>Media Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5
<b>Tray 1</b>	
<b>Capacity<sup>5</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 76.2 x 190 mm to 216 x 356 mm
<b>Weights</b>	60 to 220 gsm
<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5
<b>Up to 4 Additional Trays (Optional)</b>	
<b>Capacity<sup>5</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 76.2 x 190 mm to 216 x 356 mm

## Xerox® VersaLink® B615 Multifunction Printer

<b>Weights</b>	60 to 220 gsm
<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Card Stock Card Stock Letterhead Custom 1 - 5
<b>High Capacity Feeder (Optional)</b>	
<b>Capacity<sup>5</sup></b>	2000 sheets
<b>Sizes</b>	Standard sizes: A4 SEF
<b>Weights</b>	60 to 176 gsm
<b>Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Lightweight Card Stock Letterhead Custom 1 - 5
<b>Total Paper Capacity<sup>5</sup></b>	
<b>Standard Paper Capacity</b>	700 sheets
<b>Maximum Paper Capacity</b>	3,250 sheets
<b>Paper Output</b>	
<b>Output Tray</b>	
<b>Capacity<sup>5</sup></b>	400 sheets with tray full sensor (without Finisher or Mailbox)
<b>Automatic Two-sided Printing</b>	Standard
<b>Finisher (Optional on B615/XL)</b>	
<b>Capacity<sup>5</sup></b>	500-sheet tray, 50-sheet stapling
<b>Mailbox (Optional on B615/XL)</b>	
<b>Capacity<sup>5</sup></b>	Four 100-sheet bins
<b>Device Management</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint® FTP Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
<b>Xerox® CentreWare® Web</b>	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>

## Xerox® VersaLink® B615 Multifunction Printer

Embedded Web Server – Integrated Device Web Page	
<b>Device Status</b>	Web server embedded <ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Billing / Usage</li> <li>• Quick Links</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—view and delete
<b>Job Submission</b>	Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52
Remote Services	
<b>Automated Meter Reading (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automated Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox output devices based on actual usage, eliminating the need to manually manage supplies inventory.
<b>MaintenanceAssistant</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
What Comes in the Box	
	VersaLink B615 Multifunction Printer Standard Capacity Print Cartridge –Black: 10,300 print capacity <sup>6</sup> Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power cord Fax cord



# Xerox® VersaLink® B615 Multifunction Printer

Supplies and Accessories	Quantity	Part Number
<b>Supplies</b>		
<b>Extra-High Capacity Toner Cartridge</b>	Black: 46,700 standard pages <sup>6</sup>	106R03944
<b>High Capacity Toner Cartridge</b>	Black: 25,900 standard pages <sup>6</sup>	106R03942
<b>Standard Capacity Toner Cartridge</b>	Black: 10,300 standard pages <sup>6</sup>	106R03940
<b>Drum Cartridge</b>	Black: 60,000 pages <sup>7</sup>	101R00582
<b>Accessories / Options</b>		
<b>2,000-sheet High Capacity Feeder</b>		097S04948
<b>550-sheet Tray</b>		097S04949
<b>Finisher (500 sheets, 50-sheet stapler)</b>		097S04952
<b>4-Bin Mailbox (100 sheets per bin)</b>		097S04953
<b>Caster</b>		097S04954
<b>Stand</b>		097S04955
<b>Wireless Network Adapter (Wi-Fi Kit)</b>		497K16750

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

<sup>4</sup> Requires analogue phone line.

<sup>5</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit [www.xerox.com/about-xerox/recycling](http://www.xerox.com/about-xerox/recycling).

[www.xerox.com](http://www.xerox.com)

Configurations vary by geography.

