

## 3 Port HDMI® Auto Switch w/ IR Remote Control

StarTech ID: VS123HD



The VS123HD 3-port HDMI® Auto Switch features three prioritized HDMI input ports. If the active HDMI source is turned off, disconnected, or otherwise lost, the switch automatically selects the next available HDMI signal as the priority output, ensuring the display is always receiving a signal.

The automatic switch includes an IR Remote Control, so you'll be able to share an HD projector or display between three HDMI audio/video sources, with the option to manually control the switch from a distance or through the easy-to-use front panel toggle button.

Ideal for High-Definition applications, this 3-in/1-out HDMI switch supports true High-Definition 1080p resolutions (WUXGA/1920x1200 from PC/computer) as well as 7.1 Surround Sound audio, ensuring the best possible multimedia experience from connected devices.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Applications

- Switching between High-Definition audio-video devices e.g Blu-ray players, satellite receivers, video game consoles or computers with HDMI output
- Digital signage scenarios that require a signal always be available to a display

## Features

- Transparent, automatic HDMI switching
- IR remote control
- Built-in HDMI display cable saves you from purchasing an additional cable
- Supports HDTV resolutions up to 1080p
- Supports PC resolutions up to 1920x1200
- Easy installation and set up in minutes
- Allows for cables up to 30ft (10m) in length
- Supports High Speed HDMI device switching
- HDCP Compliant
- Supports 3D Video

## Technical Specifications

Warranty	2 Years
Color	Black
Enclosure Type	Plastic
Product Height	25 mm [1 in]
Product Length	81 mm [3.2 in]
Product Weight	99.5 g [3.5 oz]
Product Width	55 mm [2.2 in]
Audio	Yes
Industry Standards	High Speed HDMI®, HDCP
Output Signal	HDMI
Ports	3
Max Distance	10 m / 33 ft
Maximum Digital Resolutions	1920x1200
Wide Screen Supported	Yes
Connector A	1 - HDMI (19 pin) Male
Connector B	3 - HDMI (19 pin) Female
<b>Note</b>	Port 1 is set to have higher priority than port 2 or port 3 when all signals are on. Port 2 is set to have higher priority than port 3 when both signals are on, but Port 1 is off.
LED Indicators	3 - Two Green for Display Status, and one red for power.
Humidity	10% to 85%RH
Operating Temperature	0°C to 70°C (32°F to 158°F)
Storage Temperature	-65°C to 150°C (-85°F to 302°F)
Shipping (Package) Weight	178.2 g [6.3 oz]
Included in Package	1 - 3 Port High Speed HDMI® Auto Switch
Included in Package	1 - Remote Control

Included in Package 1 - IR Extender Cable

Included in Package 1 - Instruction Manual

## Certifications, Reports and Compatibility

