

## 32" Curved Fast Action 144Hz Gaming Monitor

**XG3202-C**



The ViewSonic® XG3202-C is a 32" (31.5" viewable) 144Hz gaming monitor, featuring 1800R curvature to deliver wide field of view and smooth image performance. Compatible with Free-Sync Technology, this monitor's variable refresh rate capabilities virtually eliminate screen tearing and stuttering for unbelievably fluid gameplay during fast-paced action sequences. This monitor features a 1080p SuperClear® VA panel for enhanced color accuracy and greater viewing angles. Low input lag provides smooth screen performance even in the most graphic-intense sequences. For a game-winning competitive edge, a Game Mode feature optimizes visuals for FPS, RTS and MOBA, let you enjoy better color performance of the game play.

**Key Features:**

1800R Curvature

144Hz Refresh Rate

AMD FreeSync™ Technology

Low Input Lag

SuperClear® VA

**Designed for:**

Gaming

# 32" Curved Fast Action 144Hz Gaming Monitor

**XG3202-C**

## Specifications

<b>LCD</b>	Type	32" (16:9)	
	Panel Technology	VA(curved 1800R)	
	Display Area	31.5"(698.4x392.85)	
	Optimum Resolution	1920x1080 (Full HD)	
	Brightness	300 cd/m <sup>2</sup> (Typ.)	
	Contrast Ratio	3000 :1 (Typ.)	
	Dynamic Contrast Ratio	120,000,000 :1	
	Viewing Angle	178°(H) / 178° (V)	
	Response Time	GTG(avg, scaler OD):6ms(Typ)(ultra fast of user mode)	
	Panel Surface	Anti-Glare type, Hard-coating (3H)	
	Light Source	30000 Hrs (Min.)	
	Color Support	16.7M colors	
	<b>INPUT</b>	Analog	VGA
		Digital	HDMI /DisplayPort
Frequency		Separate Sync	
Sync		Fh = 24 ~ 82 kHz ; Fv = 50 ~ 75 Hz	
<b>COMPATIBILITY</b>	PC	1920 x 1080 @60Hz for VGA 1920 x 1080 @144Hz for Dual Link DVI/HDMI/DP	
	Mac®	1920 x 1080 @60Hz for VGA 1920 x 1080 @144Hz for Dual Link DVI/HDMI/DP	
	<b>AUDIO</b>	Speaker 2W x2	
	<b>CONNECTOR</b>	Analog	VGA x1
Digital		Dual-DVI x1 / HDMI 1.4 x1 / DisplayPort 1.2a x1	
Audio in		3.5mm jack x1	
Audio Out		3.5mm jack x1	
USB		USB 2.0 down stream for charging x 1	
Power		Internal Power Board	
<b>POWER</b>		Voltage	AC 100-240V (Universal); 50/60 Hz
	Consumption	45W ; Optimize: 38W ; Conserve: 32W	
	Save mode	≤0.5 W	
<b>ERGONOMICS</b>	Tilt	13° ~ -5°	
<b>OPERATING CONDITIONS</b>	Temperature	32°F to 104°F (0°C to 40°C)	
	Humidity	20% to 90% (no condensation)	
<b>DIMENSIONS</b>	Physical (w / stand)	721.2 (W) x 495.22 (H) x 230.42 (D) mm	
<b>WEIGHT</b>	Net (w / stand)	8.1kg	
<b>REGULATIONS</b>		CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, WEEE, Custom Union, BSMI, RCM, MEPS, KC, e-Standby, CCC, CEL	
<b>WALL MOUNT</b>	VESA	100 x 100 mm	
<b>PACKAGE CONTENTS</b>		LCD Display / Power Cable / Dual Link DVI Cable/ Audio Cable / Quick Start Guide / ViewSonic Wizard CD-ROM	