

IN1110 Series

InFocus

Ultra-Portable Projectors with LightCast and PC-less Display

Part #s: IN1116, IN1118HD, IN1116LC, IN1118HDLC

The IN1110 Series mobile projectors are the brightest products on the market, lumens per pound and go anywhere. Whether you want to present from a PC, Airplay or Miracast or no external device at all, these book-sized projectors are the answer.

Key Features

- Compact and light weight for easy travel
- IN1118HD and IN1118HDLC are the only full 1080p HD products on the market at this ultra-portable size
- 2,400 lumens for bright images in any light
- PC-less display from USB drive or 4GB of memory
- LightCast ready for Airplay, Miracast and Chrome device display (Unlocked free with LC models)
- Connect via HDMI and USB with ease
- Includes carrying case for easy portability
- Durable, road-tested design that's built to last

"If you need maximum performance in a compact form factor, the InFocus IN1118HD should be on your short list. Highly recommended."

- Chris Eberle, hometheaterhifi.com

LightCast Wireless Device Collaboration

Unlock InFocus' LightCast technology to wirelessly project your Apple, Windows or Chrome device content using its native AirPlay and Miracast software or our free LightCast Sender.

LightCast also gives your projector an Internet browser and digital whiteboard to use without connecting a device. LightCast Key comes free with in the LC models.



IN1116

WXGA (1280 x 800)
2,400 lumens
1.18-1.54 throw ratio

IN1116LC

WXGA (1280 x 800)
2,400 lumens
1.18-1.54 throw ratio

IN1118HD

1080p (1920 x 1080)
2,400 lumens
1.15-1.5 throw ratio

IN1118HDLC

1080p (1920 x 1080)
2,400 lumens
1.15-1.5 throw ratio

Carry it Everywhere

At only 3.5 lbs. and the size of a small hardback novel, IN1110 Series projectors are easy to pack and carry in their included soft case, a backpack or your laptop bag. Take your presentations with you and never worry about on-site AV again.

Display from No Device at All

Leave your laptop behind and project images, audio and video directly from these projectors' on-board 4GB memory. Just load your files and go.

Built for the Road

These projectors have a recessed lens to keep them safe from impact. Plus their smooth exterior has no edges to snag or break off when putting it in or removing it from a carrying case.

Display	IN1116	IN1116LC	IN1118HD	IN1118HDLC
Resolution	WXGA (1280 x 800)		1080p (1920 x 1080)	
Video Compatibility	Standard: NTSC, NTSC 4.43, PAL/M/N, SECAM SD: 480i, 480p, 576i HD: 720p, 1080i, 1080p			
Illumination Technology	UHP Lamp 170W			
Display Technology	DLP			
Brightness (Eco/High)	1,920 / 2,400			
Contrast Ratio	14,000:1		15,000:1	
Aspect Ratio	16:10 (Standard) / 4:3 and 16:9 (Compatible)		16:9 (Standard) / 4:3 and 16:10 (Compatible)	
Projection Lens (f-stop)	F2.59 - 2.91			
Zoom Ratio	1.3:1			
Throw Distance	1.0m - 10.0m			
Throw Ratio	1.18 - 1.54		1.15 - 1.5	
Image width	30 - 300 inches			
Vertical/Offset	15%			
Auto Keystone	Yes, ± 40°			
Input Connections	HDMI 1.4a (including audio), VGA, composite, S-video, 3.5mm audio in			
Output Connections	3.5mm audio out			
Basic PC Compatibility	VGA (640x480), wVGA (854x480), SVGA (800x600), wSVGA (1024x600), XGA (1024x768), wXGA (1280x800), wXGA+ (1440x900), SXGA (1280x1024), wSXGA+ (1680x1050), UXGA (1600x1200), wUXGA (1920x1200)			
Internal Memory	4 GB			
PC-Less Compatibility	Compatible with USB HID, mouse and keyboard USB Type A x2, USB Type Micro-B, file viewer/player			
Wireless Display	LightCast ready	LightCast Key included	LightCast ready	LightCast Key included
Document Reader	Supports pdf, doc, docx, xls, xlsx, ppt, pptx, Notes			
Video Player	Supports avi, mkv, mpg, mpeg, mov, mp4, 3gp, rm, rmvb			
Photo Reader	Supports jpg, jpeg, bmp, png			
Music Player	Supports mp3, wma, wav, aac			
Internet Browser**	LightCast ready	LightCast Key included	LightCast ready	LightCast Key included
Digital Whiteboard**	LightCast ready	LightCast Key included	LightCast ready	LightCast Key included
H-Sync Range	15K-91K Hz			
V-Sync Range	24-120 Hz			
Lamp Power	170w			
Lamp Life	10,000 hours			
Power Consumption (Standby/Normal)	<0.5 / 220w			
Noise	30dBa			
Power Supply Range	90V-264V at 50-60 Hz			
Operating Conditions	32 to 95°F at 0 to 10K ft / 0 to 35° at 0 to 3,048 m (Up to 104°F / 40°C below 7.5K ft / 2,286 m)			
Storage Temperature	-4 to 140° F / -20 to 60° C			
Operating Humidity	10 - 85% RH Without Condensation			
Interface Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, S. Chinese, T. Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian			
Documentation Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, S. Chinese, Korean, Portuguese, Swedish, Russian, Arabic, Indonesian			
Speaker	1x - 2w			
Dimensions (W x D x H)	8.8 x 7.3 x 3.1 in. / 222.4 x 185 x 79.2 mm			
Weight	3.5 lbs / 1.59 kg			
Standard Accessories	Power cord, remote control, carry case, VGA cable, 3.5mm AV cable, documentation			
Warranty	1 year (product), 6 months (lamp), 90 days (accessories)			

* Product specifications, terms, and offerings are subject to change at any time without notice.

** Wireless keyboard and mouse are recommended for digital whiteboard and Internet browser usage

Accessories

- Replacement Lamp (SP-LAMP-095)
- Presenter 2 RF Remote with USB Receiver (HW-PRESENTER-2)
- Portable 16:9 Projector Screens (SC-PUW-73, SC-PUW-90)
- LightCast Key (INA-LCKEY1)
- LiteShow 4 (INLITESHOW4)
- Extended Warranty (PROJ-EW1YR-MC, PROJ-EW2YR-MC)
- Wireless Keyboard and Mouse (INA-AIRMSKB)



LightCast Key included
free with LC Models

