

Philips Signage Solutions Q-Line Display

32"
Direct LED Backlight
Full HD

SignageSolutions



32BDL3511Q

Intensify your signage experience

Easy-setup 18/7 display.

Inform and enthral with a Philips Q-Line Professional Full HD Display. This reliable solution can be up and running as quickly as you need.

Effortless setup. Total control.

- Operate, monitor and maintain with CMND and Control
- · Schedule what you want, when you want with SmartPlayer

Cost-effective system solution

- Energy-saving automatic backlight control
- Integrated media player. Easily schedule USB content
- FailOver ensures that content is always playing
- Easy control. Remotely manage networked displays



Highlights

CMND and Control



Run your display network over a local (LAN) connection. CMND and Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs, ensuring that content keeps playing even if the primary source goes down. Simply set a list of alternative inputs to be sure your business is always on.

Integrated media player

Easily schedule content to play from USB. Your Philips Professional Display will wake from

standby to play the content you want, and then return to standby once playback has finished.

SmartPlayer



Turn your USB into a true cost-effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on-screen menu, and enjoy your own playlists anytime, anywhere.









Specifications

Picture/Display

- Diagonal screen size: 31.5 inch / 80 cm
- Panel resolution: 1920 x 1080p
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 350 cd/m²
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 6.5 ms
- · Aspect ratio: 16:9
- Viewing Angle (H / V): 178 / 178 degree
- Pixel pitch: 0.36375 x 0.36375 mm
 Display colours: 16.7 Million
- Panel technology: VA
- Contrast ratio (typical): 4000:1
- Clinical image: D-Image preset (dicom part 14 compatible)
- Haze: 2%

Supported Display Resolution

Computer formats

Compacer formats	
Resolution	Refresh rate
640×480	60, 67, 72, 75 Hz
720×400	70 Hz
800×600	56, 60, 72, 75 Hz
832 x 624	75 Hz
1024×768	60, 70, 75 Hz
1152 x 864	75 Hz
1152 × 870	75 Hz
1280×720	60 Hz
1280×800	60 Hz
1280 x 1024	60 Hz
1440×900	60 Hz
1600 x 1200	60 Hz
1680 x 1050	60 Hz
1920 x 1080	60 Hz

Video formats

Resolution	Refresh rate
480i	60 Hz
480p	60 Hz
576 _P	50 Hz
576i	50 Hz
720p	60 Hz
1080i	50, 60 Hz
1080 _P	50, 60 Hz

Connectivity

- Video input: DVI-I (x 1), HDMI 2.0 (x 2), USB 2.0 (x 2)
- · Audio input: 3.5 mm jack
- Audio output: 3.5 mm jack
- External control: IR (in/out) 3.5 mm jack, RJ45, RS232C (in/out) 2.5 mm jack

Convenience

- Placement: Landscape (18/7), Portrait (18/7)
- Tiled Matrix: Up to 10 x 15
- Signal loop through: RS232, IR Loop through
- Energy-saving functions: Smart Power
- Network controllable: RS232, RJ45
- · Keyboard control: Hidden, Lockable · Remote control signal: Lockable

- Start-up: Switch on delay, Switch on status, Boot on source
- · Start-up window: enable/disable Philips logo

Operating conditions

- Temperature range (operation): 0 \sim 40 $^{\circ}$ C
- Temperature range (storage): -20 ~ 60 °C
- Altitude: 0 ~ 3000 m
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]: 20~80% RH (No condensation)
- Humidity range (storage) [RH]: 5~95% RH (No condensation)

Power

- Consumption (Typical): 45 W
- Consumption (Max): 65 W
- Standby power consumption: <0.5 W
- Mains power: 100-240 V~, 50/60 Hz
- Power Saving Features: Smart Power
- Energy Label Class: G

Sound

• Built-in speakers: 2 x 10 W RMS

Accessories

- Stand: BM02541/BM05911 (optional)
- Included Accessories: AC Switch Cover, IR sensor cable (1.8 m) (x 1), Philips logo (x 1), Quick start guide (x 1), Remote control and AAA batteries, RS232 daisy chain cable (x 1), USB Cover and screw x 1, Wire Clamper (x 3), AC power cord

Miscellaneous

- On-Screen Display Languages: Arabic, English, French, German, Italian, Japanese, Polish, Russian, Spanish, Simplified Chinese, Turkish, Traditional
- Regulatory approvals: CE, FCC, Class A, CB, EMF, VČCI, PSB, ĊŪ, ETL
- Warranty: 3 year warranty

Multimedia Applications

- USB Playback Video: H.264, JPEG, MPEG, WMV3
- USB Playback Picture: BMP, JPEG, PNG
- USB Playback Audio: AAC, WMA, MPEG, HEAAC

Dimensions

- Set dimensions (W \times H \times D): 726.5 x 425.4 x 69.1(D@Handle)/65.1(D@Wall
- Set dimensions in inch ($W \times H \times D$): 28.6 x 16.75 x 2.72 (D@Handle)/2.56 (D@Wall mount) inch
- Bezel width: 11.9 (TLR)/17.2 (B) mm
- \bullet VESA Mount: 100 mm x 100 mm, 200 mm x 200 mm, M4
- Product weight: 5.7 kg
- Product weight (lb): 12.57 lb



Issue date 2022-04-21

 $\hfill \odot$ 2022 Koninklijke Philips N.V. All Rights reserved.

Version: 1.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 78301 EAN: 87 12581 77856 9

www.philips.com