

Technical details

Special features

4-in-1 Stand, Eco button, Eco status LED: 3 colors for 3 modes, Pivot, 24/7 usage, DisplayView™ IT Suite, Integrated speakers

Stand 4-in-1 Stand

Height adjust range 130 mm

Picture height over desk (min) 50 mm

Rotation to portrait 90°

Tilt angle -5° / +35°

Swivel angle 340°

Picture performance

Panel and backlit TN/LED

Screen Surface Treatment 3H hard coating, Anti-glare

Contrast - typical 1000:1

Contrast - advanced 20,000,000:1

Response time typical 5 ms

Viewing angle (h/v) - typical 170°/170° CR5:1

Color performance 16.7 million colors (Hi-FRC)

Brightness - typical 250 cd/m²

Size and resolution

Aspect ratio 16:10

Diagonal Size 55.9 cm (22-inch)

Resolution (native) 1,680 x 1,050 pixel

Resolution (interpolated) 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel

Picture size 474 x 296 mm

Pixel Pitch 0.282 mm

Frequencies

Horizontal 30 - 82 kHz

Vertical 56 - 76 Hz

Frequencies - bandwidth 165 Mhz

Connectivity

DisplayPort 1 x DisplayPort

DVI 1 x DVI-D (HDCP)

VGA/D-SUB 1 x D-SUB

Audio signal output 3.5 mm stereo phone jack for head phone

Audio signal input 3.5 mm stereo phone jack

Audio sound output 2 x 1.5 W

USB downstream 4 x USB 2.0

USB upstream 1 x USB

Ease-of-use menu

Languages Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional

Brightness / Contrast Brightness, Contrast, Black level, Auto level

Color sRGB, 6500K, 7500K, Native, Custom Color (R,G,B)

Image adjust Clock, Phase, H-Position, V-Position, Expansion

Audio Mute, Volume

Information Model name, Serial number, Resolution/mode, Signal input

Setup Input select, Language, DDC/CI, OSD-Timeout, Factory preset

Power consumption (typical)

Soft switch off 0.16 W

Power save mode 0.19 W

Operating with EPA settings 12.54 W

Operating maximum brightness	22 W
Power supply	integrated
Power notes	Speakers off, without USB
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	Energy Efficiency Class: A+, EN 60950, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Model	B22W-7
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cUL
Australia/New Zealand	RCM
Japan	VCCI
South Korea	KC
Argentina	TÜV-S
Singapore	S-Mark
Taiwan	BSMI
China	CCC
Saudi Arabia	SASO
Global	TCO Certified Displays 6.0, ENERGY STAR® 7.0, EPEAT® Gold (dedicated regions), Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Flicker Free Certified
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Quality and Reliability	
MTBF (demonstrated)	70,000 h
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	514 x 65 x 346 mm 20.24 x 2.56 x 13.62 inch
Dimension with stand (W x D x H)	514 x 199 x 367 mm 20.24 x 7.83 x 14.45 inch
Weight (packed)	7.5 kg 16.53 lbs
Weight (unpacked)	6.0 kg 13.23 lbs
Weight (Monitor only)	3.4 kg 7.50 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
Package content	
Display delivered accessories	DVI-D Data cable 1.8 m D-SUB Data cable 1.8 m Audio cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Utility CD Warranty booklet Safety booklet
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1472-V140

Order information

EAN Code	4051554619831
Country specific order code	BDL:K1472V140-UK - with UK power cable, mandatory for Arabian countries BDL:K1472V140-CHN - with China power cable and CEL, mandatory for China BDL:K1472V140-ID - with Import label, mandatory for Indonesia BDL:K1472V140-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed

Accessories information	Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
--------------------------------	---

Warranty

Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display B22W-7 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display B22W-7 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/fts/displays>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2017-05-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH