



# HPE FlexNetwork 5130 EI Switch Series



## Key features

- Fixed 10GbE ports for high-speed stacking or uplinks
- Support for multiple services
- Comprehensive security control policies
- Diversified quality of service (QoS) policies
- Excellent manageability

## Product overview

The HPE FlexNetwork 5130 EI Switch Series comprises Gigabit Ethernet switches that support static and RIP Layer 3 routing, diversified services, and IPv6 forwarding, as well as provides four 10-Gigabit Ethernet (10GbE) interfaces. Unique Intelligent Resilient Fabric (IRF) technology creates a virtual fabric by managing several switches as one logical device, which increases network resilience, performance, and availability, while reducing operational complexity. These switches provide Gigabit Ethernet access and can be used at the edge of a network or to connect server clusters in small data centers. High availability, simplified management, and comprehensive security control policies are among the key features that distinguish this series.

## Features and benefits

### Software-defined networking

- OpenFlow

Supports OpenFlow 1.3 specification to enable SDN by allowing separation of the data (packet forwarding) and control (routing decision) paths

### Quality of service (QoS)

- Broadcast control

Allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic

- Advanced classifier-based QoS

Classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information; applies QoS policies such as setting priority level and rate limit to selected traffic on a port, VLAN, or whole switch

- Powerful QoS feature

Supports the following congestion actions: strict priority (SP) queuing, weighted round robin (WRR), and SP+WRR

- Traffic policing

Supports Committed Access Rate (CAR) and line rate

### **Management**

- Remote configuration and management

Enables configuration and management through a secure Web browser or a CLI located on a remote device

- Manager and operator privilege levels

Provides read-only (operator) and read or write (manager) access on CLI and Web browser management interfaces

- Command authorization

Leverages HWTACACS to link a custom list of CLI commands to an individual network administrator's login; also provides an audit trail

- Secure Web GUI

Provides a secure, easy-to-use graphical interface for configuring the module via HTTPS

- Multiple configuration files

Stores easily to the flash image

- Complete session logging

Provides detailed information for problem identification and resolution

- Remote monitoring (RMON)

Uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group

- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

Advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications

- sFlow® (RFC 3176)

Provides scalable ASIC-based wire-speed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes

- Management VLAN

Segments traffic to and from management interfaces, including CLI/Telnet, a Web browser interface, and SNMP

- Remote intelligent mirroring

Mirrors ingress/egress ACL-selected traffic from a switch port or VLAN to a local or remote switch port anywhere on the network

- Device Link Detection Protocol (DLDP)

Monitors a cable between two compatible switches and shuts down the ports on both ends if the cable is broken, which prevents network problems such as loops

- IPv6 management

Provides future-proof networking because the switch is capable of being managed whether the attached network is running IPv4 or IPv6; supports pingv6, tracertv6, Telnetv6, TFTPv6, DNSv6, syslogv6, FTPv6, SNMPv6, DHCPv6, and RADIUS for IPv6

- Troubleshooting

Ingress and egress port monitoring enables network problem-solving; virtual cable tests provide visibility into cable problems

- HPE Intelligent Management Center (IMC)

Integrates fault management, element configuration, and network monitoring from a central vantage point; built-in support for third-party devices enables network administrators to centrally manage all network elements with a variety of automated tasks, including discovery, categorization, baseline configurations, and software images; the software also provides configuration comparison tools, version tracking, change alerts, and more

- Network management

Offers SNMP v1/v2c/v3, with MIB-II Traps, and RADIUS Authentication Client MIB (RFC 2618); embedded HTML management tool with secure access

### **Connectivity**

- Auto-MDIX

Adjusts automatically for straight-through or crossover cables on all 10/100/1000 ports

- Flow control

Provides back pressure using standard IEEE 802.3x, reducing congestion in heavy traffic situations

- High-density connectivity

Provides up to 48 fixed 10/100/1000BASE-T ports in a Layer 2/Layer 3 switch

- IEEE 802.3at Power over Ethernet (PoE+) support

Simplifies deployment and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location

- Ethernet operations, administration, and maintenance (OAM)

Detects data link layer problems that occurred in the “last mile” using the IEEE 802.3ah OAM standard; monitors the status of the link between two devices

### **Performance**

- Non-blocking architecture

Up to 176 Gbps non-blocking switching fabric provides wire-speed switching with up to 130.9 million pps throughput

- Hardware-based wire-speed access control lists (ACLs)

Helps provide high levels of security and ease of administration without impacting network performance with a feature-rich TCAM-based ACL implementation

### **Resiliency and high availability**

- Separate data and control paths

Separates control from services and keeps service processing isolated; increases security and performance

- External redundant power supply

Provides high reliability

- Smart Link

Allows under 100 ms failover between links

- Spanning Tree/PVST+, MSTP, RSTP

Provides redundant links while preventing network loops, supports up to 64 instances of MSTP

- Intelligent Resilient Fabric (IRF)

Creates virtual resilient switching fabrics, where two to nine switches perform as a single L2 switch and L3 router; switches do not have to be co-located and can be part of a disaster-recovery system; servers or switches can be attached using standard LACP for automatic load balancing and high availability; can reduce need for complex protocols like Spanning Tree Protocol, Equal-Cost Multipath (ECMP), or VRRP, thereby simplifying network operation

**Layer 2 switching**

- 16K MAC address table

Provides access to many Layer 2 devices

- VLAN support and tagging

Supports IEEE 802.1Q with 4,094 simultaneous VLAN IDs

- IEEE 802.1ad QinQ and selective QinQ

Increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network

- 10GbE port aggregation

Allows grouping of ports to increase overall data throughput to a remote device

- Device Link Detection Protocol (DLDP)

Monitors link connectivity and shuts down ports at both ends if unidirectional traffic is detected, preventing loops in STP-based networks

- Jumbo frame support

Improves the performance of large data transfers; supports frame size of up to 9K-bytes

**Layer 3 services**

- Address Resolution Protocol (ARP)

Determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network

- Dynamic Host Configuration Protocol (DHCP)

Simplifies the management of large IP networks; supports client; DHCP Relay enables DHCP operation across subnets

- Loopback interface address

Defines an address that can always be reachable, improving diagnostic capability

- User Datagram Protocol (UDP) helper function

Allows UDP broadcasts to be directed across router interfaces to specific IP unicast or subnet broadcast addresses and prevents server spoofing for UDP services such as DHCP

- Route maps

Provides more control during route redistribution; allows filtering and altering of route metrics

- DHCP server

Centralizes and reduces the cost of IPv4 address management

**Layer 3 routing**

- Static IP routing

Provides manually configured routing for both IPv4 and IPv6 networks

- Routing Information Protocol (RIP)

Uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection

**Security**

- Access control lists (ACLs)

Provides IP Layer 2 to Layer 4 traffic filtering; supports global ACL, VLAN ACL, port ACL, and IPv6 ACL
- IEEE 802.1X  
Industry-standard method of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
- MAC-based authentication  
Client is authenticated with the RADIUS server based on the client's MAC address
- Identity-driven security and access control
  - Per-user ACLs  
Permits or denies user access to specific network resources based on user identity and time of day, allowing multiple types of users on the same network to access specific network services without risking network security or providing unauthorized access to sensitive data
  - Automatic VLAN assignment  
Automatically assigns users to the appropriate VLAN based on their identities
- Secure management access  
Delivers secure encryption of all access methods (CLI, GUI, or MIB) through SSHv2, SSL, HTTPS, and/or SNMPv3
- Secure FTP/SCP  
Allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- Guest VLAN  
Provides a browser-based environment to authenticated clients that is similar to IEEE 802.1X
- Port security  
Allows access only to specified MAC addresses, which can be learned or specified by the administrator
- Port isolation  
Secures and adds privacy, and prevents malicious attackers from obtaining user information
- STP BPDU port protection  
Blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- STP root guard  
Protects the root bridge from malicious attacks or configuration mistakes
- DHCP protection  
Blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- IP source guard  
Helps prevent IP spoofing attacks
- Dynamic ARP protection  
Blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- RADIUS/HWTACACS  
Eases switch management security administration by using a password authentication server

**Convergence**

- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

Facilitates easy mapping using network management applications with LLDP automated device discovery protocol

- LLDP-MED

Is a standard extension that automatically configures network devices, including LLDP-capable IP phones

- LLDP-CDP compatibility

Receives and recognizes CDP packets from Cisco's IP phones for seamless interoperation

- IEEE 802.3at Power over Ethernet (PoE+)

Provides up to 30 W per port that allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af-compliant end device; eliminates the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments

- PoE allocations

Supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings

- Voice VLAN

Automatically assigns VLAN and priority for IP phones, simplifying network configuration and maintenance

- IP multicast snooping (data-driven IGMP)

Prevents flooding of IP multicast traffic

**Device support**

- Pre-standard PoE Support

Detects and provides power to pre-standard PoE devices such as wireless LAN access points and IP phones

**Additional information**

- Green IT and power

Improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs

- Green initiative support

Provides support for RoHS and WEEE regulations

- Unified HPE Comware operating system with modular architecture

Provides an easy-to-enhance-and-extend feature set, which doesn't require whole-scale changes; all switching, routing, and security platforms leverage the Comware OS, a common unified modular operating system

- Energy Efficient Ethernet (EEE) Support

Reduces power consumption in accordance with IEEE 802.3az

**Warranty and support**

- Limited Lifetime Warranty

See [hpe.com/networking/warrantysummary](http://hpe.com/networking/warrantysummary) for warranty and support information included with your product purchase.

- Software releases

To find software for your product, refer to [hpe.com/networking/support](http://hpe.com/networking/support); for details on the software releases available with your product purchase, refer to [hpe.com/networking/warrantysummary](http://hpe.com/networking/warrantysummary)

## HPE FlexNetwork 5130 EI Switch Series



**HPE FlexNetwork 5130-24G-4SFP+ EI Switch (JG932A)**



**HPE FlexNetwork 5130-24G-SFP-4SFP+ EI Switch (JG933A)**



**HPE FlexNetwork 5130-48G-4SFP+ EI Switch (JG934A)**

### Specifications

	HPE FlexNetwork 5130-24G-4SFP+ EI Switch (JG932A)	HPE FlexNetwork 5130-24G-SFP-4SFP+ EI Switch (JG933A)	HPE FlexNetwork 5130-48G-4SFP+ EI Switch (JG934A)
<b>I/O ports and slots</b>	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ fixed 1000/10000 SFP+ ports	16 SFP 100/1000 Mbps ports 8 SFP dual-personality ports—10/100/1000BASE-T RJ-45 or 100/1000BASE-X Combo Ports 4 SFP+ fixed 1000/10000 SFP+ ports	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ fixed 1000/10000 SFP+ ports
<b>Additional ports and slots</b>	1 RJ-45 serial console port	1 RJ-45 serial console port	1 RJ-45 serial console port
<b>Power supplies</b>		2 power supply slots 1 minimum power supply required (ordered separately)	
<b>Physical characteristics</b>			
Dimensions	17.32(w) x 6.3(d) x 1.72(h) in. (44 x 16 x 4.36 cm) (1U height)	17.32(w) x 14.17(d) x 1.72(h) in. (44 x 36 x 4.36 cm) (1U height)	17.32(w) x 10.24(d) x 1.72(h) in. (44 x 26 x 4.36 cm) (1U height)
Weight	11.02 lb (5 kg)	17.64 lb (8 kg)	11.02 lb (5 kg)
<b>Memory and processor</b>	1 GB SDRAM, 512 MB flash; packet buffer size: 1.5 MB	1 GB SDRAM, 512 MB flash; packet buffer size: 1.5 MB	1 GB SDRAM, 512 MB flash; packet buffer size: 3 MB
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)
<b>Performance</b>			
1000 Mb Latency	< 5 $\mu$ s	< 5 $\mu$ s	< 5 $\mu$ s
10 Gbps Latency	< 3 $\mu$ s	< 3 $\mu$ s	< 3 $\mu$ s
Throughput	96 Mpps	96 Mpps	130.9 Mpps
Routing/Switching capacity	128 Gbps	128 Gbps	176 Gbps
Routing table size	512 entries (IPv4), 256 entries (IPv6)	512 entries (IPv4), 256 entries (IPv6)	512 entries (IPv4), 256 entries (IPv6)
MAC address table size	16384 entries IPv6 Ready Certified	16384 entries IPv6 Ready Certified	16384 entries IPv6 Ready Certified
<b>Environment</b>			
Operating temperature	23°F to 113°F (-5°C to 45°C)	23°F to 113°F (-5°C to 45°C)	23°F to 113°F (-5°C to 45°C)
Operating relative humidity	10% to 90%, noncondensing	10% to 90%, noncondensing	10% to 90%, noncondensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing	5% to 95%, noncondensing
Acoustic	High-speed fan: 39.7 dB; ISO 7779	Low-speed fan: 47.1 dB, High-speed fan: 50.7 dB; ISO 7779	Low-speed fan: 38.4 dB, High-speed fan: 47.0 dB; ISO 7779

Specifications (continued)	HPE FlexNetwork 5130-24G-4SFP+ EI Switch (JG932A)	HPE FlexNetwork 5130-24G-SFP-4SFP+ EI Switch (JG933A)	HPE FlexNetwork 5130-48G-4SFP+ EI Switch (JG934A)
<b>Electrical characteristics</b>			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Maximum heat dissipation	64/88 BTU/hr (67.52/92.84 kJ/hr)	102/204 BTU/hr (107.61/215.22 kJ/hr), for AC powered units. For DC powered units heat dissipation is 130 BTU/hr minimum, 232 BTU/hr maximum.	130/153 BTU/hr (137.15/161.42 kJ/hr), for AC powered units. For DC powered units heat dissipation is 130 BTU/hr minimum, 171 BTU/hr maximum.
AC voltage	100–240 VAC	100–240 VAC	100–240 VAC
DC voltage		-48 to -60 VDC	-48 to -60 VDC
Current	2 A	5 A	10 A
Maximum power rating	26 W	60 W	45 W
Idle power	19 W	30 W	38 W
Notes	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. Power ratings for AC power supply indicated above. For DC input power, idle power is 38 W and maximum is 68 W. DC maximum input current is 8 A. Units are supplied without a power supply. Customer must buy 1 or 2 JD362B (AC) or JD366B (DC) power supply.	Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. Power ratings for AC power indicated above. Current used is 5 A maximum when DC power used. For DC input power, idle power is 38 W, maximum DC power used is 50 W. When supplemented with the use of an HPE RPS1600 or RPS 800 Redundant Power System, up to 54 W of DC power can be supplied. DC input voltage range is -48 to -60 VDC. Total DC input power is 36 W typical and 54 W maximum. DC input voltage range is -48 VDC to -60 VDC. DC input source is the HPE RPS1600 or RPS 800.
<b>Safety</b>	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance
<b>Emissions</b>	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29:2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29:2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29:2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A
<b>Immunity</b>			
Generic ESD	EN 55024 EN 300 386	EN 55024 EN 300 386	EN 55024 EN 300 386
<b>Management</b>	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.



## HPE 5130 EI Switch Series



### Specifications (continued)

	<b>HPE FlexNetwork 5130-24G-PoE+-4SFP+ (370W) EI Switch (JG936A)</b>	<b>HPE FlexNetwork 5130-48G-PoE+-4SFP+ (370W) EI Switch (JG937A)</b>	<b>HPE FlexNetwork 5130-24G-2SFP+-2XGT EI Switch (JG938A)</b>
<b>I/O ports and slots</b>	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ fixed 1000/10000 SFP+ ports	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 4 SFP+ fixed 1000/10000 SFP+ ports	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 SFP+ fixed 1000/10000 SFP+ ports 2 RJ-45 1/10GBASE-T ports
<b>Additional ports and slots</b>	1 RJ-45 Serial Console Port	1 RJ-45 Serial Console Port	1 RJ-45 Serial Console Port
<b>Physical characteristics</b>			
Dimensions	17.32(w) x 11.81(d) x 1.72(h) in. (44 x 30 x 4.37 cm) (1U height)	17.32(w) x 14.17(d) x 1.72(h) in. (44 x 36 x 4.36 cm) (1U height)	17.32(w) x 6.3(d) x 1.72(h) in. (44 x 16 x 4.37 cm) (1U height)
Weight	17.64 lb (8 kg)	17.64 lb (8 kg)	6.61 lb (3 kg)
<b>Memory and processor</b>	1 GB SDRAM, 512 MB flash; packet buffer size: 1.5 MB	1 GB SDRAM, 512 MB flash; packet buffer size: 3 MB	1 GB SDRAM; Packet buffer size: 1.5 MB, 512 MB flash
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)
<b>Performance</b>			
1000 Mb Latency	< 5 μs	< 5 μs	< 5 μs
10 Gbps Latency	< 3 μs	< 3 μs	< 3 μs
Throughput	96 Mpps	130.9 Mpps	up to 96 Mpps
Routing/Switching capacity	128 Gbps	176 Gbps	128 Gbps
Routing table size	512 entries (IPv4), 256 entries (IPv6)	512 entries (IPv4), 256 entries (IPv6)	512 entries (IPv4), 256 entries (IPv6)
MAC address table size	16384 entries	16384 entries	16384 entries
	IPv6 Ready Certified	IPv6 Ready Certified	IPv6 Ready Certified
<b>Environment</b>			
Operating temperature	23°F to 113°F (-5°C to 45°C)	23°F to 113°F (-5°C to 45°C)	23°F to 113°F (-5°C to 45°C)
Operating relative humidity	10% to 90%, noncondensing	10% to 90%, noncondensing	10% to 90%, noncondensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing	5% to 95%, noncondensing
Acoustic	Low-speed fan: 49.8 dB, High-speed fan: 52.9 dB; ISO 7779	Low-speed fan: 50.6 dB, High-speed fan: 54.6 dB; ISO 7779	Low-speed fan: 19 dB, High-speed fan: 44.5 dB; ISO 7779

Specifications (continued)	HPE FlexNetwork 5130-24G-PoE+-4SFP+ (370W) EI Switch (JG936A)	HPE FlexNetwork 5130-48G-PoE+-4SFP+ (370W) EI Switch (JG937A)	HPE FlexNetwork 5130-24G-2SFP+-2XGT EI Switch (JG938A)
<b>Electrical characteristics</b>			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Maximum heat dissipation	102/1569 BTU/hr (107.61/1655.29 kJ/hr), for AC power. For DC power minimum heat dissipation is 85 BTU/hr and maximum heat dissipation is 2695 BTU/hr.	160/1671 BTU/hr (168.8/1762.91 kJ/hr), for AC power. For DC power minimum heat dissipation is 147 BTU/hr and 3037 BTU/hr maximum.	68/116 BTU/hr (71.74/122.38 kJ/hr), for AC power.
AC voltage	100–240 VAC	100–240 VAC	100–240 VAC
DC voltage	-54 to -57 VDC	-54 to -57 VDC	
Current	10 A	10 A	2 A
Maximum power rating	460 W	490 W	34 W
Idle power	30 W	47 W	20 W
PoE power	370 W PoE+	370 W PoE+	
Notes	<p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE power is the power supplied by the internal power supply. When supplemented with the use of an HPE RPS1600 Redundant Power System, up to 740 W of PoE+ can be supplied.</p> <p>Maximum current rating for DC power is 25 A. AC input power is 30 W typical, and 460 W maximum (including 370 W PoE+ consumption). DC input voltage range is -54 to -57 VDC. Total DC input power is 25 W typical and 790 W with 740 W PoE+ power consumption. DC input voltage range is -54 VDC to -57 VDC. DC input source is the HPE RPS1600.</p>	<p>Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>PoE power is the power supplied by the internal power supply. When supplemented with the use of an HPE RPS1600 Redundant Power System, up to 740 W of PoE+ can be supplied.</p> <p>Maximum current rating for DC power is 25 A. AC input power is 47 W typical, and 490 W maximum (including 370 W PoE+ consumption). DC input voltage range is -54 to -57 VDC. Total DC input power is 43 W typical and 890 W with 800 W PoE+ power consumption. DC input voltage range is -54 VDC to -57 VDC. DC input source is the HPE RPS1600.</p>	<p>Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>
<b>Safety</b>	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance
<b>Emissions</b>	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29:2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29:2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29:2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A

Specifications (continued)	HPE FlexNetwork 5130-24G-PoE+-4SFP+ (370W) EI Switch (JG936A)	HPE FlexNetwork 5130-48G-PoE+-4SFP+ (370W) EI Switch (JG937A)	HPE FlexNetwork 5130-24G-2SFP+-2XGT EI Switch (JG938A)
<b>Immunity</b> Generic ESD	EN 55024 EN 300 386	EN 55024 EN 300 386	EN 55024 EN 300 386
<b>Management</b>	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; Command-line interface; Web browser; SNMP Manager
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

## HPE 5130 EI Switch Series



**HPE FlexNetwork 5130-48G-2SFP+-2XGT EI Switch (JG939A)**



**HPE FlexNetwork 5130-24G-PoE+-2SFP+-2XGT (370W) EI Switch (JG940A)**



**HPE FlexNetwork 5130-48G-PoE+-2SFP+-2XGT (370W) EI Switch (JG941A)**

### Specifications (continued)

	HPE FlexNetwork 5130-48G-2SFP+-2XGT EI Switch (JG939A)	HPE FlexNetwork 5130-24G-PoE+-2SFP+-2XGT (370W) EI Switch (JG940A)	HPE FlexNetwork 5130-48G-PoE+-2SFP+-2XGT (370W) EI Switch (JG941A)
<b>I/O ports and slots</b>	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 SFP+ fixed 1000/10000 SFP+ ports 2 RJ-45 1/10GBASE-T ports	24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 SFP+ fixed 1000/10000 SFP+ ports 2 RJ-45 1/10GBASE-T ports	48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only 2 SFP+ fixed 1000/10000 SFP+ ports 2 RJ-45 1/10GBASE-T ports
<b>Additional ports and slots</b>	1 RJ-45 serial console port	1 RJ-45 serial console port	1 RJ-45 serial console port
<b>Physical characteristics</b>			
Dimensions	17.32(w) x 10.63(d) x 1.72(h) in. (44 x 27 x 4.37 cm) (1U height)	17.32(w) x 14.17(d) x 1.72(h) in. (44 x 36 x 4.37 cm) (1U height)	17.32(w) x 16.54(d) x 1.72(h) in. (44 x 42 x 4.37 cm) (1U height)
Weight	11.02 lb (5 kg)	13.23 lb (6 kg)	15.43 lb (7 kg)
<b>Mounting and enclosure</b>	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)	Mounts in an EIA standard 19-inch telco rack or equipment cabinet (hardware included)
<b>Performance</b>			
1000 Mb Latency	< 5 μs	< 5 μs	< 5 μs
10 Gbps Latency	< 3 μs	< 3 μs	< 3 μs
Throughput	up to 130.9 Mpps	up to 96 Mpps	up to 130.9 Mpps
Routing/Switching capacity	176 Gbps	128 Gbps	176 Gbps
Routing table size	512 entries (IPv4), 256 entries (IPv6)	512 entries (IPv4), 256 entries (IPv6)	512 entries (IPv4), 256 entries (IPv6)
MAC address table size	16384 entries IPv6 Ready Certified	16384 entries IPv6 Ready Certified	16384 entries IPv6 Ready Certified
<b>Environment</b>			
Operating temperature	23°F to 113°F (-5°C to 45°C)	23°F to 113°F (-5°C to 45°C)	23°F to 113°F (-5°C to 45°C)
Operating relative humidity	10% to 90%, noncondensing	10% to 90%, noncondensing	10% to 90%, noncondensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing	5% to 95%, noncondensing
Acoustic	Low-speed fan: 43.1 dB, High-speed fan: 53.4 dB; ISO 7779	Low-speed fan: 37.3 dB, High-speed fan: 47.1 dB; ISO 7779	Low-speed fan: 47.3 dB, High-speed fan: 50 dB; ISO 7779

Specifications (continued)	HPE FlexNetwork 5130-48G-2SFP+-2XGT EI Switch (JG939A)	HPE FlexNetwork 5130-24G-PoE+-2SFP+-2XGT (370W) EI Switch (JG940A)	HPE FlexNetwork 5130-48G-PoE+-2SFP+-2XGT (370W) EI Switch (JG941A)
<b>Electrical characteristics</b>			
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Maximum heat dissipation	122/184 BTU/hr (128.71/194.12 kJ/hr), for AC power. For DC power min heat dissipation is 122 BTU/hr and 184 BTU/hr max.	105/1450 BTU/hr (159.3/1529.75 kJ/hr), for AC power. For DC Power 68 BTU/hr and max heat dissipation is 2627.3 BTU/hr	147/1603 BTU/hr (155.08/1691.17 kJ/hr), for AC power. For DC power min heat dissipation is 102 BTU/hr and max heat dissipation is 3105 BTU/hr
AC Voltage	100–240 VAC	100–240 VAC,	100–240 VAC
DC Voltage	-48 to -60 VDC	-54 to -57 VDC	-54 to -57 VDC
Current	2 A	10 A	10 A
Maximum power rating	54 W	425 W	470 W
Idle Power	36 W	31 W	43 W
PoE Power		370 W PoE+	370 W PoE+
Notes	Power ratings for AC power indicated above. Current used is 5 A Max when DC Power used. When supplemented with the use of an HPE RPS1600 or RPS800 Redundant Power System, up to 54 W of DC power can be supplied. DC input voltage range is -48 to -60 VDC. Total DC input power is 36 W typical and 54 W maximum. DC input voltage range is -48 VDC to -60 VDC. DC input source is the HPE RPS1600 or RPS800.	PoE Power is the power supplied by the internal power supply. When supplemented with the use of an HPE RPS1600 Redundant Power System, up to 740 W of PoE+ can be supplied. Max current rating for DC power is 25 A. AC Input power is 31 W typical, and 425 W max (including 370 W PoE+ consumption). DC Input voltage range is -54 to -57 VDC. Total DC input power is 20 W Typical and 770 W with 740 W PoE+ Power consumption. DC Input Source is the HPE RPS1600.	PoE Power is the power supplied by the internal power supply. When supplemented with the use of an HPE RPS1600 Redundant Power System, up to 740 W of PoE+ can be supplied. Max current rating for DC power is 25 A. AC Input power is 43 W typical, and 470 W max (including 370 W PoE+ consumption). DC Input voltage range is -54 to -57 VDC. Total DC input power is 30 W typical and 910 W with 800 W PoE+ Power consumption. DC Input Source is the HPE RPS1600.
<b>Safety</b>	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; RoHS Compliance
<b>Emissions</b>	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29: 2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29: 2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A	EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A; EN 61000-4-11:2004; ANSI C63.4-2009; EN 61000-3-3:2008; VCCI V-4/2012.04; EN 6100-3-2:2006+A1:2009+A2:2009; EN 61000-3-2:2006+A1:2009+A2:2009; EN 61000-4-3:2006; EN 61000-4-4:2012; EN 61000-4-5:2006; EN 61000-4-6:2009; AS/NZS CISPR 22:2009 Class A; CISPR 22:2008 Class A; EN 55022:2010 Class A; EN 61000-4-29: 2000; CISPR 24:2010; EN 300 386 V1.6.1; VCCI V-3/2013.04 Class A
<b>Immunity</b>			
Generic ESD	EN 55024 EN 300 386	EN 55024 EN 300 386	EN 55024 EN 300 386
<b>Management</b>	IMC—Intelligent Management Center; Command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; Command-line interface; Web browser; SNMP Manager	IMC—Intelligent Management Center; Command-line interface; Web browser; SNMP Manager
<b>Services</b>	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at <a href="http://hpe.com/networking/services">hpe.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

**Standards and protocols**

(applies to all products in series)

<b>IP Multicast</b>	RFC 1112 IGMPv1 RFC 3376 IGMPv3		
<b>Device management</b>	RFC 1157 SNMPv1/v2c RFC 1305 NTPv3 RFC 2573 (SNMPv3 Applications)	RFC 2819 (RMON groups Alarm, Event, History, and Statistics only) RFC 3416 (SNMP Protocol Operations v2) HTML and Telnet management	Multiple Configuration Files SNMPv3 and RMON RFC support SSHv1/SSHv2 Secure Shell TACACS/TACACS+ Web UI
<b>General protocols</b>	IEEE 802.1ad Q-in-Q IEEE 802.1ak Multiple Registration Protocol (MRP) and Multiple VLAN Registration Protocol (MVRP) IEEE 802.1AX—2008 Link Aggregation IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q VLANs IEEE 802.1s Multiple Spanning Trees IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.1X PAE IEEE 802.3 Type 10BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3ac VLAN Tagging Extension IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3ae 10-Gigabit Ethernet IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet Plus IEEE 802.3az Energy Efficient Ethernet IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-X IEEE 802.3x Flow Control IEEE 802.3z 1000BASE-X RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 791 IP RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 TELNET RFC 855 Telnet Option Specification RFC 894 IP over Ethernet RFC 950 Internet Standard Subnetting Procedure	RFC 951 BOOTP RFC 959 File Transfer Protocol (FTP) RFC 1027 Proxy ARP RFC 1042 IP Datagrams RFC 1071 Computing the Internet Checksum RFC 1123 Requirements for Internet Hosts RFC 1166 IP Addresses RFC 1213 Management Information Base for Network Management of TCP/IP-based Internet RFC 1256 ICMP Router Discovery Protocol (IRDP) RFC 1305 NTPv3 RFC 1350 TFTP Protocol (revision 2) RFC 1519 CIDR RFC 1533 DHCP Options and BOOTP Vendor Extensions RFC 1591 DNS (client only) RFC 1643 Definitions of Managed Objects for the Ethernet-like Interface Types RFC 1812 IPv4 Routing RFC 1866 Hypertext Markup Language—2.0 RFC 1901 Introduction to Community-based SNMPv2 RFC 1902-1907 SNMPv2 RFC 2131 DHCP RFC 2236 IGMP Snooping RFC 2462 IPv6 Stateless Address Auto-configuration RFC 2474 Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers RFC 2475 Architecture for Differentiated Services RFC 2597 Assured Forwarding PHB Group RFC 2616 HTTP Compatibility v1.1 RFC 2665 Definitions of Managed Objects for the Ethernet-like Interface Types RFC 2668 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)	RFC 2865 Remote Authentication Dial In User Service (RADIUS) RFC 2866 RADIUS Accounting RFC 3046 DHCP Relay Agent Information Option RFC 3246 Expedited Forwarding PHB RFC 3414 User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3) RFC 3415 View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP) RFC 3416 Protocol Operations for SNMP RFC 3418 Management Information Base (MIB) for the Simple Network Management Protocol (SNMP) RFC 3576 Ext to RADIUS (CoA only) RFC 3580 IEEE 802.1X Remote Authentication Dial In User Service (RADIUS) Usage Guidelines RFC 3587 IPv6 Global Unicast Address Format RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6 RFC 4213 Basic IPv6 Transition Mechanisms RFC 4291 IP Version 6 Addressing Architecture RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches RFC 4575 A Session Initiation Protocol (SIP) Event Package for Conference State RFC 4675 RADIUS VLAN & Priority RFC 5095 Deprecation of Type 0 Routing Headers in IPv6 802.1r—GARP Proprietary Attribute Registration Protocol (GPRP)
<b>IPv6</b>	RFC 1981 IPv6 Path MTU Discovery RFC 2460 IPv6 Specification RFC 2461 IPv6 Neighbor Discovery RFC 2463 ICMPv6 RFC 2464 Transmission of IPv6 over Ethernet Networks RFC 3162 RADIUS and IPv6	RFC 3306 Unicast-Prefix-based IPv6 Multicast Addresses RFC 3315 DHCPv6 (client and relay) RFC 3484 Default Address Selection for IPv6 RFC 3736 Stateless Dynamic Host Configuration Protocol (DHCP) Service for IPv6	RFC 4291 IP version 6 Addressing Architecture RFC 4293 MIB for IP RFC 4443 ICMPv6 RFC 4861 IPv6 Neighbor Discovery RFC 4862 IPv6 Stateless Address Auto-configuration RFC 6724 Default Address Selection for Internet Protocol Version 6 (IPv6)
<b>MIBs</b>	RFC 1212 Concise MIB Definitions RFC 1213 MIB-II RFC 1493 Bridge MIB RFC 1757 Remote Network Monitoring MIB RFC 2096 IP Forwarding Table MIB RFC 2233 Interface MIB RFC 2571 SNMP Framework MIB RFC 2572 SNMP-MPD MIB	RFC 2573 SNMP-Notification MIB RFC 2573 SNMP-Target MIB RFC 2574 SNMP USM MIB RFC 2618 RADIUS Authentication Client MIB RFC 2620 RADIUS Accounting Client MIB RFC 2665 Ethernet-like-MIB RFC 2668 802.3 MAU MIB RFC 2674 802.1p and IEEE 802.1Q Bridge MIB	RFC 2737 Entity MIB (version 2) RFC 2819 RMON MIB RFC 2863 The Interfaces Group MIB RFC 2925 Ping MIB RFC 3414 SNMP-user-based-SM MIB RFC 3415 SNMP-view-based-ACM MIB RFC 3418 MIB for SNMPv3 RFC 3621 Power Ethernet MIB

<b>Network management</b>	IEEE 802.1AB Link Layer Discovery Protocol (LLDP) RFC 2579 Textual Conventions for SMLv2 RFC 2580 Conformance Statements for SMLv2	RFC 2819 four groups of RMON: 1 (statistics), 2 (history), 3 (alarm), and 9 (events)	ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED) SNMPv1/v2c/v3
<b>Security</b>	IEEE 802.1X Port-based Network Access Control RFC 1492 TACACS+ RFC 2138 RADIUS Authentication	RFC 2139 RADIUS Accounting RFC 2865 RADIUS (client only) RFC 2866 RADIUS Accounting RFC 3260 New Terminology and Clarifications for DiffServ	Secure Sockets Layer (SSL) SSHv2 Secure Shell

## HPE FlexNetwork 5130 EI Switch Series accessories

<b>Transceivers</b>	HPE X115 100M SFP LC FX Transceiver (JD102B) <sup>1</sup> HPE X110 100M SFP LC LX Transceiver (JD120B) <sup>1</sup> HPE X115 100M SFP LC BX 10-U Transceiver (JD100A) <sup>1</sup> HPE X115 100M SFP LC BX 10-D Transceiver (JD101A) <sup>1</sup> HPE X125 1G SFP LC LH40 1310nm Transceiver (JD061A) HPE X120 1G SFP LC LH40 1550nm Transceiver (JD062A) HPE X125 1G SFP LC LH70 Transceiver (JD063B) HPE X120 1G SFP LC LH100 Transceiver (JD103A) HPE X120 1G SFP LC SX Transceiver (JD118B) HPE X120 1G SFP LC LX Transceiver (JD119B) HPE X120 1G SFP LC BX 10-U Transceiver (JD098B) HPE X120 1G SFP LC BX 10-D Transceiver (JD099B) HPE X120 1G SFP RJ45 1000BASE-T Transceiver (JD089B) HPE X130 10G SFP+ LC SR Transceiver (JD092B) HPE X130 10G SFP+ LC LR Transceiver (JD094B) HPE X240 10G SFP+ SFP+ 0.65m DAC Campus-Cable (JH693A) HPE X240 10G SFP+ SFP+ 1.2m DAC Campus-Cable (JH694A) HPE X240 10G SFP+ SFP+ 3m DAC Campus-Cable (JH695A) HPE FlexNetwork X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable (JG081C)
<b>Cables</b>	HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable (AJ833A) HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable (AJ834A) HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable (AJ835A) HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable (AJ836A) HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable (AJ837A) HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable (AJ838A) HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable (AJ839A) HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A) HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A) HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A) HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A) HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A) HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)
<b>HPE FlexNetwork 5130 24G SFP 4SFP+ EI Switch (JG933A)</b>	HPE X361 150W 100-240VAC to 12VDC Power Supply (JD362B) <sup>2</sup> HPE X361 150W 48-60VDC to 12VDC Power Supply (JD366B) <sup>2</sup> HPE RPS800 Redundant Power Supply (JD183A) <sup>3</sup> HPE X290 500 V 1m RPS Cable (JD186A) <sup>3</sup>
<b>HPE FlexNetwork 5130-48G-4SFP+ EI Switch (JG934A)</b>	HPE RPS800 Redundant Power Supply (JD183A) <sup>3</sup> HPE RPS1600 Redundant Power System (JG136A) <sup>2</sup> HPE RPS1600 1600W AC Power Supply (JG137A) <sup>2</sup> HPE X290 500 V 1m RPS Cable (JD186A) HPE X290 1000 A JD5 Non-PoE 2m RPS Cable (JD188A)
<b>HPE FlexNetwork 5130-24G-PoE+-4SFP+ (370W) EI Switch (JG936A)</b>	HPE RPS1600 Redundant Power System (JG136A) <sup>2</sup> HPE RPS1600 1600W AC Power Supply (JG137A) <sup>2</sup> HPE X290 1000 A JD5 2m RPS Cable (JD187A)

## HPE FlexNetwork 5130 EI Switch Series accessories (continued)

<b>HPE FlexNetwork 5130-48G-PoE+-4SFP+ (370W) EI Switch (JG937A)</b>	HPE RPS1600 Redundant Power System (JG136A) <sup>2</sup> HPE RPS1600 1600W AC Power Supply (JG137A) <sup>2</sup> HPE X290 1000 A JD5 2m RPS Cable (JD187A)
<b>HPE FlexNetwork 5130-48G-2SFP+-2XGT EI Switch (JG939A)</b>	HPE RPS 800 Redundant Power Supply (JD183A) <sup>2</sup> HPE RPS1600 Redundant Power System (JG136A) <sup>2</sup> HPE RPS1600 1600W AC Power Supply (JG137A) <sup>2</sup> HPE X290 500 V 1m RPS Cable (JD186A) HPE X290 1000 A JD5 Non-PoE 2m RPS Cable (JD188A)
<b>HPE FlexNetwork 5130-24G-PoE+-2SFP+-2XGT (370W) EI Switch (JG940A)</b>	HPE RPS1600 Redundant Power System (JG136A) <sup>2</sup> HPE RPS1600 1600W AC Power Supply (JG137A) <sup>2</sup> HPE X290 1000 A JD5 2m RPS Cable (JD187A)
<b>HPE FlexNetwork 5130-48G-PoE+-2SFP+-2XGT (370W) EI Switch (JG941A)</b>	HPE RPS1600 Redundant Power System (JG136A) <sup>2</sup> HPE RPS1600 1600W AC Power Supply (JG137A) <sup>2</sup> HPE X290 1000 A JD5 2m RPS Cable (JD187A)

<sup>1</sup> Supported only on the HPE 5130-24G-SFP-4SFP+ EI Switch (JG933A), and only when used in the 1G downlink configuration

<sup>2</sup> Products covered by one year warrant; see details at [hpe.com/networking/warrantyquickref](http://hpe.com/networking/warrantyquickref)

<sup>3</sup> Supported on JG933A only when connected to HPE 5500 150WDC Power Supply (JD366A) or HPE X361 150W 48-60VDC to 12VDC Power Supply (JD366B) with HPE X290 500 V 1m RPS Cable (JD186A)

Learn more at  
[hpe.com/networking](http://hpe.com/networking)



Sign up for updates



© Copyright 2014–2017 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

sFlow is a registered trademark of InMon Corp. All other third-party trademark(s) is/are property of their respective owner(s).

4AA5-4495ENW, January 2017, Rev. 15