



HP Designjet T1200 HD Multifunction Printer series

Do and offer more — process, print, scan, and copy



Rely on one complete, easy, integrated solution.

- Manage large-format documents from scan through print or archive with this reliable MFP.
- Operation is intuitive and simple with a full-station 38.1 cm (15-inch) touch screen display, which also includes a virtual keyboard.
- Perform scan, copy and print functions with greater control and confidence.
- Quickly adapt to customer changes with integrated features such as real-time preview and retouch software.
- Save valuable workspace with this single, integrated solution in one compact footprint.

Do more with one device and see your productivity soar.

- Save time and paper with 2 online rolls and smart switching, so you can handle CAD and GIS projects at the same time.
- You're back to business in no time with this HP MFP that scans, copies, and prints your projects quickly.
- Batch scanning and printing is fast and easy thanks to free HP Instant Printing and collating features.
- Minimise interruptions with the 300-ml HP 726 Matte Black Ink Cartridge, reliable HP media and embedded PS.

See top quality results across a broad range of applications from any original.

- Get a high level of quality in line drawings, maps and posters with 4 camera CCD scanning technology with 600 dpi.
- Experience added versatility when you scan and print AEC, CAD, and GIS documents.
- Produce fine lines, crisp text, and vivid colour with HP Vivera inks, including 2 blacks and a grey ink.
- Transform your everyday printing using HP everyday bond papers with ColorPRO Technology and HP Recycled Bond Paper.

ECO HIGHLIGHTS

- Save paper with two roll configuration, print image nesting, blank print area detection.
- Less ink wasted thanks to efficient installation and maintenance routines.
- Free convenient cartridge and printhead recycling ¹
- Supports 100% recycled HP media

ENERGY STAR® Qualified

¹ In more than 45 countries worldwide. Please check www.hp.com/recycle for details

www.hp.com/ecosolutions





HP Designjet T1200 HD Multifunction Printer series

TECHNICAL SPECIFICATIONS

Print	
Line drawings	Fast: 28 sec/page, 103 A1 prints per hour
Print resolution	Up to 2400 x 1200 optimised dpi from 1200 x 1200 input dpi with maximum detail selected
Margins (top x bottom x left x right)	Roll: 5 x 5 x 5 x 5 mm (borderless on photo papers) Sheet: 5 x 16.75 x 5 x 5 mm
Technology	HP Thermal Inkjet
Ink types	Dye-based (C, M, Y, G, PK); pigment-based (MK)
Ink colours	6 (cyan, grey, magenta, matte black, photo black, yellow)
Ink drop	6 pl (C, M, PK, G), 9 pl (Y, MK)
Line accuracy	+/- 0.1%
Minimum line width	0.02 mm (HP-GL/2 addressable)
Guaranteed minimum line width	0.06 mm (ISO/IEC 13660:2001(E))
Maximum print length	91 m (application dependent)
Scan	
Scan speed	Colour (200 dpi/400 dpi Turbo): up to 5.1 cm/sec; Black and white (200 dpi/400 dpi Turbo): up to 15.2 cm/sec
Scan resolution	Up to 9600 dpi, with variable resolution setting from 50 dpi in increments of 1 dpi
Copy resolution	Up to 9600 dpi
Maximum scan width	1067 mm wide
Maximum scan thickness	15.2 mm
Copy	
Reduction/enlargement	1 to 10000%
Maximum copies	Up to 1000 copies
Copier settings	Type of original; image crop and align preview; lightness; saturation and RGB controls; sharpen/blur; mirror copy; enlarge/reduce; paneling; tiling; nesting; accounting; batch
Image quality	
Maximum optical density	2.15 maximum black optical density (6 L*min)
Media	
Handling	Printer: sheet feed, two automatic roll feeds, automatic roll-switching, automatic cutter; scanner: straight-through scan paper path for sheet and cardboard originals
Types	Printer: bond and coated paper (bond, coated, heavyweight coated, super heavyweight plus matte, coloured), technical paper (natural tracing, translucent bond, vellum), film (clear, matte, polyester), photographic paper (satin, gloss, semi-gloss, matte, high-gloss), backlit, self-adhesive (two-view cling, indoor paper, polypropylene, vinyl), scanner: non-abrasive paper, vellum, Mylar, sepia, blueprints, plastic, film, plastic laminate, foam board, cardboard (No plywood, stone plates, metal plates or abrasive, dirty, rough, sharp edged, metal clamped, or burned surfaces or transparencies)
Weight	60 to 328 g/m ²
Size	210 x 279 to 1118 x 1676 mm
Thickness	Up to 0.8 mm
Memory	
Standard	Printer: 32 GB (dedicated file-processing memory); scanner: 1 GB
Hard disk	Printer: standard, 160 GB; scanner: standard, 40 GB
Connectivity	
Interfaces (standard)	Printer: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0, EIO Jetdirect accessory slot; scanner: Gigabit Ethernet (1000Base-T), Hi-Speed USB 2.0, FireWire (IEEE 1394a compliant)
Interfaces (optional)	HP Jetdirect internal print servers
Print languages (standard)	Adobe® PostScript® 3, Adobe® PDF 1.7, TIFF, JPEG, HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
Drivers included	HP-GL/2, HP-RTL, PostScript® drivers for Windows (optimised for AutoCAD 2000 and higher); PostScript® drivers for Mac OS X and Linux; support for Citrix® XenApp and Citrix® XenServer environments
Recommended system requirements	
Mac	Mac OS X v10.4, v10.5: PowerPC G4, G5, or Intel® Core processor; 1 GB RAM; 2 GB available hard disk space; Mac OS X v10.6: Mac computer with Intel® Core processor; 2 GB RAM; 4 GB available hard disk space
Windows	Windows® 7: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM (32-bit) or 4 GB RAM (64-bit), 4 GB available hard disk space; Windows Vista® Home Premium/Business/Ultime: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 4 GB available hard disk space; Microsoft® Windows® XP Home/Professional (SP2 or higher): Intel® Pentium® family or AMD K6™/Athlon™/Duron™ family (1 GHz), 1 GB RAM, 2 GB available hard disk space
Dimensions (w x d x h)	
Printer	1900 x 1000 x 1600 mm
Shipping	1930 x 766 x 1529 mm
Weight	
Printer	200 kg
Shipping	280 kg
What's in the box	
CQ653A	Printer; printheads; introductory ink cartridges; 111.8 cm stand; 111.8 cm spindle; quick reference guides; setup posters; Serif PosterDesigner Pro for HP poster; start-up software; scanner; touchscreen (panel PC); scanner documentation software; system recovery software; customer service guide; USB cable; FireWire cable; Ethernet cable; power cords
Environmental ranges	
Operating Temperature	5 to 40° C
Recommended operating temperature	15 to 35° C (depending on paper type)
Storage temperature	-25 to 55° C
Recommended operating humidity	20 to 80% RH (depending on paper type)
Storage humidity	0 to 95% RH

Acoustic	
Sound Pressure	47 dB(A)
Sound Power	6.3 B(A)
Power Consumption	
Maximum	Printer: 120 watt, scanner: 300 watts maximum (active); printer: < 7 watts / < 25 watts with embedded DFE (powersave); 65.3 watts (standby); 3.6 watts
Power requirements	Input voltage (auto ranging) printer: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max; scanner: 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 5 A max
Certification	
Safety	EU (LVD and EN60950-1 compliant); Russia (GOST)
Electromagnetic	Compliance for Class A ITE products: EU (EMC Directive)
Environmental	EU RoHS; REACH; WEEE
ENERGY STAR	No
Warranty	
	Two-year limited warranty. Warranty and support options vary by product, country and local legal requirements.

ORDERING INFORMATION

Product	
CQ653A	HP Designjet T1200 HD Multifunction Printer
Accessories	
66709A	HP Designjet 44-inch Roll Feed Spindle
CN501A	HP Designjet External Hard Disk
J7961G	HP Jetdirect 635n IPv6/IPv4 Print Server
CN088A	Serif PosterDesigner Software Pro for HP Designjet Printers
CN454A	SCP reprocontrol for HP (1 printer)
CN455A	SCP reprocontrol for HP (2 printers)
Ink supplies	
C9380A	HP 72 Gray and Photo Black Printhead
C9383A	HP 72 Magenta and Cyan Printhead
C9384A	HP 72 Matte Black and Yellow Printhead
C9397A	HP 72 69-ml Photo Black Ink Cartridge
C9398A	HP 72 69-ml Cyan Ink Cartridge
C9399A	HP 72 69-ml Magenta Ink Cartridge
C9400A	HP 72 69-ml Yellow Ink Cartridge
C9401A	HP 72 69-ml Grey Ink Cartridge
C9403A	HP 72 130-ml Matte Black Ink Cartridge
C9370A	HP 72 130-ml Photo Black Ink Cartridge
C9371A	HP 72 130-ml Cyan Ink Cartridge
C9372A	HP 72 130-ml Magenta Ink Cartridge
C9373A	HP 72 130-ml Yellow Ink Cartridge
C9374A	HP 72 130-ml Grey Ink Cartridge
CH575A	HP 726 300-ml Matte Black Ink Cartridge
Media supplies	
Q6628A	HP Super Heavyweight Plus Matte Paper-1067 mm x 30.5 m (42 in x 100 ft)
C6030C	HP Heavyweight Coated Paper-914 mm x 30.5 m (36 in x 100 ft)
C6020B	HP Coated Paper-914 mm x 45.7 m (36 in x 150 ft)
C6036A	HP Bright White Inkjet Paper-914 mm x 45.7 m
Q1397A	HP Universal Bond Paper-914 mm x 45.7 m (36 in x 150 ft)
CG891A	HP Recycled Bond Paper-1067 mm x 45.7 m (42 in x 150 ft)
C3868A	HP Natural Tracing Paper-914 mm x 45.7 m (36 in x 150 ft)
C3875A	HP Clear Film-914 mm x 22.9 m (36 in x 75 ft)
Q1421A	HP Universal Semi-gloss Photo Paper-914 mm x 30.5 m (36 in x 100 ft)
Q1427A	HP Universal High-gloss Photo Paper-914 mm x 30.5 m (36 in x 100 ft)
Service & support	
UT911E	HP Care Pack, Next Business Day Designjet T1200 HD-MFP Hardware Support, 3 years
UT912E	HP Care Pack, Next Business Day Designjet T1200 HD-MFP Hardware Support, 4 years
UT913E	HP Care Pack, Next Business Day Designjet T1200 HD-MFP Hardware Support, 5 years
UT920E	HP Care Pack, 4 Hour Response Time 13x5 Designjet T1200 HD-MFP Hardware Support, 3 years
UT923PE	HP Care Pack, Post Warranty Next Business Day Designjet T1200 HD-MFP Hardware Support, 1 year
UT924PE	HP Care Pack, Post Warranty Next Business Day Designjet T1200 HD-MFP Hardware Support, 2 years
UT927PE	HP Care Pack, Post Warranty 4 Hour Response Time 13x5 Designjet T1200 HD-MFP Support, 1 year

For more HP Large Format Media substrates and sizes please visit us online at:
<http://www.hp.com/go/designjet/supplies>

For more information, visit our website at <http://www.hp.com>

© Copyright 2010 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA0-4603EEE Published in EMEA March 2010