# HP Color LaserJet Enterprise CP4525 Printer

# series





Print high-impact colour documents at high-performance speeds. Protect confidential print jobs with on-board and network security. Meet the needs of your growing business with efficient paper handling, expansive paper capacity and easy controls.

Ideal for businesses with managed workgroups of 8–20 people that need a network-ready laser printer for fast, secure, high quality colour printing.

#### Experience top-of-the-line performance for colour printing.

Boost your printing productivity with speeds up to 40 ppm A4 and a first page out in as fast as 9.5 seconds from lower power mode with Instant-on Technology. Streamline your workgroups' print jobs: store a large queue of print jobs with 1 GB of memory<sup>1</sup>. Easily install, configure, monitor, troubleshoot and manage your entire printer fleet from anywhere on the network with HP Web Jetadmin. Avoid delays and handle high volumes with a robust paper-handling capacity of up to 2,100 sheets<sup>2</sup>.

#### Produce superior colour business documents consistently.

Impress with professional quality colour: HP ImageREt 3600 and up to 1200 x 1200 dpi deliver finer details, smoother colour transitions, crisp text and sharp images. Manage colour printing usage and costs: assign access by user or application, or turn off colour printing with award-winning HP colour access control<sup>3</sup>. Get supplies tailored for high-volumes with a high-capacity black toner cartridge. Expand your options with a range of media sizes and types such as everyday and glossy papers.

#### Protect your business-critical data with advanced on-board security.

Secure your business-critical data with the HP Secure Hard Disk <sup>4</sup>, expand the number of IP addresses on your network with IPv6, and implement sophisticated network access control with 802.1x authentication and IPsec encryption. Keep sensitive material private when you retrieve stored confidential print jobs using the control panel. Conveniently connect an optional security card reader or other authentication device with the Hi-Speed USB 2.0 port.



HP Color LaserJet Enterprise CP4525n Printer



HP Color LaserJet Enterprise CP4525dn Printer



HP Color LaserJet Enterprise CP4525xh

The n and dn models feature 512 MB of memory—expandable up to 1 GB

<sup>&</sup>lt;sup>1</sup> 1 GB memory is standard for xh model only

<sup>&</sup>lt;sup>2</sup> The xh model features standard 2,100-sheet paper capacity

The n and dn models come with standard 600-sheet paper capacity expandable with an optional 500 sheet input tray and cabinet

<sup>&</sup>lt;sup>3</sup> Colour access control capabilities vary from device to device

Buyer's Lab gave HP colour control features an "Outstanding Achievement" award in December 2007

 $<sup>^{4}</sup>$  The HP Secure Hard Disk is standard on the xh model and optional for the n and dn models.

#### HP Color LaserJet Enterprise CP4525xh Printer shown

- 1. Control panel with four-line colour display
- 2. 500-sheet output bin
- 3. Front door allows convenient access to four, all-in-one HP print cartridges
- 4. Built-in automatic two-sided printing
- 5. Four 500-sheet input trays for a 2, 100-sheet total input capacity
- 6. 100-sheet multipurpose tray handles heavy custom media up to 220 g/m bond
- 7. Hi-Speed USB 2.0 port
- 8. HP Jetdirect Gigabit Ethernet embedded print server
- 9. HP Secure High Performance embedded hard disk
- 10. 1 GB (1024 MB) total memory and an 800 MHz processor quickly handle complex print jobs
- 11. One open EIO slot
- 12. Security lock slot



### Series at a glance



#### HP Color LaserJet Enterprise CP4525n Printer

- Print speed of up to 40 ppm black and colour
- ImageREt 3600
- 1200 x 1200 dpi effective output quality
- 512 MB standard memory expandable to 1024 MB
- 800 MHz processor
- Standard input capacity of 600-sheets with one 500-sheet input tray and one 100-sheet multi-purpose tray. Expandable with one optional 500-sheet input tray with or without cabinet or with 3x500 sheet input tray with printer stand.



#### HP Color LaserJet Enterprise CP4525dn Printer

As CP4525n model plus automatic two-sided printing



#### HP Color LaserJet Enterprise CP4525xh Printer

- As CP4525n model plus automatic two-sided printing
- 1 GB of memory on-board
- HP High-Performance Secure Hard Disk
- paper capacity of 2100 sheets with additional 3x 500 sheet trays and printer stand

#### Recommended accessories



#### CC422A

HP Color LaserJet 500-sheet Paper Feeder and Cabinet Spend less time loading paper and more time printing. Meet the printing needs of multiple users or a high-volume printing environments with the 500-sheet paper feeder and cabinet for the HP Color LaserJet CP4020 and CP4520 Printers and CM4540 MFP.



#### CC423A HP Color LaserJet

3x500-sheet Paper Feeder and Stand Spend less time loading paper and more time printing. Meet the printing needs of a high-volume printing environment with the 3x500-sheet paper feeder and stand for the HP Color LaserJet Enterprise CM4540 MFP (CC419A) and CP4520 Printer series.



#### CC425A

HP Color LaserJet 500-sheet Paper Tray Enhance productivity with a simple-to-install paper tray that allows you to print more pages without reloading paper and keep two different types of paper loaded.



#### CC497A

HP LaserJet Postcard Media Insert Tray HP Postcard Media Insert Tray (for tray 3) is the trouble-free solution for customers who regularly print on 10 x 15 cm postcard



#### CE467A HP 512 MB DDR2 200-pin

x32 DIMM HP printer memory improves the printing performance of complex documents and complex files like colour presentations, two-sided output, graphic-intensive PDF files and web pages.



#### J8019A

HP High-Performance Secure EIO Hard Disk Securing your business means protecting information. With the HP High-Performance Secure EIÖ Hard Disk with a Kensington-style lock, you can easily help secure valuable data at rest on your HP printer or MFP and still achieve optimal performance.

#### Ordering information



#### HP Color LaserJet Enterprise CP4525n Printer (CC493A)

Printer; power cable; 100-sheet multipurpose tray; 500-sheet input tray; HP Jetdirect Gigabit Ethernet embedded print server; HP LaserJet Black Print Cartridge (~8500 pages); HP Color LaserJet Cyan, Yellow, and Magenta Print Cartridges with HP ColorSphere Toner (~11,000 pages); Hardware and Software Installation Guide; CD-ROM with software drivers and documentation



Supplies

#### HP Color LaserJet Enterprise CP4525dn Printer (CC494A)

Printer; power cable; 100-sheet multipurpose tray; 500-sheet input tray; HP Jetdirect Gigabit Ethernet embedded print server; HP LaserJet Black Print Cartridge (~8500 pages); HP Color LaserJet Cyan, Yellow, and Magenta Print Cartridges with HP ColorSphere Toner (~11,000 pages); Hardware and Software Installation Guide; CD-ROM with software drivers and documentation



#### HP Color LaserJet Enterprise CP4525xh Printer (CC495A)

Printer; power cable; HP High-Performance Secure Hard Disk, 100-sheet multipurpose tray; 4 x 500-sheet input trays; HP Jetdirect Gigabit Ethernet embedded print server; HP LaserJet Black Print Cartridge (~8500 pages); HP Color LaserJet Cyan, Yellow, and Magenta Print Cartridges with HP ColorSphere Toner (~11,000 pages); Hardware and Software Installation Guide; CD-ROM with software drivers and documentation

# Accessories, Supplies and Support

Accessor	es			
CC422A	HP Color LaserJet 500-sheet Paper Feeder and Cabinet			
CC423A	HP Color LaserJet 3x500-sheet Paper Feeder and Stand			
CC425A	HP Color LaserJet 500-sheet Paper Tray			
CC497A	HP LaserJet Postcard Media Insert Tray			
CE467A	HP 512 MB DDR2 200-pin x32 DIMM			
J8019A	HP High-Performance Secure EIO Hard Disk			
J7972G	HP 1284B Parallel Card			
Connectiv	vity			
J7934G	HP Jetdirect 620n Fast Ethernet Print Server			
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server			
J8007G	HP Jetdirect 690n IPv6/IPsec 802.11g Wireless Print Server			
J8021A	HP Jetdirect ew2500 802.11b/g Wireless Print Server			

CE260A	HP 64/A Black laserJet Toner Cartridge Average cartridge yields 8500 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CE260X	HP 649X Black LaserJet Toner Cartridge Average cartridge yields 17,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CE261A	HP 648A Cyan LaserJet Toner Cartridge Average cartridge yields 11,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CE262A	HP 648A Yellow LaserJet Toner Cartridge Average cartridge yields 11,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CE263A	HP 648A Magenta LaserJet Toner Cartridge Average cartridge yields 11,000 standard pages. Declared yield value in accordance with ISO/IEC 19798*
CE265A	HP Color LaserJet CE265A Toner Collection Unit (36,000 pages) Toner Collection Unit capacity approximately 36,000 pages (individual experience may vary considerably based on images printed, media used, environmental conditions and other factors).
CE246A	HP Color LaserJet CE246A 110V Fuser Kit (150,000 pages)
CE247A	HP Color LaserJet CE247A 220V Fuser Kit (150,000 pages)
CE249A	HP Color LaserJet CE249A Transfer Kit (150,000 pages)

UD 6474 Plack Insertet Toner Cartridge

pages
HP Color LaserJet CE247A 220V Fuser Kit (150,000
pages)
HP Color LaserJet CE249A Transfer Kit (150,000 pages)
upplies
HP Colour Laser Paper 90 g/m <sup>2</sup> -500 sht/A4/210 x 297
mm
HP Professional Glossy Laser Paper 120 gsm-250 sht/A4/210 x 297 mm
HP Professional Glossy Laser Photo Paper 200 gsm-100 sht/A4/210 x 297 mm

## Service & support

US186E HP Care Pack, Next Business Day On-site Color LaserJet

US186E HP Care Pack, Next business buy Orisine Color Laserjer CP4525 Hardware Support, 3 years UT442E HP Care Pack, 4-Hour, 13x5 Same Business Day On-site Color Laserjet CP4525 Hardware Support, 3 years US188E HP Care Pack, Next Business Day On-site Color Laserjet

CP4525 Hardware Support, 4 years

US189E HP Care Pack, Next Business Day On-site Color LaserJet CP4525 Hardware Support, 5 years
UT440PE HP Care Pack, Post Warranty Service, Next Business Day On-site Color LaserJet CP4525 Hardware Support, 1 year
UT434PE HP Care Pack, Post Warranty Service, 4-Hour, 13x5 Same Business Day On-site Color LaserJet CP4525 Hardware Support, 1



# **Technical specifications**

Print technology	Laser					
Print speed		c: As fast as 9.5 sec, Colour: As fast as 9.5 sec				
	A4 Black: Up to 40 ppm, Colour: Up to 40 ppm					
	Exact speed varies depending on the system configuration, software application, driver and document complexity.					
Processor	800 MHz, Intel® LE80578					
Memory	CP4525n: 512 MB; CP4525dn: 512 MB; CP4525xh: 1 GB					
Print resolution	Black: Up to 1200 x 1200 dpi					
B. C. S. Dr.	Colour: Up to 120					
Print quality	HP ImageREt 3600					
Printer languages	HP PCL 6, HP PCL 5c, HP Postscript level 3 emulation, direct PDF printing v 1.4					
Typefaces/fonts	93 internal TrueType fonts scalable in HP PCL and HP Postscript level 3 emulation					
Duty cycle (monthly, A4)	Up to 120,000 pa	ges				
Recommended Monthly Page Volume	2500 to 10000					
Print margins		4.3 mm, right: 4.3 mm, bottom: 4.3 mm				
Media handling	Input	Capacity	Weight	Size		
	Tray 1	Sheets, paper (75 g/m²): 100; labels,	60 to 220 g/m <sup>2</sup>	A4, A5, A6, B5 (JIS), B6 (JIS), envelopes (C5, B5		
		transparencies, cardstock (163 g/m²): 50; cardstock (216 g/m²): 30; envelopes: 10		C6, DL ISO), 16K Postcard, Dpostcard, 76 x 127 to 216 x 356 mm		
	Tray 2	Sheets, paper (75 g/m²): 500; glossy paper	60 to 120 a/m² (plain paper) 105 to 220 a/	m <sup>2</sup> A4, A5, RA4, B5 (JIS), 16K, 148 x 210 to 216 x		
	ildy 2	(160 g/m²): 300; glossy paper (160 g/m²):	(glossy paper)	356 mm		
		250; glossy paper (220 g/m²): 100	(9.000) pape./			
	Duplex printing:	CP4525n: Manual (driver support provided);	60 to 120 g/m <sup>2</sup> (plain paper), 105 to 220 g/	m <sup>2</sup> A4, A5, B5 (JIS)		
	1 1 3	CP4525dn: Automatic (standard); CP4525xh:	(glossy paper)			
		Automatic (standard)				
		Output: Sheets: Up to 500. Envelopes: Up to 30. Transparencies: Up to 100				
Media types		bond, recycled, mid-weight, heavy, mid-weight glos		cardstock, card glossy, preprinted, prepunched,		
	coloured, rough), colour transparency, labels, letterhead, envelope, opaque film, user-defined					
Interface and connectivity	CP4525n: Hi-Speed USB 2.0 port, RI-45 port (10/100/1000Base-TX), EIO slot; CP4525dn: Hi-Speed USB 2.0 port, RI-45 port (10/100/1000Base-TX), EIO slot;					
		ed USB 2.0 port, RJ-45 (10/100/1000Base-TX), El				
Network Capabilities		/100/1000 Base-TX Ethernet embedded print serv				
Operating systems compatibility		ws® 7 Home Basic, Windows 7 Home Premium, W				
		Vista(R) Premium, Windows XP Professional, Windo				
	Windows XP Professional x64 (IPv6 only supported on Windows 2003, Windows XP Professional, and Windows XP Home, IPsec on IPv4 only on Windows 2003, Windows XP Professional, and Windows XP Home, IPsec on IPv4 only on Windows 2003, Windows XP Professional, and Windows XP Professional, and Windows XP Professional Review Revie					
	XP Professional, and Windows XP Home), Novell NetWare 5.1 or higher, Mac OS X v 10.3, 10.4, 10.5, 10.6, SAP, Linux (see http://www.hplip.net), Red Hat Linux 7.x or higher, SuSE Linux 8.x or higher, HP-UX 10.20, 11.x, 11.i, Solaris 2.5 or higher (SPARC systems only), AIX 3.2.5 or higher, MPE-IX, Citrix Presentation Server 4.0 and 4.5,					
	righer, 3052 Linux 6.x or Ingrier, ITT-0.7 10.20, 11.1x, 11.1, 30 and 2.3 in Ingrier (37ARC systems only), Alx 3.2.3 or Ingrier, MFE-1X, Clinix Fresentation Server 4.0 and 4.3, Clirix RenApp Server 5.0, Windows 2003 and 2008 Terminal Services					
	Optional: Current HP printer drivers and software can be obtained from the HP Customer Care Web site: http://www.hp.com/go/cljcp4525					
Network operating systems compatibility						
. 3, . ,	y Works with Windows 7 Home Basic; Windows 7 Home Premium; Windows 7 Professional; Windows 7 Enterprise; Windows 7 Ultimate; Windows 7 x64; Windows Vista(R); Windows Vista(R) Premium; Windows XP Professional; Windows XP Home; Windows Server 2003; Windows Server 2003 (32/64 bit); Windows XP Professional					
		Vista(R) Premium; Windows XP Professional; Windo				
	Vista(R); Windows	Vista(R) Premium; Windows XP Professional; Windows ported on Windows 2003, Windows XP Profession	ows XP Home; Windows Server 2003; Windows	Server 2003 (32/64 bit); Windows XP Professional		
	Vista(R); Windows x64; (IPv6 only sup Windows XP Home	ported on Windows 2003, Windows XP Profession ); Novell NetWare 5.1 or higher; Mac OS X v 10.	ows XP Home; Windows Server 2003; Windows nal and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir	Server 2003 (32/64 bit); Windows XP Professional		
	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA)	ported on Windows 2003, Windows XP Profession p); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AIX 3.2.5 or higher; MPE-iX; Citrix	ows XP Home; Windows Server 2003; Windows nal and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris		
Minimum system requirements	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA Microsoft® Windo	ported on Windows 2003, Windows XP Profession ); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AIX 3.2.5 or higher; MPE-iX; Citri ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 G	ows XP Home; Windows Server 2003; Windows nal and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetoFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and ux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB		
Minimum system requirements	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA Microsoft® Windo hard disk space; V	oported on Windows 2003, Windows XP Profession op); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AlX 3.2.5 or higher; MPE·1X; Citri: ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 G Vindows Vista®: Intel Pentium II or Celeron processo	ows XP Home; Windows Server 2003; Windows nal and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir X MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Inter	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and ux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003,		
Minimum system requirements	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2	ported on Windows 2003, Windows XP Profession s); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AlX 3.2.5 or higher; MPE-iX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 C Vindows Vista®: Intel Pentium II or Celeron processo 008: Intel Pentium II or Celeron processor, 256 MB	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services Be available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and ux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB tet Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5,		
Minimum system requirements	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoff® Windo hard disk space; V Windows Server 2 CD-ROM drive, US	ported on Windows 2003, Windows XP Profession op); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only]; AIX 3.2.5 or higher; MPE-iX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 008: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe	ows XP Home; Windows Server 2003; Windows nal and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lirk MetaFrame Server; Windows Terminal Services Bavailable hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet RAM, 220 MB hard disk space, Internet Explorer PC G3, G4, G5 or Intel Core processor; 256 MI	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and ux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB tet Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5,		
	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M	sported on Windows 2003, Windows XP Profession (2); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AIX 3.2.5 or higher; MPE-iX; Citricus 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor 008: Intel Pentium II or Celeron processor, 256 MB port, Mac OS X v 10.3, 10.4, 10.5, 10.6; Powe ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1	ows XP Home; Windows Server 2003; Windows nal and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Intern RAM, 220 MB hard disk space, Internet Explorer PrC G3, G4, G5 or Intel Core processor; 256 MI O GB available hard disk space	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM		
Software	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in	sported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession; Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AIX 3.2.5 or higher; MPE-iX; Citriuws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor 2008: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of the core of	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetoFrame Server; Windows Terminal Services Ba available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer PCC G3, G4, G5 or Intel Core processor; 256 MI o GB available hard disk space	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM ass		
	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x	ported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession; Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AIX 3.2.5 or higher; MPE-iX; Citri. ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power COS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 from the colour control panel display the colour	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetoFrame Server; Windows Terminal Services Ba available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer PCC G3, G4, G5 or Intel Core processor; 256 MI o GB available hard disk space	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM ass		
Software Control panel	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm ICD 64 x (Attention, Data, Re	ported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession op); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AIX 3.2.5 or higher; MPE-IX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 C Vindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fixed), endanced help with animated graphics	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetoFrame Server; Windows Terminal Services Ba available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer PCC G3, G4, G5 or Intel Core processor; 256 MI o GB available hard disk space	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM as		
Software Control panel Printer management	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, R	sported on Windows 2003, Windows XP Profession (1); Novell NetWare 5.1 or higher; Mac OS X v 10. CS systems only); AIX 3.2.5 or higher; MPE-iX; Citrikws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 CV Indows Vista®: Intel Pentium II or Celeron processor, 008: Intel Pentium II or Celeron processor, 256 MB port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete companies of the colour control panel display, 7 fready), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services Be available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer RC G3, G4, G5 or Intel Core processor; 256 MI O GB available hard disk space driver, Macintosh software drivers and status utiliticent-panel buttons (Menu, Select, Stop, Back/Exit,	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris  I: 1 GHz processor, 2 GB RAM, available 20 GB let Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM less  Help, Up arrow, Down arrow), 3 LED status lights		
Software Control panel	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windohard disk space; V Windows Server 2 CD-ROM drive, USB drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, Re HP Web Jetadmin, Requirements: Inpu	sported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession; Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AlX 3.2.5 or higher; MPE-iX; Citriums® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power ac OS X v 10.5: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fixedy), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply tivoltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/-	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet RAM, 220 MB hard disk space, Internet Explorer PTC G3, G4, G5 or Intel Core processor; 256 MI of GB available hard disk space driver, Macintosh software drivers and status utiliticont-panel buttons (Menu, Select, Stop, Back/Exit, Fr/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris  I: 1 GHz processor, 2 GB RAM, available 20 GB tel Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM ass  Help, Up arrow, Down arrow), 3 LED status lights		
Software Control panel Printer management Power	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, Re	sported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession op); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AlX 3.2.5 or higher; MPE-iX; Citriuws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fractly, enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply the voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (4) watts (powersave), 0.3 watts (off); Typical Electrici	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer RC G3, G4, G5 or Intel Core processor; 256 MI of BB available hard disk space driver, Macintosh software drivers and status utilition-panel buttons (Menu, Select, Stop, Back/Exit, F/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz ty Consumption (TEC): 6.485 kWh/Week	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris 1: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM as Help, Up arrow, Down arrow), 3 LED status lights 1: (+/- 2 Hz). Consumption: 740 watts (active), 72		
Software Control panel Printer management	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm ICD 64 x (Attention, Data, Re HP Web Jetadmin, Requirements: Inpu watts (standby), 1 Out of package: C	ported on Windows 2003, Windows XP Profession (1); Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AlX 3.25 or higher; MPE-iX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 CV (100 Nov Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe ac OS X v10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete companies of the colour control panel display, 7 for eady), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply t voltage 110 to 127 VAC (1-/-10%), 50/60 Hz (1-/-20%),	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lirk MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer PC G3, G4, G5 or Intel Core processor; 256 MI of BB available hard disk space driver, Macintosh software drivers and status utilitic ront-panel buttons (Menu, Select, Stop, Back/Exit, Fr/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz ty Consumption (TEC): 6.485 kWh/Week 522 x 420 mm; CP4525xh: 662 x 651 x 964 mm	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris 1: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM 1: 1 CD-ROM 1: 2 CD-ROM 2: 2 CD-ROM		
Software Control panel Printer management Power  Dimensions (w x d x h)	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, R HP Web Jetadmin, Requirements: Inpuwatts (standby), 15 Out of package: C Packaged: CP4525	sported on Windows 2003, Windows XP Profession (1); Novell NetWare 5.1 or higher; Mac OS X v 10. CS systems only); AIX 3.2.5 or higher; MPE-iX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 CV Indows Vista®: Intel Pentium II or Celeron processor, 256 MB port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete compared to the colour control panel display, 7 freedy), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply the voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (4 vatts (powersave), 0.3 watts (off); Typical Electric Vatts (powersave), 0.3 watts (off); Typical Electric 1746 x 644 x 549 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x 644 x 644 x 649 mm; CP4525dn: 746 x 644 x	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services Be available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer RPC G3, G4, G5 or Intel Core processor; 256 MI O GB available hard disk space driver, Macintosh software drivers and status utilitit ront-panel buttons (Menu, Select, Stop, Back/Exit, Pr/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz; Vy Consumption (TEC): 6.485 kWh/Week 522 x 420 mm; CP4525xh: 662 x 651 x 964 mm; CP4525xh: 856 x 760 x 1343 mm	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris : 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM as Help, Up arrow, Down arrow), 3 LED status lights: (+/- 2 Hz). Consumption: 740 watts (active), 72		
Software Control panel Printer management Power	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, R HP Web Jetadmin, Requirements: Inpu watts (standby), 15 Out of package: CP4525 Out of package: CP4525 Out of package: CP4525	ported on Windows 2003, Windows XP Profession ported on Windows 2003, Windows XP Profession; Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AlX 3.2.5 or higher; MPE-iX; Citri; ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power CoS X v 10.6: Intel Core processor, 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fixedy), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply tooltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+) watts (powersave), 0.3 watts (off); Typical Electrici P45255n: 540 x 522 x 420 mm; CP4525dn: 540 x 644 x 549 mm; CP4525dn: 746 x 644 x 74525n: 38.5 kg; CP4525h: 38.5 kg; CP4525h:	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services Be available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer rPC G3, G4, G5 or Intel Core processor; 256 MI O GB available hard disk space driver, Macintosh software drivers and status utilitizent-panel buttons (Menu, Select, Stop, Back/Exit, 12-2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz; C4 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz; C522 x 420 mm; CP4525xh: 662 x 651 x 964 mm; C94525xh: 856 x 760 x 1343 mm; C64.1 kg	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and uux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris : 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM as Help, Up arrow, Down arrow), 3 LED status lights: (+/- 2 Hz). Consumption: 740 watts (active), 72		
Software Control panel Printer management Power Dimensions (w x d x h) Weight	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, Requirements: Input watts (standby), 15 Out of package: CP4525 Out of packaged: CP4525 CPackaged: CP4525 CPackaged: CP4525 CPackaged: CP4525	sported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession; Novell NetWare 5.1 or higher; Mac OS X v 10. RC systems only); AlX 3.2.5 or higher; MPE-iX; Citriuws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fixed pixels, 4-line colour panel display, 10 fixed pixels, 10 fixed pixe	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space of the control	Server 2003 (32/64 bit); Windows XP Professional Windows 2003, Windows XP Professional and ux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM es Help, Up arrow, Down arrow), 3 LED status lights: (+/- 2 Hz). Consumption: 740 watts (active), 72		
Software Control panel Printer management Power  Dimensions (w x d x h)	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm ICD 64 x (Attention, Data, Re HP Web Jetadmin, Requirements: Inpu watts (standby), 19 Out of package: CP4525 Out of package: CP4525 Operating tempera	ported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession (); Novell NetWare 5.1 or higher; Mac OS X v 10. SC systems only); AlX 3.25 or higher; MPE-iX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fready), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply t voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (4 or watts (powersave), 0.3 watts (off); Typical Electrici P4525n: 540 x 522 x 420 mm; CP4525dn: 540 x 624 x P4525n: 38.5 kg; CP4525dn: 38.5 kg; CP4525dn: 38.5 kg; CP4525dn: 38.5 kg; CP4525dn: 44.0 kg; CP4525dn: 44.0 kg; CP4525dn: 48.5 thre: 10 to 30° C. Recommended operating temper	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lirk MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer PC G3, G4, G5 or Intel Core processor; 256 MI of BB available hard disk space driver, Macintosh software drivers and status utilitic ront-panel buttons (Menu, Select, Stop, Back/Exit, Fr/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz ty Consumption (TEC): 6.485 kWh/Week 522 x 420 mm; CP4525xh: 662 x 651 x 964 m 549 mm; CP4525xh: 856 x 760 x 1343 mm 641 kg kg rature: 15 to 27° C. Operating humidity: 10 to 81 arrangements.	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris 1: 1 GHz processor, 2 GB RAM, available 20 GB tet Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM es Help, Up arrow, Down arrow), 3 LED status lights 1: (+/- 2 Hz). Consumption: 740 watts (active), 72 m		
Software Control panel Printer management Power Dimensions (w x d x h) Weight	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm ICD 64 x (Attention, Data, Re HP Web Jetadmin, Requirements: Inpu watts (standby), 19 Out of package: CP4525 Out of package: CP4525 Operating tempera	ported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession (); Novell NetWare 5.1 or higher; Mac OS X v 10. SC systems only); AlX 3.25 or higher; MPE-iX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fready), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply t voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (4 or watts (powersave), 0.3 watts (off); Typical Electrici P4525n: 540 x 522 x 420 mm; CP4525dn: 540 x 624 x P4525n: 38.5 kg; CP4525dn: 38.5 kg; CP4525dn: 38.5 kg; CP4525dn: 38.5 kg; CP4525dn: 44.0 kg; CP4525dn: 44.0 kg; CP4525dn: 48.5 thre: 10 to 30° C. Recommended operating temper	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lirk MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer PC G3, G4, G5 or Intel Core processor; 256 MI of BB available hard disk space driver, Macintosh software drivers and status utilitic ront-panel buttons (Menu, Select, Stop, Back/Exit, Fr/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz ty Consumption (TEC): 6.485 kWh/Week 522 x 420 mm; CP4525xh: 662 x 651 x 964 m 549 mm; CP4525xh: 856 x 760 x 1343 mm 641 kg kg rature: 15 to 27° C. Operating humidity: 10 to 81 arrangements.	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Iwx 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROMes Help, Up arrow, Down arrow), 3 LED status lights I: (+/- 2 Hz). Consumption: 740 watts (active), 72 m		
Software Control panel Printer management Power Dimensions (w x d x h) Weight	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windohard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, R HP Web Jetadmin, Requirements: Inpuwarts (standby), 19 Out of package: CP4525 Out of packaged: CP4525 Out of package: CP4525 Operating temperc RH. Storage tempe dB(A)	ported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession; Novell NetWare 5.1 or higher; Mac OS X v 10. CR systems only); AlX 3.2.5 or higher; MPE-iX; Citrivs® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power COS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fixedy), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply I voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- watts (powersave), 0.3 watts (off); Typical Electrici P45255: 540 x 522 x 420 mm; CP4525dn: 540 x 644 x 549 mm; CP4525dn: 746 x 644 x P4525n: 38.5 kg; CP4525dn: 44.0 kg; CP4525xh: in: 44.0 kg; CP4525xh: dir. 44.0 kg; CP4525xh: 82.5 ture: 10 to 30° C. Recommended operating temper rature: 0 to 35° C. Storage humidity: 10 to 90% RF	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x Metaframe Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer RC G3, G4, G5 or Intel Core processor; 256 MI O GB available hard disk space driver, Macintosh software drivers and status utilitit cont-panel buttons (Menu, Select, Stop, Back/Exit, 100-100) and 100 mg; C4525 Mg; C64 Mg; C74525 Mg;	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM ass Help, Up arrow, Down arrow), 3 LED status lights  1: (+/- 2 Hz). Consumption: 740 watts (active), 72 m		
Software Control panel Printer management Power Dimensions (w x d x h) Weight Operating environment	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm ICD 64 x (Attention, Data, Re HP Web Jetadmin, Requirements: Inpu watts (standby), 15 Out of package: CPackaged: CP4525 Operating temperate (RH. Storage temped B(A) Safety certifications:	sported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession; Novell NetWare 5.1 or higher; Mac OS X v 10. CC systems only); AlX 3.2.5 or higher; MPE-iX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Power ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fixed processor, 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fixed pixels, 4-line colour panel display, 8 fixed pixels, 9 fixe	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lirk MetaFrame Server; Windows Terminal Services BB available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space driver, Macintosh software drivers and status utilitic nont-panel buttons (Menu, Select, Stop, Back/Exit, 1-7-2 Hz); 220 to 240 VAC (+/-10%), 50/60 Hz; YCONSUMPTION (TEC): 6.485 kWh/Week 522 x 420 mm; CP4525xh: 662 x 651 x 964 mm; CP4525xh: 856 x 760 x 1343 mm; 64.1 kg kg rature: 15 to 27° C. Operating humidity: 10 to 81. Noise level per ISO 9296: Sound power: LwAcEU), GS License (Europe), EN 60825-1+A1+A2 (	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris I: 1 GHz processor, 2 GB RAM, available 20 GB net Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM ass Help, Up arrow, Down arrow), 3 LED status lights  1: (+/- 2 Hz). Consumption: 740 watts (active), 72 m		
Software Control panel Printer management Power Dimensions (w x d x h) Weight Operating environment	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm ICD 64 x (Attention, Data, Re HP Web Jetadmin, Requirements: Inpu watts (standby), 15 Out of package: CP4525 Out of package: CP4525 Operating temperc RH. Storage tempe dB(A) Safety certifications: Voltage Directive 2	ported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession (); Novell NetWare 5.1 or higher; Mac OS X v 10. SC systems only); AIX 3.25 or higher; MPE-IX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fready), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply to voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (4 or watts (powersave), 0.3 watts (off); Typical Electric P4525n: 540 x 522 x 420 mm; CP4525dn: 540 x in: 746 x 644 x 549 mm; CP4525dn: 38.5 kg; CP4525xh: 82.5 in: 44.0 kg; CP4525xh: 82.5 thre: 10 to 30° C. Recommended operating temper rature: 0 to 35° C. Storage humidity: 10 to 90% Rts: IEC 60950-1 (International), EN 60950-1+A11 (006/95/EC with CE Marking (Europe), other safet	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services Be available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer PC G3, G4, G5 or Intel Core processor; 256 MI of Be available hard disk space driver, Macintosh software drivers and status utiliti ront-panel buttons (Menu, Select, Stop, Back/Exit, Fr/-2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz ty Consumption (TEC): 6.485 kWh/Week 522 x 420 mm; CP4525xh: 662 x 651 x 964 m 549 mm; CP4525xh: 856 x 760 x 1343 mm 64.1 kg kg rature: 15 to 27° C. Operating humidity: 10 to 81. Noise level per ISO 9296: Sound power: LwAdEU), GS License (Europe), EN 60825-1+A1+A2 (y approvals as required by individual countries	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris  I: 1 GHz processor, 2 GB RAM, available 20 GB Ret Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM ass Help, Up arrow, Down arrow), 3 LED status lights  I: (+/- 2 Hz). Consumption: 740 watts (active), 72 m		
Software Control panel Printer management Power Dimensions (w x d x h) Weight Operating environment	Vista(R); Windows x64; (IPv6 only sup Windows XP Home 2.5 or higher (SPA) Microsoft® Windo hard disk space; V Windows Server 2 CD-ROM drive, US drive; USB port; M Print drivers and in 5.16 cm LCD 64 x (Attention, Data, R (Atte	ported on Windows 2003, Windows XP Profession opported on Windows 2003, Windows XP Profession (); Novell NetWare 5.1 or higher; Mac OS X v 10. SC systems only); AIX 3.25 or higher; MPE-IX; Citrix ws® 7 (32-bit): 1 GHz processor, 1 GB RAM, 16 GVindows Vista®: Intel Pentium II or Celeron processor, 256 MB B port, Mac OS X v 10.3, 10.4, 10.5, 10.6: Powe ac OS X v 10.6: Intel Core processor; 2 GB RAM; 1 stallation software on CD-ROM, HP PCL 6 discrete of 160 pixels, 4-line colour control panel display, 7 fready), enhanced help with animated graphics HP Easy Printer Care Software, HP SureSupply to voltage 110 to 127 VAC (+/- 10%), 50/60 Hz (4 or watts (powersave), 0.3 watts (off); Typical Electric P4525n: 540 x 522 x 420 mm; CP4525dn: 540 x in: 746 x 644 x 549 mm; CP4525dn: 38.5 kg; CP4525xh: 82.5 in: 44.0 kg; CP4525xh: 82.5 thre: 10 to 30° C. Recommended operating temper rature: 0 to 35° C. Storage humidity: 10 to 90% Rts: IEC 60950-1 (International), EN 60950-1+A11 (006/95/EC with CE Marking (Europe), other safet	ows XP Home; Windows Server 2003; Windows and and Windows XP Home; IPsec on IPv4 only or 3 or higher; Red Hat Linux 7.x or higher; SuSE Lir x MetaFrame Server; Windows Terminal Services Be available hard disk space; Windows 7 (64-bit or, 512 MB RAM, 220 MB hard disk space, Internet Explorer RAM, 220 MB hard disk space, Internet Explorer RC G3, G4, G5 or Intel Core processor; 256 MI O GB available hard disk space driver, Macintosh software drivers and status utilitit ont-panel buttons (Menu, Select, Stop, Back/Exit, 1974-2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz; 1974-2 VA20 mm; CP4525xh: 662 x 651 x 964 mm; CP4525xh: 856 x 760 x 1343 mm; 64.1 kg kg  1528 x 420 mm; CP4525xh: 856 x 760 x 1343 mm; 1974-1974 children Selevel per ISO 9296: Sound power: LwAd Levis Bevelos Bevel	Server 2003 (32/64 bit); Windows XP Professional Nindows 2003, Windows XP Professional and Jux 8.x or higher; HP-UX 10.20, 11.x, 11.i; Solaris  I: 1 GHz processor, 2 GB RAM, available 20 GB tel Explorer 7; Windows XP, Windows Server 2003, 6; for all systems: Adobe Acrobat Reader 5, 8 RAM; 160 MB available hard disk space; CD-ROM ass  Help, Up arrow, Down arrow), 3 LED status lights  I: (+/- 2 Hz). Consumption: 740 watts (active), 72 m  ON RH. Recommended operating humidity: 30 to 70% 6.9 B(A), 5.0 B(A) (ready). Sound pressure: LpAm54 Class 1 Laser/LED Device) GB4943-2001, Low  EN 55024: 1998+A1+A2, FCC Title 47 CFR, Part		

http://www.hp.com/uk













