

HP LaserJet M5025 MFP



Fulfill workteam A3 printing and copying needs and provide send-to-e-mail from your MFP plus optional fax functionality, with a tool that is affordable and easy to use and makes processes simple and efficient.



HP LaserJet M5025 MFP

Ideal for workteams in SMB environments who need a black-and-white MFP that is easy to use, maintain and manage, offers a familiar LaserJet experience and reliable performance with A3 capabilities.

This MFP is extremely easy to use, install, manage and maintain with a improved control panel.

An intuitive control panel, common to all new HP MFPs, is simple to navigate and clearly displays available applications so you can easily use, manage and maintain your device. HP Web Jetadmin offers remote installation, configuration and proactive management. Experience fewer interruptions as interactive HP Smart printing technology⁴ in the print cartridge and the device optimises print quality and reliability. Enjoy best-in-class networking through the HP Jetdirect internal print server.

Enhance workteam performance with the A3 multifunction capabilities of this robust, affordable MFP.

See productivity rise with A3 print and copy, send-to-e-mail, fax¹, embedded networking and two-sided printing functionality². Set the pace for success with A3 print and copy speeds up to 25 ppm. HP's Instant-on Technology delivers a fast, first printed page even from Powersave mode. Send-to-e-mail directly from the MFP, which also maintains a simple address book and PIN authentication for security. Flexible paper input: standard capacity of 600 sheets expandable to 2,100 sheets³.

Experience familiar HP LaserJet reliability and quality for results you can always depend on.

Achieve professional quality: the HP LaserJet print cartridge and HP toner formula work together to create crisp, sharp text and lines every time you print. Increase uptime: a 460 MHz processor and 256 MB of memory (expandable to 512 MB) enable the device to process print, fax¹ and send-to email jobs easily, with a quick return to the print job's application. Print demanding jobs with HP PCL 5, HP PCL 6, and HP PostScript Level 3 emulation print drivers

¹ Fax functionality is an optional feature that can be added to the HP LaserJet M5025 MFP

² The two-sided printing unit is an optional accessory that can be added to the HP LaserJet M5025 MFP

³ Additional optional input is available in two configurations: a 500-sheet input tray with cabinet or an integrated 3 x 500-sheet input tray

⁴ Using genuine HP supplies ensures availability of all HP printing features.

HP LaserJet M5025 MFP

Series at a glance



HP LaserJet M5025 MFP

- HP LaserJet M5025 MFP: print speed of up to 25 ppm
- 256 MB memory
- 460 MHz processor
- 40GB Hard Disk
- HP Jet Direct Embedded Print Server
- Embedded Web Server
- digital sending
- standard input capacity of 600-sheets with 500-sheet input tray and 100-sheet multipurpose tray
- 50-sheet reversing automatic document feeder

Recommended accessories



J7989G
HP High Performance
Serial ATA EIO Hard
Disk



Q7719A
HP 256 MB 100-pin
DDR DIMM



Q3701A
HP LaserJet MFP Analog
Fax Accessory 300



J7972G
HP 1284B Parallel EIO
Card



Q7549A
HP LaserJet Auto Duplex
Unit

HP Kits

Q7833A
HP LaserJet
M5035/M5025 MFP
220V Printer
Maintenance Kit



Q7834A
HP LaserJet M5035/M5025
MFP 500-sheet Tray w/
Cabinet



Q7835A
HP LaserJet M5035/M5025
MFP integrated 3x500-sheet
Tray

HP Kits

Q7842A
HP LaserJet M5035/M5025
MFP ADF Maintenance Kit



J7960G
HP Jetdirect 625n Internal Print
Server (EIO,
10/100/1000TX)



J7961G
HP Jetdirect 635n IPv6/IPsec
Internal Print Server (EIO,
10/100/1000TX)

Operating and warranty specifications

Operating environment	Operating temperature: 15 to 35° C. Recommended operating temperature: 15 to 35° C. Operating humidity: 20 to 80% RH. Operating humidity recommended: 25 to 75% RH. Storage temperature: 13 to 38° C. Storage humidity: 20 to 80% RH. Noise level per ISO 9296: sound power: LwAd 6.6 B(A) (printing at 25 ppm). Sound pressure: LpAm 51 dB(A) (printing), 56 dB(A) (copy or scan)
Certifications	CISPR 22:1993/EN 55022:1994 Class A, EN 61000-3-2:2000, EN 61000-3-3:1995, EN 55024:1998, FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 4/GB9254-1998, GB17625.1-2003, EMC Directive 89/336/EEC and the Low Voltage Directive 73/23/EEC, and carries the CE-Marking accordingly. Regulatory standards: Argentina (TUV S Mark-Rs.92/98/Ds.1009/98), Australia (AS/NZ 3260), Canada (cUL-CAN/CSA C22.2 No.60950-1-03), China (GB4943), Czech Republic (CSN-IEC 60950-1; IEC 60825-1), Estonia (EEI-EN60950-1; IEC 60825-1), EU (CE Mark-Low Voltage Directive 73/23/EEC), Germany (TUV-EN60950-1; IEC 60825-1), Hungary (MEEIEC 60950-1; IEC 60825-1), Lithuania (LS-IEC 60950-1; IEC 60825-1), (Russia (GOST-R50377), Slovakia (IEC 60950-1; IEC60825-1), Slovenia (SQI- IEC 60950-1; IEC60825-1), South Africa (IEC 60950-1; IEC60825-1), US (UL-LUL 60950-1; FDA-21 CFR Chapter 1 Subchapter J for lasers), Class 1 Laser/LED Product. ENERGY STAR: Yes
Warranty	One-year, next-day, next-business-day-on-site warranty with free phone support during warranty period

Ordering information



HP LaserJet M5025 MFP (Q7840A)

HP LaserJet 5025 MFP (includes printer engine, scanner, ADF, 40 GB hard disk drive, and control panel), power cord, 15,000 page toner cartridge, control panel overlay, Getting Started Guide, wall poster, printer driver software CD

Accessories, Supplies and Support

Accessories

J7989G	HP High Performance Serial ATA EIO Hard Disk
Q7719A	HP 256 MB 100-pin DDR DIMM
Q3701A	HP LaserJet MFP Analog Fax Accessory 300
J7972G	HP 1284B Parallel EIO Card
Q7549A	HP LaserJet Auto Duplex Unit
Q7833A	HP LaserJet M5035/M5025 MFP 220V Printer Maintenance Kit
Q7834A	HP LaserJet M5035/M5025 MFP 500-sheet Tray w/ Cabinet
Q7835A	HP LaserJet M5035/M5025 MFP integrated 3x500-sheet Tray
Q7842A	HP LaserJet M5035/M5025 MFP ADF Maintenance Kit

Supplies

Q7570A	HP LaserJet Q7570A Black Print Cartridge with Smart Printing Technology 15,000 standard pages according to ISO/IEC 19752
---------------	---

Connectivity

J7960G	HP Jetdirect 625n Internal Print Server (EIO, 10/100/1000TX)
J7961G	HP Jetdirect 635n IPv6/IPsec Internal Print Server (EIO, 10/100/1000TX)

Service & support

UE719A/E	HP Care Pack, Next-Business-Day On-Site, 3 years
UE999A/E	HP Care Pack, Same Day (4 hours) 13x5, 3 years
UF002PE	HP Care Pack, Post Warranty Next-Business-Day On-Site, 1 year
UF004PE	HP Care Pack, Post Warranty Same Day (4 hours) 13x5, 1 year
UE720E	HP Care Pack, Next Business Day On-Site, 4 years
UE721E	HP Care Pack, Next Business Day On-Site, 5 years
U2014A/E	HP Care Pack, Installation & Network Configuration

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>

Technical specifications

Print technology	Monochrome Laser			
Print speed	A3: Up to 13 ppm. A4: Up to 25 ppm. First page out black: Less than 10 sec			
Processor	460 MHz. MIPS embedded in HP Custom ASIC			
Memory	256 MB. Expandable to 512 MB through one 100-pin DDR DIMM slot. Hard Disk Capacity: Standard, 40 GB			
Print	Quality	HP ProRes 1200, HP FastRes 1200, 600 dpi, 170 lpi		
	Resolution	Up to 1200 x 1200 dpi		
	Printer languages	HP Postscript Level 3 Emulation, PCL 6, PCL 5, PDF 1.4		
	Economical printing	Economode (saves up to 50% toner from 600 dpi), immediate return to Power safe mode after each print job due to Instant-on fuser technology (saves electricity), optional automatic two-sided printing and N-up printing (saves paper)		
	Duty cycle	Up to 200000 pages per month		
Fax	Print margins (mm)	Top: 2 mm. Left: 2 mm. Right: 2 mm. Bottom: 2 mm		
	Fax memory	Dependent on available free disk space		
Digital sending	File formats	PDF, JPG, TIFF, MTIFF		
	Installation	Via HP Jetdirect embedded networking, HP Jetdirect internal print servers, HP Jetdirect external print servers, HP wireless print servers, and HP connectivity cards		
Scan	Type	Flatbed, ADF. Colour scanning: Yes		
	Scan resolution	Optical: Up to 600 dpi. Enhanced: Up to 600 dpi		
	Grey scale levels	256		
	Scannable area	Maximum media size: 29.7 x 42.0 cm		
Copy	Margins for scanned items	Left: 5 mm. Top: 6 mm. Right: 5 mm. Bottom: 6 mm		
	Copy speed	Up to 25 cpm		
	Copy resolution	Up to 600 x 600 dpi		
	Multiple copies	Up to 1000		
Media handling	Reduce/enlarge	25 to 400%		
	Input:	Capacity	Weight	Size
		Tray 1	Sheets: 100, envelopes: 10	60 to 199 g/m ²
	Tray 2	Sheets: 250	60 to 120 g/m ²	A4, B4, B5 LTR, LGL, EXE, A5, 215.9 x 330.2 mm
	Tray 3	Sheets: 250	60 to 120 g/m ²	A4, B4, B5, LTR, LGL, EXE, A5, A3, LGR, 215.9 x 330.2 mm
	ADF	Sheets: 50	60 to 120 g/m ²	
Output:	Sheets: Up to 250. Envelopes: Up to 25. Transparencies: Up to 200			
Duplex printing:	Automatic (optional)			
Media types	Paper (plain, photo, banner), envelopes, labels, cards (index, greeting), transparencies			
Interface and connectivity	HP Jetdirect Fast Ethernet embedded print server, Foreign Interface Harness (FIH), USB (compatible with USB 2.0 specifications) type A port, USB (compatible with USB 2.0 specifications) type B port, open EIO slot, optional analog fax. Optional: HP Jetdirect 635n IPv6/IPsec Print Server J7961A, HP Jetdirect 625n Gigabit Ethernet Print Server J7960A, HP Jetdirect 620n Fast Ethernet Print Server J7934A, HP Jetdirect ew2400 802.11g Wireless Print Server J7951A, HP Jetdirect en3700 Fast Ethernet Print Server J7942A, HP Jetdirect 175x Fast Ethernet Print Server J6035D, HP High Performance Serial ATA Hard Disk J7989G, HP 1284B Parallel Card J7972G, HP Jetdirect Connectivity Card J4135A, HP bt450 Bluetooth Wireless Printer and PC Adapter Q6398A, HP bt400 Bluetooth Wireless Printer Adapter Q6399A			
Operating systems compatibility	Windows® 2000, XP Home, XP Professional, XP Professional x64 Edition, Windows® Server 2003; Mac OS 10.2 and higher. Optional: Windows 2000, XP Home, XP Professional, XP Professional x64, Windows Server 2003; Mac OS 10.2 and higher. The latest software and drivers are available for the HP LaserJet M5035 MFP from the HP Website at http://www.hp.com/support/ljm5035mfp			
Minimum system requirements	133 MHz processor or higher, 64 MB RAM, 40 MB available hard disk space, USB or network port connection. Mac OS 10.2 and higher, 128 MB RAM, 25 MB available hard disk space, network or USB port			
Standard software	Drivers on the web: Printing system, PCL 6 driver only, PCL 5 driver only, PS driver only, WJA applet, UPD PCL 5, UPD PS, HP Easy Printer Care Software, PC fax driver			
Control panel	4 job control buttons, 13 button numeric keypad, touch screen graphical display, 3 status lights, 1 display contrast knob			
Power	Requirements: Input voltage: 115 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 12 amp; 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 amp. Consumption: 0.1 watts maximum (off), 24 watts maximum (sleep), 280 watts maximum (ready), 600 watts maximum (printing), 1265 watts maximum (copying)			
Dimensions (w x d x h)	Out of package: 610 x 571 x 584 mm. Packaged: 766 x 721 x 852 mm			
Weight	Out of package: 55 kg. Packaged: 61.1 kg			

<http://www.hp.com/uk>



© Copyright Hewlett-Packard Development Company, L.P. 2006. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 10/06 4AA0-5299EEE

