

HP Designjet T620 Printer series

A reliable 610 mm printer for small CAD/GIS workgroups.







- Easily meet deadlines: with speeds of up to 35 seconds per A1 page¹, you can print CAD/GIS projects up to 3 times faster than with the HP Designjet 500 Printer²
- Enjoy easy sharing thanks to the built-in network card
- Print batch files³ easily without having to open any application, using the free HP Instant Printing Utility
- Intelligent technology, built into Original HP supplies, provides time-saving features to help optimise print quality and reliability



- Achieve precise, accurate line quality, true neutral greys and a wide range of vivid colours with the 6-ink printing system including 2 HP Vivera black inks (Matte black and Photo black) together with a grey ink
- Produce exacting detail with 0.02 mm minimum line width⁴ and highly accurate drawings with 0.1% line accuracy
- Create stunning large-format posters that convey your message clearly with Serif PosterDesigner Pro for HP5
- Print on new HP bond papers and HP Recycled Bond Paper

Focus on creating your designs with this fast and reliable printer.

- Work confidently with 2 GB of dedicated memory, exclusively for faster processing of the most complex files
- Experience greater operating system support with original HP-GL/2 and RTL
- Upgrade with peace of mind: colour emulation capabilities enable you to reproduce the same, consistent colours produced on your previous Designjet
- Handle prints right off the printer as fast-drying HP Vivera inks produce smudge-resistant results



















 $^{1 \}hspace{1mm} \text{Using HP-GL/2}$ accessory, Fast mode on plain paper; intervention time not included

² Compared to the HP Designjet 500 Plus Printer series, based on 4 copies of 50 A1 pages using normal print quality on plain paper; intervention time not included

 $^{3\,}_{\mbox{HP-GL/2, DWF, PDF, JPEG, TIFF, and MS Office 2007 (Word, Excel, Powerpoint) files}$

⁴ HP-GL/2 addressable

 $^{5\,}$ Serif PosterDesigner Pro for HP is an optional software accessory; please purchase separately.

HP Designjet T620 Printer series

TECHNICAL	SPECIFI	CATIONS

Print speed Line drawings	Fast: 35 sec/page, 72 A1 prints per hour
Printing	
Print resolution Margins (top x bottom x left x right)	Up to 2400 x 1200 optimised dpi Roll: 5 mm (top), 5 mm (right), 5 mm (left), 5 mm (bottom)
Margins (lop x bollom x len x right)	Sheet: 5 mm (top), 5 mm (right), 5 mm (left), 16.75 mm (bottom)
Technology	HP Thermal Inkjet
Ink types	Dye-based (C, M, Y, G, PK), pigment-based (MK)
Ink colours	6 (cyan, grey, magenta, matte black, photo black, yellow)
Ink drop	6 pl (C, M, PK, G), 9 pl (Y, MK) +/- 0.1% (+/-0.1% of the specified vector length or +/-0.1 mm - whichever
Line accuracy	greater - at 23° C, 50-60% relative humidity, on A0 printing material in
	Best or Normal mode with HP Matte Film)
Minimum line width	0.02 mm (HP-GL/2 addressable)
Guaranteed minimum line width	0.06 mm (ISO/IEC 13660:2001(E))
Maximum print length Image quality	91.4 m
Maximum optical density	2.15 maximum black optical density (6 L *min)
Media	
Handling	Sheet feed, roll feed, automatic cutter
Types	Bond and coated paper, technical paper, film, photographic paper, backlit, self-adhesive
Weight	60 to 328 g/m ²
Size	210 x 279 to 610 x 1676 mm
Thickness	Up to 0.8 mm
Memory	
Standard	2 GB dedicated file-processing memory (384 MB RAM memory)
Hard disk Connectivity	None
Interfaces (standard)	1 Fast Ethernet (100Base-T) port, 1 Hi-Speed USB 2.0 port, 1 EIO Jetdirect
onacoo (oraniaara)	accessory slot
Interfaces (optional)	HP Jetdirect print servers
Print languages (standard)	HP-GL/2, HP-RTL, CALS G4, HP PCL 3 GUI
Drivers included	HP-GL/2, HP-RTL drivers for Windows® (optimised for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; support for Citrix® XenApp
	and Citrix® XenServer environments
Recommended system requirements	
Мас	Mac OS X v10.4, v10.5: PowerPC G4, G5, or Intel® Core Processor; 1
Windows	GB RAM; 2 GB available hard disk space Microsoft® Windows® XP Home/Professional (SP2 or higher): Intel®
Wildows	Pentium® family or AMD® K6®/Athlon®/Duron® family (1 GHz), 1 GB
	RAM, 2 GB available hard disk space; Windows Vista® Home
	Premium/Business/Ultimate: 32-bit (x86) or 64-bit (x64) processor (1 GHz), 2 GB RAM, 2 GB available hard disk space
Dimensions (w x d x h)	GHZ), 2 GB KAIVI, 2 GB dvalidble hard disk space
Printer	1262 x 661 x 391 mm
Shipping	1440 x 766 x 623 mm
Weight	
Printer	47 kg
Shipping What's in the box	89 kg
CK835A	Printer, printheads (3 x 2 colours each), introductory ink cartridges, Quick
	Reference Guide, setup poster, Serif PosterDesigner Pro poster, start-up
Environmental ranges	software, power cord
Operating Temperature	5 to 40° C
Recommended operating temperature	15 to 35° C (depending on paper type)
	-25 to 55° C
Storage temperature	
Storage temperature Recommended operating humidity	0 to 80% RH (depending on paper type)
Recommended operating humidity Storage humidity	0 to 80% RH (depending on paper type) 0 to 95% RH
Recommended operating humidity Storage humidity Acoustic	0 to 95% RH
Recommended operating humidity Storage humidity Acoustic Sound Pressure	0 to 95% RH 57 dB(A), 29 dB(A) (standby)
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power	0 to 95% RH
Recommended operating humidity Storage humidity Acoustic Sound Pressure	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5 watts with embedded DFE (powersave), 0.1 watts (off)
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5 watts with embedded DFE (powersave), 0.1 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5 watts with embedded DFE (powersave), 0.1 watts (off)
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum Power requirements	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5 watts with embedded DFE (powersave), 0.1 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum Power requirements Certification	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5 watts with embedded DFE (powersave), 0.1 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum Power requirements Certification Safety Electromagnetic Environmental	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5 watts with embedded DFE (powersave), 0.1 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max EU (IVD and EN 60950-1 compliant), Russia (GOST) Compliant with Class B requirements: EU (EMC Directive) Energy Star, WEEE, EU RoHS, REACH, EUP, FEMP
Recommended operating humidity Storage humidity Acoustic Sound Pressure Sound Power Power Consumption Maximum Power requirements Certification Safety Electromagnetic	0 to 95% RH 57 dB(A), 29 dB(A) (standby) 6.9 B(A), 4.4 B(A) (standby) 120 watts maximum (active), 29 watts (standby), < 9.5 watts / < 27.5 watts with embedded DFE (powersave), 0.1 watts (off) Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max EU (IVD and EN 60950-1 compliant), Russia (GOST) Compliant with Class B requirements: EU (EMC Directive)

and support options vary by product, country and local legal requirements.

ORDERING INFORMATION

Product		
CK835A	HP Designjet T620 610 mm Printer	
Accessories		
Q6663A	HP Designjet Zx100/Tx100/Tx10 24-in Stand	
Q6700A	HP Designjet Zx100/Tx100/Tx10 24-inch Spindle	
J7961G	HP Jetdirect 635n IPv6/IPsec Print Server	
CN088A	Serif PosterDesigner Software Pro for HP Designjet Printers	
Ink supplies		
C9397A	HP 72 69-ml Photo Black Ink Cartridge	
C9398A	HP 72 69-ml Cyan Ink Cartridge	
C9399A	HP 72 69-ml Magenta Ink Cartridge	
C9400A	HP 72 69-ml Yellow Ink Cartridge	
C9401A	HP 72 69-ml Grey Ink Cartridge	
C9403A	HP 72 130-ml Matte Black Ink Cartridge	
C9370A	HP 72 130-ml Photo Black Ink Cartridge	
C9371A	HP 72 130-ml Cyan Ink Cartridge	
C9372A	HP 72 130-ml Magenta Ink Cartridge	
C9373A	HP 72 130-ml Yellow Ink Cartridge	
C9374A	HP 72 130-ml Grey Ink Cartridge	
C9380A	HP 72 Gray and Photo Black Printhead	
C9383A	HP 72 Magenta and Cyan Printhead	
C9384A	HP 72 Matte Black and Yellow Printhead	
Media supplies		
Q6626A	HP Super Heavyweight Plus Matte Paper-610 mm x 30.5 m (24 in x 100 ft)	
C6029C	HP Heavyweight Coated Paper-610 mm x 30.5 m (24 in x 100 ft)	
C6019B	HP Coated Paper-610 mm x 45.7 m (24 in x 150 ft)	
C6035A	HP Bright White Inkjet Paper-610 mm x 45.7 m	
Q1396A	HP Universal Bond Paper-610 mm x 45.7 m (24 in x 150 ft)	
CG889A	HP Recycled Bond Paper-610 mm x 45.7 m (24 in x 150 ft)	
C3869A	HP Natural Tracing Paper-610 mm x 45.7 m (24 in x 150 ft)	
C3876A	HP Clear Film-610 mm x 22.9 m (24 in x 75 ft)	
51642A	HP Matte Film-610 mm x 38.1 m (24 in x 125 ft)	
Q1427A	HP Universal High-gloss Photo Paper-914 mm x 30.5 m (36 in x 100 ft)	
Q1420A	HP Universal Semi-gloss Photo Paper-610 mm x 30.5 m (24 in x 100 ft)	
Service & support		
US261E HP Care Pa	ick, Next Business Day On Site, 5 years	
US262E HP Care Pack, Next Business Day On Site, 4 years		
US263E HP Care Pack, Next Business Day On Site, 3 years		

US263E HP Care Pack, Next Business Day On Site, 3 years
US256E HP Care Pack, 4hr 13x5 Same Business Day On Site, 3 years
US257PE HP Care Pack, Post Warranty, Next Business Day On Site, 1 year

US252PE HP Care Pack, Post Warranty, 4hr 13x5 Same Business Day On Site, 1 year

For more HP Large Format Media substrates and sizes please visit us online at: http://www.hp.com/go/designjet/supplies

For more information, visit our website at $\protect\ensuremath{\text{http://www.hp.com}}$

© Copyright 2009 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA2-8298 Published in EMEA October 2009