

# i-tec USB to Serial RS232 Adapter

i-tec USB to Serial RS232 Adapter



#### **PRODUCT DESCRIPTION**

This USB serial device provides a simple and easy way to connect universal serial bus and serial port interface. User can simply insert a cable into an available USB slot of pc or HUB and can connect any RS-232 device or DB 9P Male connector.

In case of any problems with installation, technical difficulties or faulty functionality of device find the possible solution in FAQ bookmark first.

## **PRODUCT FEATURES**

- Support RS232 serial interface
- Transfer rate 500 kbps
- Compatible with USB 1.1 specification
- Chipset Prolific PL2303
- OS Windows XP/Vista/7/8/8.1/10, Mac OS 8.6 and higher
- Product size 52 x 38 x 16 mm
- Product weight 39 g
- Package size 182 x 130 x 43 mm
- Package weight 122 g

### **SYSTEM REQUIREMENTS**

Hardware requirements: IBM compatible Pentium-233 MHz, 64 MB RAM; PC with an available USP port Operating system: Windows XP/Vista/7/8/8.1/10, Mac OS 8.6 and higher

### **PACKAGE CONTENTS**

- USB 1.1 Serial adapter (55 cm)
- Driver CD
- User's Guide



### **SPECIFICATION**

Part Number	Product Description & EAN
USBSEAD	i-tec USB to Serial RS232 Adapter EAN: 8594047312704
Hardware	
Ports/Connectors	
System Requirements	
Hardware	Hardware requirements: IBM compatible Pentium-233 MHz, 64 MB RAM; PC with an available USP port
Operating system	Windows 7/8/8.1/10 (32/64 bit) Mac OS X Windows 10 - Automatic installation of OS drivers. Other operating systems - manual driver installation. Firmware updates automatically.
Other features	
Colour	
Housing Material	
Product Dimensions	52 x 38 x 16 mm
Product Weight	39 g
Package Weight	122 g
Packaging Dimensions (LxWxH)	182 x 130 x 43 mm
Support	
Warranty period	2 years
Technical support	lifetime
Package contents	
USB 1.1 Serial adapter (55 cm)	
Driver CD	
User's Guide	

For further information regarding setup or for answers to FAQ's, please visit our website <u>i-tec.cz</u>. Specifications are subject to change without notice.

Updated 23.7.2018