



Overview

HP Z27n 27-inch Narrow Bezel IPS Display



- 1. Menu button
- **2.** Information
- 3. Input control

- 4. Color control
- 5. Luminance
- **6.** Power button/LED



- **1.** Master power switch
- 2. Power connector
- **3.** Audio output 3.5 mm
- 4. DVI-Dual Link
- **5.** HDMI v 1.4 input (MHL 2.0)

- 6. Mini-DisplayPort
- 7. DisplayPort v 1.2 in
- 8. DisplayPort v 1.2 out
- **9.** (4) USB 3.0 downstream ports (one fast charging)
- **10.** (1) USB 3.0 upstream port

Overview

Overview

Enable a virtually borderless Quad HD panorama of multiple displays¹ with the edge-to-edge screen of the HP Z27n 27-inch Narrow Bezel IPS Display.

Key features:

- Get Quad HD visuals from a three-sided borderless design that reveals more of the screen.
- Enjoy reliable color accuracy across all of your projects with a factory-calibrated 99% sRGB color gamut.
- Connect to multiple display¹ and devices with a range of integrated ports right at the display.
- Use picture-in-picture or picture-by-picture to boost your multi-tasking productivity.
- Work comfortably with customizable tilt, height adjustment, swivel, and pivot settings.
- Get world-class service and support, and extend your protection with optional HP Care Packs.²
- Reduce power consumption and help lower your costs with an energy-efficient design.
- Each display sold separately.
- Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



Technical Specifications

Models: K7C09A4, K7C09AT

Panel Type 27-inch IPS w/LED backlight

> Viewable Image Area 68,47 cm (27-inch) widescreen; diagonally measured

(diagonal)

Panel Active Area 59,67 x 33,56 cm (23.49 × 13.21 in)

(W × H)

Resolution 2560 x 1440 @ 60 Hz (QHD)

Aspect Ratio 16:9

Viewing Angle Up to 178° horizontal/178° vertical typical

Brightness 350 cd/m²

Contrast Ratio (Typical) 1000:1 Static; 5,000,000:1 Dynamic (DCR)

Response Times* 14 ms typical (G-to-G); 8ms with scalar overdrive

Pixel Pitch 0.2331 mm Pixels Per Inch (PPI) 108.8 DPI

Backlight Lamp Life 30,000 hours minimum

(to half brightness)

Color Gamut Up to 16.7 million colors with the use of FRC technology

Color Gamut (Typical) 99% sRGB

User Controls Buttons or Switches Menu, Information, Input Control, Color Control, Luminance 20

User Programmable

Modes

Languages 10 (English, Spanish, German, French, Italian, Netherlands,

Portuguese, Japanese, T-Chinese and S-Chinese)

Luminance, Color Control, Input Control, Image Control, PIP On Screen Display (OSD) User Controls Control, Power Control, OSD control, Management, Language,

Information

Audio Controls N/A

Signal Interface/ **Performance** **Horizontal Frequency** 30 - 90 kHz (DVI, DP, HDMI); 27 - 75 (MHL) Vertical Frequency 50 - 60 Hz (DVI, DP, HDMI); 24 - 60 (MHL)

Native Resolution 2560 x 1440 @ 60 Hz (QHD)

NOTE: The video card must be capable of supporting 2560 x 1440

@ 60 Hz to drive the monitor at the Preferred Mode.

Preset Graphic Modes 640 x 480 @ 60Hz (non-interlaced)

720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 800 @ 60 Hz

^{*} Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Technical Specifications

1280 x 1024 @ 60 Hz 1366 x 768 @ 60 Hz 1440 x 900 @ 60 Hz 1600 x 900 @ 60 Hz 1600 x 1200 @ 60 Hz 1680 x 1050 @ 60 Hz 1920 x 1080 @ 60 Hz 1920 x 1200 @ 60 Hz 2560 x 1440 @ 60 Hz

Maximum Pixel Clock

Speed

Anti-Glare

250 MHz(DVI, DP, HDMI); 150 MHz (MHL)

Video/Other Inputs Plug and Play Yes

Input/Output (1) DVI-Dual Link
Connectors (1) MHL 2.0¹/HDMI 1.4

Yes

(1) DisplayPort 1.2 In, (1) DisplayPort 1.2 Out

(1) Mini DisplayPort In HDCP support on all inputs

USB 4 USB 3.0 [4 downstream (one fast charging), 1 upstream]

Video Cables Included (1) DisplayPort 1,8 m (5.9 ft) (1) Mini-DisplayPort 1,8 m (5.9 ft)

(1) USB 3.0 **1,8 m** (5.9 ft)

Audio (1) 3.5 mm audio-out connects headphones or HP speaker bar*

*Sold separately.

Internal

Multimedia

Speakers N/A

Power Supply

Input Power 100 - 240 VAC 50/60 Hz

Maximum Power 83 W Typical Power 47 W

Sleep Power 0.5W (standby)
Power Cable Length 1,8 m (5.9 ft)

Mechanical

Dimensions (W × D × H)

Unpacked w/stand

61,43 x 21,82 x 53,37 cm 24.2 x 8.6 x 21.0 in

(max height)

61,43 x 21,82 x 40,37 cm 24.2 x 8.6 x 15.9 in

(min height)

Unpacked w/o stand 61,43 x 5,39 x 36,41 cm (head only) (24.2 x 2.1 x 14.3 in)

Packaged 73,1 x 28,5 x 47,9 cm

(28.8 x 11.2 x 18.9 in)

Weight Head Only 5,1 kg (11.16 lb)

 Unpacked
 7,66 kg (16.89 lb)

 Packaged
 10 kg (22.1 lb)

Technical Specifications

Ergonomic
FeaturesDetachable StandYes, ships detachedHeight Adjustment
Tilt RangeYes, 130 +/-3 mm5° to + 22° verticalSwivelYes, 45° +/-2°PivotYes, 90°

Quick Release⁵ HP QR2 quick release included

Environmental Temperature - 5° to 35° C (41° to 95° F) Operating

Temperature - Non- -20° to 60° C (-4° to 140° F)

operating
Humidity - Operating 20% to 80% non-condensing

Humidity - Non- 5% to 95%, 38.7° C max wet-bulb operating

Altitude – Non- 0 to 12,192 m (0 to 40,000 ft) **operating**

White LED Backlights Yes
CCFL Panel No
Arsenic-Free Display Yes

Glass

Low Halogen² Yes (except cables)

Mercury-Free Display Yes Backlighting



Environmental Data

| Eco-Label Certifications & declarations | This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: • IT ECO declaration • US ENERGY STAR® • TCO 6.0 • EPEAT® <gold> registered in the United States.</gold> | | | | | |
|---|--|--|--------------|-----------|--------|--|
| Energy Consumption (in accordance with US ENERGY STAR® test method) | 115VA | C, 60Hz | 230VAC, 50Hz | 100VAC, (| 50Hz | |
| Normal Operation | 28. | 2 W | 27.9 W | 28.4 V | ٧ | |
| Sleep | 0.5 W | | 0.5 W | | ٧ | |
| Off | 0. | 5 W | 0.4 W | 0.4 V | V | |
| Heat Dissipation* | 115VA | C, 60Hz | 230VAC, 50Hz | 100VAC, (| 50Hz | |
| Normal Operation | 96 B | TU/hr | 95 BTU/hr | 97 BTU | /hr | |
| Sleep | 2 BT | ΓU/hr | 2 BTU/hr | 2 BTU/ | hr hr | |
| Off | 2 B1 | ΓU/hr | 1 BTU/hr | 1 BTU/ | hr | |
| Additional Information | This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC. This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC. This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043. This product contains 37.5 % post-consumer recycled plastic (by wt.) This product is 97.6 % recycle-able when properly disposed of at end of life. | | | | | |
| Packaging Materials | External: | PAPER/Corrugated | | | 1308 g | |
| | Internal: | PLASTIC/EPS (Expanded Polystyrene) | | | 517 g | |
| | | PLASTIC/EPE-Expanded Polyethylene | | | 56.4 g | |
| RoHS Compliance | regulations, in Directive. HP's RoHS Directive eliminated (vir RoHS Directive | ckard is committed to compliance with all applicable environmental laws and including the European Union Restriction of Hazardous Substances (RoHS) P's goal is to exceed compliance obligations by meeting the requirements of the ive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually virtually = to levels below legal limits) for all HP electronic products subject to the ive, except where it is widely recognized that there is no technically feasible (as indicated by an exemption under the EU RoHS Directive). | | | | |



| Environmental Data | | | | |
|---|--|--|--|--|
| Material Usage | This product does not contain any of the following substances in excess of regulatory limits: - Asbestos - Certain Azo Colorants - Certain Brominated Flame Retardants – may not be used as flame retardants in plastics - Cadmium - Chlorinated Hydrocarbons - Chlorinated Paraffins - Formaldehyde - Halogenated Diphenyl Methanes - Lead carbonates and sulfates - Lead and Lead compounds - Mercuric Oxide Batteries - Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user Ozone Depleting Substances - Polybrominated Biphenyl Ethers (PBBEs) - Polybrominated Biphenyl Ethers (PBBEs) - Polybrominated Biphenyl Oxides (PBBOs) - Polychlorinated Biphenyl (PCB) - Polychlorinated Terphenyls (PCT) - Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications Radioactive Substances - Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO) | | | |
| Packaging | HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards. | | | |
| End-of-life Management and Recycling | Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. These instructions may be used by recycless and other WEEE treatment facilities as well as HP OEM customers who integrate and | | | |

re-sell HP equipment.

recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and



Environmental Data

| Options | HP LCD Speaker B Part number NQ57 | | Powered directly by the connected PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and dual external headphone jacks. Sold separately. For more information, refer to the product's QuickSpecs. | | |
|--|---|------------|--|--|--|
| | HP Single Monitor Arm—Part number BT861AA | | The flexible design of the HP Single Monitor Arm provides a seemingly endless range of display adjustments with an amazing 13 inches of lift, 75 degrees of tilt, and 360 degrees of pan and rotation – all at your fingertips helping you stay comfortable and productive throughout the day. | | |
| | HP DisplayPort Cable Kit —Part number VN567AA | | Connects a DisplayPort connector on an HP Business Desktop computer to a DisplayPort connector on a monitor | | |
| HP Quick Release Bracket— Part numb EM870AA ⁵ | | mber | An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document. | | |
| | HP Business PC Security Lock Kit — Part number PV606AA | | Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point. | | |
| What's in the box? | Monitor and Accessories Documentation | | HP Z27n 27-inch Narrow Bezel IPS Display, AC power cord (1.8m) 5.9 ft, DisplayPort cable 1,8 m (5.9 ft), Mini-DisplayPort cable 1,8 m (5.9 ft), USB 3.0 cable 1,8 m (5.9 ft) CD (includes user guide, warranty, drivers) | | |
| | Software | | HP Display Assistant | | |
| Other | User Guide Languages | German, Gr | rabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, reek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish. | | |
| | German, G | | abic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, reek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, ortuguese, Russian, Slovenian, Spanish, Swedish and Turkish. | | |
| | Color | Black | | | |

VESA Mounting 100 mm VESA mount

Security Lock-Ready Yes
Country of Origin China

Certification and Compliance

TCO Certified, CEL Grade 2, ENERGY STAR® Qualified, EPEAT® Gold³, CB; TUV/GS; TUV/Ergo; TUV-S; UL; TCO Edge; CCC; CECP; CEL; SEPA; BSMI; CE; FCC(Canada); BSMI; KC; VCCI; C-Tick; Microsoft WHQL Certification (Windows 8.1 and Windows 7); SmartWay Transport Partnership (NA)

Compatibility Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.

Environmental Data

Service and Warranty Protected by HP, including a 3 year standard limited warranty. Optional HP Care Pack Services are extended service contracts that extend your protection beyond the standard warranties.4

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR® and the ENERGY STAR® mark are registered trademarks of the U.S. Environmental Protection Agency.

- 1. MHL 2.0 port will charge a MHL compatible smart phone and tablet battery. Requires the smart phone or tablet to be enabled for MHL or have an HDMI dongle to connect to the monitor. See your mobile device specifications.
- 2. Power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
- 3. EPEAT® registered where applicable. EPEAT® registration varies by country.
- 4. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply.
- 5. The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

