



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUMNV20HV2

**Single-Phase Monitored PDU, 20A 200-240V, 0U 35.5 in. Vertical Rackmount, C13 & C19 outlets, C20 inlet and NEMA L6-20P cable**



### Highlights

- Monitored 16/20A 200-240V PDU; 0U 35.5 in / 90.2cm vertical rackmount
- Reports voltage, frequency & loading information via ethernet interface
- Visual current meter; Toolless button-mount installation
- C20 inlet; 10ft / 3m L6-20P power cable included
- 20 outlets (18 C13 & 2 C19); cord retention brackets included
- Temperature, humidity and contact-closure monitoring options

### Description

Tripp Lite Monitored PDU / Power Distribution Unit offers real-time remote monitoring of voltage, frequency and load levels via built-in network connection. PowerAlert interface supports custom notification of user-specified remote conditions via email, secure web, SNMP, Telnet or SSH interface. PDU output current consumption in amps is displayed via front panel lighted digital display and can be monitored remotely to warn of potential overloads before critical IT mains breakers trip.

#### Applications

- Ideal for network configurations requiring a monitored PDU system

#### Package Includes

- Rackmount PDU
- Plug retention plates
- Rack mounting brackets
- Owner's manual

### Features

- 200/208/230/240V Monitored PDU with built-in web/network interface in 0U 35.5 in. / 90.2cm rackmount form factor; 20A maximum capacity (agency de-rated to 16A)
- C20 inlet supports user supplied input cabling; 10ft / 3m L6-20P power cord included
- 20 outlets (18 C13 & 2 C19)
- 0U 35.5in / 90.2cm vertical rackmount form factor
- Network interface provides PDU control and data regarding input voltage, frequency and loading information
- Digital display reports load level information in amps
- Supports user-specified alarm notification thresholds
- In-rack environmental reporting with optional ENVIROSENSE temperature / humidity sensor and rack access notification with up to 4 optional SRSWITCH door sensors
- DHCP/Manual configuration support
- 10/100 Mbps auto-sensing
- Real-time clock backup maintains the time of day and date even if the PDU is unpowered
- Tiered access privileges allow an administrator and a guest to login via web browser
- Alert notifications via email or SNMP traps offer immediate event notification
- Firmware upgrade ability supports future product enhancements

- Supports HTTP, HTTPS, PowerAlert Network Management System, SMTP, SNMPv1, SNMPv2, Telnet, SSH, FTP, DHCP, BOOTP, NTP protocols
- Fully compatible with FREE PowerAlert Network Management System / NMS Software
- Included cord retention brackets
- Toolless mounting supported in button-mount compatible racks, plus nut-and-bolt mounting brackets for other mounting applications

## Specifications

OVERVIEW	
PDU Type	Monitored
OUTPUT	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	200/208/230/240V
Outlet quantity / type	18 C13, 2 C19
INPUT	
PDU Input Voltage	200; 208; 230; 240
Maximum Input Amps (A)	20
Input connection type	C20 inlet accepts included L6-20P input cable. Alternate C19 input cordsets supported.
PDU Plug Type	NEMA L6-20P; IEC-320 C20
Input cord length (ft.)	10
Input cord length (m)	3
Phase	Single-Phase
LEDS ALARMS & SWITCHES	
Front panel LEDs	Front panel digital display confirms power availability and PDU output current level in 1 amp increments
PHYSICAL	
Shipping weight (lbs)	6.5
Shipping weight (kg)	3
Unit Dimensions (HWD/in)	35.5 x 2.2 x 1.85
Unit Dimensions (HWD/cm)	90.2 X 5.6 X 4.7
Shipping Dimensions (HWD/in)	42.8 x 4 x 6
Shipping Dimensions (HWD/cm)	108.7 x 10.2 x 15.2
Unit weight (lbs)	6.5
Unit weight (kg)	3
Style	Vertical Rackmount
Form factors supported	0U vertical rackmount installation supported with included mounting brackets; supports toolless mounting in button-mount compatible racks
PDU Form Factor	Vertical (0U)
ENVIRONMENTAL	

<b>Relative Humidity</b>	0-95% non-condensing
<b>COMMUNICATIONS</b>	
<b>SNMP compatibility</b>	Pre-installed <a href="#">SNMPWEBCARD</a> provides remote monitoring via web, Telnet, and SNMP management systems
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL 60950-1 (USA, Canada), CE (International), Class A (Emissions), NOM (Mexico), RoHS compliant
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	2-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">WEXT3-PDU-MN</a>	3-Year Extended Warranty - For MN Monitored PDUs	1
<a href="#">WEXT5-PDU-MN</a>	5-Year Extended Warranty - For MN Monitored PDUs	1
<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires UPS with SNMPWEBCARD, monitored PDU or switched PDU.)	1
<a href="#">SRSWITCH</a>	Magnetic Door Switch Kit for front and rear doors; requires ENVIROSENSE	1
<a href="#">P004-002-13LA</a>	AC Power Extension Cable - C13 Left Angle to C14 - 2'	1
<a href="#">P004-002-13RA</a>	AC Power Extension Cable - C13 Right Angle to C14 - 2 ft.	1
<a href="#">P005-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
<a href="#">P005-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
<a href="#">P036-002-19LA</a>	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 Left Angle to IEC-320-C20)	1
<a href="#">P036-002-19RA</a>	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 Right Angle to IEC-320-C20)	1
<a href="#">P036-006</a>	6-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20)	1
<a href="#">P052-008</a>	8-ft. Power cord (IEC-320-C19 to BS1363 UK Plug)	1
<a href="#">P050-008</a>	8-ft. Power cord (IEC-320-C19 to CEE 7/7 SCHUKO)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=5058](http://www.tripplite.com/en/products/model.cfm?txtModelID=5058).

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.