

Spec Sheet

Conference Table Connectivity Box – HDMI / VGA / Mini DisplayPort to HDMI Output with Fast Charge USB Port

StarTech ID: BOX4HDECP



The BOX4HDECP Automatic Conference Table Connectivity Box features a concealed, in-table design that lets you connect a VGA, Mini DisplayPort, HDMI or composite video source device to an HDMI display or projector. When the video switch isn't in use, you can simply slide the stylish cover panel over the connectors, hiding them inside the table or podium surface.

Convenient Accessibility

Presenters can conveniently share content from their own device with the table top switch automatically converting any attached audio/video source device source into a single HDMI output. The switch box also offers stylish integration into your modern boardroom or classroom with a discreet hideaway panel. For added convenience the BOX4HDECP features a USB charging port to charge your mobile device and an Ethernet pass-through port for Internet connectivity in boardrooms where WiFi is not available.

Connectivity Options

With support for different video inputs including: HDMI, VGA, Mini DisplayPort, and composite, the video switch ensures support for almost any laptop, Ultrabook[™] or mobile device such as MacBook[®], Microsoft[®] Surface[™] Pro 2 & 3, and Lenovo X1[™]. The switch panel even works with legacy audio/video devices such as DVD player, and supports the use of video adapters for your iPhone[®] or iPad[®].

Collaborate Easily

The A/V switch makes your large display accessible to any presenter's video source device, by installing directly into the surface of your table or podium, and automatically outputs the most recently connected video source. Plus, support for high-definition video resolutions up to 1920x1080 (1080p) ensures the quality of your presentation is maintained.

www.startech.com 1 800 265 1844



Spec Sheet

The BOX4HDECP is backed by a StarTech.com 2-year warranty, and free lifetime technical support.

Applications

- Build directly into a boardroom table for video presentations and video conferencing
- Build into a podium, for live presentation control
- Connect your device to a projector or large display and switch from one computer to another, or to a mobile device automatically, to collaborate during a boardroom meeting
- Use in a boardroom or classroom where a projector or display may not have the required connectivity ports
- Hide your unsightly cables and switch box by building directly into your table or podium

Features

- Concealed table installation clears boardroom cable clutter
- Enable boardroom connection compatibility with laptops and Ultrabooks
- Single cable connection to your HDMI Display
- In-table installation
- Automatic audio / video switching
- Hideaway panel
- Supports VGA, HDMI, mDP and composite audio / video sources
- Built-in USB charging port
- Ethernet pass through port for network connectivity
- Supports video resolutions up to 1080p

www.startech.com 1 800 265 1844



Hard-to-find made easy*

Technical Specifications

Warranty	2 Years
Ports	4
Audio	Yes
USB Pass-Through	No
Output Signal	HDMI
Connector A	1 - HDMI (19 pin) Female
Connector B	1 - HDMI (19 pin) Male
Connector A	1 - VGA (15 pin; High Density D-Sub) Female
Connector A	1 - 3.5 mm Mini-Jack (3 Position) Female
Connector B	1 - RJ-45 Female
Connector A	1 - Composite Video (1 x RCA) Female
Connector A	1 - RJ-45 Female
Connector A	1 - USB A (4 pin) Female
Connector A	1 - Mini-DisplayPort (20 pin) Female
Connector A	1 - Stereo Audio (2 x RCA) Female
Maximum Analog Resolution	s 1920x1080
Maximum Digital Resolutions	i 1920x1080
Supported Resolutions	1920x1080 (1080p)
• •	
Wide Screen Supported	Yes
	Yes 7.1 Surround sound (HDMI, Mini DisplayPort)
Wide Screen Supported Audio Specifications	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA)
Wide Screen Supported Audio Specifications Product Length	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm]
Wide Screen Supported Audio Specifications Product Length Product Width	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm]
Wide Screen Supported Audio Specifications Product Length Product Width Product Height	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm]
Wide Screen Supported Audio Specifications Product Length Product Width Product Height Product Weight	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g]
Wide Screen Supported Audio Specifications Product Length Product Width Product Height Product Weight Input Voltage	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC
Wide Screen Supported Audio Specifications Product Length Product Width Product Height Product Weight Input Voltage Output Voltage	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC 12 DC
Wide Screen Supported Audio Specifications Product Length Product Width Product Height Product Weight Input Voltage Output Voltage Output Current	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC 12 DC 2A
Wide Screen Supported Audio Specifications Product Length Product Width Product Height Product Weight Input Voltage Output Voltage Output Current Operating Temperature	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC 12 DC 2A 0°C to 40°C (32°F to 104°F)
Wide Screen Supported Audio Specifications Product Length Product Width Product Height Product Height Input Voltage Output Voltage Output Voltage Output Current Operating Temperature Storage Temperature	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC 12 DC 2A 0° C to 40° C (32° F to 104° F) - 20° C to 60° C (-4° F to 140° F)
Wide Screen Supported Audio Specifications Product Length Product Width Product Weight Input Voltage Output Voltage Output Voltage Output Current Operating Temperature Storage Temperature Humidity	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5 mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC 12 DC 2A 0°C to 40°C (32° F to 104°F) -20°C to 60°C (-4°F to 140°F) 10% to 85% (Non-condensing)
 Wide Screen Supported Audio Specifications Product Length Product Width Product Weight Product Weight Input Voltage Output Voltage Output Current Operating Temperature Storage Temperature Humidity Shipping (Package) Weight 	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC 12 DC 2A 0°C to 40°C ($32^{\circ}F$ to $104^{\circ}F$) -20°C to 60°C ($-4^{\circ}F$ to $140^{\circ}F$) 10% to 85% (Non-condensing) 3.7 lb [1.7 kg]
Wide Screen Supported Audio Specifications Product Length Product Width Product Weight Input Voltage Output Voltage Output Voltage Output Current Operating Temperature Storage Temperature Humidity	Yes 7.1 Surround sound (HDMI, Mini DisplayPort) 2-Channel Stereo (3.5 mm, RCA) 6.7 in [170 mm] 3.9 in [100 mm] 3.9 in [100 mm] 58.6 oz [1661 g] 100 ~ 240 AC 12 DC 2A 0°C to 40°C (32° F to 104°F) -20°C to 60°C (-4°F to 140°F) 10% to 85% (Non-condensing)

www.startech.com 1 800 265 1844



Hard-to-find made easy*

Spec Sheet

Included in Package Included in Package 1 - DieCut Outline

1 - Instruction Manual

Certifications, Reports and Compatibility





www.startech.com 1 800 265 1844