


Overview

**HP recommends
Windows Vista® Business**


Microtower



1. (2) 5.25" external bays and (2) 3.5" internal bays
2. (1) 3.5" external bay for optional HP 16-in-1 Media Card Reader, diskette drive, or other 3.5" device
3. 300-watt power supply
Optional: 85% efficient energy saving power supply
4. Rear I/O: (6) USB 2.0, (1) standard serial port, (1) optional serial port, (1) optional parallel port, (2) PS/2, (1) RJ-45, (1) VGA, (1) audio in, (1) audio out
5. (1) full-height PCI slot, (2) full-height PCIe x1 slots, (1) full-height PCIe x16 (ADD2/SDVO) slot
6. Front I/O: (2) USB 2.0, headphone and microphone, Dual Colour Diagnostic LEDs
7. 2-Button Scroll Mouse (PS/2, Optical Scroll Mouse (PS/2 or USB), or USB Laser Mouse
8. HP Standard Keyboard (PS/2 or USB) or HP USB Smartcard Keyboard
9. Monitor (sold separately)

Overview

Small Form Factor



1. (1) 3.5" external bay for optional HP 16-in-1 Media Card Reader, diskette drive, or other 3.5" device; (1) 3.5" internal bay
2. (1) 5.25" external bay for optional optical drive, or other 5.25" device (bay tilts up for device removal and insertion)
3. 240-watt power supply
Optional: 85% efficient energy saving power supply
4. Rear I/O: (6) USB 2.0, (1) standard serial port, (1) optional serial port, (1) optional parallel port, (2) PS/2, (1) RJ-45, (1) VGA, audio in/out
5. (1) low profile PCI slot, (2) low profile PCIe x1 slots, (1) low profile PCIe x16 (SDVO/ADD2) slot
6. Front I/O: (2) USB 2.0, headphone and microphone, Dual Colour Diagnostic LEDs
7. 2-Button Scroll Mouse (PS/2), Optical Scroll Mouse (PS/2 or USB), or USB Laser Mouse
8. HP Standard Keyboard (PS/2 or USB) or HP USB Smartcard Keyboard
9. Monitor (sold separately)

Overview

At A Glance


- The HP Compaq dc5800 offers a stable solution with mainstream features and flexibility that exceed basic business requirements
- Intel® Q33 Express chipset, Intel Core™ 2 Duo processors, Intel Core 2 Quad processors, and Intel Graphics Media Accelerator 3100 integrated graphics
- Embedded TPM1.2 compliant security module* (Vista Bit-Locker ready)
- Support for up to 500-GB SATA 3.0Gb/s Smart IV hard drives
- Value-added software on select models
 - HP Total Care Advisor
 - HP Backup and Recovery Manager
 - HP Software Agent
 - Altiris Deployment Solution Agent
 - McAfee Anti-Virus with 60 day Live Update Subscription
 - HP Insight Diagnostics software
 - Microsoft Office 2007
 - Verdiem Surveyor remote power management agent
 - PDF Complete
 - Computrace for Desktops (select countries)
- Value-added software available for free download from the Web (<http://www.hp.com/go/easydeploy>)
- HP Client Automation – Starter Edition
- HP Client Manager for Altiris
- Altiris Out-of-Band Management Solution
- HP SoftPaq Download Manager
- HP System Software Manager
- HP Client Catalog for Microsoft SMS
- Verdiem Surveyor remote power management agent
- Fully compatible software OS image across all models (Microtower, Small Form Factor)
- HP BIOS for security, manageability and software image stability
- Standard 3-years parts, 3-years labour, and 3-years on-site warranty services (terms and conditions vary by country; certain restrictions and exclusions apply)
- HP Insight Diagnostics software
- Selected configurations with global availability easily set up and ordered through HP.com Business to Business portals (<http://h10019.www1.hp.com/business-site/index.html>)
- Tailored HP Factory Express deployment and lifecycle services available (<http://h71028.www7.hp.com/enterprise/cache/97688-0-0-225-121.aspx>)

*TPM module disabled where use is restricted by law; for example, Russia.

Configurable Components - Select Models (localized by Regions)

Model Key and Example

NOTE: This diagram is an example that illustrates how to read the model number. It is not intended to give every available configuration choice specified in the body of this document and may include references to modules that are out of date and no longer available.



Standard Features and Configurable Components

Operating System –
One of the following

Preinstalled

Genuine Windows Vista Business 32*
Genuine Windows Vista Business 64*
Genuine Windows Vista Home Basic 32*
Genuine Windows Vista Ultimate 32*
Genuine Windows Vista Business 32 downgrade to
Genuine Windows XP Professional 32+
FreeDOS†

Certified

Red Hat Enterprise Linux
SUSE Linux Enterprise Desktop 10

* Certain Windows Vista product features require advanced or additional hardware. See <http://www.microsoft.com/windowsvista/getready/hardwarereqs.msp> and <http://www.microsoft.com/windowsvista/getready/capable.msp> for details. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit <http://www.windowsvista.com/upgradeadvisor>.

+ Windows Vista Business disk also included for future upgrade if desired. To qualify for this downgrade an end user must be a business (including governmental or educational institutions) and is expected to order annually at least 25 customer systems with the same custom image.

† The following features are not supported by Linux:

- HP 16-in-1 Media Card Reader with PCI Card
- Integrated 1.2 TPM Embedded Security Chip
- Intel PRO/1000 PT PCIe Gigabit NIC
- Intel VT-x
- Broadcom NetXtreme Gigabit Ethernet PCIe NIC Card
- Wireless A+G PCI Card (full height bracket and low profile bracket)
- HP BT450 USB Bluetooth Wireless Printer and PC Adapter
- 2006 Agere PCI 56K International SoftModem (full height and low profile)
- HP ADD2 SDVO PCIe DVI-D adapter
- NVIDIA Quadro NVS 290 256MB DH PCIe x16 Graphics Card
- NVIDIA GeForce 8400 GS 256MB DH PCIe x1 Graphics Card
- NVIDIA GeForce 8400 GS 256MB SH PCIe x16 Graphics Card
- ATI Radeon HD 2400 XT 256MB DH PCIe x16 Graphics Card
- HP FireWire / IEEE 1394 PCI Card (full height and low profile)
- 2nd serial port adapter (including low profile)
- 1-GB Flash Module for Vista ReadyBoost
- HP USB Smartcard Keyboard

Standard Features and Configurable Components

Value-added Software (on select models; not included with FreeDOS)

HP Software Agent
Altiris Out-of-Band Management Solution
HP Insight Diagnostics (available via HP Backup and Recovery Manager)
Computer Setup Utility
HP Backup and Recovery Manager

McAfee Total Protection Anti-Virus with 60 day trial Subscription
Sonic/Roxio DigitalMedia Plus 7.2 (select models)
or
Easy Media Creator 9 (select models)

HP Total Care Advisor
Microsoft Office 2007 Basic
Microsoft Office 2007 Personal
Microsoft Office 2007 Professional
Microsoft Office 2007 Small Business
Microsoft Works 8.5
Microsoft Internet Explorer with AOL Toolbar
PDF Complete
CompuTrace for Desktops (select countries)
Verdiem Surveyor agent
InterVideo WinDVD 5.0 (select models)
Firefox-HP Virtual Browser

Value-added Software (available for free download from the Web <http://www.hp.com/go/easydeploy>)

HP Client Automation – Starter Edition
HP Client Manager for Altiris
HP SoftPaq Download Manager

HP Client Catalog for Microsoft SMS
HP Systems Software Manager
Verdiem Surveyor agent

Value-added Services and Features

HP Stable Platform Program
Business-to-Business Portals
HP Global Series Services

Factory Express Deployment and Lifecycle Services
TPM 1.2 Security chip*

* TPM module disabled where use is restricted by law; for example, Russia.

Service and Support

On-site Warranty and Service¹ This three-year (3-3-3), limited warranty and service offering delivers three years of parts, labour and on-site repair. Response time is next business-day² and includes free telephone support³ 24 x 7. Global coverage² ensures that any product purchased in one country and transferred to another non-restricted country will remain fully covered under the original warranty and service offering. Some countries/regions do not offer one year onsite and labour. For HP Care Pack services see <http://www.hp.com/go/lookuptool>.

¹Terms and conditions may vary by country. Certain restrictions and exclusions apply.

²On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.

³Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

Standard Features and Configurable Components

	Microtower	Small Form Factor		
Chassis Dimensions (H x W x D)	14.85 x 6.95 x 16.85 in (37.72 x 17.65 x 42.80 cm)	3.95 x 13.3 x 14.9 in (10.03 x 33.78 x 37.85 cm)		
Optional Tower Stand Dimensions (H x W x D)	N/A	1.05 x 6.95 x 7.83 in (26.75 x 176.46 x 198.87 mm)		
System weight*	19.75 lb (8.96 kg)	17.86 lb (8.10 kg)		
System volume	1739 cu in	941.63 cu in		
Shipping weight*	28.79 lb (13.06 kg)	26.70 lb (12.11 kg)		
Maximum supported weight (desktop orientation)	77.1 lb (35 kg)	77.1 lb (35 kg)		
Shipping box dimensions (H x W x D)	12.0 x 19.76 x 23.62 in	9.72 x 19.68 x 22.67 in		
<i>* Configured with 1 hard drive, 1 optical drive, no diskette drive, and no PCI card.</i>				
Power Supply	300W power supply – passive PFC	240W power supply – active PFC		
Energy Efficient Power Supply	300W 85% efficient power supply – active PFC	240W 85% efficient power supply – active PFC		
Ports				
USB 2.0	8 (2 front, 6 rear)			
Serial	1 standard with 2 nd optional			
Parallel	1 optional			
PS/2	1 keyboard, 1 mouse			
Video	analog for integrated graphics			
DVI output	available via ADD2 card in PCIe x16 connector			
Support for Multi-Monitor	available via ADD2 card in PCIe x16 connector or via PCIe graphics cards			
Audio	Integrated High Definition audio with internal speaker Front – mic and headphone Rear – input (supports microphone or line input), line out			
NIC (RJ-45)	Integrated Intel 82566DM Gigabit Network Connection Ethernet			
			MT	SFF
Chipset	Intel Q33 Express chipset		X	X

Standard Features and Configurable Components

Processor and Speed* One of the following	Intel Celeron Processors:		
	Intel Celeron 430 Processor (1.8-GHz, 512K L2 cache, 800-MHz FSB)	X	X
	Intel Celeron 450 Processor (2.2-GHz, 512K L2 cache, 800-MHz FSB)	X	X
	Intel Celeron Dual-Core Processors		
	Intel Celeron E1200 Processor (1.6-GHz, 512K L2 cache, 800-MHz FSB)	X	X
	Intel Celeron E1400 Processor (2.0-GHz, 512K L2 cache, 800-MHz FSB)	X	X
	Intel Celeron E1500 Processor (2.2-GHz, 512K L2 cache, 800-MHz FSB)	X	X
	Intel Pentium Dual-Core Processors:		
	Intel Pentium E2180 Processor (2.0-GHz, 1-MB L2 cache, 800-MHz FSB)	X	X
	Intel Pentium E2200 Processor (2.2-GHz, 1-MB L2 cache, 800-MHz FSB)	X	X
	Intel Pentium E2220 Processor (2.4-GHz, 1-MB L2 cache, 800-MHz FSB)	X	X
	Intel Pentium dual-core E5300 Processor (2.6-GHz, 2MB L2 cache, 800-MHz FSB)	X	X
	Intel Pentium Dual Core E5400 Processor (2.70-GHz, 2MB L2 cache, 800-MHz FSB)	X	X
	Intel Core 2 Duo Processors:		
	Intel Core 2 Duo E4600 Processor (2.40-GHz, 2 MB L2 cache, 800-MHz FSB)	X	X
	Intel Core 2 Duo E6550 Processor (2.33-GHz, 4 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Duo E6750 Processor (2.66-GHz, 4 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Duo E7200 Processor (2.53-GHz, 3 MB L2 cache, 1066-MHz FSB)	X	X
	Intel Core 2 Duo E7300 Processor (2.66-GHz, 3 MB L2 cache, 1066-MHz FSB)	X	X
	Intel Core 2 Duo E7400 Processor (2.80-GHz, 3 MB L2 cache, 1066-MHz FSB)	X	X
	Intel Core 2 Duo E7500 Processor (2.93-GHz, 3 MB L2 cache, 1066-MHz FSB)	X	X
	Intel Core 2 Duo E8300 Processor (2.83-GHz, 6 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Duo E8400 Processor (3.0-GHz, 6 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Duo E8500 Processor (3.16-GHz, 6 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Duo E8600 Processor (3.33-GHz, 6 MB L2 Cache, 1333-MHz FSB)	X	X
	Intel Core 2 Quad Processors:		
	Intel Core 2 Quad Q6700 Processor (2.66-GHz, 8 MB L2 cache, 1066-MHz FSB)	X	X
	Intel Core 2 Quad Q8200 Processor (2.33-GHz, 4 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Quad Q8300 Processor (2.50-GHz, 4 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Quad Q9300 Processor (2.50-GHz, 6 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Quad Q9400 Processor (2.66-GHz, 6 MB L2 cache, 1333-MHz FSB)	X	X
	Intel Core 2 Quad Q9650 Processor (3.0-GHz, 12 MB L2 cache, 1333-MHz FSB)	X	X

* Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families.

Standard Features and Configurable Components

Memory

DDR2 SYNCH DRAM NON-ECC MEMORY

Memory upgrades are accomplished by adding single or multiple DIMMs of the same or varied sizes. This chart does not represent all possible memory configurations. The Intel Q33 Express chipset supports non-ECC DDR2 PC2-6400 (800-MHz) memory.

CAUTION: You must shut down the computer and disconnect the power cord before adding or removing memory modules. Regardless of the power-on state, voltage is always supplied to the memory modules as long as the computer is plugged in to an active AC outlet. Adding or removing memory modules while voltage is present may cause irreparable damage to the memory modules or system board.

HP recommends dual-channel symmetric configurations for maximum performance.

For best performance, add the same amount of total memory to each channel and do not mix speeds. For dual-channel symmetric performance, the total amount of memory in each channel must be equal. If speeds are mixed, speed will default to the slowest DIMM.

Microtower and Small Form Factor

Maximum Memory*

Supports up to 16-GB of DDR2 SYNCH DRAM. *Slot 1 is black and must always be populated. Not all memory configurations possible are represented below.*

NOTE: For systems configured with more than 3 GB of memory and a 32-bit operating system, all memory may not be available due to system resource requirements. Addressing memory above 4 GB requires a 64-bit operating system.

DIMM Size	Slot			
	Channel A		Channel B	
	1 (black)	2 (white)	3 (black)	4 (white)
512-MB	512-MB			
1-GB	1-GB			
1-GB (dual-channel symmetric)	512-MB		512-MB	
2-GB (dual-channel symmetric)	1-GB		1-GB	
2-GB (dual-channel symmetric)	512-MB	512-MB	512-MB	512-MB
3-GB (dual-channel symmetric)	1-GB	512-MB	1-GB	512-MB
4-GB (dual-channel symmetric)	1-GB	1-GB	1-GB	1-GB
8-GB (dual-channel symmetric)	2-GB	2-GB	2-GB	2-GB
16-GB (dual-channel symmetric)	4-GB	4-GB	4-GB	4-GB

* The Intel Q33 Express chipset includes a built-in Management Engine (ME), which allocates memory for manageability functions. Management Engine memory is shared with system memory. If the PC contains a single DIMM, 16 MB of memory is pre-allocated for it at system startup. If the PC contains two DIMMs, 32 MB of memory is pre-allocated. This memory is not made available to the operating system, just as pre-allocated video memory is not available.

Standard Features and Configurable Components


		MT	SFF
Memory Configurations	512-MB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (1 x 512)	X	X
One of the following	1-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (1 x 1GB)	X	X
	1-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (2 x 512)	X	X
	2-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (1 x 2GB)	X	X
	2-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (2 x 1GB)	X	X
	2-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (4 x 512)	X	X
	3-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (3 x 1GB)	X	X
	4-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (4 x 1GB)	X	X
	4-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (2 x 2GB)	X	X
	8-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (4 x 2GB)	X	X
	16-GB DDR2 Synch Dram PC2-6400 (800-MHz) Non ECC (4 x 4GB)	X	X

Expandability	Microtower	Small Form Factor
PCI slots	1 full-height	1 low-profile
Max power per slot	35W	35W
PCIe x1 slot	2	2
Max power per slot	10W	10W
PCIe x16 slot (also functions as SDVO/ADD2 slot)	1 full-height	1 low-profile
Max power per slot	60W	25W
External Bays		
3.5"	1	1
5.25"	2	1
IDE		
Internal 3.5" HDD Bays	2	1
Hard Drive Controller (SATA) Supported	SATA	SATA
Hard Drive Interfaces Supported	SATA 3.0Gb/s	SATA 3.0Gb/s


QuickSpecs

Standard Features and Configurable Components

Microtower



Small Form Factor



Storage – Drive Support

	Microtower			Small Form Factor		
	Media Card Reader or Diskette Drive (optional)	5.25" Serial ATA Devices	3.5" Serial ATA Devices	Media Card Reader or Diskette Drive (optional)	5.25" Serial ATA Devices	3.5" Serial ATA Devices
Quantity Supported	1	2	2	1	1	2
Position Supported	3	1, 2	3, 4, 5	2	1	2, 3
Controller	USB/Diskette	SATA	SATA	USB/Diskette	SATA	SATA

Standard Features and Configurable Components

		MT	SFF
Hard Drive	80-GB SATA 3.0-Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
One or two of the following	160-GB SATA 3.0-Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	250-GB SATA 3.0-Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	320-GB SATA 3.0-Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	500-GB SATA 3.0-Gb/s Hard Drive (16MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	80-GB SATA 3.0-Gb/s Hard Drive (16MB Cache, 10,000 RPM, NCQ, Smart III)	X	X
	160-GB SATA 3.0-Gb/s Hard Drive (16MB Cache, 10,000 RPM, NCQ, Smart III)	X	X
	3.5" Removable 80-GB SATA 3.0 Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	3.5" Removable 160-GB SATA 3.0 Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	3.5" Removable 250-GB SATA 3.0 Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	2 nd hard drive, 80-GB SATA 3.0-Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	2 nd hard drive, 250-GB SATA 3.0-Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	2 nd hard drive, 320-GB SATA 3.0-Gb/s Hard Drive (8MB Cache, 7200 RPM, NCQ, Smart IV)	X	X
	2 nd hard drive, 500-GB SATA 3.0-Gb/s Hard Drive (16MB Cache, 7200 RPM, NCQ, Smart IV)	X	
	2 nd hard drive, 80-GB SATA 3.0-Gb/s Hard Drive (16MB Cache, 10,000 RPM, NCQ, Smart III)	X	X
	2 nd hard drive, 160-GB SATA 3.0-Gb/s Hard Drive (16MB Cache, 10,000 RPM, NCQ, Smart III)	X	X

NOTE: NCQ functionality requires a user set-up BIOS setting.

Removable Storage – One or more of the following depending on form factor (see Storage – Drive Support section above)	Diskette Drives		
	1.44-MB Diskette Drive	X	X
	Media Reader		
	HP 16-in-1 Media Reader (USB connection on the system board)	X	X
	Optical Drives		
	SATA DVD-ROM Drive ¹	X	X
	SATA CD-RW/DVD-ROM Combo Drive ^{1,2}	X	X
SATA SuperMulti LightScribe DVD Writer Drive ^{1,2,3}	X	X	
¹ For playing DVDs, InterVideo WinDVD 5			
² For writing CDs, choice of Sonic/Roxio DigitalMedia Plus 7.2 (Windows XP only) or Easy Media Creator 9			
³ For writing CDs and DVDs, video editing and authoring DVDs, choice of Sonic/Roxio DigitalMedia Plus 7.2 (Windows XP only) or Easy Media Creator 9			

Standard Features and Configurable Components

Media Card Reader – One of the following	HP 16-in-1 3.5" Media Card Reader	X	X
	HP 22-in-1 3.5" Media Card Reader	X	X
	HP 22-in1 3.5" Media Card Reader with 1394	X	X
<hr/>			
Security	Integrated 1.2 TPM Embedded Security Chip*	X	X
	HP Desktop Security lock kit (lock and cable)	X	X
	Security cable with Kensington lock	X	X
	Optional HP ProtectTools security software suite	X	X
	Optional USB Port Disable at factory (user configurable via BIOS)	X	X
* TPM module disabled where use is restricted by law; for example, Russia.			
<hr/>			
NIC	Intel 82566DM Gigabit Network Connection (integrated on system board)	X	X
	Broadcom NetXtreme Gigabit Ethernet PCIe NIC Card	X	X
	Broadcom NetXtreme Gigabit Ethernet Plus PCIe NIC Card	X	X
	Intel Gigabit CT Desktop NIC	X	X
	Intel PRO/1000 PT PCIe Gigabit NIC	X	X
<hr/>			
Wireless	Wireless A+G PCI Card (full height bracket)	X	
	Wireless A+G PCI Card (low profile bracket)		X
	HP 802.11 b/g/n Wireless PCIe x1 card (full height bracket)	X	
	HP 802.11 b/g/n Wireless PCIe x1 card (low profile bracket)		X
<hr/>			
Modem	2006 Agere PCI 56K International SoftModem (full height)	X	
	2006 Agere PCI 56K International SoftModem (low profile)		X
	LSI PCIe x1 Hi-Speed 56K International SoftModem	X	X

Standard Features and Configurable Components

Graphics	Integrated Intel Graphics Media Accelerator 3100	X	X
	HP ADD2 SDVO PCIe DVI-D adapter	X	X
	HP DisplayPort to VGA Adapter	X	X
	ATI Radeon HD 3470 (256 SH) PCIe x16 Graphics Card	X	X
	ATI Radeon HD 3650 (512MB DH) PCIe x16 Graphics Card	X	
	NVIDIA Quadro NVS 290 256MB DH PCIe x16 Graphics Card	X	X
	NVIDIA GeForce 8400 GS 256MB DH PCIe x1 Graphics Card ^{†*}	X	X
	NVIDIA GeForce 8400 GS 256MB SH PCIe x16 Graphics Card [†]	X	X
	ATI Radeon HD 2400 XT 256MB DH PCIe x16 Graphics Card	X	X

[†] 1GB of system memory required. Graphics cards use part of the total system memory to enhance graphics performance.

* Two NVIDIA GeForce 8400 GS 256MB DH PCIe x1 graphics cards can be installed to provide support for four monitors.

Audio	Integrated High Definition audio with ADI1884 codec (all ports are stereo)	X	X
	Microphone and Headphone front ports	X	X
	Line-out and Line-In rear ports*	X	X
	Multistreaming capable*	X	X
	Internal Speaker	X	X

* Rear audio input port is re-taskable as Line-in or Microphone-in. External speakers must be powered externally. Multistreaming can be enabled in the ADI control panel to allow independent audio streams to be sent to/from the front and rear jacks. This allows for different audio applications to use separate audio ports on the system. For example, the front jacks could be used with a headset for a communications application while the rear jacks are being used with external speakers and a multimedia application.

Input Devices	Keyboard – One of the following		
	HP PS/2 Standard Keyboard	X	X
	HP USB Standard Keyboard	X	X
	Mouse – One of the following		
	USB 2-Button Laser Mouse	X	X
	PS/2 2-Button Optical Scroll Mouse	X	X
	USB 2-Button Optical Scroll Mouse	X	X

Miscellaneous	HP FireWire / IEEE 1394 PCI Card (full height)	X	
	HP FireWire / IEEE 1394 PCI Card (low profile)		X
	2 nd serial port adapter	X	
	2 nd serial port adapter (low profile)		X
	Tower stand		X
	1-GB Flash Module for Vista ReadyBoost	X	X

After-Market Options (availability may vary by region)

		MT	SFF	Part Number
Office 2007 Media-less License Kits (MLK's)				
	MS Office Basic Edition 2007 – Media-less License Kit	X	X	RZ361A#ABA
	MS Office Small Business Edition 2007 – Media-less License Kit	X	X	RZ365A#ABA
	MS Office Professional Edition 2007 – Media-less License Kit	X	X	RZ363A#ABA
<hr/>				
Communications	Wireless LAN			
	HP 802.11 b/g/n Wireless PCIe x1 card	X	X	FH971AA
	NICs			
	Broadcom NetXtreme Gigabit Ethernet Plus PCIe NIC Card	X	X	FS215AA
	Intel Gigabit CT Desktop NIC	X	X	FH969AA
	Modem			
	LSI PCIe x1 Hi-Speed 56K International SoftModem	X	X	FH970AA
	Connectivity			
	Bundle Connectivity Starter Kit - Surge Protector/LAN cable/Printer cable	X	X	RT174AA
<hr/>				
Graphics	Single head solutions			
	ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card	X	X	FH972AA
	Multi head solutions			
	NVIDIA Quadro NVS 290 Dual Head PCIe x16, low profile Graphics Card	X	X	KG748AA
	NVIDIA Quadro NVS 290 Dual Head PCIe x1, low profile Graphics Card	X	X	KN586AA
	NVIDIA GeForce 8400 GS 256MB DH PCIe x1 Graphics Card*	X	X	GJ120AA
	ATI HD 2400 XT 256MB Dual Head PCIe x16, low profile Graphics Card	X	X	KD060AA
	ATI Radeon HD 3650, 512MB Dual Head PCIe x16, full height Graphics Card	X		KS505AA
	ATI HD 4550 PCIe x16 (256GB/DDR3) Dual Head Graphics Card	X	X	AT042AA
	* 1GB of system memory required. Graphics cards use part of the total system memory to enhance graphics performance.			
<hr/>				
Hard Drives	Serial ATA Hard Drives			
	HP 80-GB SATA (NCQ/Smart IV) 3.0-Gb/s Hard Drive	X	X	PY276AA
	HP 160-GB SATA (NCQ/Smart IV) 3.0-Gb/s Hard Drive	X	X	PY277AA
	HP 250-GB SATA (NCQ/Smart IV) 3.0-Gb/s Hard Drive	X	X	PY278AA
	HP 320-GB SATA (NCQ/Smart IV) 3.0-Gb/s Hard Drive	X	X	FH963AA
	HP 500-GB SATA 3.0-Gb/s SMART IV Hard Drive	X	X	KW347AA

After-Market Options (availability may vary by region)

Input/Output Devices				
HP Business Mouse Pad		X	X	AT485AA
HP 2.4GHz Wireless Keyboard and Mouse		X	X	NB896AA
HP PS/2 Standard Keyboard		X	X	DT527A
HP USB Standard Keyboard		X	X	DT528A
HP USB Smartcard Keyboard		X	X	ED707AA
HP USB Mini Keyboard		X	X	AS601AA
HP USB PS2 Washable Keyboard		X	X	VF097AA#ABA (launching July 27th)
HP USB Laser Mouse		X	X	GW405AA
HP PS/2 2-Button Optical Scroll Mouse		X	X	EY703AA
HP USB 2-Button Optical Scroll Mouse		X	X	DC172B

Memory (DIMMs)	PC2-6400 (DDR2, 800 MHz) DIMMs Non-ECC			
	Promo - 2GB (2 x 1GB) PC2-6400 DDR2-800	X	X	NQ604AT
	Promo - 4GB (2 x 2GB) PC2-6400 DDR2-800	X	X	NQ605AT
	HP 4-GB PC2-6400 (DDR2 800 MHz) DIMM	X	X	FH977AA
	HP 2-GB PC2-6400 (DDR2 800 MHz) DIMM	X	X	AH060AA
	HP 1-GB PC2-6400 (DDR2 800 MHz) DIMM	X	X	AH058AA
	1GB Flash Module for Windows Ready Boost	X	X	KG274AA

Monitors	CRTs		3PO Offering
	Value Series Monitors		
	HP LV156w 15-inch Widescreen LCD Monitor		NJ711AA#ABA
	Business LCD Monitors		
	HP L1506 15-inch LCD Monitor		PX848AA#ABA
	HP w17e 17-inch LCD Monitor		GV537AA#ABA
	HP L1710 17-inch LCD Monitor		GS917AA#ABA
	HP L1910 19-inch LCD Monitor		GS918AA#ABA
	HP L1910i 19-inch LCD Monitor with Integrated Work Stand		GS581AA#ABA
	HP L1908w 19-inch Widescreen LCD Monitor		GP536AA#ABA
	HP L1908wm 19-inch Widescreen LCD Monitor with multimedia		KA214AA#ABA
	HP L1908wi 19-inch Widescreen LCD Monitor with Integrated Work Stand		GP537AA#ABA
	HP L2208w 22-inch Widescreen LCD Monitor		GX007AA#ABA
	Advantage Series Monitors		
	HP L1745 17-inch LCD Monitor		GE178AA#ABA
	HP L1750 17-inch LCD Monitor		GF904AA#ABA
	HP L1750 17-inch LCD Monitor - TAA Compliant		GF904A2#ABA
	HP L1950g 19-inch LCD Monitor		KR145AA#ABA
	HP L1950g TAA 19-inch LCD Monitor - TAA Compliant		KR145A2#ABA

After-Market Options (availability may vary by region)

HP L1945w 19-inch Widescreen LCD Monitor	KD286AA#ABA
HP L2045w 20-inch Widescreen LCD Monitor	RD125AA#ABA
HP L2245wg 22-inch Widescreen LCD Monitor	FL472AA#ABA
HP L2445w 24-inch Widescreen LCD Monitor	KT931AA#ABA
Performance Series Monitors	
HP LP1965 19-inch LCD Monitor	RA373AA#ABA
HP LP2065 20-inch LCD Monitor	EF227A4#ABA
HP LP2275 22-inch Widescreen LCD Monitor	KE289A4#ABA
HP LP2275 22-inch Widescreen LCD Monitor Bulk Pack (6 baseless units)	KD289A6#ABA
HP LP2475w 24-inch Widescreen LCD Monitor	KD911A4#ABA
HP LP2480zx 24-inch DreamColor Widescreen LCD Monitor	GV546A4#ABA
HP LP3065 30-inch Widescreen LCD Monitor	EZ320A4#ABA
Digital Signage	
HP LD4200 42-inch LCD Monitor	NH322AA#ABA
Touchscreen Monitor	
HP L5006tm 15-inch Touch Screen LCD Monitor	RB146AA#ABA
Options	
HP USB 2.0MP Business WebCam	NX252AA
HP Flat Panel Speaker Bar	EE418AA
HP Quick Release Kit	EM870AA
HP Integrated Work Stand (stand alone)	GN783AA
HP DreamColor Advanced Profiling Solution (aka Puck)	KZ300AA
HP LCD Hood Kit	KZ301AA
3M 17-in Privacy Screen Filter	KM218AA
3M 19-in Privacy Screen Filter	KZ310AA
Digital Signage Speaker	NK352AA
Digital Signage Stand	NK353AA

Multimedia	Thin USB Powered Speakers	X	X	KK912AA
	Wired Premium Headset (VoIP and Overture Conf)	X	X	AQ704AA

Optical Drives	DVD-ROM Drive			
	HP SATA DVD-ROM Drive	X	X	AH047AA
	DVD Writer			
	HP SATA SuperMulti LightScribe DVD Writer Drive	X	X	GF343AA
	CD-RW/DVD-ROM Combo Drive			

After-Market Options (availability may vary by region)

Removable Storage	Diskette and Digital Drives			
	HP 1.44-MB External USB Diskette Drive	X	X	DC141B
	HP 1.44-MB Internal Diskette Drive	X	X	AH053AA
	Multimedia			
	HP 22-in-1 Media Card Reader with 1394 with PCI Card	X	X	KN518AA
	Removable Hard Drive			
	HP Removable SATA Hard Drive Enclosure (Frame & Carrier)	X	X	RY102AA
	HP Removable SATA Hard Drive Enclosure (Carrier Only)	X	X	RY103AA
<hr/>				
Security	Kensington lock	X	X	PC766A
	HP Business PC Security Lock Kit	X	X	PV606AA
	HP Chassis Security Kit	X	X	AR639AA
	HP 2007 Wall Mount/Security Sleeve		X	GF344AA
	HP ProtectTools Version 4.0	X	X	FH974AA
	HP USB Smartcard Keyboard	X	X	ED707AA
<hr/>				
Brackets/Stand	HP 2007 SFF Tower Stand		X	GJ118AA
<hr/>				
Miscellaneous Accessories	HP USB Graphics Adapter	X	X	NL571AA
	DisplayPort TO VGA Adapter	X		AS615AA
	DisplayPort TO DVI-D Dual Link Adapter (WKS offering)	X		NR078AA (launching July 6th)
	HP ADD2 SDVO DVI-D Adapter	X	X	DY674A
	HP DMS59 DVI Dual-head Connector Cable	X	X	DL139A
	HP DVI to DVI Cable	X	X	DC198A
	HP DisplayPort To DVI-D Adapter	X		FH973AA
	HP 2 nd Serial Port Adapter	X	X	PA716A
	HP Parallel Port Adapter	X	X	KD061AA
	Belken USB to Serial Adapter	X	X	EM449AA
	HP FireWire / IEEE 1394 PCI Card	X	X	PA997A
	5.25" Blank Bezel Kit (Carbonite 50/Bulk Pack)	X	X	DC177B
	Local Area Network (LAN) cable, Ethernet cable	X	X	AH122AA
	Firewire (1394) Cable	X	X	AH123AA
	7-outlet Surge Protector	X	X	AG290AA
	HP 1TB Media Vault Pro MV5140	X	X	GX667AA#ABA
HP 1.5TB Media Vault Pro MV5150	X	X	GX668AA#ABA	

Technical Specifications

Unit Environment and Operating Conditions	Microtower	Small Form Factor
General Unit Operating Guidelines <ul style="list-style-type: none"> Keep the computer away from excessive moisture, direct moisture and the extremes of heat and cold, to ensure that unit is operated within the specified operating range. Leave a 10.2 cm (4 in) clearance on all vented sides of the computer to permit the required airflow. Never restrict airflow into the computer by blocking any vents or air intakes. Do not stack computers on top of each other or place computers so near each other that they are subject to each other's recirculated or preheated air. Occasionally clean the air vents on the front, back, and any other vented side of the computer. Lint, dust and other foreign matter can block the vents and limit the airflow. If the computer is to be operated within a separate enclosure, intake and exhaust ventilation must be provided on the enclosure, and the same operating guidelines listed above will still apply. 		
Temperature Range	Operating: 50° to 95° F (10° to 35° C)* Non-operating: -22° to 140° F(-30° to 60° C)	
Relative Humidity	Operating: 10% to 90% (non-condensing at ambient) Non-operating: 5% to 95% (non-condensing at ambient)	
Maximum Altitude (unpressurized)	Operating: 10,000 ft (3048 m) Non-operating: 30,000 ft (9144 m)	
* Operating temperature is de-rated 1.0 deg C per 300 m (1000 ft) to 3000 m (10,000 ft) above sea level, no direct sustained sunlight. Maximum rate of change is 10 deg C/Hr. The upper limit may be limited by the type and number of options installed.		

	Microtower		Small Form Factor	
Power Supply	300-watt BTX power supply – Passive PFC 115v/230v line switch	300-watt 85% efficient* BTX power supply – Active PFC	240-watt BTX power supply – Active PFC 115v/230v line switch	240-watt 85% efficient* BTX power supply – Active PFC
Operating Voltage Range	90 to 132VAC, or 180 to 264VAC	90 to 264VAC	90 to 132VAC, or 180 to 264VAC	90 to 264VAC
Rated Voltage Range	100 to 127VAC, or 200 to 240VAC	100 to 240VAC	100 to 127VAC, or 200 to 240VAC	100 to 240VAC
Rated Line Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Operating Line Frequency Range	47–63 Hz	47–63 Hz	47–63 Hz	47–63 Hz
Rated Input Current	8A/4A	5A/2.5A	6A/3A	3.5A/1.75
Heat Dissipation	Typical 315 btu/hr (79 kg-cal/hr) Maximum 1575 btu/hr (397 kg-cal/hr)	Typical 270 btu/hr (68 kg-cal/hr) Maximum 1280 btu/hr (322 kg-cal/hr)	Typical 315 btu/hr (79 kg-cal/hr) Maximum 1260 btu/hr (317 kg-cal/hr)	Typical 270 btu/hr (68 kg-cal/hr) Maximum 1025 btu/hr (258 kg-cal/hr)
Power Supply Fan	Variable speed fan	Variable speed fan	Variable speed fan	Variable speed fan
ENERGY STAR Compliant		X		X
FEMP Standby Power Compliant (<2W in S5 – Power Off)**	X	X	X	X

Technical Specifications

Power Consumption in ES Mode – Suspend to RAM (S3) (Instantly Available PC)	<4W	<3W	<4W	<3W
---	-----	-----	-----	-----

* Energy efficient power supply is a requirement for ENERGY STAR qualification in conjunction with a select range of processors and module.

** Power consumption in the Off/Apparent Off mode is measured and reported with the network interface controller “Wake on LAN” feature disabled in F10 Setup (default is “enabled”).

ROM BIOS Information

Key features of the HP BIOS in the dc5800 include:

- Deployment and manageability – HP BIOS provides several technologies that help integrate the HP Business desktop computer into the enterprise, such as PXE, remote configuration, remote control, and F10 Setup support for 12 languages.
- Stability – HP BIOS supports the HP stable product roadmap by releasing only critical BIOS changes to the factory and advanced change notification.
- Security – HP BIOS offers a robust and flexible set of security features to help the system administrator secure their systems from removal of sensitive data, and help prevent access by unauthorized users.
- Tracking and tracing capabilities in case of theft available in select countries (subscription sold separately).
- Thermal and power management – The HP BIOS provides and enables thermal and power management technologies to assist in operating the HP Business Desktop computer in any enterprise environment.
- Serviceability – HP BIOS provides diagnostic and detailed service information.
- Upgrades and recovery – HP BIOS provides numerous ways to upgrade HP Business Desktop computers, including BIOS updates from within DOS (Flashlite), BIOS updates from within Windows (HPQFlash, SSM), HP Client Manager, and fail-safe recovery. In addition, the HP Business Desktop BIOS Utilities tool enables replicated BIOS setup throughout the Enterprise; it is available from within the BIOS software and from the support website.

Additional HP BIOS Features

- Administrator password – Also known as the setup password, this helps prevent unauthorized changes to the system configuration. If the administrator password is not known, the BIOS version cannot be changed and changes cannot be made to BIOS settings using F10 setup or under the OS.
- Advanced Configuration and Power Interface (ACPI) – Represents a significant innovation in power and configuration management, allowing operating systems and applications to manage power based on activity and usage. Provides power conservation features under Windows XP.
- Ability to mute the internal speaker

Other Features	Description
ACPI-Ready Hardware	Advanced Configuration and Power Management Interface (ACPI). <ul style="list-style-type: none"> • Allows the system to wake from a low power mode. • Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system.
SMBIOS Ver. 2.6	System Management BIOS, previously known as DMI BIOS, for system management information
Wired for Management Support	Intel-driven, industry-wide initiative to make Intel architecture-based PCs, servers and mobile computers more inherently manageable right out of the box and over the network
Dual-State Power Button	Power button acts as both an on/off button and suspend-to-sleep button

Technical Specifications

Serviceability Features of System		
Dual Color Power LED on Front of Computer (Indicates Normal Operations and Fault Conditions)		
Diagnostic LED Explanation Table	Number of 1-second red LED blinks followed by 2-second pause, then repeats: 2-processor thermal protection activated 3-processor not installed 4-power supply failure 5-memory error 6-video error 7-PCA failure (ROM detected failure prior to video) 8-invalid ROM, bootblock recover mode	
<ul style="list-style-type: none"> System/Emergency ROM 	<ul style="list-style-type: none"> Flash ROM 	<ul style="list-style-type: none"> CMOS Battery Holder for easy Replacement
<ul style="list-style-type: none"> Flash Recovery with Video 	<ul style="list-style-type: none"> 5 Aux Power LED on System PCA 	<ul style="list-style-type: none"> Processor ZIF Socket for easy Upgrade
<ul style="list-style-type: none"> Over-Temp Warning on Screen (Requires IM Agents) 	<ul style="list-style-type: none"> Clear Password Jumper 	<ul style="list-style-type: none"> DIMM Connectors for easy Upgrade
<ul style="list-style-type: none"> Restore CD 	<ul style="list-style-type: none"> Clear CMOS Switch 	<ul style="list-style-type: none"> NIC LEDs (integrated) (Green & Amber)

Serviceability Features of Chassis		
<ul style="list-style-type: none"> Dual Color Power and HD LED – To Indicate Normal Operations and Fault Conditions 	<ul style="list-style-type: none"> Color coordinated cables and connectors 	<ul style="list-style-type: none"> Tool-less Hood Removal (thumbscrews for Microtower, spring-latch for Small Form Factor)
<ul style="list-style-type: none"> Front power switch 	<ul style="list-style-type: none"> System memory can be upgraded upgraded on Microtower without removing any internal components 	<ul style="list-style-type: none"> Tool-less Hard Drive, CD & Diskette Removal
Feature	Description	
Towerable	Product can be oriented as a tower (in addition to desktop orientation)	
Drive Self Tests (DPS)	<ul style="list-style-type: none"> Drive Protection System A diagnostic hard drive self test. It scans critical physical components and every sector of the hard drive for physical faults and then reports any faults to the user. Running independently of the operating system, it can be accessed through a Windows-based diagnostics utility or through the computer's setup procedure. It produces an evaluation on whether the hard drive is the source of the problem and needs to be replaced. The system expands on the Self-Monitoring, Analysis, and Reporting Technology (SMART), a continuously running systems diagnostic that alerts the user to certain types of failures. 	
DPS Access through F10 Setup during Boot		
SMART IV Technology* (Self-Monitoring, Analysis and Reporting Technology)	<p>Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted</p> <ul style="list-style-type: none"> Predicts failures before they occur. Tracks fault prediction and failure indication parameters such as re-allocated sector count, spin retry count, calibration retry count By avoiding actual hard drive failures, SMART hard drives act as “insurance” against unplanned user downtime and potential data loss from hard drive failure 	

Technical Specifications - Audio

High Definition Audio	Type	Integrated
	High Definition Stereo Codec	Yes – 4-channel ADI 1884 codec
	Audio Jacks	Front microphone-In (150-K ohm Input Impedance) Rear Line-In/Microphone input (150-K ohm Input Impedance, function is configurable by audio driver) Rear Line-Out* (190 ohms Output Impedance, expects at least a 10-K ohm load) Front Headphone-Out (0.5 Ohm Output Impedance, expects at least a 32 ohm load)
	<i>* Internal Speaker Amplifier is for Internal Speaker only. External Speakers need to be powered externally. Rear Line in audio port is re-taskable as Line-in or Microphone-in.</i>	
	Multistreaming Capable	Multistreaming can be enabled in the ADI control panel to allow independent audio streams to be sent to/from the front and rear jacks.
	Sampling	8 kHz – 192 kHz
	Wavetable Syntheses (software)	Yes – Uses OS soft wavetable
	Analog Audio	Yes
	Number of Channels on Line-Out (mono/stereo)	Stereo (Left & Right channels)
	Internal Audio Speaker Power Rating	1.5 W
	Internal Speaker	Yes; ability to mute internal speaker through F10 Setup
	External Speaker Jack (Line-Out)	Yes

Technical Specifications - Communications

Integrated Intel 82566DM Gigabit Network Connection	Connector	RJ-45
	Controller	Intel Nineveh Gigabit platform LAN Connect Networking Controller
	Memory	Integrated 96KbB on chip buffer memory
	Data rates supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3 ab and 802.3u compliant,
	Bus architecture	GLCI, LCI interface. Intel specific MAC to PHY interface
	Data transfer mode	At gigabit GLCI (802.3 serdes) is for Data, LCI (parallel bus)for MDIO, at 10/100 LCI for both data and MDIO, GLCI is idle.
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power requirement	Require 3.3Vaux, 1.8V and 1.0V or just 3.3V with integrated regulators Power consumption 1.16 Watts for 82566, whole LOM 2.53 Watts
	ACBS	Intel Auto Connect Battery Saving feature
	Boot ROM support	Yes
	Network transfer mode	Full-duplex
		Half-duplex (not available for the 1000BASE-T transceiver)
	Network transfer rate	10BASE-T (half-duplex) 10 Mbps
10BASE-T (full-duplex) 20 Mbps		
100BASE-TX (half-duplex) 100 Mbps		
100BASE-TX (full-duplex) 200 Mbps		
1000BASE-T (full-duplex) 2000 Mbps		
Environmental	Operating temperature	32° to 131°F (0° to 55° C) To 70° C for external regulator
	Operating humidity	85% at 131° F (55° C)
Management capabilities	WOL, auto MDI crossover, PXE, Muti-port teaming, RSS, Advanced cable diagnostic.	

Technical Specifications - Communications

Intel Gigabit CT Desktop NIC	Connector	RJ-45
	Controller	Intel WG82574L Gigabit Ethernet Controller
	Memory	Integrated Dual 48K configurable transmit receive FIFO Buffers
	Data rates supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus architecture	PCI-E 1.0a
	Data path width	X1, 250 MB/s, Bi-directional interface
	Data transfer mode	Bus-master DMA
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power requirement	Aux 3.3V, 3.0 Watts in 1000base-T and 2.0 Watts in 100Base-T
	Boot ROM support	Yes
	Network transfer rate	10BASE-T (half-duplex) 10 Mbps
		10BASE-T (full-duplex) 20 Mbps
		100BASE-TX (half-duplex) 100 Mbps
		100BASE-TX (full-duplex) 200 Mbps
1000BASE-T (full-duplex) 2000 Mbps		
Environmental	Operating temperature	32° to 131°F (0° to 55° C)
	Operating humidity	85% at 131° F (55° C)
Dimensions	4.75 x 2.25 x 0.8 in (12.1 x 5.7 x 2.0 cm)	
Operating system driver support	Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows XP Professional or Windows XP Home 32*. No driver is required for this device. Native support is provided by the operating system. Red Hat Linux 7.2, Linux 7.3 and Red Hat Enterprise Linux 3	
	<p>* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: http://www.windowsvista.com/upgradeadvisor. For Windows Vista system requirements, visit: http://www.windowsvista.com/systemrequirements.</p>	
Management capabilities	WOL , PXE, DMI, WFM 2.0	

Technical Specifications - Communications

Broadcom NetXtreme Gigabit Ethernet PCIe NIC Card	Connector	RJ-45
	Controller	Broadcom 5751 PCI-Express LAN Controller
	Memory	Integrated 96Kb frame buffer memory
	Data rates supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus architecture	PCI-E
	Data path width	Single channel, PCI-E
	Data transfer mode	Bus-master DMA
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power requirement	3.1 watts @ +3.3V AUX supply with 5V tolerance
	Boot ROM support	Yes
	Network transfer mode	Full-duplex
		Half-duplex (not available for the 1000BASE-T transceiver)
	Network transfer rate	10BASE-T (half-duplex) 10 Mbps
		10BASE-T (full-duplex) 20 Mbps
		100BASE-TX (half-duplex) 100 Mbps
		100BASE-TX (full-duplex) 200 Mbps
		1000BASE-T (full-duplex) 2000 Mbps (actual rate limited by PCI Bus)
	Environmental	Operating temperature
Operating humidity		85% at 131° F (55° C)
Dimensions	4.4 x 2.2 x 0.08 in (11.2 x 5.5 x 2 cm)	
Management capabilities	ACPI, WOL and DMI 2.0, PXE 2.1, WfM 2.0, Broadcom mgmt utility	

HP Wireless A+G PCI	Dimensions	4.99 x 2.54 x 0.71 in (126.8 x 64.4 x 18.0 mm)
	Weight	0.268 lb (65 g)
	Controller system interface	Atheros AR5414X chipset PCI Spec 2.2
	Network standard	IEEE 802.11a/b/g
	Frequency band	5.1500 to 5.8500 GHz
		2.4000 to 2.4835 GHz
		2.4465 to 2.4835 GHz (Europe, Middle East, Asia and Asia Pacific – excluding Japan)
		2.4000 to 2.4697 GHz (Japan)
	Operating temperature	32° to 140° F (0° to 60° C), operating
	Storage temperature	-4° to 176° F (-20° to 80° C), non-operating
	Humidity	10% to 85% non-condensing
Operating voltage	5V ± 5%	
Power consumption	Tx/Rx peak 560/250mA @ 3.3V (max.)	

Technical Specifications - Communications

Output power (approximately)	15 dBm \pm 2dB	
Receive sensitivity	-90dBm at 11 Mbps (typical)	
Data transfer rate	Standard rates of 1, 2, 5.5, 11, 6, 9, 12, 18, 24, 48, 54 and Super AG Mode108-Mbps	
Spreading	DSSS (Direct Sequence Spread Spectrum)	
Security	64(40h) bit, 128(104h) bit, WPA, IEEE802.1X, AES-OCB, AES-CCM, Microsoft PEAP,TKIP, WEP.	
Antenna	External 5dBi antenna	
Throughput	108 Mbps (only with Belkin 54G or above router that supports 108 Mbps speed)	200 ft (60.96 m) – Indoor
	54 Mbps	200 ft (60.96 m) – Indoor
	11 Mbps	200 ft (60.96 m) – Indoor
Certifications	Wi-Fi certified	
Certifications for use by country	North America: United States, Canada Europe: Austria, Belgium, Cyprus, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Liechtenstein, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom Australia New Zealand	

HP 802.11b/g/n Wireless PCIe x1 Card	Dimensions (L x H)	3.3 x 4.7 inches (8.5 x 12 cm)		
	Weight	0.08 pounds (40 g)		
	Controller	Ralink RT2790		
	System interface	PCIExpress x1		
	Network standard	802.11 b/g/n		
	Frequency band	2.400 - 2.497 GHz		
	Operating temperature	14° to 149°F, operating (-10° to 65°C, operating)		
	Storage temperature	-40° to 176°F, non-operating (-40° to 80°C, non-operating)		
	Humidity	10-90% operating 5-95% non-operating		
	Operating voltage	3.3V +/- 9% 12V +/- 8%		
	Power consumption	Platform/WLAN Mode	Power Consumption	
		Maximum Power Consumption	10 Watts	
		Transmit Only	4 Watts maximum averaged power over 1 second	
	Transmit Packet or Active Scanning	1000 mA peak current for 100 microseconds or longer		
	Receive Only Mode or Idle without IEEE PSP mode enabled	3 Watts maximum averaged over 1 second		

Technical Specifications - Communications

	Idle, with IEEE PSP mode enabled	1.0 Watts maximum averaged over 1 second	
	Transmit Disabled (turned off in software)	50 mW maximum, averaged over 1 second	
	Platform in S3 or S4 (power removed from Low Profile PCI Express Card)	5 mW maximum, averaged over 1 second	
Output power (approximately)	802.11b modes	802.11g modes	EWC modes
	+19 dBm +/- 1.0 dB maximum	+17 dBm +/- 1.0 dB maximum	+17 dBm +/- 1.0 dB maximum (total power in all transmit chains)
Receive sensitivity	Mode	Data rate	Sensitivity
	802.11b	1 Mbps	-94 dBm
	802.11b	11 Mbps	-85 dBm
	802.11g	6 Mbps	-91 dBm
	802.11g	18 Mbps	-85 dBm
	802.11g	48 Mbps	-75 dBm
	802.11g	54 Mbps	-72 dBm
	EWC (2.4 GHz)	6.5 Mbps	-87 dBm
	EWC (2.4 GHz)	54 Mbps	-82 dBm
	EWC (2.4 GHz)	81 Mbps	-78 dBm
	EWC (2.4 GHz)	162 Mbps	-74 dBm
	EWC (2.4 GHz)	270 Mbps	-68 dBm
	EWC (2.4 GHz)	300 Mbps	-64 dBm
Data transfer rate	Data Rate (MCS)	Minimum Throughput	
	1 Mbps (802.11 b)	700 kbps	
	2 Mbps (802.11 b)	1.4 Mbps	
	5.5 Mbps (802.11 b)	3.5 Mbps	
	11 Mbps (802.11 b)	5.9 Mbps	
	12 Mbps (802.11 g)	6 Mbps	
	18 Mbps (802.11 g)	9 Mbps	
	24 Mbps (802.11 g)	12 Mbps	
	36 Mbps (802.11 g)	18 Mbps	
	48 Mbps (802.11 g)	21 Mbps	
	54 Mbps (802.11 g)	22.5 Mbps	
	6.5 Mbps (20 MHz EWC)	4.5 Mbps	
	13 Mbps (20 MHz EWC)	9 Mbps	
	19.5 Mbps (20 MHz EWC)	13.5 Mbps	
	26 Mbps (20 MHz EWC)	18 Mbps	
	39 Mbps (20 MHz EWC)	27 Mbps	
	52 Mbps (20 MHz EWC)	36 Mbps	

Technical Specifications - Communications

58.5 Mbps (20 MHz EWC)	40 Mbps
65 Mbps (20 MHz EWC)	45 Mbps
78 Mbps (20 MHz EWC)	54 Mbps
104 Mbps (20 MHz EWC)	72 Mbps
117 Mbps (20 MHz EWC)	81 Mbps
130 Mbps (20 MHz EWC)	91 Mbps
13.5 Mbps (40 MHz EWC)	8 Mbps
27 Mbps (40 MHz EWC)	16 Mbps
40.5 Mbps (40 MHz EWC)	24 Mbps
54 Mbps (40 MHz EWC)	32 Mbps
81 Mbps (40 MHz EWC)	48 Mbps
108 Mbps (40 MHz EWC)	64 Mbps
121.5 Mbps (40 MHz EWC)	72 Mbps
135 Mbps (40 MHz EWC)	81 Mbps

Security

- IEEE and WiFi compliant 64 / 128 bit WEP encryption
- AES: CCM
- 802.1x authentication
- WPA: 802.1x. WPA-PSK and TKIP
- WPA2 certification
- IEEE 802.11i
- Cisco Certified Extensions, all versions through V5

Antenna

HP part number 497792-001

Certifications

Wi-Fi certified

Certifications for use by country

United States, Canada, Peru, Taiwan

2006 Agere PCI 56K International SoftModem

Data Transmission

Technology speeds: 56,000 Kbps maximum downstream data, controllerless

NOTE: 56 Kbps technology refers to download speeds only and requires compatible modems at server sites. Other conditions may limit modem speed. FCC limitations allow a maximum of 53 Kbps during download transmissions.

Data Speeds

(Upload only)
33,600/31,200/28,800/26,400/21,600/19,200/16,800/14,400/12,000/
9,600/7,200/4,800/2,400/1,200/300

Data Standards

ITU-T V.90, ITU-T, ITU-T V.34, V.44, V.42, V.42bis21, V.32bis, Bell 212A, and Bell 103

Fax Speeds

14,400/12,000/9,600/7,200/4,800/2,400/1,200/300 b/s

Fax Mode Capabilities

ITU-T T.31 class 1 FAX, V. 17, V.29, V.27ter, and V.21 Channel 2

Error Correction and Data Compression

V.44, 42bis, V.42 and MNP2-5

Power Management

ACPI; PPM1 1.1 and wake support with PME and Vaux; meets PCI 2.3 requirements and PC 2001 requirements

Upgradeability

Driver upgradeable for future enhancements

Video

ITU-T V.80 video ready interface

Technical Specifications - Communications

Other	TIA/EIA 602 standard AT command set Integrated DTE interface with speeds of up to 115.2 Kbps, parallel 16550a UART-compatible interface Optional ring wakeup signal
Operating Temperature	32° to 158° F (0° to 70° C)
Operating Humidity	20% to 90%, non-condensing
Power	Requires a 3.3-V auxiliary power rail on PCI bus Uses only one PCI load (i.e., one grant/request pair), one shared IRQ, one electrical load
Chipset	Agere Systems SV92PL – Integrated PCI interface with 5-V tolerant buffers and CardBus support
Dimensions (L X H)	Complies with PCI low profile specifications–6.7 x 2.3 in (17.0 x 5.8 cm) and supports high- and low-profile brackets
Connection	Single RJ-11 connector
Other Features	Digital line protection, call progress monitoring via on-board piezo device, support for high profile and low profile brackets, PnP ID support
Safety	UL recognized to UL 1950, 3 rd edition (U.S. and Canada); IEC 950 (TUV, NEMKO, DEMKO, SEMKO); CE Mark, EC 950 (TUV, NEMKO, DEMKO, SEMKO, CE mark
EMC	FCC Part 15, IC ES003, EN 55022, 3rd edition, EN 55024, annex A, EN 61000-4-6, EN 61000-4-8
Telecom	FCC Part 68, IC-CS-03 (Canada); Worldwide PTT approvals Not available in Korea or the Republic of South Africa.
Health	Bare PCB material compliant to 94V-0 or better (marked as such)
Other	PC 2001 compliant, PCI version 2.3, WHQL approved; ACPI compliant

Technical Specifications - Graphics

Integrated Graphics Media Accelerator 3100	3D/2D Controller	Microsoft DirectX® 9 based with support for Pixel Shader 2.0, 4:1 anisotropic filtering, Gaussian texture filtering, shadow maps, volumetric textures, double-sided stencil buffers, and 4 pixel pipes.
	VGA Controller	Integrated
	Bus Type	PCI Express™ x16 (If an external graphics card is installed in a PCI or PCIe x1 slot, the internal graphics can be enabled or disabled using the system's BIOS setup utility. If a graphics card other than an SDVO/ADD2 card is installed in the PCI Express™ x16 slot, the internal graphics cannot be enabled).
	RAMDAC	Integrated, 350 MHz (2048x1536@75 Hz)
	Memory	Graphics memory is shared with system memory. Graphics memory usage varies depending on the amount of system memory installed and system load. 8 MB is pre-allocated for graphics use at system boot time. Additional memory is allocated for graphics as needed using Intel's Dynamic Video Memory Technology (DVMT), to provide an optimal balance between graphics and system memory use.
		System memory equal or greater than 512 MB 8 MB pre-allocated + 248 MB DVMT = max frame buffer of 256 MB
	Overlay Planes	Single overlay support with 5x3 filtering
	Maximum Colour Depth	32 bits/pixel
	Maximum Vertical Refresh Rate	85 Hz at up to 1920x1440, 75 Hz at 2048x1536. Varies with mode and configuration. See table below.
	Multi-display Support	Support for one CRT via the motherboard's VGA connector on SFF and MT. Support for an additional display on SFF/MT can be accomplished with the addition of SDVO/ADD2 option installed in PCIe x16 slot.
	Graphics/Video API Support	Microsoft DirectX®9, DirectXVA®, VMR9, GDI/GDI+; OpenGL® 1.4.

Resolutions Supported ¹	Resolution	Maximum Refresh Rate (Hz)	
		Analog Monitor	Digital Monitor
	640 x 480	85	60
	800 x 600	85	60
	1024 x 768	85	60
	1280 x 1024	85	60
	1600 x 1200	85	60
	1920 x 1080	85	60
	1920 x 1200	85	60
	1920 x 1440	85	N/A
	2048 x 1536	75	N/A

¹ Modes listed are supported with a single active display. The supported mode list for multiple active displays is a subset of this list. Not all modes will support video playback and some supported modes may use software MC (motion compensation) rather than hardware MC. Not all modes will support 3D acceleration depending on the system configuration (e.g., resolution selected, size of frame buffer, number of installed memory modules, etc.).

NOTE: Other resolutions and refresh rates may be selectable but are not recommended.

Technical Specifications - Graphics

DVI ADD2 Graphics¹

Models	HP ADD2 SDVO DVI-D Out Adapter
Form Factor	Low-profile card
DVI-D Connector	Digital connection only
Dual Head Support	Yes, when used with the integrated VGA connector
Display Devices Supported	HP L1740 HP L1940T HP L2045W HP LP1965

NOTE: These graphics adapters offer optimal performance with any display that meets applicable VESA standards.

Colour Depth	All modes support 8-bpp, 16-bpp, and 24-bpp colour depths
Host Interface Connector	Mechanically compliant with PCI-E standard Complies with the Intel ADD2 and Intel Serial Digital Video Output (SDVO) specifications
Dot Clock	165 MHz maximum
Display Modes	Supports display modes that require up to 165-MHz bandwidth on the link, as shown in the following table.

Resolution		60-Hz LCD	60-Hz	75-Hz	85-Hz
Blanking		5% reduced	GTF	GTF	GTF
640 x 480	VGA	Yes	Yes	Yes	Yes
800 x 600	SVGA	Yes	Yes	Yes	Yes
1024 x 768	XGA	Yes	Yes	Yes	Yes
1280 x 1024	SXGA	Yes	Yes	No	No
1600 x 1200	UXGA	Yes	Yes	No	No

ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card

Bus type	PCI Express (x16 lanes)								
Maximum vertical refresh rate	85 Hz								
Display support	Integrated 400 MHz RAMDAC								
Display max resolution	2560x1600 digital, 2048 x 1536 analog								
Board display options	Supports two displays via the DisplayPort and DVI connectors								
Board configuration	<table> <thead> <tr> <th>Specification</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Graphics Chip</td> <td>RV620</td> </tr> <tr> <td>Core clock</td> <td>750 MHz</td> </tr> <tr> <td>Memory clock</td> <td>500 MHz</td> </tr> </tbody> </table>	Specification	Description	Graphics Chip	RV620	Core clock	750 MHz	Memory clock	500 MHz
Specification	Description								
Graphics Chip	RV620								
Core clock	750 MHz								
Memory clock	500 MHz								
Frame buffer	256 MB DDR2, 64 bit wide								
Languages supported	24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish								
Operating systems support	Windows Vista Business 64*, Windows Vista Business 32*, Windows Vista Home Basic 32*, Windows XP Professional or Windows XP Home 32*.								

Technical Specifications - Graphics

* Certain Windows Vista product features require advanced or additional hardware. Windows Vista Upgrade Advisor can help you determine which features of Windows Vista will run on your computer. To download the tool, visit: <http://www.windowsvista.com/upgradeadvisor>. For Windows Vista system requirements, visit: <http://www.windowsvista.com/systemrequirements>.

Linux x86 and x86_64 distributions using XFree86 or X.Org**.

** Linux drivers are available from ATI's website and may be available in a Linux distribution. Refer to the Open Source and Linux from HP website: <http://www.hp.com/wwsolutions/linux/products/clients/> for support information.

Core power

22 W (max)

Dimensions (H x D)

2.71 in x 6.60 in (68.90 mm x 167.65 mm)

Weight

0.30 lb (134.3 g)

Option kit contents

- ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card with full height bracket attached
- DVI to VGA adapter
- Software CD with graphics drivers
- Low profile bracket to convert the card for using in a low profile chassis

Warranty documentation

Compliance standards

EMC Emissions:

- FCC Part 15, Subpart B - Unintentional Radiators, Class B Computing Devices for Home & Office Use
- CISPR22: 1997/EN 55022:1998 - Class B - Limits and methods of measurement of radio disturbance characteristics of Information Technology Equipment
- Canadian Standard ICES-003 is equivalent to CISPR22
- Taiwanese Standard BSMI
- Japanese VCCI
- Australian C-Tick
- Korean (MIC)

EMC Immunity:

CISPR 24:1997/EN 55024:1998 - Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurement.

Technical Specifications - Graphics

ATI Radeon HD 3470 (256MB SH) PCIe x16 Graphics Card display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	60*

* Only supported when using a dual-link DVI or DP connection

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections.

NVIDIA Quadro NVS 290 256MB PCIe Dual Head	Form Factor	Low Profile
	Bus Type	PCIe x16
	Memory	256 MB 400MHz DDR2 SDRAM unified frame buffer, Z-buffer and Texture storage
	Connector	DMS-59, includes DMS-59 to Dual VGA cable
	Display Resolution Support	Dual integrated analog display controllers supporting up to two analog displays at 2048x1536 @ 85Hz on both displays or dual digital displays at 1920x1200 (single-link). NVIEW advanced multi-display desktop and application management seamlessly integrated into Microsoft Windows
	RAMDAC	Integrated dual 400MHz
	Colour planes	32-bit colour buffer
	Overlay planes	Hardware supported
	nView architecture	Advanced multi-display desktop & application management seamlessly integrated into Microsoft Windows.
	Multi-Monitor support	Dual monitor support
	DVI support	DMS-59 (to dual DVI-SL)
	High-definition Video Processor (HDVP)	Full-screen, full-frame video playback of HDTV and DVD content DVD-ready motion compensation for MPEG-2 Independent hardware colour controls for video overlay Hardware colour-space conversion (YUV 4:2:2 and 4:2:0) IDCT motion compensation 5-tap horizontal by 3-tap vertical filtering 8:1 up/down scaling

Technical Specifications - Graphics

Supported graphics APIs OGL 2.1 & DX10 Support; Shader Model 4.0

NVIDIA GeForce 8400 GS (256 MB SH) PCIe x16 Graphics Controller	Bus type	PCI Express (x16 lanes)		
	Maximum vertical refresh rate	85 Hz		
	Display support	Integrated 400 MHz RAMDAC		
	Display max resolution	2048 x 1536 (analog), 2560 x 1600 (digital)		
	Input/Output connectors	DVI-I (DVI port supports dual-link and HDCP) TV-out (4 pin S-video)		
	Board display options	DVI-I + TV DVI-I supports analog CRT or flat panel or digital flat panel (using DVI-A, DVI-D or DVI-I connector) DVI-I supports analog CRT or flat panel (with VGA connector and DVI-I to VGA dongle) TV connector is a 4-pin mini-DIN S-video connector		
	Board configuration	Specification	Description	
		Graphics Chip	NVIDIA P413-260	
		Core clock	460 MHz	
		Memory clock	200 MHz	
	Frame buffer	256 MB DDR2		
Languages supported	24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish			
System memory	1GB of system memory required			
Core power	25 W (Max board power)			

NVIDIA GeForce 8400 GS (256 MB SH) PCIe x16 Graphics Controller display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP.

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	60*

Technical Specifications - Graphics

* Only supported when using a dual-link DVI or DP connection

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

NVIDIA GeForce 8400 GS (256 MB DH) PCIe x1 Graphics Controller	Bus type	PCIe x1		
	Maximum vertical refresh rate	85 Hz		
	Display support	Integrated 400 MHz RAMDAC		
	Display max resolution	2048 x 1536 (analog), 2560 x 1600 (digital)		
	Input/Output connectors	DMS59 (DMS-59 port supports Dual VGA or Dual DVI connections) TV-out (4 pin S-video)		
	Board display options	DMS59 + TV DMS59 supports either 2 VGA displays with the included cable or 2 DVI displays with optional HP DMS59 DVI Dual-head Connector Cable kit #DL139A TV connector is a 4-pin mini-DIN S-video connector		
	Board configuration	Specification	Description	
		Graphics Chip	NVIDIA GeForce 8400 GS	
		Core clock	460 MHz	
		Memory clock	200 MHz	
	Frame buffer	256 MB DDR2		
Languages supported	24 languages: English, Arabic, Chinese Simplified, Chinese Traditional, Czechoslovakian, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Thai, Turkish			
System memory	1GB of system memory required			
Core power	25 W (Max board power)			

NVIDIA GeForce 8400 GS (256 MB DH) PCIe x1 Graphics Controller display resolutions and refresh rates

NOTE: Other resolutions may be available but are not recommended as they may not have been tested and qualified by HP.

Resolution	Maximum Refresh Rate (Hz)	
	Analog Connection	Digital Connection
640x480	85	60
800x600	85	60
1024x768	85	60
1280x720	85	60
1280x1024	85	60
1440x900	75	60
1600x1200	85	60
1680x1050	75	60
1920x1080	85	60-R
1920x1200	85	60-R
1920x1440	85	N/A
2048x1536	75	N/A
2560x1600	N/A	N/A

Technical Specifications - Graphics

NOTE: 60-R denotes reduced blanking timings are used on single-link DVI connections and may be used with other digital connections

Technical Specifications - Hard Drives

7200 RPM Serial ATA Hard 500-GB Drives

Capacity	500,107,862,016 bytes	
Height	1 in (2.54 cm)	
Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)	
Interface	Serial ATA (3.0 Gb/s)	
Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s	
Buffer	16 MB	
Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2.0 ms
	Average	11 ms
	Full-Stroke	21 ms
Rotational Speed	7,200 rpm	
Logical Blocks	976,773,168	
Operating Temperature	41° to 131° F (5° to 55° C)	

320 GB

Capacity	320,072,933,376 bytes	
Height	1 in (2.54 cm)	
Width	Media diameter: 3.5 in (8.9 cm) Physical size: 4 in (10.2 cm)	
Interface	Serial ATA (3.0 Gb/s)	
Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s	
Buffer	8 MB	
Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2.0 ms
	Average	11 ms
	Full-Stroke	21 ms
Rotational Speed	7,200 rpm	
Logical Blocks	625,142,448	
Operating Temperature	41° to 131° F (5° to 55° C)	

250-GB

Capacity	250,059,350,016 bytes	
Height	1 in (2.54 cm)	
Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)	
Interface	Serial ATA (3.0 Gb/s)	
Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s	
Buffer	8 MB	

Technical Specifications - Hard Drives

	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2.0 ms
		Average	11 ms
		Full-Stroke	21 ms
	Rotational Speed		7,200 rpm
	Logical Blocks		488,397,168
	Operating Temperature		41° to 131° F (5° to 55° C)
160-GB	Capacity		160,041,885,696 bytes
	Height		1 in (2.54 cm)
	Width		Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)
	Interface		Serial ATA (3.0 Gb/s)
	Synchronous Transfer Rate (Maximum)		Up to 3 Gb/s
	Buffer		8 MB
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2.0 ms
		Average	11 ms
		Full-Stroke	21 ms
	Rotational Speed		7,200 rpm
	Logical Blocks		312,581,808
	Operating Temperature		41° to 131° F (5° to 55° C)
80-GB	Capacity		80,026,361,856 bytes
	Height		1 in (2.54 cm)
	Width		Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)
	Interface		Serial ATA (3.0 Gb/s)
	Synchronous Transfer Rate (Maximum)		Up to 3 Gb/s
	Buffer		8 MB
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2.0 ms
		Average	11 ms
		Full-Stroke	21 ms
	Rotational Speed		7,200 rpm
	Logical Blocks		156,301,488
	Operating Temperature		41° to 131° F (5° to 55° C)

Technical Specifications - Input/Output Devices

PS/2 Standard Keyboard	Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
		Dimensions (L x W x H)	18.0 x 6.4 x 0.98 in (45.8 x 16.3 x 2.5 cm)
		Weight	2 lb (0.9 kg) minimum
	Electrical	Operating voltage	+ 5VDC ± 5%
		Power consumption	50-mA maximum (with three LEDs ON)
		System interface	PS/2 6-pin mini din connector
		ESD	CE level 4, 15-kV air discharge
		EMI – RFI	Conforms to FCC rules for a Class B computing device
	Mechanical	Microsoft PC 99 – 2001	Functionally compliant
		Languages	38 available
		Keycaps	Low-profile design
		Switch actuation	55-g nominal peak force with tactile feedback
		Switch life	20 million keystrokes (using Hasco modified tester)
		Switch type	Contamination-resistant switch membrane
		Key-leveling mechanisms	For all double-wide and greater-length keys
		Cable length	6 ft (1.8 m)
		Microsoft PC 99 – 2001	Mechanically compliant
	Environmental	Acoustics	43-dBA maximum sound pressure level
		Operating temperature	50° to 122° F (10° to 50° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)
		Operating humidity	10% to 90% (non-condensing at ambient)
		Non-operating humidity	20% to 80% (non-condensing at ambient)
		Operating shock	40 g, six surfaces
		Non-operating shock	80 g, six surfaces
		Operating vibration	2-g peak acceleration
		Non-operating vibration	4-g peak acceleration
		Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
		Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence
	Approvals	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC	
	Ergonomic compliance	ANSI HFS 100, ISO 9241-4, and TUVGS	

Technical Specifications - Input/Output Devices

HP PS/2 Optical Scroll Mouse	Dimensions (H x L x W)	3.95 x 6.21 x 11.7 cm (1.56 x 2.44 x 4.61 in)	
	Weight	4.44 oz (126 g)	
	Environmental	Operating temperature	-32° to 104°F (0° to 40° C)
		Non-operating temperature	-4° to 140°F (-20° to 60° C)
		Operating humidity	10% to 90% (non condensing at ambient)
		Non-operating humidity	10% to 90% non condensing
		Operating shock	40 g, 6 surfaces
		Non-operating shock	80 g, 6 surfaces
		Operating vibration	2 g peak acceleration
		Non-operating vibration	4 g peak acceleration
Drop (out of box)		80 cm height onto asphalt tile over concrete or equivalent, 5-drop in 5 direction except the cable face	
Electrical	Operating voltage	5 VDC ± 10%	
	Power consumption	100mA	
	System consumption	PS/2 mini-din connector	
	ESD	CE level 4, 15 kV air discharge	
	EMI-RFI	Conforms to FCC rules for a Class B computing device	
Mechanical	Microsoft PC99 – 2001	Functionally compliant	
	Resolution	400 ± 20% DPI	
	Tracking speed	10 in/s (25.4 cm/s) maximum	
	Acceleration	100 in/s/s (2.54 m/s/s)	
	Switch actuation	61 g nominal peak force	
	Switch life	3,000,000 operations (using Hasco modified tester)	
	Switch type	Low force micro-switches	
	Tracking mechanism life	155 mi (250 km) at average speed of 10 in/s	
	Cable length	6 ft (1.8 m)	
	Microsoft PC99 – 2001	Mechanically compliant	
Scroll wheel	Width	8 mm	
	Diameter	1.01 in (25.6 mm)	
	Maximum rotation speed	48 rats/sec	
	Switch type	Light force micro-switch	
	Switch life	1 million operations	
Regulatory approvals	Mechanical life	Minimum 200,000 revolutions	
	Compliant	UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC	

Technical Specifications - Input/Output Devices

HP USB Optical Scroll Mouse	Dimensions (H x L x W)	1.5 x 4.5 x 2.5 in (3.8 x 11.6 x 6.3 cm)
	Weight	0.27 lb (0.12 kg)
	Cable length	72.8 in (185 cm)

Technical Specifications - Optical Storage

HP SATA SuperMulti LightScribe DVD Writer Drive	Height	5.25-inch, half-height, tray-load			
	Orientation	Either horizontal or vertical			
	Interface type	SATA/ATAPI			
	Disc capacity	8.5 GB DL or 4.7 GB standard			
	Dimensions (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)			
	Weight (max)	2.6 lb (1.2 kg)			
	Write speeds	DVD-RAM	Up to 12X		
		DVD+R	Up to 16X		
		DVD+RW	Up to 8X		
		DVD+R DL	Up to 8X		
		DVD-R DL	Up to 8X		
		DVD-R	Up to 16X		
		DVD-RW	Up to 6X		
		CD-R	Up to 48X		
		CD-RW	Up to 32X		
		Read speeds	DVD-RAM	Up to 12X	
			DVD+RW, DVD-RW, DVD+R DL, DVD-R DL	Up to 8X	
			DVD-ROM DL	Up to 8X	
			DVD-ROM, DVD+R, DVD-R	Up to 16X	
	CD-ROM, CD-R		Up to 48X		
	CD-RW		Up to 32X		
	Access time (typical reads, including settling)		Random	DVD: < 140 ms (typical), CD: < 125 ms (typical)	
Full Stroke		DVD: < 250 ms (seek), CD: < 210 ms (seek)			
Power	Source	SATA DC power receptacle			
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p			
		12 VDC ± 5%-200 mV ripple p-p			
	DC Current	5 VDC (< 1000 mA typical, 1600 mA maximum) 12 VDC (< 600 mA typical, 1400 mA maximum)			
Environmental conditions (operating – non-condensing)	Temperature	41° to 122° F (5° to 50° C)			
	Relative Humidity	10% to 90%			
	Maximum Wet Bulb Temperature	86° F (30° C)			

Technical Specifications - Optical Storage

SATA CD-RW/DVD-ROM Combo Drive	Height	5.25-inch, half-height, tray-load	
	Orientation	Either horizontal or vertical	
	Interface type	SATA/ATAPI	
	Disc capacity	Single layer: Up to 4.7 GB (6 times capacity of CD-ROM) Double layer: Up to 8.5 GB (12 times capacity of CD-ROM)	
	Dimensions (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)	
	Weight (max)	2.6 lb (1.2 kg)	
	Write speeds	CD-R	Up to 48X
		CD-RW	Up to 32X
	Read speeds	DVD+R/-R/+RW/-RW/+R DL /-R DL	Up to 8X
		DVD-ROM	Up to 16X
		CD-ROM, CD-R	Up to 48X
		CD-RW	Up to 32X
	Access time (typical reads, including settling)	Random	DVD: < 140 ms (typical), CD: < 125 ms (typical)
		Full Stroke	DVD: < 250 ms (typical), CD: < 210 ms (typical)
	Power	Source	SATA DC power receptacle
		DC Power Requirement	5 VDC \pm 5%-100 mV ripple p-p
			12 VDC \pm 5%-200 mV ripple p-p
	Environmental (all conditions non-condensing)	Temperature	5 VDC (< 1000 mA typical, < 1600 mA maximum)
			12 VDC (< 600 mA typical, < 1400 mA maximum)
			Relative Humidity
Maximum Wet Bulb Temperature			10% to 90%
		86° F (30° C)	

SATA DVD-ROM Drive	Height	5.25-inch, half-height, tray-load	
	Orientation	Either horizontal or vertical	
	Interface type	SATA/ATAPI	
	Disc capacity	Single layer: Up to 4.7 GB (6 times capacity of CD-ROM) Double layer: Up to 8.5 GB (12 times capacity of CD-ROM)	
	Dimensions (W x H x D)	5.9 x 1.7 x 8.0 in (15.0 x 4.4 x 20.3 cm)	
	Weight (max)	2.6 lb (1.2 kg)	
	Read speeds	DVD+R/-R/+RW/-RW/+R DL /-R DL	Up to 8X
		DVD-ROM	Up to 16X
		DVD-RAM	Up to 4X
		CD-ROM, CD-R	Up to 48X
		CD-RW	Up to 32X

Technical Specifications - Optical Storage

Removable Storage – Media Compatibility – DVD-ROM	Media	Read	Write
	CD-ROM	Yes	No
	CD-R	Yes	No
	CD-RW	Yes	No
	DVD-ROM	Yes	No
	DVD-ROM DL	Yes	No
	DVD-RAM	Yes	No
	DVD+R	Yes	No
	DVD+R DL	Yes	No
	DVD+RW	Yes	No
	DVD-R	Yes	No
	DVD-RW	Yes	No
	DVD-R DL	Yes	No
Access times (typical reads, including setting)	Random	DVD: < 140 ms (typical), CD: < 125 ms (typical)	
	Full Stroke	DVD: < 250 ms (seek), CD: < 210 ms (seek)	
	Cache Buffer	2 MB (minimum)	
	Data Transfer Modes	ATA PIO mode 4 (16.7 MB/s); ATA Multi-word DMA mode 2 (16.7 MB/s); ATA UltraDMA Mode 3 (44.4 MB/s -default)	
Power	Source	SATA DC power receptacle	
	DC Power Requirement	5 VDC ± 5%-100 mV ripple p-p 12 VDC ± 5%-200 mV ripple p-p	
	DC Current	5 VDC – <1000 mA typical, < 1600 mA maximum 12 VDC –< 600 mA typical, < 1400 mA maximum	
Environmental (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)	
	Relative Humidity	10% to 90%	
	Maximum Wet Bulb Temperature	86° F (30° C)	

Technical Specifications - Removable Storage

HP 16-in-1 Media Card Reader	USB Interface	USB 2.0 High-speed device
	Advance protocol support	Supports hardware ECC (Error Correction Code) function <ul style="list-style-type: none"> • Supports hardware CRC (Cyclic Redundancy Check) function • Supports MS 4-bit parallel transfer mode • Supports MS-PRO 4-bit parallel transfer mode • Supports SD 4-bit parallel transfer mode • Supports high-speed 50-MHz SD 4-bit card (version 1.1) • Support high-speed 52-MHz MultiMediaCard 8-bit card
	Supported media type with card adapter	<ul style="list-style-type: none"> • MicroSD (T-Flash) • Memory Stick Micro
	Mechanical	
	Environmental	Operational Environmental Extremes Test Parameters/Conditions – Power applied, unit operating on system $\pm 5\%$ nominal supply voltage. 10°C 10% R.H. = 24 hours 10°C 90% R.H. = 24 hours 20°C 90% R.H. = 24 hours 30°C 90% R.H. = 24 hours 40°C 90% R.H. = 24 hours 50°C 90% R.H. = 24 hours 50°C 10% R.H. = 24 hours Storage Environmental Extremes Test Parameters/Conditions 60°C @ 80% R.H. for 96 hours -30°C @ 20% R.H. for 48 hours No power applied Delta °C < 1.0°C/min Delta % R.H. < 1.5% R.H./min
	Approvals	USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0, Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.2 FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUV-T

HP 22-in-1 (with 1394) Media Card Reader	USB Interface	USB 2.0 High-speed interface
		NOTE: Requires the USB cable to be connected to the internal USB 2.0 port or a USB 2.0 PCI card.
	1394 Interface	Two IEEE-1394a external ports; 1 IEEE-1394a internal port (connects to the pass through cable on the media card reader)
	Advance protocol support	<ul style="list-style-type: none"> • Supports hardware ECC (Error Correction Code) function • Supports hardware CRC (Cyclic Redundancy Check) function • Supports MS 4-bit parallel transfer mode • Supports MS-PRO 4-bit parallel transfer mode • Supports MS PRO-HG Duo 4-bit parallel transfer mode • Supports SD 4-bit parallel transfer mode • Supports high-speed 50Mhz SD 4-bit card (version 2.0) • Supports high-speed 52Mhz MultiMediaCard 8-bit card (version 4.2) • Supports CF v4.0 with PIO mode 6 and Ultra DMA mode

Technical Specifications - Removable Storage

Supported media type

- CompactFlash Type I
- CompactFlash Type II
- Microdrive
- MultiMediaCard
- Reduced Size MultiMediaCard (RS MultiMediaCard)
- MultiMediaCard 4.2 (MultiMediaCard Plus, including MultiMediaCard Plus HC)
- Reduced Size MultiMediaCard 4.2 (MultiMediaCard Mobile, including MultiMediaCard Mobile HC)
- Secure Digital Card (SD)
- Secure Digital High Capacity (SDHC)
- miniSD
- miniSD High Capacity
- Micro SD (T-Flash)
- Micro SD HC
- Memory Stick
- Memory Stick Select
- Memory Stick Duo (MS Duo)
- Memory Stick PRO (MS PRO)
- Memory Stick PRO Duo (MS PRO Duo)
- Memory Stick PRO-HG Duo
- MagicGate Memory Stick (MG)
- MagicGate Memory Stick Duo
- Picture Card

Supported media type with card adapter

- Memory Stick Micro (M2)
- MultiMediaCard Micro

Environmental

Operational

Environmental Extremes

Test Parameters/Conditions - Power applied, unit operating on system $\pm 5\%$ nominal supply voltage.
10°C 10% R.H. = 24 hours
10°C 90% R.H. = 24 hours
20°C 90% R.H. = 24 hours
30°C 90% R.H. = 24 hours
40°C 90% R.H. = 24 hours
50°C 90% R.H. = 24 hours
50°C 10% R.H. = 24 hours

Storage Environmental Extremes

Test Parameters/Conditions
140°F (60°C) @ 80% R.H. for 96 hours
-22°F (-30°C) @ 20% R.H. for 48 hours
No power applied
Delta °C < 1.0°C/min
Delta % R.H. < 1.5% R.H./min

Approvals

USB-IF, WHQL, Compliant with USB Mass Storage Class Bulk only Transport Specification Rev. 1.0, Compliant Intel Front Panel I/O Connectivity Design Guide V. 1.3
FCC, CE, BSMI, C-Tick, VCCI, MIC, cUL, TUV-T

Technical Specifications - Environmental Data

Eco-Label Certifications and declarations This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- US ENERGY STAR®
- US Federal Energy Management Program (FEMP)
- Taiwan Green Mark
- China Energy Conservation Program
- IT ECO declaration
- EPEAT™ Rated – GOLD
- Korea Eco-label
- Japan PC Green label*

* This product conforms to the examination standards (2003 version) under JEITA's 'PC Green Label System.'

Small Form Factor

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Small Form Factor Desktop model is based on a typically configured product.

Energy Consumption

AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz

	AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz	AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz
Normal Operation On-Idle (ENERGY STAR Idle (S0))	56.48 W	55.47 W	57.01 W
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Enabled)	3.28 W	3.56 W	3.27 W
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Disabled)	3.28 W	3.56 W	3.27 W
ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Enabled)	1.6 W	1.87 W	1.58 W
ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Disabled)	0.9 W	1.16 W	0.88 W

Heat Dissipation*

AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz

	AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz	AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz
Normal Operation On-Idle (ENERGY STAR Idle (S0))	192.709 BTU/hr	189.263 BTU/hr	194.518 BTU/hr
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Enabled)	11.191 BTU/hr	12.146 BTU/hr	11.147 BTU/hr
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Disabled)	11.191 BTU/hr	12.146 BTU/hr	11.147 BTU/hr
ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Enabled)	5.459 BTU/hr	6.38 BTU/hr	5.39 BTU/hr

Technical Specifications - Environmental Data

ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Disabled)	3.07 BTU/hr	3.957 BTU/hr	3.002 BTU/hr
---	-------------	--------------	--------------

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

This product is in compliance with US executive order 13221, WOL (wake on LAN) disabled.

Declared Noise Emissions

(in accordance with
ISO 7779 and ISO 9296)

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
System Fan Off		
Idle	3.8	27
Fixed Disk (random writes)	3.9	28

Longevity and Upgrading This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- Intel LGA775 processor socket
- 8 USB ports
- 1 empty PCI slot
- 2 empty PCIe x1 slots
- 1 empty PCIe x16 slot
- 1 internal drive slot
- 1 SATA optical drive slot
- 4 memory slots
- 1 Serial Port (optional)
- 1 external diskette drive (optional)

Spare parts are available throughout the warranty period and or for up to 5 years after the end of production

Batteries

This product complies with ISO standards:

- EU Directive 91/ 157/ EEC
- EU Directive 93/ 86/ EEC
- EU Directive 98/ 101/ EEC

Batteries used in the product do not contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight
- Lead greater than 2000ppm by weight.

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.

Technical Specifications - Environmental Data

- This product is in compliance with the IEEE 1680 (EPEAT) standard at the GOLD level, see: www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product contains 0% recycled materials (by wt.)
- This product is 93% recyclable when properly disposed of at end of life.

Packaging Materials		
Corrugated Paper		1915 g
EPE Foam		135 g
LDPE Bag		25 g

- The EPE foam packaging material is made from 30 to 60% industrial recycled content.
- The corrugated paper packaging materials contain at least 80% post consumer recycled content.

Minitower

System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Minitower Desktop model is based on a typically configured product.

Energy Consumption

	AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz	AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz
Normal Operation On-Idle (ENERGY STAR Idle (S0))	57.72 W	57.16 W	58.12 W
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Enabled)	3.01 W	3.32 W	2.99 W
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Disabled)	3.01 W	3.32 W	2.98 W
ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Enabled)	1.47 W	1.76 W	1.45 W
ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Disabled)	0.81 W	1.09 W	0.79 W

Heat Dissipation*

	AC Input Voltage at 115 VAC +/- 5 VAC, 60 Hz +/- 3 Hz	AC Input Voltage at 230 VAC +/- 5 VAC, 50 Hz +/- 3 Hz	AC Input Voltage at 100 VAC +/- 5 VAC, 50 Hz +/- 3 Hz
Normal Operation On-Idle (ENERGY STAR Idle (S0))	196.94 BTU/hr	195.029 BTU/hr	198.305 BTU/hr
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Enabled)	10.27 BTU/hr	11.327 BTU/hr	10.201 BTU/hr
ENERGY STAR "Sleep" (S3) (Wake On LAN (WOL) Disabled)	10.27 BTU/hr	11.327 BTU/hr	10.167 BTU/hr
ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Enabled)	5.015 BTU/hr	6.005 BTU/hr	4.947 BTU/hr
ENERGY STAR "Standby" (Off) (S5) (Wake On LAN (WOL) Disabled)	2.763 BTU/hr	3.719 BTU/hr	2.695 BTU/hr

Technical Specifications - Environmental Data

* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

This product is in compliance with US executive order 13221, WOL (wake on LAN) disabled.

Declared Noise Emissions

(in accordance with ISO 7779 and ISO 9296)

	Sound Power (LWAd, bels)	Sound Pressure (LpAm, decibels)
Idle	3.8	27
Fixed Disk (random writes)	3.9	28

Longevity and Upgrading This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include:

- Intel LGA775 processor socket
- 8 USB ports
- 1 empty PCI slot
- 2 empty PCIe x1 slots
- 1 empty PCIe x16 slot
- 2 internal drive slots
- 3 external SATA drive slots
- 4 memory slots
- 1 Serial Port (optional)
- 1 external diskette drive (optional)

Spare parts are available throughout the warranty period and or for up to "X" years after the end of production.

Batteries

This product complies with ISO standards:

- EU Directive 91/ 157/ EEC
- EU Directive 93/ 86/ EEC
- EU Directive 98/ 101/ EEC

Batteries used in the product **do not** contain:

- Mercury greater the 5ppm by weight
- Cadmium greater than 10ppm by weight
- Lead greater than 2000ppm by weight.

Battery size: CR2032 (coin cell)

Battery type: Lithium

Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the GOLD level, see: www.epeat.net
- Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product contains 0% recycled materials (by wt.)

Technical Specifications - Environmental Data

- This product is 93% recyclable when properly disposed of at end of life.

Packaging Materials	Corrugated Paper	1700 g
	EPE Foam	138 g
	LDPE Bag	50 g

- The EPE foam packaging material is made from 30 to 60% industrial recycled content.
- The corrugated paper packaging materials contains at least 80% post consumer recycled content.

Small Form Factor, Minitower

RoHS Compliance

Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances were virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at:

http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.

Technical Specifications - Environmental Data

- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

© Copyright 2009 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Intel and Pentium are U.S. registered trademarks of Intel Corporation. Microsoft and Windows are U.S. registered trademarks of Microsoft Corporation. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.