

# Lexmark Forms Printer 2580+ Series



## Fast, Reliable Forms Printing

The Lexmark Forms Printer 2580+ series provides high-speed forms printing and features such as high-yield ribbons, multi-part form support, and character and page monitoring.



Black



Up to 618 cps at  
12 cpi



Multi-Part  
Forms



Network  
Model



Lexmark Forms Printer 2580+

## Overview:

### Reliability and performance

With fast print speeds up to 618 cps at 12 cpi and a rugged design that can handle extreme environments and workloads, the Lexmark Forms Printer 2580+ series helps you to be productive no matter where you are. Benefit from the 2MB of built-in flash memory that expands support for bar codes, non-volatile fonts and remote management.

### Flexible paper handling

Easily switch between push and pull feeds and select the type of paper-handling that best suits your needs. Use the optional Automatic Sheet Feeder to load stacks of cut-sheet media, envelopes or multi-part forms. Use the Tractor 2 option to simultaneously load two types of continuous forms.

### Flexible media support

Print on multiple types of media, including single-part or multi-part continuous forms, and single-part or multi-part cut forms. Multi-part forms can include one original and up to five copies.

### Easy to use

The easy-to-use operator panel lets you access all of the printer functions, as well as monitor printer usage with character and page counts. The panel also includes a font preview, so you can make sure that the correct font is used on your document.

### Easy to maintain

For multi-national groups, the universal power supply reduces the need to maintain separate low-voltage and high-voltage power supplies. On the 2580n+ and 2581n+, the embedded web server and Lexmark Markvision Enterprise help you easily maintain multiple devices from a centralized location.

### Easy to connect

Connecting to your network is easy and secure with built-in Ethernet and security features such as IPSec, HTTPS, SNMPv3 and 802.1x authentication with the Forms Printer 2580n+ and 2581n+.

### Long lasting supplies

Replace supplies less often with powerful printheads that last up to 300 million characters and the availability of re-inking ribbons that can print up to 8 million characters.

**LEXMARK**  
TM

# Lexmark Forms Printer 2580+ Series

## Product specifications

### Lexmark Forms Printer 2580+

### Lexmark Forms Printer 2580n+

### Lexmark Forms Printer 2581+

### Lexmark Forms Printer 2581n+

Printing				
Printer Part Number	11C0099	11C0109	11C0111	11C2956
Print Technology	9-Pin Dot Matrix			
Print Speeds	Up to 100 cps Near Letter Quality @ 12 cpi, Up to 400 cps Draft @ 12 cpi, Up to 618 cps Fast Draft @ 12 cpi	Up to 400 cps Draft @ 12 cpi, Up to 618 cps Fast Draft @ 12 cpi, Up to 100 cps Near Letter Quality @ 12 cpi	Up to 100 cps Near Letter Quality @ 12 cpi, Up to 400 cps Draft @ 12 cpi, Up to 618 cps Fast Draft @ 12 cpi	Up to 400 cps Draft @ 12 cpi, Up to 618 cps Fast Draft @ 12 cpi, Up to 100 cps Near Letter Quality @ 12 cpi
Maximum Print Line	8.0 inches		13.6 inches	
Resolution	240 x 144 dots per inch			
Memory	512 KB			
Mean Time Between Failures (MTBF)	12,500 POH @ 25% duty cycle			
Supplies Yield	Standard 4 million characters (draft mode at 10 cpi) - Re-Inking Ribbon, Optional 8 million characters (draft mode at 10 cpi)- Re-Inking Ribbon			
Supplies Part Number	3070169 - High Yield Black Re-Inking Ribbon 3070166 - Standard Yield Black Re-inking Ribbon			
Text Fonts	Fast Draft, Draft, Courier, Gothic, 10, 12, 15, 17.1, 20 cpi, Proportional Spaced (PS)	Fast Draft, Draft, Courier, Gothic, Proportional Spaced (PS), 10, 12, 15, 17.1, 20 cpi	Fast Draft, Draft, Courier, Gothic, 10, 12, 15, 17.1, 20 cpi, Proportional Spaced (PS)	Fast Draft, Draft, Courier, Gothic, Proportional Spaced (PS), 10, 12, 15, 17.1, 20 cpi
Noise Level, Idle	15 dBA			
Print Noise Level, Operating	56 dBA		57 dBA	
Paper Handling				
Paper Handling Standard	Front Tractor Feeder			
Paper Handling Optional	Tractor 2 (narrow), Automatic Sheet Feeder (narrow)	Automatic Sheet Feeder (narrow), Tractor 2 (narrow)	Tractor 2 (wide), Automatic Sheet Feeder (wide)	Automatic Sheet Feeder (wide), Tractor 2 (wide)
Paper Option Part Number	12T0693 - Automatic Sheet Feed (narrow) 12T0695 - Tractor 2 (narrow) 12T0697 - Cut Sheet Output Support Stand		12T0696 - Tractor 2 (wide) 12T0694 - Automatic Sheet Feed (wide) 12T0697 - Cut Sheet Output Support Stand	
Media Sizes Supported	Single-part or multi-part Cut Forms, Narrow Sheet Fed Paper, Single-part or multi-part Continuous Forms	Narrow Sheet Fed Paper, Single-part or multi-part Continuous Forms	Single-part or multi-part Cut Forms, Wide Sheet Fed Paper, Single-part or multi-part Continuous Forms	Wide Sheet Fed Paper, Single-part or multi-part Continuous Forms
Media Types Supported	Forms or Paper - 16 to 24 lbs, 60 to 90 gsm (0.0045" or 0.11mm maximum paper thickness), Single-part forms - 16 to 24 lbs, 60 to 90 gsm (0.0045" or 0.11 mm paper thickness), Multi-part forms - Up to 1+5 Parts (up to 0.020" or 0.51 mm paper thickness)			
General				
Size (in. - H x W x D)	7.7 x 19.4 x 11.4 in.		7.7 x 24.9 x 11.4 in.	
Weight (lb.)	17.6 lb.		21.6 lb.	
Limited Warranty - See Statement of Limited Warranty	2-Year Advanced Exchange			
Product Certifications	www.lexmark.ca			
Specified Operating Environment	Temperature: 10 to 40°C (50 to 104°F), Humidity: 8 to 90% Relative Humidity			
Compatibility				
Linux Operating Systems Supported	SUSE Linux 10.0, 10.1, 10.2, Linspire Linux 5.0, Debian GNU/Linux 3.1, 4.0, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10, 11	SUSE Linux Enterprise Server 8.0, 9.0, 10, 11, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, Debian GNU/Linux 3.1, 4.0, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2	SUSE Linux 10.0, 10.1, 10.2, Linspire Linux 5.0, Debian GNU/Linux 3.1, 4.0, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, SUSE Linux Enterprise Server 8.0, 9.0, 10, 11	SUSE Linux Enterprise Server 8.0, 9.0, 10, 11, Red Hat Enterprise Linux WS 3.0, 4.0, 5.0, Debian GNU/Linux 3.1, 4.0, Linspire Linux 5.0, SUSE Linux 10.0, 10.1, 10.2
Microsoft Windows Operating Systems Supported	Server 2008 R2, Windows 7 x64, Windows 7, Server 2008 x64, Server 2008, 2000, Vista, Server 2003 x64, XP x64, Server 2003, XP	XP, Server 2003, XP x64, Server 2003 x64, Vista, Vista x64, Server 2008, Server 2008 x64, Windows 7, Windows 7 x64, Server 2008	Server 2008 R2, Windows 7 x64, Windows 7, Server 2008 x64, Server 2008, 2000, Vista, Server 2003 x64, XP x64, Server 2003, XP	XP, Server 2003, XP x64, Server 2003 x64, Vista, Vista x64, Server 2008, Server 2008 x64, Windows 7, Windows 7 x64, Server 2008
Standard Ports	Centronics IEEE 1284 Bidirectional Parallel, USB	Ethernet 10/100BaseTX (RJ-45), USB	Centronics IEEE 1284 Bidirectional Parallel, USB	Ethernet 10/100BaseTX (RJ-45), USB
Optional Local Ports	Internal RS-232C serial			
Optional Network Ports	External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7002e Fast Ethernet (parallel), External MarkNet™ N7000e Fast Ethernet (USB)	External MarkNet™ N7020e Gigabit Ethernet	External MarkNet™ N7020e Gigabit Ethernet, External MarkNet™ N7002e Fast Ethernet (parallel), External MarkNet™ N7000e Fast Ethernet (USB)	External MarkNet™ N7020e Gigabit Ethernet
Printer Languages (Standard)	Okidata MICROLINE Emulation, Personal Printer Data Stream (PPDS), Epson Emulation	Okidata MICROLINE Emulation, Epson Emulation, Personal Printer Data Stream (PPDS)	Okidata MICROLINE Emulation, Personal Printer Data Stream (PPDS), Epson Emulation	Okidata MICROLINE Emulation, Epson Emulation, Personal Printer Data Stream (PPDS)

## Which model is best for you?



	2580+	2580n+	2581+	2581n+
9-pin	9-pin	9-pin	9 pin	9 pin
Narrow format	Narrow format	Wide format	Wide format	Wide format
	Network ready		Network ready	Network ready