



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: N516-10M

10M (33-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)



Highlights

- Premium PVC 50/125 multimode patch cables
- Attenuation loss meets or exceeds the latest industry standards
- Higher Bandwidth, optimized for Gigabit and 10Gbps networks
- Backward compatible with 62.5 micron fiber
- Built-in headroom for future applications

Description

Tripp Lite's 10-meter multimode duplex Fibre Channel SC/LC patch cable is manufactured from 50/125 zipcord fiber. The cable has SC connectors on one end, and LC at the other, a PVC jacket, and is FDDI and OFNR rated. 50/125 Duplex multimode fiber is most commonly used in Fibre Channel applications. It is backward compatible with 62.5 micron fiber and built-in headroom for future applications. The cable provides higher bandwidth optimized for Gigabit and 10Gbps networks as well. Also available in 1, 2, 3, 5, 15, 20, 30, and 50 meter lengths. Search "N516-" to bring up all lengths. Also search "N506-" for SC-SC cables, and "N520-" for LC-LC cables.

System Requirements

- Any Fiber Optic hardware or NIC card requiring Multimode Duplex cable with LC/SC connectors

Package Includes



- 10M Duplex MMF Cable LC/SC 50/125 Fiber

Features

- Constructed with 50/125 micron cable
- Length - 10M
- Use on fiber and fibre channel installations
- SC male to LC male connectors
- Higher bandwidth optimized for gigabit and 10Gbps networks
- Backward compatible with 62.5 micron fiber
- Built-in headroom for future applications
- Number of fibers: 2
- Fiber type: all glass graded index
- Core diameter: two 50+/-3 microns
- CLAD diameter: 125+/-2 microns
- Primary coating diameter: 245+/-15 microns
- Primary coating material: acrylate
- Secondary coating diameter: 900+/-50 microns
- Secondary coating material: PVC
- Attenuation @850NM: 3.5DB/KM maximum, @1300NM: 1.0DB/KM maximum

- Bandwidth @850NM: 220 MHZ-KM minimum, @1300NM: 600 MHZ-KM minimum
- Numeric aperture: .275 nominal
- Proof test level: 100,000 PSI
- Insertion loss testing performed on every connector (0.2db typical) and provided with cable
- Beveled edge on ends of glass makes insertion of plug a breeze

Specifications

OVERVIEW	
Attenuation @ 1300NM	1.0 DB/KM maximum
Attenuation @ 850NM	3.5 DB/KM maximum
Bandwidth @ 1300NM	600 MHZ-KM minimum
Bandwidth @ 850NM	220 MHZ-KM minimum
Clad Diameter	125 +/- 2 microns
Core Diameter	Two 50 +/- 3 microns
Fiber Type	All glass graded index
Number of Fibers	2
Numerical Aperture	.275 nominal
Primary Coating Diameter	245 +/- 15 microns
Primary Coating Material	Acrylate
Proof Test Level	100,000 PSI
Secondary Coating Diameter	900 +/- 50 microns
Secondary Coating Material	PVC
Intended Application	Computer Networking (Fiber)
INPUT	
Cable Length (m)	10
PHYSICAL	
Color	Orange
Style	Fiber Optic
CONNECTIONS	
Connector A	 LC
Connector B	 SC
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Fiber Optic Cables & Adapters	N506-10M	10M (33-ft.) Duplex MMF 50/125 Patch Cable (SC/SC)	1
Fiber Optic Cables & Adapters	N516-01M	1M (3-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)	1
Fiber Optic Cables & Adapters	N516-02M	2M (6-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)	1
Fiber Optic Cables & Adapters	N516-03M	3M (10-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)	1
Fiber Optic Cables & Adapters	N516-05M	5M (16-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)	1
Fiber Optic Cables & Adapters	N516-15M	15M (50-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)	1
Fiber Optic Cables & Adapters	N516-30M	30M (100-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)	1
Fiber Optic Cables & Adapters	N516-50M	50M (164-ft.) Duplex MMF 50/125 Patch Cable (LC/SC)	1
Fiber Optic Cables & Adapters	N520-10M	10M (33-ft.) Duplex MMF 50/125 Patch Cable (LC/LC)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.triplite.com/en/products/model.cfm?txtModelID=2188.

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.