

TeraStation™ Pro 6 WSS

Network Attached Storage

WS-6VL/R5


High Performance NAS Powered by Windows





WS-6VL/R5

TeraStation™ Pro 6 WSS Storage Server provides high performance six hard drive RAID based network storage with the power of a Windows Server operating system. Powered by Microsoft Windows® Storage Server 2008 R2 Workgroup Edition, TeraStation™ Pro 6 WSS provides seamless capability with Windows computers and servers. The TeraStation™ Pro 6 WSS incorporates the powerful Intel® Atom™ Dual-Core Processor providing class-leading performance, enabling the ability to focus on concurrent tasks with minimal performance degradation: experience maximum network throughput while a replication job runs in the background or perform fast search indexing while an anti-virus scan is occurring. Additionally, TeraStation™ Pro 6 WSS supports full disk encryption and support for NTFS for very specific file-level security. Native Active Directory support provides integration with large Windows networks.



Features and Benefits

- · Intel® Atom™ 1.66GHz Dual Core / 2GB RAM
- · Windows Storage Server 2008 R2 Workgroup Edition
- iSCSI Target and Initiator
- Active Directory support
- Disk quota (soft quota) support prevents users/groups from consuming too much disk space
- Scheduled shut down eliminates unnecessary access and reduces energy costs
- DFS (Distributed File System), Namespace & Replication support
- Hot swap hard drive trays behind the front panel for easy drive access and replacement
- Improved CPU speed enables faster data transfer
- 10/100/1000 Gigabit Ethernet with Jumbo Frame
- Two Ethernet ports for port trunking and load balancing
- Works with VMware and Hyper-V (SAN Storage for Virtual Machines)

- · Supported RAID levels: 0, 1, 5, JBOD (Individual Disks)
- Two large silent fans cool the hard drive efficiently
- · Advanced ventilation design reduces internal heat
- LCD Display shows important TeraStation™ information and disk status
- Windows Server 2008 Server Manager Utility for easy deployment and configuration
- Internet Information Services (IIS) support
- 2 USB 3.0 ports and 2 USB 2.0 ports for external drive, printer and UPS connectivity
- 10 licenses of NovaBACKUP® Business Essentials v12 Included: Back up 10 Windows PCs, Windows Servers, Exchange or MS SQL databases
- 3-Year Limited Warranty

RAID Support for Maximum Flexibility and Reliability



In RAID 0 (Striping) mode data are written on all HDDs simultaneously no redundancy but fast



In RAID 1 (Mirrioring)
mode data are written
on a HDD are copied to
a second HDD
simultaneously - best
redundancy



In RAID 5 mode data are written on a HDDs simultaneously - the also will be information to recreate a missing




JBOD - just a bundle of disks, you use all HDDs as individual drives - no redundancy



n spanning mode are all HDDs put one after another like a

NovaBACKUP® Business Essentials





Comprehensive Backup Solution for up to IO PCs, Servers or SQL databases



TeraStation™ Pro 6 WSS

Network Attached Storage

WS-6VL/R5

SPECIFICATIONS

LAN Interface

Standard Compliance IEEE802.3ab/IEEE802.3u/IEEE802.3 Standard

(1000BASE-T/100BASE-TX/10BASE-T)

Data Transfer Rates 10/100/1000Mbps

Connector Type RJ-45 Number of Ports 2

Internal Hard Drives

Number of Drives 6

Drive Interface SATA 3Gb/s
Hard Drive Sizes 1.0TB, 2.0TB
Total Capacity 6TB, 12TB
Supported RAID Levels 0, 1, 5, IBOD

USB Interface

Standard Compliance

Number of Ports

Data Transfer Rates

Standard Compliance

USB 3.0/USB 2.0

2 USB 3.0/2 USB 2.0

Max. 5Gbps* (USB 3.0)

Max. 480Mbps (USB 2.0)

Protocol Support

Networking TCP/IP

File Sharing CIFS/SMB, NFS
Directory Integration LDAP, Active Directory

Management Remote Desktop Connection (RDP), Terminal Services Client

Time Synchronisation NTP

Other

Dimensions (WxHxD) 300 x 215 x 230mm

Weight approx. 11.5kg

Operating Environment 5-35°C

Setup Utility OS Support Windows® Operating Systems, Mac OS

Client OS Support Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows® XP,

Windows® 2000, Windows Server® 2008, Windows Server® 2003, Windows® 2000 Server

Power Supply Internal, AC 100-240V 50/60Hz

Part Numbers

WS-6V6.0TL/R5-EU WS-6V12TL/R5-EU

1TB= 1,000,000,000,000 Bytes. Actual data throughput and range will vary depending upon network conditions and environmental factors, including volume of network traffic and network overhead.

About Buffalo

www.buffalo-technology.com

Buffalo Technology is a leading global provider of award-winning storage, networking, memory, and multimedia solutions for the home and small business environments as well as for system builders and integrators. With more than three decades of networking and computer peripheral experience, Buffalo has proven its commitment to delivering innovative solutions that have put the company at the forefront of infrastructure technology.

^{* 5}Gbps is the maximum transfer rate derived from the specifications of the Universal Serial Bus 3.0 and the ExpressCard. Actual transfer rate will vary depending upon environmental factors. Data rate, features and performance may vary based on the configuration of your system and other factors.